

SearchCommand or control key
⌘/ctrl
K key
K
Ask AI
Kong
Platform
Explore the platform
Konnect
Build APIs
Kong Insomnia API Design API Testing and Debugging
Run APIs
API Gateway AI Gateway Event Gateway Service Mesh Kong Ingress Controller Kubernetes Operator
Govern APIs
Observability Metering & Billing Kong Identity Context Mesh API Security & Access Control
Discover APIs
Developer Portal Catalog
Tools



We Value Your Privacy
English
By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.
(Privacy Policy)
Accept All
Customize Choices
Ask AI




- kongctl

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)




- Inso CLI

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



- Koh CLI

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



- Terraform

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



- Ingress controller
- View all →

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



Why Kong?

lify managing and securing APIs.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ecK kongctl Inso CLI Koh CLI

- Plugins
  API Gateway Plugins
  AI Authentication Security Traffic Control Serverless Analytics & Monitoring Transformations Logging Monetization
  View all →
  Event Gateway Policies
  Security Traffic Control Transformations Data Quality
  View all →
  AI Gateway Policies
  AI Authentication Security Traffic Control Serverless Analytics & Monitoring Transformations Logging Monetization
  View all →
  Service Mesh Policies View all →
- APIs
- Support
  - Knowledge Base
  - Community
  - Github
  - Community Forum
  - Kong Pricing
  - Demos
  - User Calls
  - Workshops
  - Help & Support

Theme

Get a Demo Start Free Trial


Home / Kong Gateway

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

For product versions that have reached the end of sunset support, see the changelog archives.

3.16.0.1

Release date 2026/10/12

Feature

Plugin

- ai-a2a-proxy:
  - Added A2A v1.0 wire-format support alongside v0.3.
  - now rewrites the URL for all `supportedInterfaces` in the agent card.

Bugfix

Plugin

- ai-proxy-advanced:
  - Added prompt cache control mappings across OpenAI, Anthropic, and Amazon Bedrock chat formats.
  - Fixed an issue where request bodies were re-encoded with a non-deterministic JSON key order; content-neutral transforms now forward the client's original request bytes.
  - Fixed an issue where xAI reasoning tokens were not folded when visible completion tokens exceeded reasoning tokens.
  - Fixed an issue where gen_ai.request.max_tokens attribute was missing from OpenTelemetry spans.
  - Fixed an issue where the consistent-hashing balancer routed requests with the same hash_on_header value to different targets when multiple workers were running.
- basic-auth:
  - `brute_force_protection` is now enforced for principal-based (Kong Identity) authentication, matching the existing behavior for local credentials.
  - `brute_force_protection` now rate-limits each `Proxy-Authorization` and `Authorization` credential independently.
- degraphql:
  - Fixed an issue where the plugin router did not refresh after an incremental sync update on a Data Plane, leaving routes stale until the next full config push.
- graphql-rate-limiting-advanced:
  - Fixed an issue where `pass_all_downstream_headers` forwarded stale `Content-Length`, `Content-Encoding`, and `Transfer-Encoding` headers, breaking schema introspection.
  - Fixed an issue where a longer fixed window was incorrectly marked as exhausted if a shorter window denied a request.
- oas-validation:
  - Fixed an issue where OpenAPI 3.1.x parameter patterns using ECMA-262 `\uXXXX` Unicode escapes failed to match correctly, because PCRE does not support that escape syntax.
- opa:
  - Fixed an issue where Kong Gateway did not send an SNI to the OPA server. It now sends `opa_host` as the SNI when that is a hostname; with `ssl_verify =`

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

RM response returned a 500 error; the plugin now rejects such callbacks with a 401 authentication failure.

metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series

correctly marked as exhausted if a shorter window denied a request.

correctly marked as exhausted if a shorter window denied a request.

C

- **Balancer**: Fixed an issue where a plugin could not override the upstream target when the Gateway Service `host` was a literal IP address. The balancer kept the IP that it derived from the Service, so the request went to the Service host and the override was silently lost. This affected `kong.service.set_target` and every plugin that replaces `ngx.ctx.balancer_data.host`, for example `route-transformer-advanced` and `canary`.
- Fixed an issue where a malformed JSON document could corrupt the shared JSON decoder of a worker. Later requests that decoded valid JSON on the same worker then failed until the node restarted. The JWT plugin returned `Bad token; invalid JWT payload` for known-good tokens.
- Fixed an issue where `dnf upgrade kong-enterprise-edition` could not resolve an upgrade on RPM systems. The FIPS packages declared an unversioned `Obsoletes: kong-enterprise-edition`, so an installed non-FIPS package had two mutually conflicting successors and dnf reported "cannot install the best update candidate". The RPM packages now obsolete the other Enterprise variants only below the version being built. This also keeps `dnf install kong-enterprise-edition-fips` on the FIPS artifact. Debian and Alpine packages do not change.
- Fixed an issue where Kong Gateway in DB-less mode could fail to detect configuration changes during reconfiguration, leaving the router or plugins iterator stale.
- Fixed an issue where the `SameSite` attribute of the `Set-Cookie` header was incorrectly set to `Same-Site` by session-affinity (sticky-session) balancing.
- Fixed issues where upstream lookup failures interrupted balancer initialization and incomplete rebuilds left stale targets after a configuration rollback.
- **RBAC**: Fixed an issue where a temporary database outage during an RBAC user's group lookup cached a wrong value, breaking every later Admin API request from that user.

Clustering

- Fixed an issue where Kong tiny clustering payload sizes were logged for every message. It now only logs when the payload size exceeds `30%` of the configured `cluster_max_payload` limit.
- Fixed an issue where sync validation rejected valid configurations when a referenced entity was in a non-default workspace.
- Fixed an issue where the control plane sent incremental sync v2 notifications to a data plane that had fallen back to legacy sync v1, logging a misleading error.
- Fixed an issue where the Data Plane router rebuild could falsely abort with a concurrent-change error when the router spanned more than one page, leaving routes stale until the next config push.

Dependency

Core

- Bumped lua-resty-jq from 0.2.0 to 0.2.2.
- Bumped lua-resty-simdjson from 1.3.0 to 1.3.1 (updates simdjson to 4.6.11).

Performance

Core

- Improved performance when `untrusted_lua` is set to `sandbox`. Previously, Kong rebuilt the Lua environment, including a module reload, on every compile of a sandboxed function.

3.16.0.0

Release date 2026/09/15

Breaking Change

Core

end from `cel-rust` 0.11.6 to `cel-cpp` 0.15.0. This is a breaking change for conditional plugin execution:
small number of expressions involving quote-escaped strings or missing map keys (`kong.ctx.shared`,
k breaking changes for details.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

p, `snappy`, and `lz4` record batches.

ion that lets the producer compress message batches before sending them to the Kafka broker. Supported
Compression applies only to the Kong-to-broker hop and is independent of any HTTP-level `Content-`

    - Added a `payload_encoding` option (`avro_json` or `simple_json`) to the schema registry `value_schema` and `key_schema` configuration. When set to `simple_json`, the gateway accepts plain JSON request bodies for Avro schemas and resolves union/nullable branches against the schema, so clients no longer need to type-tag union fields (e.g. `{"int": 1}`, `{"null": null}`). Defaults to `avro_json` to preserve existing behavior.

- acl:
    - Added `allow_when`/`deny_when` fields that evaluate CEL boolean expressions against the request context to provide more expressive access-control policies.
- ai-proxy-advanced:
    - Added `cache_read_cost` and `cache_write_cost` to `model.options` so cached and cache-write prompt tokens can be priced per 1M tokens, alongside `input_cost` / `output_cost`.
    - Added filtering for empty Anthropic thinking blocks in request history.
    - Added support for reporting prompt cache token metrics when using native (non-OpenAI) request/response formats.
    - Added support for reporting prompt cache token metrics in OpenAI-compatible format.
    - Added support for per-cache-TTL cache-write pricing, context-window pricing factors, and service-tier pricing factors via `model.options` (`cache_write_cost_list`, `context_window_factor`, `service_tier_factor`). Anthropic (cache TTL + service tier), OpenAI, and Gemini service tiers are collected from upstream responses.
- confluent:
    - Added `producer_config_enabled` (default `false`) to opt into honoring the `producer_*` delivery settings (asynchronous mode, request acks/limits/retries), which the plugin previously ignored while always producing synchronously. The default preserves the existing synchronous behavior for current configurations.
- datakit:
    - Added a `ca_certificates` config option. When set, `call` nodes verify the server's TLS certificate against a trust store built solely from the referenced CA certificates instead of the global `lua_ssl_trusted_certificate` set. Ignored when a node's `ssl_verify` is disabled.
    - Added support for reading the authenticated Kong Identity principal with the `property` node using `kong.client.principal` and nested fields such as `kong.client.principal.metadata.rate_tier`.
- entitlement-enforcement:
    - Added the Entitlement Enforcement plugin, which enforces per-customer access policies (credit balance and feature entitlements) retrieved from an OpenMeter entitlement access endpoint.
- metering-and-billing:
    - Added the `allow_status_codes` config option to limit usage-event logging to responses whose status code falls within the given ranges, for example `200-299`.
- oas-validation:
    - Added a new configuration field `rfc9457_error_response` which, when set to `true`, returns validation errors in the RFC 9457 `application/problem+json` format for HTTP requests.
- opa:
    - Added WebSocket (`ws`/`wss`) protocol support. OPA is evaluated at handshake time before the connection is established.
- openid-connect:
    - Added actor token support to token exchange. Configure `token_exchange.request.actor_token` to include an actor token, read from a request header or a static token value, in the token exchange request.
    - Added `protected_resource_metadata` configuration to support RFC 9728 OAuth 2.0 Protected Resource Metadata, enabling automatic authorization server
    nent and enriching `WWW-Authenticate` challenge headers with `resource_metadata` and `scope` attributes.

-Of flow through a new `token_exchange.grant_type = jwt_bearer` (RFC 7523) mode, plus
ider.

JWKS keys. Use an RSA-PSS or NIST-curve ECDSA key instead.

to the FIPS 3 package for compliance with FIPS 140-3, please note that this is a breakin

config option. When enabled, the principal attributes are added to the metrics when an authenticated

.set_serialize_value to the access log export, so users no longer need `custom_attributes_by_lua` to

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Added `cache_by_principal` configuration option to switch cache key segmentation by Principal when using Kong Identity Directory. When enabled, the authenticated Principal's ID is used to compose the cache key.

- proxy-cache:
    - Added `cache_by_principal` configuration option to switch cache key segmentation by Principal when using Kong Identity Directory. When enabled, the authenticated Principal's id is used to compose the cache key.
- rate-limiting-advanced:
    - Added `expressions.limit` to drive individual limit entries via CEL, falling back to the static value on error.
    - Added support for rate limiting by Kong Identity Directory Principal, via `identifier: principal`, and for overriding the rate-limiting key entirely via the new, expressible `custom_key` field.
- rate-limiting:
    - Added a `custom_key` field for overriding the rate-limiting key entirely. The field is expressible, so it can be driven by a CEL expression, for example to rate limit by a Kong Identity Directory Principal's metadata.
    - Added support to rate limiting by Kong Identity Directory Principal.
    - The `second`, `minute`, `hour`, `day`, `month`, and `year` fields are now expressible, so the rate limit value itself can be driven by a CEL expression, for example to vary the limit by a Kong Identity Directory Principal's metadata.
- request-transformer-advanced:
    - Added a `max_request_body_size` configuration option that lets the plugin apply body transformations to request bodies that Nginx buffers to a temporary file (bodies larger than `client_body_buffer_size`). Previously such bodies were never read, so the configured body transformations were silently skipped and the original body was proxied upstream. The option defaults to `-1`, which preserves that behavior; set it to a positive byte limit to opt in (or `0` for unlimited, still bounded by Nginx's `client_max_body_size`).
- request-validator:
    - Added a new config option `enforcement_mode` (default `block`) that allows users to set the plugin to `log_only` mode, where validation failures are logged but requests are not rejected.
- upstream-oauth:
    - added support for the `private_key_jwt` OAuth client authentication method.
- ai-aws-guardrails, **ai-azure-content-safety**: Added `last_message` as new optional value for `config.text_source`.
- kafka-upstream / **confluent**: Added optional async connection-health gating (`producer_async_health_gating`, default `false`): when the producer is sustainedly failing SASL authentication with, or connectivity to, the broker, asynchronous requests fail fast with HTTP 503 instead of returning 200 and silently dropping the message, and recover automatically once the producer can authenticate and reach the broker again. Transient produce errors keep async best-effort buffering.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Added `schema_registry.confluent.authentication.logical_cluster_id` and `.identity_pool_id` configuration options, sent as the `target-sr-cluster` and `Confluent-Identity-Pool-Id` request headers when authenticating to Confluent Cloud Schema Registry with `oauth2` mode.

Core

- Added a FIPS-compliant variant of the distroless image.
- Added an info-level log entry at startup that records the running Kong Gateway version.
- Added an optional queue-level circuit breaker (`failure_threshold`, `breaker_cooldown`; off by default) for all plugins using `config.queue` that sheds buffered entries when a destination is permanently down instead of retrying indefinitely.
- Added Debian 13 (Trixie) support for building packages.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

al authentication and lookup attempts. Kong Gateway now logs the identity service's failure reason, for

elds with a CEL expression, evaluated per request and falling back to the field's static value if unset or if

owing operators to disable the Konnect analytics feature while keeping `konnect_mode` enabled. It defaults

ption. It selects how Kong Gateway orders plugins that declare a dynamic `ordering` rule. The default, ge plugin execution order. Set the option to `priority_preserving` to move only the plugins that declare gured priority order. This is a node-level setting. In hybrid mode, set it on each data plane and restart the gin, or names the plugin itself, now logs a warning each time the configuration changes. It previously

the debug server (`debug_listen`/`debug_listen_local`) with `kong debug log_level set`. The Admin nnot be protected by RBAC.

0-3 artifacts, and configured those builds to use AES-based TLS 1.3 ciphersuites. The FIPS-140-2 artifacts

- **Hashicorp Vault**: The AWS IAM credential fields `aws_access_key_id`, `aws_secret_access_key`, and `aws_assume_role_arn` are now referenceable, so you can store them as vault references instead of literal values.
- Kong now publishes one artifact per FIPS certification level. The `kong-enterprise-edition-fips` package and the `<version>-<distro>-fips` image keep the OpenSSL FIPS provider 3.0.9 (FIPS 140-2). The new `kong-enterprise-edition-fips-140-3` package and the `<version>-<distro>-fips-140-3` image use the provider 3.1.2 (FIPS 140-3).
- **Konnect Only**. Added support for annotating custom lua code frames in CPU Profiling.
- **Konnect Only**. **Analytics**: Added the OpenID Connect plugin's `credential_claim` identity to Analytics events, so requests are attributed under the auth dimension in Konnect without a Kong Consumer.
- **Plugin conditions**: Plugin condition expressions are now type-checked at configuration time. Expressions whose result is provably non-boolean (for example `1 + 1`, `"foo"`, or `size(x)`) are rejected when the plugin is configured, instead of failing at request time. Boolean and statically-unknown expressions are accepted as before.
- The FIPS-140-3 artifacts serve an explicit TLS 1.2 cipher list: four ECDHE suites with AES-GCM. The FIPS-140-2 artifacts keep the OpenSSL FIPS alias, which also admits static RSA key transport and SSLv3-era suites. To serve a different list, set `ssl_cipher_suite = custom` and `ssl_ciphers`.

CLI Command

- Added a `kong workspace` CLI command. `kong workspace rename OLD_NAME NEW_NAME` renames a workspace (cascading the new name to RBAC role-endpoint permissions), and `kong workspace detect-admin-endpoint-conflicts` lists workspaces whose names collide with admin API URL prefixes.

PDK

- Added a new Metrics PDK (`kong.metrics`) that enables custom plugins to define and record metrics, with initial support integrated into the `opentelemetry` plugin.
- Added the `kong.client.get_principal()` PDK function. It returns the Kong Identity principal authenticated for the current request, similar to `kong.client.get_consumer()`.
- Added the `principal` field to the log serialization output. The field reports the `id` and `display_name` of the authenticated principal for the request.

Clustering

- Added dynamic log levels for hybrid data planes.

Configuration

- Added OAuth 2.0 token-based authentication for Redis connections. Set `cloud_authentication.auth_provider` to `oauth` on any Redis configuration (Rate Limiting Advanced, Proxy Cache Advanced, OpenID Connect, and other Redis-backed plugins) to authenticate using a bearer token from an OAuth 2.0 token endpoint instead of a static password.

Kong Manager

- Migrated all plugin configuration forms to the new FreeForm renderer.

Bugfix

Plugin

- **AI Gateway**:
  - Added Gemini and Vertex mapping for the `googleSearch` tool grounding metadata chunks, which are now mapped into the `annotations` section of the OpenAI-format chat response.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ector index could be spuriously dropped and recreated — emptying it — causing transient empty results
okups. The `FT.INFO` index-compatibility check now reads index attributes by key name instead of by
ged and dropped.

Datakit tracing events so Konnect Debugger can reconstruct the Datakit node graph from captured trace

base plugin plus clones) that ran in one request overwrote each other's active-tracing capture. Each datakit
plugin id, and the capture payload carries the `plugin_name` field. Datakit plugin spans also carry a
lugin name.

se from the third-party service made the plugin return `500`.

uardrail plugins couldn't work properly with Claude Code.

  - Fixed an issue where the ACL plugin returned 403 for authenticated credentials with no consumer and no groups (e.g. ACE / Dev Portal application credentials) when configured with a deny list. A group-less identity cannot match a deny list and should be allowed through.
  - Fixed an issue where the ACL plugin ignored a consumer's ACL groups when `include_consumer_groups` was enabled and the consumer belonged to an enterprise consumer group, causing incorrect `403` denials (with `allow`) or incorrect access (with `deny`) for authenticated and anonymous consumers. The plugin now falls back to the consumer's ACL groups when no third-party authenticated groups are present.

- acme:
  - Fixed an issue where an expired `fail_backoff` key would keep blocking certificate issuance. Retries are now rejected only while the backoff timestamp is still in the future.

- ai-aws-guardrails:
  - Fixed an issue where the plugin ignored the configured `text_source` option when `allow_masking` was enabled, masking the entire raw request body instead.
  - Fixed an issue where the request to the AWS Guardrails service could return a 500 error due to a failure in request signature.

- ai-mcp-oauth2:
  - Fixed a JWT security vulnerability.

- ai-mcp-proxy:
  - Fixed an issue where the ACL decision cache has collision.
  - Fixed an issue where non-managed MCP listeners advertised unsupported SSE streams.
  - Fixed an issue where converted HTTPS MCP tool calls lost the original forwarded port on the internal TLS Unix socket.
  - Fixed an issue where gzip-compressed and malformed MCP request bodies were incorrectly rejected with HTTP 413.

- ai-prompt-guard:
  - Fixed an issue where the plugin failed to inspect requests sent in a provider's native format instead of the OpenAI-compatible format.

- ai-proxy-advanced:
  - Fixed a bug where a response from Anthropic could fail to decode when the client's request advertised Brotli support, since Anthropic's edge may then return a Brotli-encoded body that Kong's response decompression – which only understands gzip – can't inflate. Kong now normalizes the outgoing `Accept-Encoding` request header before proxying to any LLM provider: `gzip, identity` when the client accepts gzip, and `identity` otherwise, so a client that cannot inflate gzip is never handed a compressed body on the paths that pass the upstream response through untouched.
  - Fixed an issue where Gemini and Anthropic token usage metadata was lost in streaming responses.
  - Fixed an issue where modern OpenAI output token limits were discarded or overridden during request normalization.
  - Fixed an issue where some Claude Code MCP tools did not correctly handle empty 'requires' array.
  - Fixed an issue where `cache_creation_input_tokens` and `cache_read_input_tokens` were excluded from prompt token counts, causing undercounting when Anthropic prompt caching was active.
  - Fixed an issue where `stream_options` was forwarded to Databricks upstreams, causing a 400 error since Databricks does not support this field.
  - Fixed an issue where native Anthropic streaming counted provisional `message_start` output tokens and summed cumulative `message_delta` usage.
  - Fixed an issue where cache_control in Bedrock Anthropic format requests using ARN model IDs was lost.
  - Fixed an issue where Bedrock native converseStream requests using ARN model IDs could fail while handling streamed responses.
  - Fixed an issue where the `context-management-2025-06-27` Anthropic beta flag was dropped when routing to a Bedrock target, causing Bedrock to reject requests carrying `context_management` with a `400` error on failover from an Anthropic target.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ed as zero for Bedrock native format request to AWS models like Nova.

cks with omitted text were removed from request history.

uld report zero usage when it targets Bedrock's own model via conversion.

lancer state even when plugin configs were unchanged.

ealtime upstream URLs using `wss` were downgraded to `ws`.

ear unredacted in access logs when using AWS temporary credentials with Bedrock.

sage content arrays.

t as bedrock/gemini system message which only support string.

g. `api-key`, `x-api-key`) leaked the provider credential into access logs instead of being redacted.

uests using the compaction beta was undercounted. Kong now sums `usage.iterations` when present kens / `output_tokens`, which only reflect non-compaction iterations.

in a Gemini provider's `service_account_json` caused crash with SIGSEGV

  - Fixed an issue where adapted Anthropic responses omitted cache and reasoning usage details.
  - Fixed an issue where Claude Sonnet 5 and Opus 5 rejected OpenAI-format reasoning requests on Bedrock due to an unsupported thinking.type value.
  - Fixed an issue where repeated cumulative usage in streaming responses inflated token counts.
  - Fixed an issue where Gemini non-streaming responses that reached `max_tokens` reported a `stop` finish reason instead of `length`.
  - Fixed an issue where a Gemini response with JSON `null` token counts in `usageMetadata` caused an HTTP 500 on non-streaming chat requests and an empty HTTP 200 response on streaming chat requests.
  - Fixed an issue where provider-reported reasoning-token details were not correctly reported.
  - Fixed an issue where xAI reasoning tokens were not folded into completion_tokens, breaking the OpenAI usage identity.
  - Fixed an issue where Gemini's tool-use token usage (billed when server-side tools such as grounding, code execution, or URL context are used) was not counted in the reported token usage or cost.
  - Fixed Azure OpenAI responses support in deployment style.
  - Fixed Gemini image generation token accounting to include reasoning tokens (`thoughtsTokenCount`) in `output_tokens` and report them as `output_tokens_details.reasoning_tokens`. Previously the reasoning tokens were dropped, which under-reported output tokens, analytics, and calculated cost for thinking-enabled image models.
  - Fixed Gemini realtime (Live API) token accounting to include reasoning tokens (`thoughtsTokenCount`) in the reported output tokens, and to report them as `output_tokens_reasoning_tokens_count`. Previously the reasoning tokens were dropped, which under-reported the output and total token counts of thinking-enabled realtime sessions.
  - Fixed multipart video generation requests to OpenAI-compatible providers leaking internal multipart metadata into JSON upstream bodies, which caused the requests to fail.
  - Fixed token usage statistics being silently dropped for `audio/v1/audio/transcriptions` requests. Token-billed OpenAI/Azure transcription models (e.g. `gpt-4o-transcribe`) now report `input_tokens`/`output_tokens`/`total_tokens` and the `text_tokens`/`audio_tokens` breakdown in the analytics log when `logging.log_statistics` is enabled.

- ai-proxy:
  - Fixed an issue where the Azure managed identity token was cached indefinitely and never refreshed, causing requests to fail with 401 after the token expired (roughly one hour).
  - Fixed Gemini token accounting to include reasoning tokens in `completion_tokens` for both OpenAI-format and native-format proxying.
- ai-rag-injector:
  - Fixed an issue where a chunk lookup against an Amazon MemoryDB vector store failed with `unexpected search response: no value found in result set`. The MemoryDB driver now reads the `FT.SEARCH` fields by name instead of by position, treats the vector distance as optional, and requests as many rows as `fetch_chunks_count` asks for.
- ai-rate-limiting-advanced:
  - Fixed an issue where policies using a consumer `custom_id` matcher resolved to consumer username.
- ai-sanitizer:
  - Fixed an issue where the input field for the llm/v1/responses route was not recognized.
  - Fixed an issue where Cohere native chat requests and responses were not extracted, so the plugin now detects and redacts PII in Cohere-format traffic.
  - Fixed an issue where AI Sanitizer returned a 500 status code when the provider was using another model, such as a `claude-*` model served by the `gemini` provider on Vertex AI.
- datakit:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

stale upstream validators and representation metadata.

`nt-Type: application/octet-stream` for `json_to_xml` output. It now defaults to `application/xml`

`dy` without a correct `Content-Type`. It now uses the content type that the source node declares, for `t`, and defaults to `application/octet-stream` in the request phase.

`thm` to the verification key's type in the `jwt_verify` node, so a symmetric algorithm can no longer be `uthentication` bypass where an attacker forges tokens by using the public key as an HMAC shared secret, `ey` string and `allowed_algorithms` is unset (any algorithm accepted).

`request` nodes when the body input is a JSON null. The nodes sent the internal Lua value as the string `dy`. The `service_request` node now keeps the upstream request body.

`UNIMPLEMENTED` status to HTTP 500 instead of 501. The new option `use_standard_grpc_status_codes`

`e` for a repeated integer or enum field failed to transcode, so such values are now correctly mapped to the gRPC request.

- ip-restriction:
  - Fixed an issue where warn log messages did not include the plugin name, making it difficult to identify the source of blocked requests.
- jwt-signer:
  - Fixed an issue where the plugin failed to set the signed access token header on the upstream request, when `access_token_upstream_header` (or `original_access_token_upstream_header`) had the same name as `channel_token_request_header`.
- jwt:
  - Fixed an issue where the plugin failed to decode standard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.
- key-auth:
  - Fixed an issue where an invalid API key was not falling back to the configured anonymous consumer when `principals.error_on_miss` was set to `false`, unlike every other authentication failure.
- mocking:
  - Fixed a memory leak where the plugin config cache did not use weak keys due to a misspelled `__mode` metatable field.
- oas-validation:
  - Added a warning when structured_errors is enabled without verbose_response, as both options must be enabled together.
  - Fixed an issue where readOnly and writeOnly properties in OpenAPI 3.1.x specifications were not correctly validated.
- oauth2-introspection:
  - Fixed an authentication bypass where a revoked or expired token stayed authorized indefinitely instead of being rejected. An authoritative `active:false` result is now also cached briefly (5 seconds).
- opa:
  - Fixed an issue where OPA decision headers could break the WebSocket handshake.
- openid-connect:
  - Fixed an issue where `token_exchange` scope and audience conditions matched only the claims `scope` and `aud`. Support for `scopes_claim`/`audience_claim` is now added to `token_exchange`.
  - Fixed an issue where a request that authenticated but failed an authorization check (such as `scopes_required`) was not attributed to its consumer, consumer groups, or Kong Identity principal in logs and analytics.
  - Fixed an issue where a revoked or inactive token from the introspection endpoint was cached using the default/positive TTL instead of `cache_ttl_neg`, keeping the token marked inactive in the cache longer than configured.
  - Fixed an issue where the `redirect_uri` parameter was sent to the token endpoint for all grant types. It is now included only for the `authorization_code` grant, as required by RFC 6749.
  - Fixed an issue where a token endpoint response with `expires_in <= 0` was cached indefinitely with the proactive expiry re-check disabled, causing the plugin to silently forward an already-expired token to the upstream until a worker/process restart.
  - Fixed an issue where `token_endpoint_auth_method`, custom token headers, and extra token POST args were ignored during token exchange, causing the exchange request to always use `client_secret_basic` regardless of configuration.
  - Fixed an issue where `token_exchange.cache` defaulted to disabled instead of its documented enabled default when omitted.
  - Fixed an issue where a session was not saved on a request that performed a token exchange. A session-restored request now reuses the exchanged identity instead of re-exchanging.
  - Fixed an issue where disabling `verify_signature` gave no warning, even though it also skips signature verification for bearer tokens from clients. The plugin `lse` and `auth_methods` includes `bearer`. It logs a notice instead when `bearer` is not enabled.
    for a different issuer now also warn when they don't set `verify_signature` to `true`.
  - `gle` request (via `client_arg`) failed to use the matching client's JWK.
  - `e` resolved when the groups claim was only available from the user info endpoint, which resulted in a `500`
  - `s` subject token, mixing entries across `grant_type`/`provider`/client, and serving stale results after a plugin `tokens_salt` to scope the cache further.
  - when it is set, because it turns off JWS signature verification for the listed grants.
  - `g` token counts for non-text-generation AI categories (image, video, realtime, and audio transcription `_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `e` categories are logged under.
  - `a` key that conflicts with an existing log field stopped the log handlers of the plugins that run later.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where metrics were rarely (or never) exported on data planes whose configuration is rebuilt more frequently than the metrics `push_interval`. The periodic metrics push timer is no longer cancelled and recreated on every configuration rebuild, so its `push_interval` countdown is preserved.
  - Fixed an issue where OpenTelemetry metrics only supported integer values by adding support for floating-point values in the OTLP exporter.
  - Fixed an issue where the `kong.dp.cluster_cert.expiry` metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series as stale.
  - Reduced per-request overhead of `resource_attributes` by skipping template rendering entirely for static (non-templated) fields.
- prometheus:
  - Fixed `kong_ai_llm_tokens_total` never reporting token counts for non-text-generation AI categories (image, video, realtime, and audio transcription generation), because it only read the legacy `prompt_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `input_tokens`/`input_tokens_details` fields those categories are logged under.
  - A histogram's series (its buckets, `_count` and `_sum`) is now read as one atomic group during a scrape. Previously the exporter yielded and flushed output between individual samples, so an observation landing mid-scrape could bump `_count`/`_sum` after the buckets were already read, producing an internally inconsistent histogram in a single response.
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
  - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.
  - Histograms now expose every bucket (including those with a value of `0`) starting from the first observation of a given label set. Previously only buckets greater than or equal to the observed value were created, so lower buckets appeared lazily on later scrapes.
- proxy-cache-advanced:
  - Fixed an issue where the cache key did not correctly segment by consumer group.
- proxy-cache:
  - Fixed an issue where the cache key did not correctly segment by consumer group.
- request-callout:
  - Fixed an issue where empty `callouts[].request.body.custom` or `upstream.body.custom` maps caused the plugin to send `{}` request bodies.
  - Fixed an issue where a callout that failed and then succeeded on retry still returned the earlier failed response. The plugin now returns the response from the successful retry.
- request-transformer:
  - Fixed a regression where `remove.headers` entries in `header:value` format (e.g. `correlationId:1222`) failed to remove the header. The value part is now correctly ignored during removal, restoring the behavior from 3.11.
- response-transformer-advanced:
  - Fixed an issue where gzipped response handling attempted to change the status during body filtering.
- saml:
  - Fixed an unreachable code path that prevented the plugin from falling back to validating the `samlp:Response`-level signature when the `saml:Assertion` was not individually signed. With `validate_assertion_signature` enabled, an unsigned assertion inside a signed Response is now accepted (and a Response with no valid signature on either the assertion or the root is rejected), so IdPs that sign the Response envelope rather than the assertion no longer require signature validation to be turned off. Relates to the Response-level fallback described in CVE-2026-14917.
  - Fixed CVE-2026-14917 by validating the `samlp:Response` signature whenever an `idp_certificate` is configured – even when `validate_assertion_signature` is disabled – and logging a warning when neither is set, preventing an unauthenticated attacker from impersonating any r configurations that set `validate_assertion_signature` to `false`.

ure Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that s, so a signature can no longer be bound to a different element than the one that provides the identity. A me-document fragment is now rejected.

d for session storage, concurrent authentication requests could result in race condition and session creation

array gets cleared before the asynchronous timer thread can safely encode it.

uardrail, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-**
re AI Gateway guardrail plugins' request extractors did not correctly honor the configured `text_source`

uardrail, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-**
re AI Gateway guardrail plugins failed to extract prompt text from OpenAI-native requests using the

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ai-proxy, **ai-proxy-advanced**: Fixed an issue where Gemini streaming analytics could over-report token usage. Gemini repeats its usage metadata on every stream chunk as a running request-level total, but the counts were summed across chunks instead of replaced, multiplying the reported usage by the number of chunks. Reasoning tokens were affected the most, because Gemini reports them in full on the first chunk and does not change them afterwards. A chunk that carried no usage metadata also reset the recorded output token count to zero.
- ai-proxy and **ai-proxy-advanced**: Fixed a 500 crash on Bedrock Converse requests when a `cachePoint` content block immediately followed a `toolResult` block in the same message.
- ai-semantic-prompt-guard, **ai-semantic-response-guard**, **ai-proxy-advanced**, **ai-semantic-cache**: Fixed vector database indexes and cached embedding records being left behind when a plugin instance was deleted.
- kafka-consume, **confluent-consume**: Fixed an issue where the consumer group subscription declared protocol version 1 but carried the version 0 layout, so a topic-rewriting proxy rejected it.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed the confluent schema registry client caching fetched schemas and subjects under keys that did not account for the registry URL or authentication. Instances configured with different credentials could be served each other's cached lookups, letting an unauthorized instance bypass schema-registry authentication once any authorized instance had warmed the cache. Cache entries are now scoped to the registry identity, and the configured `schema_registry.confluent.ttl` is now applied to these cache entries.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a crash that occurred when a plugin set `schema_registry.confluent.authentication.mode` to `oauth2` but omitted the `oauth2_client` record. Previously this returned a 500 from the Admin API during validation, and once saved it also crashed at runtime while fetching the schema registry OAuth2 token. The absent `oauth2_client` is now handled and falls back to the default authentication method, so a configuration without `oauth2_client` works end-to-end.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.

Core

- Applied upstream nginx security patches for CVE-2026-42533.
- Applied upstream nginx security patches for CVE-2026-56434.
- Applied upstream nginx security patches for CVE-2026-60005.
- Applied upstream nginx security patches for CVE-2026-42055 and CVE-2026-48142.
- **Balancer**: Fixed a race during incremental sync (and admin-API driven updates) under the default `worker_consistency = eventual`. When an upstream and its first target arrived in the same batch, the synchronous target event could run before the deferred balancer creation, log `balancer not found` and drop the target, leaving a window where a live route had no balancer (surfacing as 503 / DNS name errors). The target event now creates the balancer itself when it is missing.
- Fixed Admin API route ambiguity where `/routes/services` could match either `/routes/:name` or `/:workspace_name/services`. Now non workspace-specific routes like `/routes/:name` are prioritized over workspace-specific routes like `/:workspace_name/services`, ensuring correct route matching for Admin API endpoints.
- Fixed an error in balancer target event handling that aborted the balancer rebuild when the worker-local target cache was empty and the event carried a partial target entity.
- Fixed an issue where a failed balancer creation leaked the per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.
- Fixed an issue where a failure in a `dao:*:post` hook during insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.
- Fixed an issue where a healthcheck counter value of 255 crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`, `http_failures`) are now limited to 254.
- Fixed an issue where a request context in the stream TLS proxying path was not returned to the internal context pool, which could reduce the pool's efficiency under sustained TLS stream traffic.
- Fixed an issue where an in-flight request that completed after its upstream target became unavailable could restore the target to the latency balancer and route

diately with `no_wait = true` when node level mutex is being held by another worker.

d_lua set to `sandbox` could no longer create global variables or modify allowed library tables.

re still sandboxed when `untrusted_lua` was set to `on`, so schema code that needed to opt out of y respected `on`) was incorrectly rejected on both the control plane and the data plane.

) leaked into the downstream phases (`header_filter`, `body_filter`, `response`, `log`). Dynamic ordering phases execute in static plugin-priority order.

errors could be reported as subsequent socket write failures.

osing a WebSocket connection.

n preread phase when the upstream could not be resolved, due to calling an HTTP-only API in the L4

ored the gateway's `db_cache_ttl` and `db_cache_neg_ttl` settings. The gateway now uses the lower of the ed TTL. If neither side provides a usable TTL, the gateway falls back to a bounded internal default instead

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where Kong skipped the WebSocket `ws_close` phase when it could not proxy the request.
- Fixed an issue where memory tracing didn't generate any events.
- Fixed an issue where response buffering was forced on routes with a plugin that has a response handler, breaking streaming responses even when the plugin did not read the response. Response buffering is now decided after the access phase, so plugins can no longer read the final value of `ngx.ctx.buffered_proxying` in `access` phase.
- Fixed an issue where `/status/ready` could report a data plane ready before the new router and plugins iterator became active. Kong now reports readiness only after plugin configuration completes and the live objects are installed.
- Fixed an issue where streamed custom plugins were not recognized when configured in the `ordering` field of `plugins` on Data Planes.
- Fixed an issue where the error wrapper was not being freed after sandboxed template rendering in plugins such as `request-transformer` and `response-transformer`.
- Fixed an issue where the priority field of a cloned plugin could not be updated while it was still referenced by plugin instances.
- Fixed an issue where upstream failover could return intermittent 503 responses while a failover target remained healthy.
- Hardened HashiCorp Vault cloud authentication (AWS, Azure, GCP): Kong keeps credentials out of internal cache keys, truncates Vault error responses in logs, sets timeouts on all authentication requests, and applies `ssl_verify` to every outbound TLS call.
- **Keyring**: Fixed a Lua error in the keyring cluster strategy's `request_missing_keys` timer callback that crashed (`attempt to index a nil value`) when the database became unavailable, because the `keyring_meta:each()` iterator yields a nil row alongside the error. The error is now logged and the row skipped.
- **Konnect Only**. **Debugger**: Added new debugger span attributes `tls.client.server_name`, `proxy.kong.upstream.address`, `proxy.kong.request.host`, `http.request.header.connection`, `proxy.kong.client.connection.request_count`. Removed debugger span attributes `proxy.kong.upstream.host`, `proxy.kong.upstream.addr`, `http.request.header.host`, `proxy.kong.client.keepalive`
- **Konnect Only**. **Debugger**: Fixed an error that could occur under sustained HTTPS traffic.
- **Konnect Only**. **Debugger**: Fixed an issue where a plugin that ended the request early with `kong.response.exit` during the response phase (for example a Datakit exit node) left the response phase span and its plugin spans unfinished in the exported trace.
- **Konnect Only**. **Debugger**: Fixed an issue where instrumenting third-party HTTP client calls produced two indistinguishable `kong.io.http.request` spans for `httpc:request_uri()`. It is now traced under a dedicated `kong.io.http.request_uri` span, and the `connect`, DNS, and internal `request` spans it triggers are nested beneath it. The `kong.io.http.request` span now also reports the `http.url` attribute.
- **Konnect Only**. **Debugger**: Fixed an issue where deep copy of the worker logs stack overflowed by replacing `deep_copy` with `cycle_aware_deep_copy`.
- **Konnect Only**. **Debugger**: Fixed an issue where the response body of the external HTTP call `httpc:request()` was not captured.
  - Added a new span `kong.io.http.read_resp_body` to instrument to the `ready_body()` and `body_reader()` functions to capture the response body.
  - Added a `kong.3p.external_request_id` span attribute to the new `kong.io.http.read_resp_body` span and the `kong.io.http.request` span.
  - Added span linkage from the `kong.io.http.read_resp_body` span to the associated `kong.io.http.request` span.
  - Added an `external_request_id` attribute to the captured request/response headers/body items.
  - Skipped body capture upon low-level reading errors (e.g. network errors, timeouts, etc.) to avoid capturing corrupted data.
  - Improved external I/O latency measurement by removing the creation time of spans.
  - Moved capturing of request headers/body and response headers from `kong.io.http.request_uri` span to the `kong.io.http.request` span.
- **Konnect Only**. Fixed an issue where a failed Kong Identity principal lookup was cached for up to 15 minutes. It now uses the feature's shorter default TTL instead.
- On shell-free (distroless) images, the pluginserver query and start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with a clear error on an unterminated quote or `${`, instead of passing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.
- **PostgreSQL OAuth auth**: Refined the token cache key to be derived only from the fields that identify an OAuth configuration.
- **PostgreSQL OAuth auth**: The OAuth discovery/token requests issued during the `init` phase now trust the CAs configured via `lua_ssl_trusted_certificate`. Previously this init-phase path used LuaSocket/LuaSec, which only honors the OS trust store, so an HTTPS identity provider using a private CA failed TLS verification during `kong start` even when its CA was configured.

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

in DP could prevent a recovery connection with CP.

ng-running calls: a data plane now cancels a timed-out RPC so a late response cannot disrupt later calls, lls are still in flight instead of being dropped as a missed heartbeat.

empty stat object instead of null before the first sync has run, keeping the response shape consistent.

oes not support a datakit configuration, the control plane now removes only the incompatible datakit plugin s the Konnect control plane version-compatibility behavior.

LS certificate setup failures instead of loading their backup configuration.

ull sync from resuming.

an entity referenced a non-exported entity, for example rbac_users.

erged non-adjacent deltas of the same entity, which could drop an entity's earlier create and keep only a ced it (e.g. a plugin instance referencing a cloned plugin by name) and causing validation to fail with essive deltas of the same entity, preserving the causal order the data plane relies on.

- Fixed an issue where pushing a configuration with a datakit plugin whose node `inputs` contained a null value to an older data plane could crash the control plane's config compatibility checker with "attempt to index local 'value' (a userdata value)".
- Fixed an issue where self-managed control planes rejected updates to a streamed plugin's handler while the plugin was referenced by a plugin instance.
- Fixed an issue where the control plane could crash while handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as a ping/pong control frame) arrived before the `basic_info` frame. The control plane now drains and responds to control frames during the handshake until the expected frame is received, instead of dereferencing a nil plugin list.
- Fixed an issue where updates to a streamed plugin's definition (e.g. `handler`), or to a cloned plugin's definition (e.g. `priority`), were not applied on data planes when no referencing plugin instances changed. The data plane now rebuilds its plugins iterator so the updated definition takes effect, instead of continuing to execute the previous version.
- Fixed an issue where, with plugin streaming enabled, a single incremental sync validation failure would wipe out all plugin subschemas because the currently loaded plugins were not correctly excluded from the subschema unload.

PDK

- Fixed a race condition issue where the `tries` field of log serialization was not copied, causing data mutations when logs were generated concurrently via async timers.
- Fixed an issue on HTTP/2 connections where the request method and query were reported incorrectly, or could raise an error, when a request hit the error handler such as a 502 from an upstream connection reset.
- Fixed an issue where dynamic upstream TLS settings set via the PDK were lost during buffered proxying.
- Fixed an issue where `kong.response.set_header()` and `kong.response.clear_header()` could not replace or clear upstream `WWW-Authenticate` headers.
- Fixed an issue where the HTTP-to-gRPC status mappings for 400, 404, 429, 502, and 504 were incorrect. The new configuration option `use_standard_grpc_status_codes` (default `off`) enables the fix.

Admin API

- Fixed an issue where resetting the password of an admin or developer failed with "Old password is invalid" when the credential was created before the basic-auth hashing algorithm was upgraded from SHA1 to SHA256 (e.g. a `kong_admin` user created in an older version and carried over through an upgrade). The old password is now verified with the backward-compatible verification logic that supports both SHA1 and SHA256 hashed passwords.
- Fixed an issue where the Admin API returned HTTP 500 for HTTP/2 POST, PUT, and PATCH requests that omitted both Content-Type and Content-Length.
- Fixed an issue where the keyring Admin API endpoints could return an internal server error instead of a clear 400 response when given malformed or missing parameters.

CLI Command

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Configuration

- Increased the default `proxy_ssl_verify_depth` and `lua_ssl_verify_depth` from `1` to `5`.

Dependency

Default

- Added RHEL 10 (el10) to build.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

nstalled to `/usr/local/kong/lib`) so the Kafka plugins' `lz4` codec no longer depends on the base image

C

0-3 artifacts. The FIPS-140-2 artifacts keep the provider 3.0.9.

and image.

es SCRAM channel binding failing to connect to a PostgreSQL server whose certificate is signed with

- Bumped kong-redis-cluster from 1.6.0 to 1.6.1. This accepts the `x.y` Redis version format reported by some managed services (e.g. AWS ElastiCache Serverless Valkey) by making the patch component optional, and only warns on Redis version `9.0` or newer instead of `8.0` or newer.
- Bumped libexpat to 2.8.4.
- Bumped libxml2 to 2.15.4.
- Bumped lua-kong-nginx-module from 0.20.0 to 0.21.0.
- Bumped lua-resty-cel from 0.2.0 to 0.5.0.
- Bumped lua-resty-lmdb from 1.6.1 to 1.6.2 (includes LMDB library bump from 0.9.33 to 0.9.35).
- Bumped lua-resty-openssl to 1.9.0.
- Bumped lua-resty-simdjson from 1.2.0 to 1.3.0 (updates simdjson from 3.12.0 to 4.6.4).
- Bumped msgpack-c to 7.0.2.
- Bumped OpenSSL from 3.5.7 to 3.5.8.
- Bumped PCRE2 to 10.48.
- Bumped Solace from 0.1.0 to 0.2.0 (updates Solace client from 7.33.0.3 to 7.33.2.3).
- Now uses `cel-cpp` `0.15.0` instead of `cel-rust` `0.11.6` for Common Expression Language backend.
- Removed the legacy libpcre3 package dependency from Kong Gateway .deb packages since Kong Gateway already bundles PCRE2.
- Removed the legacy pcre package dependency from Kong Gateway .rpm packages since Kong gateway already bundles PCRE2 and RHEL 10 no longer ships legacy PCRE package.

Performance

Clustering

- **Clustering**: Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.
- **Clustering**: Improved DP performance when applying a large incremental config update.
- Improved the configuration synchronization latency when incremental sync enabled under some circumstances.
- Optimized performance of clustering payload handling for version compatibility. This reduces CPU usage and transient memory pressure.

Core

- **Core**: Reduced config update latency on hybrid data planes by notifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in parallel.
- Improved router update performance during incremental sync by updating service data in place instead of triggering a full router rebuild when only service attributes change.
- Improved schema performance through miscellaneous tweaks.
- Improved the performance of dynamic plugin ordering. When a workspace's `ordering` rules do not depend on the request – for example, when they are declared only on global plugins – Kong Gateway now computes the plugin order once and reuses it for later requests, instead of recomputing it on every request. Workspaces with route-, service-, or consumer-scoped `ordering` rules keep computing the order per request, because that order can depend on the request. This change does not affect plugin execution order.

retrieved from a pool. This prevents unnecessary table rehashes.

g Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

A

unter=true. Entity counts for the whole page are now retrieved with one grouped query per entity type
space, while keeping the counts exact.

P

ssary hash computation. Enabling the plugin now adds much less latency and CPU overhead to requests.

deferring OTLP payload conversion to export time.

d asynchronous Kafka producer, opt-in via the new `new_kafka_async_producer` config option (default false). When enabled, it batches and sends messages more efficiently under high load. Messages without a key are packed into larger per-partition batches; because

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Kafka does not guarantee ordering across partitions, their relative order may change. Set a message key if ordering matters — keyed messages are unaffected. The legacy producer remains the default.

3.15.0.6

Release date 2026/09/16

Bugfix

Plugin

- **ai-guardrails**:
  - Fixed an issue where a JSON `null` field in a response from the third-party service made the plugin return `500`.
- ai-aws-guardrails:
  - Fixed a issue where the request to the AWS Guardrails service could return a 500 error due to a failure in request signing.
- ai-mcp-proxy:
  - Fixed an issue where converted HTTPS MCP tool calls lost the original forwarded port on the internal TLS Unix socket.
  - Fixed an issue where gzip-compressed and malformed MCP request bodies were incorrectly rejected with HTTP 413.
- ai-proxy-advanced:
  - Fixed an issue where a Gemini response with JSON `null` token counts in `usageMetadata` caused an HTTP 500 on non-streaming chat requests and an empty HTTP 200 response on streaming chat requests.
  - Fixed an issue where provider-reported reasoning-token details were not correctly reported.
  - Fixed an issue where xAI reasoning tokens were not folded when visible completion tokens exceeded reasoning tokens.
  - Fixed an issue where xAI reasoning tokens were not folded into `completion_tokens`, breaking the OpenAI usage identity.
  - Fixed an issue where Gemini and Anthropic token usage metadata was lost in streaming responses.
  - Fixed an issue where modern OpenAI output token limits were discarded or overridden during request normalization.
  - Fixed an issue where Bedrock native converseStream requests using ARN model IDs could fail while handling streamed responses.
  - Fixed an issue where full-sync reconfigure reset balancer state even when plugin configs were unchanged.
  - Fixed an issue where an OpenAI content array was sent as a Bedrock/Gemini system message, which only supports strings.
  - Fixed an issue where a malformed RSA private key in a Gemini provider's `service_account_json` caused a crash with SIGSEGV.
  - Fixed an issue where adapted Anthropic responses omitted cache and reasoning usage details.
  - Fixed an issue where Claude Sonnet 5 and Opus 5 rejected OpenAI-format reasoning requests on Bedrock due to an unsupported `thinking.type` value.
  - Fixed an issue where repeated cumulative usage in streaming responses inflated token counts.
  - Fixed an issue where Gemini non-streaming responses that reached `max_tokens` reported a `stop` finish reason instead of `length`.
  - Fixed an issue where `cache_control` in Bedrock Anthropic format requests using ARN model IDs was lost.
  - Fixed multipart video generation requests to OpenAI-compatible providers leaking internal multipart metadata into JSON upstream bodies, which caused the requests to fail.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

azon MemoryDB vector store failed with `unexpected search response: no value found in result`
RCH fields by name instead of by position, treats the vector distance as optional, and requests as many rows

tom_id matcher resolved to the consumer username instead.

atus code when the provider was using another model, such as a `claude-*` model served by the `gemini`

nd responses were not extracted, so the plugin now detects and redacts PII in Cohere-format traffic.

alling back to the configured anonymous consumer when `principals.error_on_miss` was set to `false`,

- datakit:
  - Fixed an issue where the `exit` node sent a string body without a correct `Content-Type`. It now uses the content type that the source node declares, for example `application/xml` for `json_to_xml` output, and defaults to `application/octet-stream` in the request phase.
  - Fixed the body handling of the `exit` and `service_request` nodes when the body input is a JSON null. The nodes sent the internal Lua value as the string `"userdata: NULL"`. The `exit` node now sends no body, and the `service_request` node now keeps the upstream request body.
- jwt:
  - Fixed an issue where the plugin failed to decode standard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.
- key-auth:
  - Fixed an issue where an invalid API key was not falling back to the configured anonymous consumer when `principals.error_on_miss` was set to `false`, unlike every other authentication failure.
- oas-validation:
  - Added a warning when `structured_errors` is enabled without `verbose_response`, as both options must be enabled together.
  - Fixed an issue where `readOnly` and `writeOnly` properties in OpenAPI 3.1.x specifications were not correctly validated.
  - Fixed an issue where OpenAPI 3.1.x parameter patterns using ECMA-262 `\uXXXX` Unicode escapes failed to match correctly, because PCRE does not support that escape syntax.
- openid-connect:
  - Fixed an issue where disabling `verify_signature` gave no warning, even though it also skips signature verification for bearer tokens from clients. The plugin now logs a warning when `verify_signature` is `false` and `auth_methods` includes `bearer`. It logs a notice instead when `bearer` is not enabled. `token_exchange.subject_token_issuers` entries for a different issuer now also warn when they don't set `verify_signature` to `true`.
- opentelemetry:
  - Fixed an issue where a `custom_attributes_by_lua` key that conflicts with an existing log field stopped the log handlers of the plugins that run later.
  - Fixed an issue where metrics were rarely (or never) exported on data planes whose configuration is rebuilt more frequently than the metrics `push_interval`. The periodic metrics push timer is no longer cancelled and recreated on every configuration rebuild, so its `push_interval` countdown is preserved.
- request-callout:
  - Fixed an issue where a callout that failed and then succeeded on retry still returned the earlier failed response. The plugin now returns the response from the successful retry.
- ai-proxy and **ai-proxy-advanced**: Fixed a 500 crash on Bedrock Converse requests when a `cachePoint` content block immediately followed a `toolResult` block in the same message.
- ai-semantic-prompt-guard, **ai-semantic-response-guard**, **ai-proxy-advanced**, **ai-semantic-cache**: Fixed vector database indexes and cached embedding records being left behind when a plugin instance was deleted.
- kafka-consume, **confluent-consume**: Fixed an issue where the consumer group subscription declared protocol version 1 but carried the version 0 layout, so a topic-rewriting proxy rejected it.

Clustering

- **datakit**: When a data plane older than the control plane does not support a Datakit configuration, the control plane now removes only the incompatible Datakit plugin instead of rejecting the whole configuration. This matches the Konnect control plane version-compatibility behavior.

Core

- Fixed an issue where Kong Identity principal caching ignored the gateway's `db_cache_ttl` and `db_cache_neg_ttl` settings. The gateway now uses the lower of the ed TTL. If neither side provides a usable TTL, the gateway falls back to a bounded internal default instead

ose phase when it could not proxy the request.

ributes `tls.client.server_name`, `proxy.kong.upstream.address`, `proxy.kong.request.host`, t.connection.request_count`. Removed debugger span attributes `proxy.kong.upstream.host`, st`, `proxy.kong.client.keepalive`.

ity principal lookup was cached for up to 15 minutes. It now uses the feature's shorter default TTL instead.

P

`kong.response.clear_header()` could not replace or clear upstream `WWW-Authenticate` headers.

D

C

- Bumped avro-c to 1.12.2.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped jansson to 2.15.1.
- Bumped libexpat to 2.8.4.
- Bumped libxml2 to 2.15.4.
- Bumped lua-resty-openssl to 1.9.0.
- Bumped msgpack-c to 7.0.2.
- Bumped OpenSSL from 3.5.7 to 3.5.8.
- Bumped PCRE2 to 10.48.

Performance

Clustering

- **Clustering**: Improved DP performance when applying a large incremental config update.
- Improved configuration synchronization latency in some cases when incremental sync is enabled.

Core

- Improved performance when `untrusted_lua` is set to `sandbox`. Previously, Kong rebuilt the Lua environment, including a module reload, on every compile of a sandboxed function.

Plugin

- oas-validation:
  - Improved plugin performance by removing unnecessary hash computation. Enabling the plugin now adds much less latency and CPU overhead to requests.

3.15.0.5

Release date 2026/08/24

Feature

CLI Command

- Added a `kong workspace` CLI command. `kong workspace rename OLD_NAME NEW_NAME` renames a workspace (cascading the new name to RBAC role-endpoint permissions), and `kong workspace detect-admin-endpoint-conflicts` lists workspaces whose names collide with admin API URL prefixes.

Bugfix

Plugin

- datakit:
  - Fixed an issue where the `response` node set `Content-Type: application/octet-stream` for `json_to_xml` output. It now defaults to `application/xml` when no explicit `Content-Type` is provided.
- grpc-gateway:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where the `redirect_uri` parameter was sent to the token endpoint for all grant types. It is now included only for the `authorization_code` grant, as required by RFC 6749.
  - The `ignore_signature` option now logs a warning when it is set, because it turns off JWS signature verification for the listed grants.
- opentelemetry:
  - Fixed an issue where the `kong.dp.cluster_cert.expiry` metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series as stale.
  - Reduced per-request overhead of `resource_attributes` by skipping template rendering entirely for static (non-templated) fields.
- prometheus:
  - A histogram's series (its buckets, `_count` and `_sum`) is now read as one atomic group during a scrape. Previously the exporter yielded and flushed output between individual samples, so an observation landing mid-scrape could bump `_count`/`_sum` after the buckets were already read, producing an internally inconsistent histogram in a single response.
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
  - Histograms now expose every bucket (including those with a value of `0`) starting from the first observation of a given label set. Previously only buckets greater than or equal to the observed value were created, so lower buckets appeared lazily on later scrapes.
- saml:
  - Hardened signature validation against XML Signature Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that names the `ID` of the element it digests and consumes, so a signature can no longer be bound to a different element than the one that provides the identity. A response whose reference URI is empty or not a same-document fragment is now rejected.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed the confluent schema registry client caching fetched schemas and subjects under keys that did not account for the registry URL or authentication. Instances configured with different credentials could be served each other's cached lookups, letting an unauthorized instance bypass schema-registry authentication once any authorized instance had warmed the cache. Cache entries are now scoped to the registry identity, and the configured `schema_registry.confluent.ttl` is now applied to these cache entries.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a crash that occurred when a plugin set `schema_registry.confluent.authentication.mode` to `oauth2` but omitted the `oauth2_client` record. Previously this returned a 500 from the Admin API during validation, and once saved it also crashed at runtime while fetching the schema registry OAuth2 token. The absent `oauth2_client` is now handled and falls back to the default authentication method, so a configuration without `oauth2_client` works end-to-end.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed an issue where OAuth2 authentication against Confluent Cloud Schema Registry failed because the client did not send the required `target-sr-cluster` header.

PDK

- Fixed an issue on HTTP/2 connections where the request method and query were reported incorrectly, or could raise an error, when a request hit the error handler such as a 502 from an upstream connection reset.
- Fixed an issue where the HTTP-to-gRPC status mappings for 400, 404, 429, 502, and 504 were incorrect. The new configuration option `use_standard_grpc_status_codes` (default `off`) enables the fix.

Core

- Fixed an issue where a failed balancer creation leaked the per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`,

fter its upstream target became unavailable could restore the target to the latency balancer and route

d_lua` set to `sandbox` could no longer create global variables or modify allowed library tables.

re still sandboxed when `untrusted_lua` was set to `on`, so schema code that needed to opt out of y respected `on`) was incorrectly rejected on both the control plane and the data plane.

itions forwarded the enclosing schema as a second argument. This changed the call signature and could eter. The single-argument call signature is restored.

plane ready before the new router and plugins iterator became active. Kong now reports readiness only are installed.

could not be updated while it was still referenced by plugin instances.

mittent 503 responses while a failover target remained healthy.

zure, GCP): Kong keeps credentials out of internal cache keys, truncates Vault error responses in logs, sets timeouts on all authentication requests, and applies `ssl_verify` to every outbound TLS call.

- **Konnect Only**. **Debugger**: Fixed an issue where deep copy of the worker logs stack overflowed by replacing `deep_copy` with `cycle_aware_deep_copy`.
- **PostgreSQL OAuth auth**: Refined the token cache key to be derived only from the fields that identify an OAuth configuration.

Clustering

- Fixed an issue where heavy packet loss could prevent the full sync from resuming.
- Fixed an issue where incremental config sync failed when an entity referenced a non-exported entity, for example rbac_users.
- Fixed an issue where incremental sync delta coalescing merged non-adjacent deltas of the same entity, which could drop an entity's earlier create and keep only a later update, reordering it after a delta that already referenced it (e.g. a plugin instance referencing a cloned plugin by name) and causing validation to fail with "plugin '' not enabled". Coalescing now only merges successive deltas of the same entity, preserving the causal order the data plane relies on.
- Fixed an issue where self-managed control planes rejected updates to a streamed plugin's handler while the plugin was referenced by a plugin instance.
- Fixed an issue where the control plane could crash while handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as a ping/pong control frame) arrived before the `basic_info` frame. The control plane now drains and responds to control frames during the handshake until the expected frame is received, instead of dereferencing a nil plugin list.
- Fixed an issue where updates to a streamed plugin's definition (e.g. `handler`), or to a cloned plugin's definition (e.g. `priority`), were not applied on data planes when no referencing plugin instances changed. The data plane now rebuilds its plugins iterator so the updated definition takes effect, instead of continuing to execute the previous version.
- Fixed an issue where, with plugin streaming enabled, a single incremental sync validation failure would wipe out all plugin subschemas because the currently loaded plugins were not correctly excluded from the subschema unload.

Kong Manager

- Fixed an issue where the Export button on the Vitals Reports page did not download the report CSV.

Dependency

Core

- Bumped kong-pgmoon from 2.3.4.0 to 2.3.5.0, which fixes SCRAM channel binding failing to connect to a PostgreSQL server whose certificate is signed with SHA-512.

Performance

Clustering

- Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.
- Optimized performance of clustering payload handling for version compatibility. This reduces CPU usage and transient memory pressure.

Admin API

- Improved the performance of listing workspaces with `?counter=true`. Entity counts for the whole page are now retrieved with one grouped query per entity type instead of a separate count query per entity type per workspace, while keeping the counts exact.

Plugin

- opentelemetry:

deferring OTLP payload conversion to export time.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

otifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in

o `model.options` so cached and cache-write prompt tokens can be priced per 1M tokens, alongside `input_cost` / `output_cost`.

  - Added filtering for empty Anthropic thinking blocks in request history.
  - Added support for reporting prompt cache token metrics in OpenAI-compatible format.
  - Added support for reporting prompt cache token metrics when using native (non-OpenAI) request/response formats.
  - Usage cost now supports per-cache-TTL cache-write pricing, context-window pricing factors, and service-tier pricing factors via `model.options` (`cache_write_cost_list`, `context_window_factor`, `service_tier_factor`). Anthropic (cache TTL + service tier), OpenAI, and Gemini service tiers are collected from upstream responses.
- ai-aws-guardrails, **ai-azure-content-safety**: Added `last_message` as a new optional value for `config.text_source`.

Bugfix

Plugin

- **ai guardrail plugins**:
  - Fixed issues where the ai-sanitizer plugin and ai-aws-guardrail plugin could not work properly with Claude code.
- ai-aws-guardrails:
  - Fixed an issue where the plugin ignored the configured `text_source` option when `allow_masking` was enabled, masking the entire raw request body instead.
- ai-prompt-guard:
  - Fixed an issue where the plugin failed to inspect requests sent in a provider's native format instead of the OpenAI-compatible format.
- ai-proxy-advanced:
  - Fixed a bug where a response from Anthropic could fail to decode when the client's request advertised Brotli support, since Anthropic's edge may then return a Brotli-encoded body that Kong's response decompression – which only understands gzip – can't inflate. Kong now normalizes the outgoing `Accept-Encoding` request header before proxying to any LLM provider: `gzip, identity` when the client accepts gzip, and `identity` otherwise, so a client that cannot inflate gzip is never handed a compressed body on the paths that pass the upstream response through untouched.
  - Fixed an issue where token usage for Anthropic requests using the compaction beta was undercounted. Kong now sums `usage.iterations` when present instead of relying solely on the top-level `input_tokens` / `output_tokens`, which only reflect non-compaction iterations.
  - Fixed an issue where Gemini's tool-use token usage (billed when server-side tools such as grounding, code execution, or URL context are used) was not counted in the reported token usage or cost.
  - Fixed an issue where signed Anthropic thinking blocks with omitted text were removed from request history.
  - Fixed an issue where `cache_creation_input_tokens` and `cache_read_input_tokens` were excluded from prompt token counts, causing undercounting when Anthropic prompt caching was active.
  - Fixed an issue where native Anthropic streaming counted provisional `message_start` output tokens and summed cumulative `message_delta` usage.
  - Fixed an issue where the `context-management-2025-06-27` Anthropic beta flag was dropped when routing to a Bedrock target, causing Bedrock to reject requests carrying `context_management` with a `400` error on failover from an Anthropic target.
  - Fixed an issue where output token usage was reported as zero for Bedrock native format request to AWS models like Nova.
  - Fixed an issue where Anthropic-format requests could report zero usage when it targets Bedrock's own model via conversion.
  - Fixed an issue where OpenAI, Azure, and Gemini realtime upstream URLs using `wss` were downgraded to `ws`.
  - Fixed an issue where a credential header could appear unredacted in access logs when using AWS temporary credentials with Bedrock.
  - Fixed an issue where Ollama rejected OpenAI message content arrays.

s did not correctly handle empty 'requires' array.

o include reasoning tokens (`thoughtsTokenCount`) in `output_tokens` and report them as viously the reasoning tokens were dropped, which under-reported output tokens, analytics, and calculated

g to include reasoning tokens (`thoughtsTokenCount`) in the reported output tokens, and to report them as busly the reasoning tokens were dropped, which under-reported the output and total token counts of

for `audio/v1/audio/transcriptions` requests. Token-billed OpenAI/Azure transcription models (e.g. tput_tokens/total_tokens and the `text_tokens`/`audio_tokens` breakdown in the analytics log when

g tokens in `completion_tokens` for both OpenAI-format and native-format proxying.

esponses route was not recognized.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- opentelemetry:

    - Fixed `gen_ai.client.token.usage` never reporting token counts for non-text-generation AI categories (image, video, realtime, and audio transcription generation), because it only read the legacy `prompt_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `input_tokens`/`input_tokens_details` fields those categories are logged under.

- prometheus:
    - Fixed `kong_ai_llm_tokens_total` never reporting token counts for non-text-generation AI categories (image, video, realtime, and audio transcription generation), because it only read the legacy `prompt_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `input_tokens`/`input_tokens_details` fields those categories are logged under.
- ai-aws-guardrails, **ai-azure-content-safety**, **ai-custom-guardrail**, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-guard**, **ai-semantic-response-guard**: Fixed an issue where AI Gateway guardrail plugins' request extractors did not correctly honor the configured `text_source` option.
- ai-aws-guardrails, **ai-azure-content-safety**, **ai-custom-guardrail**, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-guard**, **ai-semantic-response-guard**: Fixed an issue where AI Gateway guardrail plugins failed to extract prompt text from OpenAI-native requests using the `input_text` content type.
- ai-proxy, **ai-proxy-advanced**: Fixed an issue where Gemini streaming analytics could over-report token usage. Gemini repeats its usage metadata on every stream chunk as a running request-level total, but the counts were summed across chunks instead of replaced, multiplying the reported usage by the number of chunks. Reasoning tokens were affected the most, because Gemini reports them in full on the first chunk and does not change them afterwards. A chunk that carried no usage metadata also reset the recorded output token count to zero.

CLI Command

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Core

- On shell-free (distroless) images, the pluginserver query and start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with a clear error on an unterminated quote or `${`, instead of passing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.

3.15.0.3

Release date 2026/08/10

Bugfix

Plugin

- ai-mcp-oauth2:
    - Fixed a JWT security vulnerability.
- datakit:
    - Security: Fixed CVE-2026-14916 by binding the JWT algorithm to the verification key's type in the `jwt_verify` node. This means that a symmetric algorithm can no longer be verified against an asymmetric key, preventing an authentication bypass where an attacker forges tokens by using the public key as an HMAC shared secret, under configurations where the node uses a PEM key string and `allowed_algorithms` is unset (any algorithm accepted).
- saml:
    - Security: Fixed CVE-2026-14917 in the SAML plugin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly, and logging a warning if misconfigured. This prevents a crafted unsigned SAML response from silently bypassing authentication when `validate_assertion_signature` is set to false.

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

2533.

6434.

0005.

2055 and CVE-2026-48142.

D

C

3

R

Bugfix

Plugin

- **Konnect Only**. **datakit**:
  - Added node source and runtime phase metadata to Datakit tracing events so Konnect Debugger can reconstruct the Datakit node graph from captured trace data.
- **otel**:
  - Fixed an issue where OpenTelemetry metrics only supported integer values by adding support for floating-point values in the OTLP exporter.
- ai-proxy:
  - Fixed OpenAI-compatible completions requests with string array prompts.
- ip-restriction:
  - Fixed an issue where warn log messages did not include the plugin name, making it difficult to identify the source of blocked requests.
- prometheus:
  - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.

Clustering

- **Clustering**: The `/status/sync` endpoint now returns an empty stat object instead of null before the first sync has run, keeping the response shape consistent.

PDK

- Fixed a race condition issue where the `tries` field of log serialization was not copied, causing data mutations when logs were generated concurrently via async timers.

Core

- Fixed an issue where dynamic plugin ordering (`ordering`) leaked into the downstream phases (`header_filter`, `body_filter`, `response`, `log`). Dynamic ordering now again applies only to the `access` phase; downstream phases execute in static plugin-priority order.
- Fixed an issue where memory tracing didn't generate any events.
- Fixed an issue where streamed custom plugins were not recognized when configured in the `ordering` field of `plugins` on Data Planes.
- **Konnect Only**. **Debugger**: Fixed an error that could occur under sustained HTTPS traffic.
- **Konnect Only**. **Debugger**: Fixed an issue where the response body of the external HTTP call `httpc:request()` was not captured. This includes the following changes: - Added a new span `kong.io.http.read_resp_body` to instrument to the `ready_body()` and `body_reader()` functions to capture the response body. - Added a `kong.3p.external_request_id` span attribute to the new `kong.io.http.read_resp_body` span and the `kong.io.http.request` span. - Added span linkage from the `kong.io.http.read_resp_body` span to the associated `kong.io.http.request` span. - Added an `external_request_id` attribute to the captured request/response headers/body items. - Skipped body capture upon low-level reading errors (e.g. network errors, timeouts, etc.) to avoid capturing corrupted data. - Improved external I/O latency measurement by removing the creation time of spans. - Moved capturing of request headers, body, and response headers from `kong.io.http.request_uri` span to the `kong.io.http.request` span.
- **Konnect Only**. **Debugger**: Fixed an issue where instrumenting third-party HTTP client calls produced two indistinguishable `kong.io.http.request` spans for `httpc:request_uri()`. It is now traced under a dedicated `kong.io.http.request_uri` span, and the `connect`, DNS, and internal `request` spans it triggers are nested beneath it. The `kong.io.http.request` span now also reports the `http.url` attribute.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

pts the `x.y` Redis version format reported by some managed services (e.g. AWS ElastiCache Serverless
ly warns on Redis version `9.0` or newer instead of `8.0` or newer.

sync by updating service data in place instead of triggering a full router rebuild when only service attributes

g Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

Release date 2026/07/07

Bugfix

Plugin

- acl:
  - Fixed an issue where the ACL plugin returned a 403 error for authenticated credentials with no consumer and no groups (e.g. ACE / Dev Portal application credentials) when configured with a deny list. A group-less identity cannot match a deny list and should be allowed through.
  - Fixed an issue where the ACL plugin ignored a consumer's ACL groups when `include_consumer_groups` was enabled and the consumer belonged to an enterprise consumer group, causing incorrect 403 denials (with `allow`) or incorrect access (with `deny`) for authenticated and anonymous consumers. The plugin now falls back to the consumer's ACL groups when no third-party authenticated groups are present.
- openid-connect:
  - Fixed an issue where a token endpoint response with `expires_in <= 0` was cached indefinitely with the proactive expiry re-check disabled, causing the plugin to silently forward an already-expired token to the upstream until a worker/process restart.
  - Fixed an issue where switching clients within a single request (via `client_arg`) failed to use the matching client's JWK.
  - Fixed an issue where consumer groups could not be resolved when the groups claim was only available from the user info endpoint, which resulted in a `500` error.
- request-transformer:
  - Fixed a regression where `remove.headers` entries in `header:value` format (e.g. `correlationId:1222`) failed to remove the header. The value part is now correctly ignored during removal, restoring the behavior from 3.11.
- tcp-log:
  - Fixed the race condition where the balancer `tries` array was cleared before the asynchronous timer thread could safely encode it.

Core

- Fixed an issue where a failure in a `dao:*:post` hook during insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.
- Fixed an issue where immediate cosocket SSL handshake errors could be reported as subsequent socket write failures.
- Fixed an issue where the error wrapper was not being freed after sandboxed template rendering in plugins such as `request-transformer` and `response-transformer`.

Clustering

- Fixed an issue where data planes retried unrecoverable TLS certificate setup failures instead of loading their backup configuration.
- Fixed an issue where pushing a configuration with a Datakit plugin whose `inputs` node contained a null value to an older data plane crashed the control plane's config compatibility checker with the error `"attempt to index local 'value' (a userdata value)"`.

Admin API

- Fixed an issue where resetting the password of an admin or developer failed with the error `Old password is invalid`, which happened when the credential was created before the basic auth hashing algorithm was upgraded from SHA1 to SHA256 (e.g. a `kong_admin` user created in an older version and carried over through an upgrade). The old password is now verified with the backward-compatible verification logic that supports both SHA1 and SHA256 hashed passwords.

Configuration

- Increased the default `proxy_ssl_verify_depth` and `lua_ssl_verify_depth` from `1` to `5`.

3

R

F

C

-only, the same way it already behaves once a license has expired past its grace period. The proxy data
l set of endpoints stays writable so the gateway can recover: `/licenses` to upload a new license, and
t/raw` so a keyring-encrypted license can be decrypted across restarts before the licensing subsystem
te access to the Admin API.

PI routes are no longer allowed. If you have an existing workspace name that conflicts with a admin route,
e reserved first-level segments.

F

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Core

- Added error attribution for plugin execution errors (HTTP 500). Kong classifies errors as `kong` (bundled plugins) or `custom` (custom plugins), and Prometheus exposes this via the `source` label to separate custom plugin failures from internal Kong errors.
- **Conditional Plugin Execution**: The plugin `condition` field now uses Common Expression Language (CEL) with broader operator and type support, aligned across UI, Control Plane, and Data Plane. Refer to the official documentation for the full syntax, supported variables, operators, and types.
- Added a Distroless Docker image variant for Kong API Gateway. The Distroless image ships only the Kong binary and its runtime dependencies, with no package managers, no shells or any other programs you would expect to find in a standard Linux distribution.
- Added a file system vault (`fs`).
- Added plugin cloning support. You can now clone existing bundled plugins, give them a new name, and optionally specify a priority. This is useful when you want to have multiple instances of a plugin with different configurations running in the same request. Currently, the cloneable plugins are: `openid-connect`, `acl`, `pre-function`, `post-function`, `request-transformer-advanced`, `request-transformer`, `response-transformer-advanced`, `response-transformer`, `key-auth`, `file-log`, `http-log`, `tcp-log`, `ip-restriction`, `route-by-header`, `opa`, `datakit`.
- Added plugin streaming support. You can now stream custom plugins dynamically from the control plane to its data planes. Refer to the documentation for more details on how to use this feature.
- Added support for `kong.router.get_route` and `kong.router.get_service` in the strict sandbox environment.
- Added the ability to reference the `cert` field of CA certificates.
- **analytics**: Added workspace information to the analytics payload.
- **vault**: Added a new `azure-certs` vault type for storing TLS certificates in Azure Key Vault.

Plugin

- **kafka-consume, confluent-consume**:
  - Added `consumer_group` configuration to allow explicit control over the Kafka consumer group ID.
- **kafka-upstream, kafka-consume, confluent, confluent-consume**:
  - Added the `error_handling.return_error_message` configuration option to surface Kafka client error messages in HTTP error responses. When enabled, the full error detail (such as authentication failures) is returned to the client instead of a generic message, aiding development and debugging. Defaults to `false` to preserve existing secure behavior.
- aws-lambda:
  - Added a `preserve_lambda_api_error_code` config field. When enabled, Kong returns the same HTTP status code the Lambda API returned (4xx or 5xx), with a sanitized body.
- basic-auth:
  - Added support for authentication via the Kong Identity service with caching, consumer compatibility, and basic analytics.
- datakit:
  - Added a `non_nil` config attribute to the `property` node. When set to `true`, GET operations fail with an error if the property is unset, and SET operations fail with an error if the input is nil/null.
  - Added Konnect Debugger support for Datakit execution, including per-node spans, sanitized trace content capture with vault-aware redaction, and local debug trace responses using the same tracing event model with inline values.
- forward-proxy:
  - Added a `ca_certificates` option for per-plugin TLS verification. This setting allows certificate chain and hostname checks against specified CAs instead of

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`ient_certificate` config field.

ntity service with caching, consumer compatibility, and basic analytics.

w `structured_errors` field, which provides structured error details. Use the `max_structured_errors` returned errors in structured format; when unset, all errors are returned. When `structured_errors` is ctured error format.

for mTLS PoP validation via HTTP header when TLS is pre-terminated by downstream.

after token verification, enabling consumer and consumer group mapping from Kong Identity with caching

    - Added support for reading bearer tokens from a custom header.
    - Added the `cluster_cache_items` configuration option. This option controls which items are stored in the cluster cache backend configured via `cluster_cache_strategy`. Token material is AES-encrypted before being written to the cache.
    - Added `verify_signature` and `jwks_uri` fields to `token_exchange.subject_token_issuers` for verifying incoming subject token signatures before exchange.
- opentelemetry:
    - Added support for the `OTEL_RESOURCE_ATTRIBUTES` environment variable. You can now set custom resource attributes for OpenTelemetry instrumentation as secondary resource attributes to the `resource_attributes` configuration.
- rate-limiting-advanced:
    - Added the `counter_key` field to let you choose which consumer attribute is now used as the rate-limiting counter identifier. Supported values are `consumer.id`, `consumer.username`, and `consumer.custom_id`.
- ace Added Kong Identity principal fetching after authentication, enabling consumer and consumer group mapping from the Konnect identity service.
- kafka-upstream, **confluent**: Added support for forwarding HTTP request headers as native Kafka record headers.
- kafka-upstream, **kafka-log**, **kafka-consume**, **confluent**, **confluent-consume**: Added SASL OAUTHBEARER authentication support.
- solace-upstream, **solace-log**, **solace-consume**: Added support for OAuth2 client credentials authentication. Configured with the `CLIENT_CREDENTIALS` scheme, tokens are cached and renewed automatically.

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which can help avoid frequent disconnections and reconnection attempts and improve performance. When this happens, Kong now emits a log entry containing the config payload size and the configured `cluster_max_payload` size.

PDK

- Added `kong.request.get_raw_headers()` to return request headers parsed from raw request headers for HTTP/1.x requests.

Kong Manager

- Migrated some plugin configuration forms, including custom plugins, to the new FreeForm renderer.

Bugfix

Plugin

- **ai-advanced-proxy**:
    - Fixed an issue where we never stored the response model in the streaming path. It always fell back to the request model.
- **ai-guardrail**:
    - Fixed an issue where latency metrics were missing in the Prometheus output.
- **ai-guardrails**:
    - Fixed an issue where multiple guardrail plugins couldn't function together.
- **ai-transformers**:

d `ai-response-tranformer` plugins did not work properly with the `ollama` provider.

confluent-consume:

cross different SASL credentials and TLS verification settings.

alid legacy ACL group credentials were rejected with a 403 error when `include_consumer_groups` was ssigned.

body_filter chunks and dropped oversized events safely, preventing `sse_last_event` type errors that

e_use_managed_identity was enabled.

hen the LLM response content was empty. Empty content now skips the content-safety check and passes through.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Fixed an issue where the response guard was sending the entire JSON response body to Azure Content Safety instead of just the assistant message content, which caused false positives when response metadata fields matched blocklist entries.

- ai-mcp-oauth2:
    - Fixed an issue where token introspection crashed when `client_auth` was set to `private_key_jwt` and `client_jwk` was provided as a JSON string.
    - Fixed an issue where downstream scope-based ACL evaluation used claims from the inbound token instead of the exchanged token when token exchange was enabled.
    - Fixed an issue where token exchange actor tokens were not sourced correctly from `token_exchange.request`, ensuring correct forwarding of actor tokens configured in headers or plugin config.
    - Fixed an issue where `token_exchange.cache.enabled = false` was ignored and exchanged tokens were still cached because the cache toggle incorrectly read `token_exchange.cache.ttl` instead of `token_exchange.cache.enabled`.
- ai-mcp-proxy:
    - Fixed an issue where raw non-200 upstream responses triggered misleading MCP body parse warnings.
    - Fixed an issue where the `WWW-Authenticate: Bearer error="insufficient_scope"` header was not emitted.
    - Fixed an issue where internal unix-socket subrequests lost the original client IP address, causing IP-aware plugins like IP Restriction to reject legitimate requests.
    - Fixed an issue where, since 3.14, call tools converted from API could fail when Kong used a self-signed certificate.
    - Fixed an issue where the tool ID might be repeated.
    - Fixed an issue where empty JSON arrays in MCP server responses were rewritten to empty objects when the plugin re-encoded the body for ACL list filtering.
    - Fixed stale tools cache after full-sync reconfigure (e.g. `deck sync`), causing `tools/list` to return empty results.
- ai-prompt-decorator:
    - Fixed an issue where the plugin corrupted native-format requests (gemini, anthropic, bedrock, cohere, huggingface) by forwarding an OpenAI-shaped body upstream instead of the original native body shape.
- ai-proxy-advanced:
    - Fixed an issue where we didn't support the Azure GA version of Realtime API.
    - Fixed an issue where OpenAI-format chat reasoning requests were not mapped consistently across Anthropic, Gemini, Bedrock, and other providers.
    - Fixed an issue where system prompts from Claude Code were truncated when doing non-passthrough proxy.
    - Fixed an issue where we didn't support Anthropic format for the Databricks provider.
    - Fixed an issue where we didn't use the Huggingface's token usage if available.
    - Fixed an issue where we didn't collect the model name in OpenAI streaming response from Azure.
    - Fixed an issue where we didn't correctly ungzip streaming responses.
    - Fixed an issue where dashscope replied with a 500 error to inference requests.
    - Fixed an issue where GenAI spans were not finished sometimes.
    - Fixed an issue where observability errors occurred when `gpt-image-1.5` returned image token usage details.
    - Fixed an issue where Azure OpenAI authentication failed during load balancer failover due to token refresh attempts in `balancer_by_lua`. Tokens are now pre-fetched in the `access` phase.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - could race to initialize the semantic routing vectorDB index, causing `"Index already exists"` errors on
    - c response as gzipped.
    - by Vertex AI in Anthropic-native requests.
    - ay never be used for the Azure provider.
    - cs were missing when using an Anthropic model via the Bedrock provider.
    - mini-native fields (e.g. `cachedContent`, `safetySettings`) and Vertex AI-only fields (e.g. `labels`) during
    - not respected in native mode.
    - rs on 429 responses from policies that partition by `provider` or `model`.
    - Fixed an issue with token counters being decremented on AI Semantic Cache hits.

  - Fixed an issue where `model` or `provider` matchers without `partition_by` were skipped, causing rate limits to be missed.
  - Fixed policy integration with `ai-proxy` for single-target and multi-target AI proxy routes.
- ai-sanitizer:
  - Fixed an issue where the AI Sanitizer plugin could not parse the request body correctly.
- ai-semantic-response-guard:
  - Fixed an issue where the plugin failed to populate Redis with rule documents due to using worker ID gating instead of worker mutex for vectordb operations.
- aws-lambda:
  - Fixed an issue where empty JSON array bodies (`[]`) were incorrectly converted to objects (`{}`) when using `is_proxy_integration=true` and `empty_arrays_mode=correct` alongside the Exit Transformer plugin.
  - Fixed an issue where a 500 error occurred when `is_proxy_integration` was enabled and the Lambda function returned `null` values in `headers` or `multiValueHeaders`. Null values are now converted to empty strings.
- datakit:
  - Added Lua control plane compatibility checks to prevent unsupported Datakit configurations from being pushed to older data planes in hybrid mode.
- exit-transformer:
  - Fixed an issue where a response body that was a JSON primitive (e.g. `false`) caused a 500 internal error.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the GraphQL Rate Limiting Advanced plugin's API threw 500 errors when handling HTTP PUT requests.
- ip-restriction:
  - Fixed an issue where the plugin handled requests from unix socket incorrectly.
- jwt:
  - Fixed an issue where malformed JWT tokens (e.g. tokens without dots) caused a 500 Internal Server Error instead of returning 401 Unauthorized.
- kafka-log:
  - Fixed an issue where cached producers could cause memory leaks.
- key-auth:
  - Fixed an issue where a null value was accidentally blocked on identity_realms.
- mocking:
  - Fixed an issue where `$ref` dereferencing failed with `invalid ref: <code>` when bare-numeric keys were used under `components.responses`. Now supports numeric-key fallback.
- oas-validation:
  - Fixed an issue where the OAS specification cache failed to distinguish between different values of `api_spec_encoded` for the same specification content.
  - Fixed an issue where path parameters were extracted from the wrong URI segment when `custom_base_path` was used with bare `/{param}` paths.
- openid-connect:
  - Fixed an inconsistency where `credential_claim` resolved the same claim name to a different value than `upstream_headers_claims` because it consulted the `id_token` before the `access_token`, while the upstream headers resolver consulted the `access_token` first. With IdPs (e.g. Okta) that set distinct `sub` values hot match the upstream header the plugin set on the same request.

esolved correctly.

could fail when Redis connections were routed through a proxy.

re not written when the `cluster_cache_strategy` was updated using incremental sync.

449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.

tributes could leak across concurrent queued `traces`, `logs`, and access log exports when the plugin was

es in plugin configuration didn't work as expected for metrics.

or balancer failures occurred during upstream retries.

API did not work when the `redis` strategy configuration was provided via a partial.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- rate-limiting:
  - Fixed an issue where the sync timer did not use updated configuration.
- request-transformer:
  - Fixed a regression where `remove.body` entries in `key:value` format (e.g. `scope:USER`) failed to remove the field from the request body. The value part is now correctly ignored during removal, restoring the behavior from 3.11.
- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.
- service-protection:
  - Fixed an issue where the Service Protection plugin could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after Rate Limiting Advanced and only evaluates requests that pass rate limiting, by updating its priority from 915 to 901.
- solace-upstream:
  - Fixed an issue where requests under high concurrency could fail with connection timeouts despite a sufficient `connect_timeout` being configured.
- ai-semantic-prompt-guard, **ai-semantic-response-guard**: Fixed an issue where full-sync reconfigure rebuilt semantic vectorDB indexes even when the plugin configuration was unchanged.
- Fixed AI Proxy Advanced Gemini failover handling when a target sets `upstream_url` to `ngx.null`, avoiding an empty trailing query string in the computed upstream URI.
- Fixed Kafka broker returning failed connections to the keepalive pool, added SSL handshake retry, and improved error propagation.

Core

- Added the missing PDK functions to sandbox environments.
- Applied upstream nginx security patches for CVE-2026-40701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.
- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).
- **debugger**: Fixed an issue where Debugger would not set the status code of connections that were closed by the client.
- **Debugger**: Fixed an issue where Redis command arguments were incorrectly included in Redis spans.
- **debugger**: Fixed an issue where response body content capture consumed streaming response chunks.
- **Debugger**: Fixed an issue where the Konnect Debugger concatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g. `unix:/<prefix>/sockets/am:tls`).
- **Debugger**: Fixed an issue where the time spent during the TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side latency.
- **Debugger**: Fixed an issue where the default key name `apikey` of the `key-auth` and `key-auth-enc` plugins was not redacted when captured by the Debugger. This has been resolved by adding `apikey` to the list of default redacted headers.
- Fixed a bug where tables in `strict` and `lax` `untrusted_lua` modes were not properly protected against modification.
- Fixed an issue where anonymous reports omitted model usage when one provider used multiple models.
- Fixed an issue where Kong Manager users authenticated through IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim changes, or end up with inconsistent mappings during concurrent authentication requests.
- Fixed an issue where `kong.service.set_tls_cert_key` did not update the upstream keepalive pool name. It now includes a cert fingerprint for proper connection isolation.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

h the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` is
dy messages for 501 and 505 status codes.

VAL environment variable was not correctly applied to the analytics flush interval.

ol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497
ted prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from
l added `error_page` 497 routing through `kong_error_handler`.

tatables from previous TLS connections, leading to cross-request context leakage and increased memory

returned HTTP 404 when using `router_flavor=expressions` due to incorrect protocol matching

orrectly passed to `error()`. The error level is now `0`, ensuring sandbox error messages are reported

- **websocket**: Fixed an issue where the response body from an upstream was silently dropped when the upstream rejected the WebSocket handshake with a non-101 HTTP status code (e.g. 400, 401, 403). The body is now read from the TCP socket before it is closed and forwarded to the client, supporting both `Content-Length` and `Transfer-Encoding: chunked` framing.

Clustering

- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.
- Fixed an issue where a Data Plane failed to load config updates when a CA certificate expired. The Data Plane now accepts the config and logs a warning.
- Fixed an issue where DP syncing failed with large configs. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful full-sync.
- Fixed an issue where hybrid data planes retried unrecoverable CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable reconnect storms.
- Fixed an issue where incremental DP (sync v2) would not export config to fallback storage when the control plane used periodic polling instead of `notify_new_version`.
- Fixed an issue where incremental sync (ICS) would crash and stop further sync attempts.
- Fixed an issue where paginated full sync could keep stale pending foreign-key references across a failed resume, causing spurious validation failures.
- Fixed an issue where the DP may spawn multiple sync timers when downgrading sync protocol to v1, which may cause excessive load on CP and lead to performance degradation.
- Fixed clustering sync reliability issues by immediately failing pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

PDK

- Fixed an issue where `kong.service.request.clear_query_arg()` would destructively rewrite unrelated query arguments by normalizing `+` to `%20` and stripping the `=` from empty-valued arguments. The remaining query arguments are now preserved verbatim.
- Fixed an issue where the array log entries could not be customized by array indices, like `kong.upstream.try[1].balancer_latency_ns: 'return 140545'` or `x.y.foo[2]: "return [[how are you?]]"`. Only positive integers are supported as array indices.
- Fixed an issue where the `kong.request.get_body()` function incorrectly parsed the `Content-Disposition` name parameter if it wasn't double-quoted.

CLI Command

- Fixed an issue where the `kong restart` command did not respect the command `prefix` argument.

Default

- **jwt-signer**: Fixed an issue where the plugin failed to load configuration and errored when `null` or `nil` values were passed to `access_token_keyset` or `channel_token_keyset`.

Admin API

- Kong no longer allows using a license referenced by a vault to be applied via the Admin API.
- **RBAC**: Fixed an issue where `PATCH /rbac/roles/{name_or_id}/entities/{entity_id}` returned a misleading `404` response instead of the correct error (e.g. a `400` schema violation) when the update failed.

Kong Manager

created on workspace creation.

ning non-ASCII characters.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

issue in the GraphQL query syntax that caused a parsed AST error in DeGraphQL plugin.

s SHA-384 support for SCRAM channel binding during PostgreSQL SSL authentication.

- Bumped libexpat from 2.8.0 to 2.8.1.
- Bumped libxml2 from 2.15.1 to 2.15.3.
- Bumped libxslt from 1.1.43 to 1.1.45.
- Bumped lua-resty-gcp from 0.0.19 to 0.0.20 to add support for proxy options.
- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2
- Bumped lua-resty-mail from 1.1.0 to 1.2.0.
- Bumped lua-resty-openssl from 1.7.0 to 1.7.1.
- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped LuaRocks from 3.12.2 to 3.13.0.
- Bumped multipart from 0.5.11 to 0.5.12.
- Bumped OpenResty from 1.27.1.2 to 1.29.2.5.
- Bumped OpenSSL from 3.4.3 to 3.5.7.
- Bumped penlight from 1.14.0 to 1.15.0.
- Updated libpasswdqc from 2.0.3 to 2.1.0.

CLI Command

- Bumped ca-certificates (debug tool) from 2025-12-02 to 2026-03-19.
- Removed bundled cURL debug binary (curl, nghttp2, ca-certs) from Kong packages.

Performance

Core

- Improved performance of analytics data collection by introducing a shared payload pool and reducing the default local buffer size.

Plugin

- opentelemetry:
  - Reduced the OTel trace-pipeline CPU overhead.

3.14.0.16

Release date 2026/10/14

Feature

Plugin

- ai-a2a-proxy:
  - Added A2A v1.0 wire-format support alongside v0.3.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

would keep blocking certificate issuance. Retries are now rejected only while the backoff timestamp is

AI, Anthropic, and Amazon Bedrock chat formats.

kens attribute was missing from OpenTelemetry spans.

er routed requests with the same `hash_on_header` value to different targets when multiple workers were

  - `brute_force_protection` now rate-limits each `Proxy-Authorization` and `Authorization` credential independently.

- degraphql:
  - Fixed an issue where the plugin router did not refresh after an incremental sync update on a Data Plane, leaving routes stale until the next full config push.
- graphql-rate-limiting-advanced:
  - Fixed an issue where `pass_all_downstream_headers` forwarded stale `Content-Length`, `Content-Encoding`, and `Transfer-Encoding` headers, breaking schema introspection.
  - Fixed an issue where a longer fixed window was incorrectly marked as exhausted if a shorter window denied a request.
- opa:
  - Fixed an issue where Kong Gateway did not send an SNI to the OPA server. It now sends `opa_host` as the SNI when that is a hostname; with `ssl_verify = true`, the certificate must include `opa_host`.
- openid-connect:
  - Fixed an issue where a callback with an invalid JARM response returned a 500 error; the plugin now rejects such callbacks with a 401 authentication failure.
- opentelemetry:
  - Fixed an issue where a WebSocket handshake that never opened a connection drove `kong.websocket.server.active_connections` negative, reported a false duration and was not counted.
  - Fixed an issue where the description of `kong.websocket.handshake.error.count` was ambiguous. It now states that the metric counts only protocol validation failures.
  - Fixed an issue where the `kong.shared_dict.size` metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series as stale.
- rate-limiting-advanced:
  - Fixed an issue where a longer fixed window was incorrectly marked as exhausted if a shorter window denied a request.
- service-protection:
  - Fixed an issue where a longer fixed window was incorrectly marked as exhausted if a shorter window denied a request.

Core

- **Balancer**: Fixed an issue where a plugin could not override the upstream target when the Gateway Service `host` was a literal IP address. The balancer kept the IP that it derived from the Service, so the request went to the Service host and the override was silently lost. This affected `kong.service.set_target` and every plugin that replaces `ngx.ctx.balancer_data.host`, for example `route-transformer-advanced` and `canary`.
- Fixed an issue where a malformed JSON document could corrupt the shared JSON decoder of a worker. Later requests that decoded valid JSON on the same worker then failed until the node restarted. The JWT plugin returned `Bad token; invalid JWT payload` for known-good tokens.
- Fixed an issue where `dnf upgrade kong-enterprise-edition` could not resolve an upgrade on RPM systems. The FIPS packages declared an unversioned `Obsoletes: kong-enterprise-edition`, so an installed non-FIPS package had two mutually conflicting successors and dnf reported “cannot install the best update candidate”. The RPM packages now obsolete the other Enterprise variants only below the version being built. This also keeps `dnf install kong-enterprise-edition-fips` on the FIPS artifact. Debian packages do not change.
- Fixed an issue where Kong Gateway in DB-less mode could fail to detect configuration changes during reconfiguration, leaving the router or plugins iterator stale.
- Fixed an issue where the `SameSite` attribute of the `Set-Cookie` header was incorrectly set to `Same-Site` by session-affinity (sticky-session) balancing.
- Fixed issues where upstream lookup failures interrupted balancer initialization and incomplete rebuilds left stale targets after a configuration rollback.
- **RBAC**: Fixed an issue where a temporary database outage during an RBAC user’s group lookup cached a wrong value, breaking every later Admin API request

C

, in data planes could prevent a recovery connection with the control plane.

were logged for every message. It now only logs when the payload size exceeds `30%` of the configured

gurations when a referenced entity was in a non-default workspace.

ync v2 notifications to a data plane that had fallen back to legacy sync v1, logging a misleading error.

falsely abort with a concurrent-change error when the router spanned more than one page, leaving routes

I

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped lua-resty-jq from 0.2.0 to 0.2.2.
- Bumped lua-resty-simdjson from 1.2.0 to 1.3.1 (updates simdjson to 4.6.11).

3.14.0.15

Release date 2026/09/17

Feature

Core

- Added error attribution for plugin execution errors (HTTP 500). Kong classifies errors as `kong` (bundled plugins) or `custom` (custom plugins), and Prometheus exposes this via the `source` label to separate custom plugin failures from internal Kong errors.

Bugfix

Plugin

- **ai-guardrails**:
  - Fixed an issue where a JSON `null` field in a response from the third-party service made the plugin return `500`.
- ai-aws-guardrails:
  - Fixed a issue where the request to the AWS Guardrails service could return a 500 error due to a failure in request signing.
- ai-mcp-proxy:
  - Fixed an issue where gzip-compressed and malformed MCP request bodies were incorrectly rejected with HTTP 413.
- ai-proxy-advanced:
  - Fixed an issue where non-legacy OpenAI output token limits were discarded or overridden during request normalization.
  - Fixed an issue where adapted Anthropic responses omitted cache and reasoning usage details.
  - Fixed an issue where repeated cumulative usage in streaming responses inflated token counts.
  - Fixed an issue where Gemini non-streaming responses that reached `max_tokens` reported a `stop` finish reason instead of `length`.
  - Fixed an issue where a Gemini response with JSON `null` token counts in `usageMetadata` caused an HTTP 500 on non-streaming chat requests and an empty HTTP 200 response on streaming chat requests.
  - Fixed an issue where provider-reported reasoning-token details were not correctly reported.
  - Fixed an issue where xAI reasoning tokens were not folded when visible completion tokens exceeded reasoning tokens.
  - Fixed an issue where xAI reasoning tokens were not folded into `completion_tokens`, breaking the OpenAI usage identity.
  - Fixed an issue where Gemini and Anthropic token usage metadata was lost in streaming responses.
  - Fixed an issue where a malformed RSA private key in a Gemini provider's `service_account_json` caused a crash with SIGSEGV.
  - Fixed multipart video generation requests to OpenAI-compatible providers leaking internal multipart metadata into JSON upstream bodies, which caused the requests to fail.
- ai-rag-injector:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- jwt:
  - Fixed an issue where the plugin failed to decode standard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.
- oas-validation:
  - Fixed an issue where readOnly and writeOnly properties in OpenAPI 3.1.x specifications were not correctly validated.
  - Fixed an issue where OpenAPI 3.1.x parameter patterns using ECMA-262 `\uXXXX` Unicode escapes failed to match correctly, because PCRE does not support that escape syntax.
- openid-connect:
  - Fixed an issue where disabling `verify_signature` gave no warning, even though it also skips signature verification for bearer tokens from clients. The plugin now logs a warning when `verify_signature` is `false` and `auth_methods` includes `bearer`. It logs a notice instead when `bearer` is not enabled.
- opentelemetry:
  - Fixed an issue where a `custom_attributes_by_lua` key that conflicts with an existing log field stopped the log handlers of the plugins that run later.
- request-callout:
  - Fixed an issue where a callout that failed and then succeeded on retry still returned the earlier failed response. The plugin now returns the response from the successful retry.
- ai-proxy and **ai-proxy-advanced**: Fixed a 500 crash on Bedrock Converse requests when a `cachePoint` content block immediately followed a `toolResult` block in the same message.
- ai-semantic-prompt-guard, **ai-semantic-response-guard**, **ai-proxy-advanced**, **ai-semantic-cache**: Fixed an issue that failed to delete vector database indexes and cached embedding records when a plugin instance was deleted.
- kafka-consume, **confluent-consume**: Fixed an issue where the consumer group subscription declared protocol version 1 but carried the version 0 layout, so a topic-rewriting proxy rejected it.

Clustering

- **datakit**: When a data plane older than the control plane does not support a Datakit configuration, the control plane now removes only the incompatible Datakit plugin instead of rejecting the whole configuration. This matches the Konnect control plane version-compatibility behavior.
- Fixed an issue where a data plane failed to load config updates when a CA certificate expired. The data plane now accepts the config and logs a warning.
- Fixed an issue where self-managed control planes rejected updates to a streamed plugin's handler while the plugin was referenced by a plugin instance.
- Fixed an issue where updates to a streamed plugin's definition (e.g. `handler`) were not applied on data planes when no referencing plugin instances changed. The data plane now rebuilds its plugins iterator so the updated definition takes effect, instead of continuing to execute the previous version.

Core

- Fixed an issue where custom streamed plugin schemas were still sandboxed when `untrusted_lua` was set to `on`. Schema code that needed to opt out of sandboxing, unlike custom plugin handlers that already respected `on`, was incorrectly rejected on both the control plane and the data plane.
- Fixed an issue where Kong skipped the WebSocket `ws_close` phase when it could not proxy the request.
- Fixed an issue where the error wrapper was not being freed after sandboxed template rendering in plugins such as `request-transformer` and `response-transformer`.
- **Konnect Only**. **Debugger**: Added new debugger span attributes `tls.client.server_name`, `proxy.kong.upstream.address`, `proxy.kong.request.host`, `http.request.header.connection`, `proxy.kong.client.connection.request_count`. Removed debugger span attributes `proxy.kong.upstream.host`, `proxy.kong.upstream.addr`, `http.request.header.host`, `proxy.kong.client.keepalive`.
- **plugin streaming**: Fixed an issue where custom plugins weren't loaded on all workers on all nodes.

I

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Performance

Clustering

- **Clustering**: Improved DP performance when applying a large incremental config update.
- Improved configuration synchronization latency in some cases when incremental sync is enabled.

Core

- Improved performance when `untrusted_lua` is set to `sandbox`. Previously, Kong rebuilt the Lua environment, including a module reload, on every compile of a sandboxed function.

Plugin

- oas-validation:
  - Improved plugin performance by removing unnecessary hash computation. Enabling the plugin now adds much less latency and CPU overhead to requests.

3.14.0.14

Release date 2026/08/26

Feature

Core

- Enabled TLS 1.3 for the FIPS cipher suite in the FIPS-140-3 artifacts, and configured those builds to use AES-based TLS 1.3 ciphersuites. The FIPS-140-2 artifacts keep TLS 1.2.
- Kong now publishes one artifact per FIPS certification level. The `kong-enterprise-edition-fips` package and the `<version>-<distro>-fips` image keep the OpenSSL FIPS provider 3.0.9 (FIPS 140-2). The new `kong-enterprise-edition-fips-140-3` package and the `<version>-<distro>-fips-140-3` image use the provider 3.1.2 (FIPS 140-3).
- The FIPS-140-3 artifacts serve an explicit TLS 1.2 cipher list: four ECDHE suites with AES-GCM. The FIPS-140-2 artifacts keep the OpenSSL FIPS alias, which also admits static RSA key transport and SSLv3-era suites. To serve a different list, set `ssl_cipher_suite = custom` and `ssl_ciphers`.

Plugin

- openid-connect:
  - KONG_FIPS=on no longer generates default EdDSA JWKS keys. Use an RSA-PSS or NIST-curve ECDSA key instead.

    If you migrate from the FIPS package to the FIPS-140-3 package, this change breaks existing EdDSA-based configurations.

Bugfix

Plugin

- datakit:
  - Fixed an issue where the `response` node set `Content-Type: application/octet-stream` for `json_to_xml` output. It now defaults to `application/xml` when no explicit `Content-Type` is provided.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ned access token header on the upstream request, when `access_token_upstream_header` (or
the same name as `channel_token_request_header`.

e did not use weak keys due to a misspelled `__mode` metatable field.

expired token stayed authorized indefinitely instead of being rejected. An authoritative `active:false`

ıt failed an authorization check (such as `scopes_required`) was not attributed to its consumer, or

when it is set, because it turns off JWS signature verification for the listed grants.

  - Fixed an issue where metrics were rarely (or never) exported on data planes whose configuration is rebuilt more frequently than the metrics `push_interval`. The periodic metrics push timer is no longer canceled and recreated on every configuration rebuild, so its `push_interval` countdown is preserved.
  - Fixed an issue where the `kong.dp.cluster_cert.expiry` metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series as stale.
  - Reduced per-request overhead of `resource_attributes` by skipping template rendering entirely for static (non-templated) fields.
- prometheus:
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
- saml:
  - Hardened signature validation against XML Signature Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that names the `ID` of the element it digests and consumes, so a signature can no longer be bound to a different element than the one that provides the identity. A response whose reference URI is empty or not a same-document fragment is now rejected.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed an issue where OAuth2 authentication against Confluent Cloud Schema Registry failed because the client did not send the required `target-sr-cluster` header.

PDK

- Fixed an issue on HTTP/2 connections where the request method and query were reported incorrectly, or could raise an error, when a request hit the error handler such as a 502 from an upstream connection reset.
- Fixed an issue where the array log entries could not be customized by array indices, like `kong.upstream.try[1].balancer_latency_ns: 'return 140545'` or `x.y.foo[2]: "return [[how are you?]]"`. Only positive integers are supported as array indices.

Core

- Fixed an issue where a failed balancer creation leaked the per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.
- Fixed an issue where a healthcheck counter value of 255 crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`, `http_failures`) are now limited to 254.
- Fixed an issue where an in-flight request that completed after its upstream target became unavailable could restore the target to the latency balancer and route subsequent requests to it.
- Fixed an issue where `/status/ready` could report a data plane ready before the new router and plugin iterator became active. Kong now reports readiness only after plugin configuration completes and the live objects are installed.
- Fixed an issue where upstream failover could return intermittent 503 responses while a failover target remained healthy.
- Hardened HashiCorp Vault cloud authentication (AWS, Azure, GCP): Kong keeps credentials out of internal cache keys, truncates Vault error responses in logs, sets timeouts on all authentication requests, and applies `ssl_verify` to every outbound TLS call.
- **Konnect Only**. **Debugger**: Fixed a stack overflow in the deep copy of worker logs. The fix replaces `deep_copy` with `cycle_aware_deep_copy`.

Clustering

- Fixed an issue where heavy packet loss could prevent the full sync from resuming.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Added the OpenSSL FIPS provider 3.1.2 for the FIPS-140-3 artifacts. The FIPS-140-2 artifacts keep the provider 3.0.9.
- Bumped kong-pgmoon from 2.3.4.0 to 2.3.5.0, which fixes SCRAM channel binding failing to connect to a PostgreSQL server whose certificate is signed with SHA-512.

Performance

Clustering

- Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.
- Optimized performance of clustering payload handling for version compatibility. This reduces CPU usage and transient memory pressure.

Admin API

- Improved the performance of listing workspaces with `?counter=true`. Entity counts for the whole page are now retrieved with one grouped query per entity type instead of a separate count query per entity type per workspace, while keeping the counts exact.

Plugin

- opentelemetry:
  - Reduced memory usage of the access log queue by deferring OTLP payload conversion to export time.

Core

- Reduced config update latency on hybrid data planes by notifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in parallel.

3.14.0.13

Release date 2026/08/19

Feature

Core

- Added a Distroless Docker image variant for Kong API Gateway. The Distroless image ships only the Kong binary and its runtime dependencies, with no package managers, no shells, and no other programs you would expect to find in a standard Linux distribution.

Plugin

- ai-proxy-advanced:
  - Added `cache_read_cost` and `cache_write_cost` to `model.options` so cached and cache-write prompt tokens can be priced per 1M tokens, alongside `input_cost` / `output_cost`.
  - Added filtering for empty Anthropic thinking blocks in request history.
  - Added support for reporting prompt cache token metrics in OpenAI-compatible format.
  - Added support for reporting prompt cache token metrics when using native (non-OpenAI) request/response formats.
  - Usage cost now supports per-cache-TTL cache-write pricing, context-window pricing factors, and service-tier pricing factors via `model.options` `or`, `service_tier_factor`). Anthropic (cache TTL + service tier), OpenAI, and Gemini service tiers are

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d fail to decode when the client's request advertised Brotli support, since Anthropic's edge may then return pression – which only understands gzip – can't inflate. Kong now normalizes the outgoing `Accept-` LM provider: `gzip, identity` when the client accepts gzip, and `identity` otherwise, so a client that ody on the paths that pass the upstream response through untouched.

unted provisional `message_start` output tokens and summed cumulative `message_delta` usage.

ted as zero for Bedrock native format request to AWS models like Nova.

uld report zero usage when it targets Bedrock's own model via conversion.

- Fixed an issue where OpenAI, Azure, and Gemini realtime upstream URLs using `wss` were downgraded to `ws`.

    - Fixed an issue where token usage for Anthropic requests using the compaction beta was undercounted. Kong now sums `usage.iterations` when present instead of relying solely on the top-level `input_tokens` / `output_tokens`, which only reflect non-compaction iterations.
    - Fixed an issue where Gemini's tool-use token usage (billed when server-side tools such as grounding, code execution, or URL context are used) was not counted in the reported token usage or cost.
    - Fixed an issue where signed Anthropic thinking blocks with omitted text were removed from request history.
    - Fixed an issue where some Claude Code MCP tools did not correctly handle empty 'requires' array.
    - Fixed Gemini image generation token accounting to include reasoning tokens (`thoughtsTokenCount`) in `output_tokens` and report them as `output_tokens_details.reasoning_tokens`. Previously the reasoning tokens were dropped, which under-reported output tokens, analytics, and calculated cost for thinking-enabled image models.
    - Fixed Gemini realtime (Live API) token accounting to include reasoning tokens (`thoughtsTokenCount`) in the reported output tokens, and to report them as `output_tokens_reasoning_tokens_count`. Previously the reasoning tokens were dropped, which under-reported the output and total token counts of thinking-enabled realtime sessions.
    - Fixed token usage statistics being silently dropped for `audio/v1/audio/transcriptions` requests. Token-billed OpenAI/Azure transcription models (e.g. `gpt-4o-transcribe`) now report `input_tokens`/`output_tokens`/`total_tokens` and the `text_tokens`/`audio_tokens` breakdown in the analytics log when `logging.log_statistics` is enabled.
- ai-proxy:
    - Fixed Gemini token accounting to include reasoning tokens in `completion_tokens` for both OpenAI-format and native-format proxying.
- opentelemetry:
    - Fixed `gen_ai.client.token.usage` never reporting token counts for non-text-generation AI categories (image, video, realtime, and audio transcription generation), because it only read the legacy `prompt_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `input_tokens`/`input_tokens_details` fields those categories are logged under.
- prometheus:
    - Fixed `kong_ai_llm_tokens_total` never reporting token counts for non-text-generation AI categories (image, video, realtime, and audio transcription generation), because it only read the legacy `prompt_tokens`/`prompt_tokens_details` analytics log fields instead of falling back to the `input_tokens`/`input_tokens_details` fields those categories are logged under.
- ai-proxy, **ai-proxy-advanced**: Fixed an issue where Gemini streaming analytics could over-report token usage. Gemini repeats its usage metadata on every stream chunk as a running request-level total, but the counts were summed across chunks instead of replaced, multiplying the reported usage by the number of chunks. Reasoning tokens were affected the most, because Gemini reports them in full on the first chunk and does not change them afterwards. A chunk that carried no usage metadata also reset the recorded output token count to zero.

CLI Command

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Core

- On shell-free (distroless) images, the pluginserver query and start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with a clear error on an unterminated quote or `${`, instead of passing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.

3.14.0.12

Release date 2026/08/10

Bugfix

P

thm to the verification key's type in the `jwt_verify` node, so a symmetric algorithm can no longer be
n authentication bypass where an attacker forges tokens by using the public key as an HMAC shared
PEM key string and `allowed_algorithms` is unset (any algorithm accepted).

gin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly
ng a crafted unsigned SAML response from silently bypassing authentication under configurations that set

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Applied upstream nginx security patches for CVE-2026-42533.
- Applied upstream nginx security patches for CVE-2026-56434.
- Applied upstream nginx security patches for CVE-2026-60005.
- Applied upstream nginx security patches for CVE-2026-42055 and CVE-2026-48142.

Dependency

Core

- Bumped jq from 1.8.1 to 1.8.2.

3.14.0.11

Release date 2026/08/06

Feature

Plugin

- ai-aws-guardrails, **ai-azure-content-safety**: Added `last_message` as a new optional value for `config.text_source`.

Bugfix

Plugin

- ai-aws-guardrails:
  - Fixed an issue where the plugin ignored the configured `text_source` option when `allow_masking` was enabled, masking the entire raw request body instead.
- ai-prompt-guard:
  - Fixed an issue where the plugin failed to inspect requests sent in a provider's native format instead of the OpenAI-compatible format.
- ai-aws-guardrails, **ai-azure-content-safety**, **ai-custom-guardrail**, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-guard**, **ai-semantic-response-guard**: Fixed an issue where AI Gateway guardrail plugins' request extractors did not correctly honor the configured `text_source` option.
- ai-aws-guardrails, **ai-azure-content-safety**, **ai-custom-guardrail**, **ai-gcp-model-armor**, **ai-lakera-guard**, **ai-prompt-guard**, **ai-sanitizer**, **ai-semantic-prompt-guard**, **ai-semantic-response-guard**: Fixed an issue where AI Gateway guardrail plugins failed to extract prompt text from OpenAI-native requests using the `input_text` content type.
- ai-sanitizer, **ai-aws-guardrails**: Fixed an issue where the plugins were prevented from working properly with Claude Code.

Core

- Fixed an issue where custom Lua running with `untrusted_lua` set to `sandbox` could no longer create global variables or modify allowed library tables.

3.14.0.10

Release date 2026/07/29

Feature

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

s in the agent card.

E

P

hen the LLM response content was empty. Empty content now skips the content-safety check and passes

as not treated as a system prompt when transforming requests to Bedrock and Gemini providers.

  - Fixed an issue where Ollama rejected OpenAI message content arrays.
  - Fixed an issue where the OpenAI content array was sent as a Bedrock/Gemini system message which only support string.
  - Fixed an issue where the configured auth header (e.g. `api-key`, `x-api-key`) leaked the provider credential into access logs instead of being redacted.
  - Fixed an issue where the `context-management-2025-06-27` Anthropic beta flag was dropped when routing to a Bedrock target, causing Bedrock to reject requests carrying `context_management` with a `400` error on failover from an Anthropic target.
- ai-proxy:
  - Fixed Gemini driver dropping Gemini-native fields (e.g. `cachedContent`, `safetySettings`) and Vertex AI-only fields (e.g. `labels`) during OpenAI-to-Gemini request transformation.
- ai-rate-limiting-advanced:
  - Fixed an issue where `model` or `provider` matchers without `partition_by` were skipped, causing rate limits to be missed.
- ai-sanitizer:
  - Fixed an issue where the input field for the llm/v1/responses route was not recognized.
- ip-restriction:
  - Fixed an issue where warn log messages did not include the plugin name, making it difficult to identify the source of blocked requests.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a crash that occurred when a plugin set `schema_registry.confluent.authentication.mode` to `oauth2` but omitted the `oauth2_client` record. Previously this returned a 500 from the Admin API during validation, and once saved it also crashed at runtime while fetching the schema registry OAuth2 token. The absent `oauth2_client` is now handled and falls back to the default authentication method, so a configuration without `oauth2_client` works end-to-end.

Clustering

- **Clustering**: Improved RPC connection stability during long-running calls: a data plane now cancels a timed-out RPC so a late response cannot disrupt later calls, and the connection is kept alive (within a bound) while calls are still in flight instead of being dropped as a missed heartbeat.
- **Clustering**: The `/status/sync` endpoint now returns an empty stat object instead of null before the first sync has run, keeping the response shape consistent.

PDK

- Fixed a race condition issue where the `tries` field of log serialization was not copied, causing data mutations when logs were generated concurrently via async timers.
- Fixed an issue where dynamic upstream TLS settings set via the PDK were lost during buffered proxying.

Core

- **Konnect Only**. **Debugger**: Fixed an error that could occur under sustained HTTPS traffic.
- **Konnect Only**. **Debugger**: Fixed an issue where the response body of the external HTTP call `httpc:request()` was not captured.
- **PostgreSQL OAuth auth**: Refined the token cache key to be derived only from the fields that identify an OAuth configuration.

Performance

Core

- Improved router update performance during incremental sync by updating service data in place instead of triggering a full router rebuild when only service attributes

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

supported integer values by adding support for floating-point values in the OTLP exporter.

for authenticated credentials with no consumer and no groups (e.g. ACE / Dev Portal application
oup-less identity cannot match a deny list and should be allowed through.

    - Fixed an issue where the ACL decision cache had collisions.

- ai-proxy-advanced:
    - Fixed an issue where we didn't handle SSE event headers correctly.
    - Fixed an issue where native Bedrock request parsing dropped string message content in Kong's internal format, causing other plugins to receive invalid data.
    - Fixed Azure OpenAI Responses API support for deployment-style routing.
- ai-proxy:
    - Fixed an issue where the Bedrock driver could not handle the OpenAI `content_parts` format in system messages, user/assistant messages, and array-typed tool results.
    - Fixed OpenAI-compatible completions requests with string array prompts.
- ai-rate-limiting-advanced:
    - Fixed token counters being decremented on AI Semantic Cache hits.
- openid-connect:
    - Fixed an issue where switching clients within a single request (via `client_arg`) failed to use the matching client's JWK.
    - Fixed an issue where consumer groups could not be resolved when the groups claim was only available from the user info endpoint, which resulted in a `500` error.
- prometheus:
    - A histogram's series (its buckets, `_count` and `_sum`) is now read as one atomic group during a scrape. Previously, the exporter yielded and flushed output between individual samples, so an observation landing mid-scrape could bump `_count`/`_sum` after the buckets were already read, producing an internally inconsistent histogram in a single response.
    - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously, samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.
    - Histograms now expose every bucket (including those with a value of `0`) starting from the first observation of a given label set. Previously, only buckets greater than or equal to the observed value were created, so lower buckets appeared lazily on later scrapes.
- request-transformer:
    - Fixed a regression where `remove.headers` entries in `header:value` format (e.g. `correlationId:1222`) failed to remove the header. The value part is now correctly ignored during removal, restoring the behavior from 3.11.

Core

- **Debugger**: Fixed an issue where instrumenting third-party HTTP client calls produced two indistinguishable `kong.io.http.request` spans for `httpc:request_uri()`. It is now traced under a dedicated `kong.io.http.request_uri` span, and the `connect`, DNS, and internal `request` spans it triggers are nested beneath it. The `kong.io.http.request` span now also reports the `http.url` attribute.
- Fixed an issue where dynamic plugin ordering (`ordering`) leaked into the downstream phases (`header_filter`, `body_filter`, `response`, `log`). Dynamic ordering now again applies only to the `access` phase; downstream phases execute in static plugin-priority order.

Admin API

- Fixed an issue where resetting the password of an admin or developer failed with the error `Old password is invalid`, which happened when the credential was created before the basic auth hashing algorithm was upgraded from SHA1 to SHA256 (e.g. a `kong_admin` user created in an older version and carried over through an upgrade). The old password is now verified with the backward-compatible verification logic that supports both SHA1 and SHA256 hashed passwords.

D

C

, a breaking change in `refresh_slots` that could lead to a lock issue, optimizes hot paths (slot iteration and g strings. This also accepts the `x.y` Redis version format reported by some managed services (e.g. AWS ponent optional, and only warns on Redis version `9.0` or newer instead of `8.0` or newer.

3

R

E

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Fixed an issue where the ACL plugin ignored a consumer's ACL groups when `include_consumer_groups` was enabled and the consumer belonged to an enterprise consumer group, causing incorrect `403` denials (with `allow`) or incorrect access (with `deny`) for authenticated and anonymous consumers. The plugin now falls back to the consumer's ACL groups when no third-party authenticated groups are present.

- ai-mcp-oauth2:
    - Fixed an issue where token-related 401 responses omitted the protected resource metadata URL when a token was provided.
- ai-mcp-proxy:
    - Fixed an issue where non-managed MCP listeners advertised unsupported SSE streams.
- ai-proxy-advanced:
    - Fixed an issue where Gemini service-account authentication probed `metadata.google.internal` when a service account JSON was configured.
    - Fixed an issue where `cache_control` was lost in Bedrock Anthropic format requests using ARN model IDs.
    - Fixed an issue where Bedrock native ConverseStream requests using ARN model IDs could fail when handling streamed responses.
    - Fixed an issue where balancer retries could continue using the last selected targetafter all priority peers were exhausted.
    - Fixed an issue where `cache_creation_input_tokens` and `cache_read_input_tokens` were excluded from prompt token counts, causing undercounting when Anthropic prompt caching was active.
    - Fixed intermittent upstream 401s caused by reused expired Azure managed-identity tokens.
- datakit:
    - Fixed an issue where configuration parsing failed in packaged builds due to a missing jq parser file.
- openid-connect:
    - Fixed an issue where token endpoint responses with `expires_in <= 0` were cached indefinitely when proactive expiry re-check was disabled, causing the plugin to silently forward already-expired tokens to the upstream until a worker/process restart.

Clustering

- Fixed an issue where data planes retried unrecoverable TLS certificate setup failures instead of loading their backup configuration.
- Fixed an issue where pushing a configuration with a datakit plugin whose node `inputs` contained a null value to an older data plane could crash the control plane's config compatibility checker with "attempt to index local 'value' (a userdata value)".

Core

- **router**: Fixed an issue where WebSocket routes (`ws`/`wss`) returned HTTP 404 when using `router_flavor=expressions` due to incorrect protocol matching expressions being generated.

3.14.0.7

Release date 2026/06/23

Bugfix

Core

- Added the missing PDK functions to sandbox environments.

apture consumed streaming response chunks.

ikey of the `key-auth` and `key-auth-enc` plugins was not redacted when captured by the Debugger. This redacted headers.

ng insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.

diately with `no_wait = true` when node level mutex is being held by another worker.

errors could be reported as subsequent socket write failures.

did not update the upstream keepalive pool name. Now includes a cert fingerprint for proper connection

VAL environment variable was not correctly applied to the analytics flush interval.

P

confluent-consume:

cross different SASL credentials and TLS verification settings.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ai-mcp-oauth2:
  - Fixed an issue where token introspection crashed when `client_auth` was set to `private_key_jwt` and `client_jwk` was provided as a JSON string.
- ai-mcp-proxy:
  - Fixed an issue where internal unix-socket subrequests lost the original client IP address, causing IP-aware plugins like ip-restriction to reject legitimate requests.
  - Fixed an issue where empty JSON arrays in MCP server responses were rewritten to empty objects when the plugin re-encoded the body for ACL list filtering.
- ai-proxy-advanced:
  - Fixed an issue where Anthropic streaming finish reasons are not mapped in OpenAI to Anthropic conversion.
  - Fixed an issue where the Anthropic driver dropped the `top_p`, `top_k`, and `stop` parameters when translating OpenAI-format requests. The driver now also omits `temperature`, `top_p`, and `top_k` for models that reject them (Claude Opus 4.7, Opus 4.8, and Fable), preventing upstream 400 errors.
  - Fixed an issue where unsafe model names could construct upstream AI provider paths.
  - Fixed an issue where unsafe batch id could cause upstream AI provider path traversal.
  - Fixed an issue where an unsafe model name in native format adapters could cause upstream AI provider path traversal.
  - Fixed an issue where the xAI driver nested `reasoning_effort` under `reasoning.effort` and did not normalize `reasoning_content` in responses.
  - Fixed an issue where native-format requests using a model alias were incorrectly proxying to upstream model.
- ai-proxy:
  - Fixed an issue where responses with unsupported content types could be returned with an incorrect gzip header.
  - Fixed an issue where the Azure managed identity token was cached indefinitely and never refreshed, causing requests to fail with 401 after the token expired (roughly one hour).
- ai-rate-limiting-advanced:
  - Emitted the documented `X-AI-RateLimit-*` headers on `429` responses from policies that partition by `provider` or `model`.
  - Fixed policy integration with `ai-proxy` for single-target and multi-target AI proxy routes.
- ai-request-transformer:
  - Fixed an issue where unsafe model name could cause upstream AI provider path traversal.
- ai-semantic-response-guard:
  - Fixed an issue where the plugin failed to populate Redis with rule documents due to using worker ID gating instead of worker mutex for vectordb operations.
- datakit:
  - Added Lua control plane compatibility checks to prevent unsupported Datakit configurations from being pushed to older data planes in hybrid mode.
- exit-transformer:
  - Fixed an issue where a response body that was a JSON primitive (e.g. `false`) caused a 500 internal error.
- openid-connect:
  - Fixed an inconsistency where `credential_claim` resolved the same claim name to a different value than `upstream_headers_claims` because it consulted the `id_token` before the `access_token`, while the upstream headers resolver consulted the `access_token` first. With IdPs (like Okta) that set distinct `sub` values in the two tokens, `authenticated_entity.id` did not match the upstream header the plugin set on the same request.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

was sent to the token endpoint for all grant types. It is now included only for the `authorization_code`

`tributes` could leak across concurrent queued `traces`, `logs`, and access log exports when the plugin was

or balancer failures occurred during upstream retries.

uests using Postgres for session storage caused race conditions and session creation collisions.

ay gets cleared before the asynchronous timer thread can safely encode it.

s. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful full-sync.

- Fixed an issue where hybrid data planes retried unrecoverable CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable reconnect storms.
- Fixed an issue where paginated full sync could keep stale pending foreign-key references across a failed resume, causing spurious validation failures.

Configuration

- Increased the default `proxy_ssl_verify_depth` and `lua_ssl_verify_depth` from `1` to `5`.

Dependency

Core

- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

Performance

Plugin

- **ai**:
  - Removed unused redis connection when setting up Redis vectordb.

Core

- **RBAC**: Improved PostgreSQL performance when deleting Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

3.14.0.6

Release date 2026/06/11

Bugfix

Core

- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).

3.14.0.5

Release date 2026/06/04

Feature

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which could avoid the frequent disconnections and reconnection attempts and improve performance. Emitted a log entry telling the config payload size and the configured `cluster_max_payload` size when this happens.

Bugfix

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ock embeddings API were not properly handled, leading to incorrect feedback to the client.

ldn’t function together.

alls lost the original forwarded port on the internal TLS Unix socket.

on (e.g. after a `deck sync`), causing `tools/list` to return empty results.

ld reset the balancer state even when plugin configs were unchanged.

rrors or stream metadata in the wrong return position.

  - Fixed an issue where OpenAI-compatible Anthropic chat requests only preserved the last system message.
  - Fixed an issue where the configured model name wasn't used for the Azure provider.
  - Fixed an issue where we didn't collect the model name in OpenAI streaming responses from Azure.
  - Fixed an issue where the `stream_options` field was forwarded to Databricks upstreams, causing a 400 error since Databricks does not support this field.
- ai-request-transformer:
  - Fixed an issue where runtime template placeholders (e.g. `$(uri_captures.*)`) in `config.llm.model.*` fields were not interpolated.
- ai-response-transformer:
  - Fixed an issue where runtime template placeholders (e.g. `$(uri_captures.*)`) in `config.llm.model.*` fields were not interpolated.
- aws-lambda:
  - Fixed an issue where empty JSON array bodies (`[]`) were incorrectly converted to objects (`{}`) when using `is_proxy_integration=true` and `empty_arrays_mode=correct` alongside the exit-transformer plugin.
  - Fixed an issue where a 500 error occurred when `is_proxy_integration` was enabled and the Lambda function returned `null` values in `headers` or `multiValueHeaders`. Null values are now converted to empty strings.
- forward-proxy:
  - Added the `ca_certificates` parameter for per-plugin TLS verification. This setting allows certificate chain and hostname checks against specified CAs instead of global settings, ensuring explicit trust.
- jwt-signer:
  - Fixed an issue where the plugin failed to load configuration and errored when `null` or `nil` values were passed to `access_token_keyset` or `channel_token_keyset`.
- oas-validation:
  - Fixed an issue where the OAS specification cache failed to distinguish between different values of `api_spec_encoded` for the same specification content.
  - Fixed an issue where path parameters were extracted from the wrong URI segment when `custom_base_path` was used with bare `/{param}` paths.
- openid-connect:
  - Fixed an issue where Redis-backed session storage could fail when Redis connections were routed through a proxy.
- opentelemetry:
  - Fixed an issue where the template `resource_attributes` in the plugin configuration didn't work as expected for metrics.
- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.
- ai-semantic-prompt-guard, **ai-semantic-response-guard**: Fixed an issue where full-sync reconfiguration rebuilt semantic vectorDB indices even when the plugin configuration was unchanged.

Clustering

- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.
- Fixed an issue where incremental DP (sync v2) would not export config to fallback storage when the control plane used periodic polling instead of `notify_new_version`.

C

hrough IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim
ncurrent authentication requests.

D

C

P

C

oducing a shared payload pool and reducing the default local buffer size.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

3.14.0.4

Release date 2026/05/28

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-40701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.
- Security: Fixed CVE-2026-6338 in core proxy request header handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header cleanup, preventing CL.0 request smuggling with crafted `Connection: Content-Length` headers on requests with a body.

Dependency

Core

- Bumped libexpat from 2.7.3 to 2.8.1 to address the issues: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-2026-41080, and CVE-2026-45186.
- Bumped OpenSSL from 3.5.5 to 3.5.6 to address the issues: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-2026-28390, and CVE-2026-31789.

3.14.0.3

Release date 2026/05/25

Bugfix

Plugin

- **ai-guardrail**:
  - Fixed an issue where latency metrics were missing in the Prometheus output.
- ai-azure-content-safety:
  - Fixed a crash (HTTP 500) that occurred when `azure_use_managed_identity` was enabled.
- ai-mcp-oauth2:
  - Fixed an issue where downstream scope-based ACL evaluation used claims from the inbound token instead of the exchanged token when token exchange was enabled.
- ai-mcp-proxy:
  - Fixed an issue where, since 3.14, call tools converted from API could fail when Kong used a self-signed certificate.
  - Fixed an issue where the tool ID might be repeated.
  - Fixed an issue where raw non-200 upstream responses triggered misleading MCP body parse warnings.
- ai-prompt-decorator:
  - Fixed an issue where the plugin corrupted native-format requests (Gemini, Anthropic, Bedrock, Cohere, Hugging Face) by forwarding an OpenAI-shaped body upstream instead of the original native body shape.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d sometimes.

ersion of Realtime API.

g requests were not mapped consistently across Anthropic, Gemini, Bedrock and more providers.

le was truncated when doing non-passthrough proxy.

token usage when it was available.

model in the streaming path, causing it to always fall back to the request model.

e requests with a 500.

not parse the request body correctly.

C

- Fixed an issue where anonymous reports omitted model usage when one provider used multiple models.
- Fixed an issue where the request context could inherit metatables from previous TLS connections, leading to cross-request context leakage and increased memory usage.

3.14.0.2

Release date 2026/04/28

Bugfix

Plugin

- **ai-transformers**:
  - Fixed an issue where AI Request Transformer and AI Response Transformer plugins did not work properly with the Ollama provider.
- acl:
  - Fixed an issue where anonymous consumers with valid legacy ACL group credentials were rejected with 403 when `include_consumer_groups` was enabled and no enterprise consumer groups were assigned.
- ai-mcp-oauth2:
  - Fixed an issue where token exchange actor tokens were not sourced correctly from `token_exchange.request`, ensuring correct forwarding of actor tokens configured in headers or plugin config.
  - Fixed an issue where `token_exchange.cache.enabled = false` was ignored and exchanged tokens were still cached because the cache toggle incorrectly read `token_exchange.cache.ttl` instead of `token_exchange.cache.enabled`.
- ai-mcp-proxy:
  - Fixed an issue where the `WWW-Authenticate: Bearer error="insufficient_scope"` header was not emitted.
- ai-proxy-advanced:
  - Fixed an issue where observability errors occurred when `gpt-image-1.5` returned image token usage details.
  - Fixed an issue where Azure OpenAI authentication failed during load balancer failover due to token refresh attempts in `balancer_by_lua`. Tokens are now pre-fetched in the `access` phase.
  - Fixed an issue where we treated plaintext Anthropic response as gzipped.
  - Fixed an issue where we didn't correctly ungzip the streaming response.
  - Fixed an issue where Claude Code (or CLI) statistics were missing when using an Anthropic model via the Bedrock provider.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the GraphQL Rate Limiting Advanced plugin's API threw 500 errors when handling HTTP PUT requests.
- jwt:
  - Fixed an issue where malformed JWT tokens (e.g. tokens without dots) caused a 500 Internal Server Error instead of returning 401 Unauthorized.
- kafka-log:
  - Fixed an issue where cached producers could cause memory leaks.
- opa:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ion/json content-type with charset, ensuring proper handling of JSON request bodies.

449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.

could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after ts that pass rate limiting, by updating its priority from 915 to 901.

C

nts were incorrectly included in Redis spans.

e TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side

oncatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g.

- Fixed a bug where tables in `strict` and `lax` `untrusted_lua` modes were not properly protected against modification.
- Fixed an issue where `$remote_addr` was not replaced with the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` is enabled on the proxy listener. Also added proper error body messages for 501 and 505 status codes.
- Fixed an issue where the real client IP from Proxy Protocol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497 plain HTTP to HTTPS port) or when the client disconnected prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from `$proxy_protocol_addr` on early request termination, and added `error_page` 497 routing through `kong_error_handler`.

Clustering

- Fixed an issue where Incremental Sync (ICS) would crash and stop further sync attempts.
- Fixed an issue where the DP could spawn multiple sync timers when downgrading sync protocol to v1, which could cause excessive load on the CP and lead to performance degradation.
- Fixed clustering sync reliability issues by immediately failing pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

Kong Manager

- Fixed an issue where the `tls_sans` field was missing in the service entity form.

Dependency

Core

- Bumped kong-gql from 0.2.3 to 0.2.4 to fix the null value issue in the GraphQL query syntax that caused a parsed AST error in DeGraphQL plugin.
- Bumped kong-pgmoon from 2.3.3.0 to 2.3.4.0, which adds SHA-384 support for SCRAM channel binding during PostgreSQL SSL authentication.
- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2.

3.14.0.1

Release date 2026/04/10

Bugfix

Plugin

- openid-connect:
  - Fixed an issue where nested claim paths were not resolved correctly.

3.14.0.0

Release date 2026/04/07

Breaking Change

Core

- **Configuration**: The `tls_certificate_verify` option is now enabled by default, preventing Kong from bypassing certificate verification on any secure connection.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Plugin

- ai-rate-limiting-advanced:
  - Removed the `parse-request` shared filter and deprecated the `llm_format` configuration field.

Feature

Plugin

- **AI Plugins**:
  - Added support for custom GCP OAuth token and metadata endpoints via `gcp_oauth_token_url` and `gcp_metadata_url` configuration options in the `auth` section. This enables GCP authentication in restricted network environments or with custom GCP endpoints.
- **llm**:
  - Added bytes-based tokenizer.
  - Added `conf.model.metadata` configuration to specify model options separately from the main configuration. Metadata options are merged into the model options during request normalization
- **solace-upstream, solace-log, solace-consume**:
  - Added support for the global `tls_certificate_verify` option. When enabled, plugins using secure protocols (tcps://, wss://, https://) must have `ssl_validate_certificate` set to `true`.
- **vectordb**:
  - Added Valkey support for vector database operations, providing an alternative to Redis Stack for vector search capabilities.
  - The option `ssl_verify`, which control SSL certificate verification for the pgvector database, is now enabled by default.
- acl:
  - Added WebSocket protocol support (`ws`/`wss`). The plugin now enforces allow/deny group rules during the WebSocket handshake phase.
- acme:
  - Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `storage_config.redis.tls_verify` setting cannot be disabled.
- ai-a2a-proxy:
  - Added A2A analytics support for Konnect, enabling visibility into A2A protocol operations including method calls, latencies, and task states.
  - Added new plugin for Google A2A (Agent-to-Agent) protocol support, enabled AI agent interoperability with JSON-RPC and REST bindings, built-in observability.
  - Added Prometheus and OpenTelemetry observability with A2A-specific metrics and tracing spans.
- ai-aws-guardrails:
  - the `ssl_verify` option to validate TLS certificate when connecting to the bedrock service is now enabled by default.
- ai-azure-content-safety:
  - the `ssl_verify` option to verify the certificate presented by the Azure Content Safety service when using HTTPS is now enabled by default.
- ai-custom-guardrail:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

s integration with 3rd party guardrail service.

ds.

credential.

ns before accessing MCP Server.

claims to upstream headers using path-based access. Mutually exclusive with `claim_to_header`.

uth is set to something other than client_secret_basic or client_secret_post

er and `consumer_groups`.

e when doing MCP conversion.

  - Added support for ACL with OAuth claim.

- ai-proxy-advanced:
  - Added ACL support that blocks requests matching deny rules, requires allow rules to pass when present, and resolves consumer/model values once per request.
  - Added native passthrough support for Vertex AI multimodal embeddings. Introduced new `llm/v1/multimodal-embeddings` route type.
  - Added support for DeepSeek provider.
  - Added support for proxying cohere embeddings models on bedrock.
  - Added support for vLLM provider.
  - Added support for databricks provider.
  - Added the ability to select target models by request models in same AI Proxy Advanced plugin.
  - Added the Ollama provider, for native support for all Ollama-hosted models.
  - Updated to use /v2/chat when proxying text generation request to cohere provider.
- ai-proxy:
  - Added native Anthropic streaming mode support, enabling direct passthrough of Anthropic SSE events with proper message reordering for tool calls.
  - Added support for batch API in openai-compatible mode when providers are anthropic, bedrock, gemini and gemini vertex.
- ai-rate-limiting-advanced:
  - Added a policy-based rate limiting mode with multi-dimensional match conditions and request counting strategy.
  - Added prompt token estimation for `prompt_tokens`, `total_tokens`, and `cost` strategies in policies mode, enabling early request rejection before the upstream responds.
- aws-lambda:
  - Added `ssl_verify` config field to control SSL certificate verification when connecting to AWS APIs.
- azure-functions:
  - the `https_verify` option to validate the Azure Functions server certificate is now enabled by default.
- basic-auth:
  - Uses SHA256 by default even in non-FIPS mode instead of SHA1.
- confluent-consume:
  - the `security.ssl_verify` option to validate the server certificate is now enabled by default.
- confluent:
  - the `security.ssl_verify` option is now enabled by default.
- datakit:
  - Added JWT nodes: `jwt_decode` for decoding tokens without verification, `jwt_verify` for signature verification and claim validation using JWKS, and `jwt_sign` for creating and signing JWTs.
  - Added more implicit node outputs: * `request.path` * `request.raw_path` * `request.port` * `request.method` * `request.scheme` * `request.version` * `service_response.status` * service_response.raw_body * call.raw_body
  - Consumer can now be set via property node.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

S certificate when making HTTPS requests is now enabled by default.

on verifies the upstream server certificate presented after the plugin establishes a `CONNECT` tunnel through

certificate presented by the server of the OCSP responder's URL and by the server of the CRL Distribution

MAC-SHA1 from the default set of algorithms (still supports HMAC-SHA1 when configured).

nt server certificate is now enabled by default.

- Added support for `allow_non_json_requests` configuration to allow non-JSON requests to bypass all checks.

- jwt-signer:
  - The options `access_token_endpoints_ssl_verify` and `channel_token_endpoints_ssl_verify`, which control SSL certificate verification for signature verification and introspection endpoints, are now enabled by default.
- kafka-consume:
  - Added support for posting commit offsets.
- kafka-log:
  - The options `security.ssl_verify` which control SSL certificate verification for Kafka endpoints, are now enabled by default.
- kafka-upstream:
  - The option `security.ssl_verify`, which controls the verification of the certificate presented by the server, is now enabled by default.
- ldap-auth-advanced:
  - the `verify_ldap_host` option to validate the LDAP server certificate is now enabled by default.
- ldap-auth:
  - the `verify_ldap_host` option to validate the LDAP server certificate is now enabled by default.
- metering-and-billing:
  - Added a new plugin for metering and billing.
- mtls-auth:
  - Added WebSocket protocol support. This authentication plugin can now protect WebSocket connections (`ws` and `wss` protocols) in addition to HTTP/HTTPS. In hybrid mode, using `ws`/`wss` with this plugin requires data planes running DP >= 3.14, or explicit removal of `ws`/`wss` protocols from configurations targeting older data planes.
  - the `ssl_verify` option to validate verification of the certificate presented by the server of the OCSP responder's URL and by the server of the CRL Distribution Point is now enabled by default.
- oauth2-introspection:
  - The authenticated token is now stored in the request context via `kong.client.set_token`.
- oauth2:
  - The authenticated token is now stored in the request context via `kong.client.set_token`.
  - Uses SHA256 for access token cache key instead of SHA1.
- openid-connect:
  - Added `consumer_claims` to support mapping consumers from multiple claim paths, while retaining and supporting the existing `consumer_claim` as a shorthand configuration.
  - Added `jwks_endpoint` configuration to override the discovered `jwks_uri` when a custom JWKS endpoint is required.
  - Added support for token exchange from multiple IdPs based on RFC8693.
  - Added `upstream_headers` and `downstream_headers` schema fields that support nested claims.
  - Added WebSocket protocol support. This authentication plugin can now protect WebSocket connections (`ws` and `wss` protocols) in addition to HTTP/HTTPS. In hybrid mode, WebSocket protocol support for this plugin requires data planes running Kong Gateway 3.14 or later; for older data planes, ensure routes do
    be blocked.

    rospection_endpoint are now supported as vault references.

    t context via `kong.client.set_token`.

    er certificate) and the `session_memcached_ssl_verify`(for verifying session storing memcached server
    ell.

    lember ID attributes to OpenTelemetry metrics in Konnect mode.

    code snippets. The previous `access_logs_endpoint` schema field has been deprecated in favor of a new
    longside the `access_logs.custom_attributes_by_lua` field to specify Lua code snippets for custom

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Added support for official MCP metrics
  - Added the Konnect Cluster ID and the optional Cluster Member ID to access logs.
  - Support WebSocket related metrics to OpenTelemetry plugin for enhanced observability.
- request-callout:
  - The option `callouts.http_opts.ssl_verify`, which controls the verification of the certificate presented by the server, is now enabled by default.
- solace-upstream:
  - Added `content_type` / `content_encoding` (with request-header fallback) and `forward_body_raw_only` for raw payload passthrough; headers can be forwarded into Solace user properties.
- tcp-log:
  - the `ssl_verify` option is now enabled by default.

Core

- **active-tracing**: Added auto-decompression for gzipped bodies when capturing payload
- Added request and response content evolution support to the debugger session. This allows the debugger to capture and compare request and response contents across different phases of the request lifecycle, providing insights into how the contents change as they flow through Kong Gateway.
- Added support for PostgreSQL OAuth/OAUTHBEARER SASL authentication. Kong can now authenticate with PostgreSQL using OAuth 2.0 bearer tokens obtained via client credentials grant from an identity provider. This requires PostgreSQL 18+ with OAUTHBEARER support and the updated pgmoon library with OAUTHBEARER SASL implementation.
- Added support for sampling rate in sessions of active tracing
- **Conditional Plugin Execution**: Added support for conditional plugin execution through a new `condition` field in the plugin configuration. Plugins can now be conditionally skipped at runtime based on request attributes such as HTTP method, path, headers, query parameters, consumer, route, service, and network information. The condition expression uses the ATC expression language and is evaluated once during the collecting phase; skipped plugins are excluded from all downstream phases automatically.
- **core**: Added support for decoding JSON null values in objects as Lua `nil` via `cjson.decode_null_object_value_as_nil` (and exposed as `kong.tools.cjson.decode_null_object_value_as_nil`).
- **debugger**: Add CPU profiling support for debugger to Kong.
- **debugger**: Added sanitization support for payload using configurable redaction rules.
- **debugger**: Added status code and status message to plugin span attributes when using kong.response to exit.
- **DP Resilience**: Added support for Azure Blob Storage in config sync backup strategy.
- **event-hooks**: The options `ssl_verify` for the webhook type handler are now enabled by default.
- **Hashicorp Vault**: Added AWS auth method authentication to the HashiCorp Vault backend.
- **Hashicorp Vault**: Added Azure authentication to the HashiCorp Vault backend.
- **Hashicorp Vault**: Added GCP auth method authentication to the HashiCorp Vault backend.
- **Hashicorp Vault**: Added `ssl_verify` config field to control SSL certificate verification when connecting to Hashicorp Vault servers.
- Kong will validate the database connection configuration at startup and will not start if errors are detected.
- **sandbox**: Added `strict` and `lax` modes for `untrusted_lua`. The default mode changed from `sandbox` to `strict`.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

C

ict_mode that controls the behavior when a deprecated alias field and its canonical replacement field are
rror preserves the existing strict validation behavior. Setting it to warn accepts the configuration with a
owing upgrades to proceed without requiring all legacy plugin configurations to be corrected first.

hory LRU cache size.

ection parameters on Control Plane.

P

eve a decoded JWT token payload.

ve a decoded JWT token header.

shared authenticated token.

- Added `kong.client.set_token()` function to share authenticated token with other plugins.

Performance

- **metrics**: Added metrics to show the time consumption excluding upstream, third-party I/O, and client in the HTTP context for Prometheus, Analytics, and logs.

Bugfix

Plugin

- **confluent, confluent-consume**:
  - Fix issue where Kafka plugin failed to encode and validate message keys when using Confluent Schema Registry.
- **kafka**:
  - Fix issue where Kafka plugin produced records with incorrect `offsetDelta` in the record package.
  - Fixed issue where Kafka message key deserialization failed silently, returning raw string data instead of deserialized objects.
- **kafka-consume, confluent-consume**:
  - Increased the minimum API version of FetchRequest from 0 to 4 for Kafka 3.x. For Kafka 4.0 it is already using version 4.
- **kong.service.request.clear_query_arg**:
  - Fixed an issue where an extra = was appended to empty query arguments.
- **llm**:
  - Fixed an issue where we could not specify the correct dimensions for Gemini embeddings model provider.
  - Removed ineffective `ssl_cafile` parameter from HTTP requests. This parameter is not supported by lua-resty-http and was silently ignored. TLS verification relies on the global `lua_ssl_trusted_certificate` nginx directive.
- **solace-upstream, solace-log, solace-consume**:
  - Fixed an issue where enabling `ssl_validate_certificate` would fail because `SESSION_SSL_TRUST_STORE_DIR` was not set.
- acl:
  - Fixed an issue where the ACL plugin did not check consumer groups from all sources, causing it to incorrectly deny access when consumer groups were set by other plugins like ACE in `ngx.ctx.authenticated_consumer_groups`.
- ai-aws-guardrails:
  - Allowed streaming of responses when `guarding_mode` was set to `INPUT` with `allow_masking` enabled.
- ai-gcp-model-armor:
  - By default now blocks unrecognized/new filters added to GCP Model Armor.
- ai-mcp-oauth2:
  - Fixed an issue where we didn't clear header for absent claim.
- ai-mcp-proxy:
  - Fixed an issue where ACL denial caused parsing body failure.
  - Fixed an issue where the ACL metric label value was incorrect.
  - Fixed an issue where `tools/list` could expose tools to consumers denied by tool ACL in listener mode.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

MCP conversion.

to konnect since 3.13.

error.

fines the Authorization error codes which are different from ours.

API was unavailable in Cohere native format.

in multiple drivers.

penAI format was broken.

-200 response of streaming request, was overridden.

actively refreshed before expiration.

re incorrect according to https://opentelemetry.io/docs/specs/semconv/gen-ai/gen-ai-spans.

  - Fixed excessive DNS warning logs for template variable endpoints like `$(headers.x_gcp_endpoint)`. These warnings appeared on every configuration change because template variables cannot be resolved until request time.
  - Fixed structured output and tool calls for Ollama (also Llama2 and Mistral) providers.
  - Fixed `usage.cost` for OpenAI `llm/v1/files/{file_id}/content` batch output analytics.
  - Fixed zero usage statistics for OpenAI `llm/v1/responses` in streaming mode.
  - Updated mappings for Ollama (also Llama2 and Mistral) providers.
- ai-proxy:
  - Fixed a crash in the observability module when upstream returned `choices: null` (JSON null). The `header_filter` phase would crash with "attempt to get length of field 'choices' (a userdata value)" because `ngx.null` is truthy in Lua.
  - Fixed an issue where format-compatible streaming routes did not collect metrics and logging.
  - Fixed streaming token count metrics for third-party models hosted on Vertex AI (claude-, *mistral*-, jamba-*) that reported inflated totals because incremental counts were treated as cumulative.
- ai-rate-limiting-advanced:
  - Extended deferred rate limiting callback to support model-partitioned policies and cost strategy.
  - Fixed an issue where the plugin did not validate whether the configured `dictionary_name` exists before use, which could lead to runtime errors.
- ai-sanitizer:
  - fixed an issue where the sanitizer plugin always sanitize the entire request body, which was fixed with latest message only.
- ai-semantic-prompt-guard:
  - Fixed an issue where a vectorDB error occurred during initialization or config reload.
- aws-lambda:
  - Fixed an issue where headers from Lambda proxy responses were not merged correctly, causing case-insensitive header deduplication to fail. User-supplied headers now properly overwrite existing headers regardless of casing.
  - Fixed an issue where Lambda responses with empty or null body caused 500 errors when `is_proxy_integration` is enabled.
- basic-auth:
  - Brute Force Protection: when using redis strategy and the connection fails, the plugin will now fall back to using the memory strategy.
- datakit:
  - Fixed an issue where datakit cache node instantiate proxy-cache-advanced redis module at config time causing dependency issue on Koko.
  - Fixed type system bug to allow defining maps with string values for vault node.
  - Fixed xml_to_json node to recognize `text/xml` content-type in addition to `application/xml` for XML request body processing, ensuring RFC 7303 compliance.
- degraphql:
  - Fixed an issue where the plugin failed to parse GraphQL variables with nested array types like `[String]!`. The error `attempt to index field 'name' (a nil value)` occurred because the type parser did not correctly handle deeply nested type structures such as `nonNullType(listType(namedType))`.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the plugin could fail to connect to the upstream server to introspect the upstream schema.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

o certain injection patterns.

t Alternative Name (SAN) DirectoryName extensions caused authentication errors. Added a new
cify which Distinguished Name attributes from the SAN DirectoryName extension should be used for

used a runtime crash when `collect_all_errors` was enabled.

  - Fixed an issue where swagger `formData` parameters were not properly handled.
  - Fixed an issue where `minLength` and `maxLength` constraints defined in a Swagger 2.0 parameter schema were not enforced.
  - Fixed an issue where the validator cache did not account for the `collect_all_errors` setting.
  - Fixed an issue where response body buffering was not properly disabled when `validate_response_body` was set to `false`.
- opa:
  - Fixed json body processing to recognize `application/json` content-type with charset, ensuring proper handling of JSON request bodies.
- openid-connect:
  - Fixed an issue where the `username` and `password` were used for Redis Sentinel and no authentication supported for Redis, causing `NOAUTH Authentication Required` errors.
  - Fixed an issue where client-provided headers could be forwarded to upstream services when the corresponding JWT claim was missing from the token. The plugin now clears client headers before processing `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or downstream.
- opentelemetry:
  - Fixed an issue where invalid `x-b3-flags` header values caused 500 responses.
  - Fixed an issue where the `kong.upstream.status_code` field of access logs was incorrectly populated with string value instead of integer value when there was one or more retries to the upstream.
  - Fixed an issue where the `http.response.status_code` attribute of the `http.server.request.count` metric was incorrectly set to `kong.response.status_code`. Now, the attribute name follows the OTel specification.
  - Fixed an issue where valid response codes from vendor endpoints were incorrectly rejected when exporting `traces`, `logs` or `metrics`.
- request-callout:
  - Fixed keepalive support in callout HTTP requests to improve connection reuse and performance.
- request-transformer:
  - Fixed an issue where the `add.headers` operation lowercased the header name, causing the configured letter case to be lost when adding new headers to the request.

Core

- Apply Nginx patch for a man-in-the-middle upstream response injection (CVE-2026-1642)
- **core**: Resolved an issue where HTTPS was incorrectly detected if multiple `X-Forwarded-Proto` values were provided.
- Fixed an issue where context sensitive plugins would not execute when dynamic ordering is enabled in the plugins iterator.
- Fixed an issue where DP's proxy listener could not be verified because of it was disabled in CP.
- Fixed an issue where functions in required sandbox modules could not be called in sandboxed Lua code due to the `__call` metamethod not being properly handled.
- Fixed an issue where GCP Vault authentication method order could not be set by the `GCP_AUTH_METHOD_ORDER` environment variable.
- Fixed an issue where in the postinstall script that changed /etc/kong/kong.logrotate's ownership and permissions; the script now restores ownership to root:root and sets permissions to 0644.
- Fixed an issue where `kong health` command would fail to run when kong configuration contains vault references.
- Fixed an issue where PDK logs were not captured by observability when your gateway log level was higher than the log entry level.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

orrect `latencies.client` values due to not capturing the access end time properly. This fix ensures that
f Active Tracing being active or not.

OpenTelemetry traces showed the same hostname for all retry attempts instead of capturing the specific

re cannot fetch a correct credential for connecting to Azure Redis, especially when using Azure Workload

eaders and body) of external HTTP or Redis calls were not being recorded in the Content Evolution

Sandbox environment.

fy option is enabled, service entities with an unset tls_verify field would fail validation. The tls_verify field
ot explicitly set.

on via token caching.

esponses when RPC calls fail, instead of silently ignoring the failures.

- **vault**: Fixed an issue where `kong.vault.update()` changed the secret to an empty string temporarily after changed vault config.
- **websocket**: Fixed an issue where proxied WebSocket services did not fall back to Nginx's `proxy_ssl_verify` when `tls_verify` was left unset.

Clustering

- Fixed an issue where a SQL injection vulnerability existed in the clustering RPC procedure, ensuring safer SQL operations.
- Fixed an issue where the balancer's health checker is not properly clean up when config changed in CP/DP mode.
- Fixed an issue where using Google Cloud Storage cannot use the Application Default Credentials method order when the environment variable GCP_AUTH_METHOD_ORDER is set to "adc".

Configuration

- Fixed an issue where disabling `tls_certificate_verify` via `kong reload` did not take effect because the derived `proxy_ssl_verify` directive persisted in `.kong_env` from a previous reload.

Dependency

Core

- Bumped lua-resty-gcp from 0.0.16 to 0.0.19 to address GCP access token handling improvements.
- Bumped OpenSSL from 3.4.3 to 3.5.5 to address the issue: CVE-2025-15467.

Performance

Plugin

- ai-mcp-proxy:
  - reduced tool cache build time and avoided long blocking.
- ai-proxy-advanced:
  - decoded OpenAI response only when necessary.

Core

- **core**: Reduced transient table churn and associated GC pressure by introducing preallocated table pools for hot-path table allocations.

Admin API

- Optimized `GET /kong` endpoint to use `SELECT DISTINCT` for populating `enabled_in_cluster` instead of iterating all plugin rows.

3.13.0.11

Release date 2026/09/28

Bugfix

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

would keep blocking certificate issuance. Retries are now rejected only while the backoff timestamp is

calls lost the original forwarded port on the internal TLS Unix socket.

models hosted on Vertex AI (claude-, *mistral*-, jamba-*) that reported inflated totals because incremental

dy without a correct `Content-Type`. It now uses the content type that the source node declares, for
t, and defaults to `application/octet-stream` in the request phase.

ode when the body input is a JSON null. The node sent the internal Lua value as the string "userdata:
body.

- jwt:
  - Fixed an issue where the plugin failed to decode standard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.
- openid-connect:
  - Fixed an issue where disabling `verify_signature` gave no warning, even though it also skips signature verification for bearer tokens from clients. The plugin now logs a warning when `verify_signature` is `false` and `auth_methods` includes `bearer`. It logs a notice instead when `bearer` is not enabled.
- prometheus:
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
  - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.
- request-callout:
  - Fixed an issue where a callout that failed and then succeeded on retry still returned the earlier failed response. The plugin now returns the response from the successful retry.
- kafka-consume, **confluent-consume**: Fixed an issue where the consumer group subscription declared protocol version 1 but carried the version 0 layout, so a topic-rewriting proxy rejected it.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.

Clustering

- Fixed an issue where a data plane failed to load config updates when a CA certificate expired. The data plane now accepts the config and logs a warning.
- Fixed an issue where the data plane router rebuild could falsely abort with a concurrent-change error when the router spanned more than one page, leaving routes stale until the next config push.

Core

- Fixed an issue where an in-flight request that completed after its upstream target became unavailable could restore the target to the latency balancer and route subsequent requests to it.
- Fixed an issue where Kong API Gateway skipped the WebSocket `ws_close` phase when it could not proxy the request.
  - Fixed an issue where Kong API Gateway in DB-less mode could fail to detect configuration changes during reconfiguration, leaving the router or plugins iterator stale.
- **Konnect Only**. **Debugger**: Added new debugger span attributes `tls.client.server_name`, `proxy.kong.upstream.address`, `proxy.kong.request.host`, `http.request.header.connection`, `proxy.kong.client.connection.request_count`. Removed debugger span attributes `proxy.kong.upstream.host`, `proxy.kong.upstream.addr`, `http.request.header.host`, `proxy.kong.client.keepalive`

Dependency

Core

- Bumped avro-c to 1.12.2.
- Bumped jansson to 2.15.1.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

P

C

incremental config update.

incremental sync enabled under some circumstances.

Plugin

- oas-validation:
  - Improved plugin performance by removing unnecessary hash computation. Enabling the plugin now adds much less latency and CPU overhead to requests.

3.13.0.10

Release date 2026/08/20

Bugfix

Plugin

- ai-proxy-advanced:
  - Fixed a bug where a response from Anthropic could fail to decode when the client's request advertised Brotli support, since Anthropic's edge may then return a Brotli-encoded body that Kong's response decompression – which only understands gzip – can't inflate. Kong now normalizes the outgoing `Accept-Encoding` request header before proxying to any LLM provider: `gzip, identity` when the client accepts gzip, and `identity` otherwise, so a client that cannot inflate gzip is never handed a compressed body on the paths that pass the upstream response through untouched.
- datakit:
  - Fixed an issue where the `response` node set `Content-Type: application/octet-stream` for `json_to_xml` output. It now defaults to `application/xml` when no explicit `Content-Type` is provided.
- jwt-signer:
  - Fixed an issue where the plugin failed to set the signed access token header on the upstream request, when `access_token_upstream_header` (or `original_access_token_upstream_header`) had the same name as `channel_token_request_header`.
- mocking:
  - Fixed a memory leak where the plugin config cache did not use weak keys due to a misspelled `__mode` metatable field.
- oauth2-introspection:
  - Fixed an authentication bypass where a revoked or expired token stayed authorized indefinitely instead of being rejected. An authoritative `active:false` result is now also cached briefly (5 seconds).
- openid-connect:
  - Fixed an issue where the `redirect_uri` parameter was sent to the token endpoint for all grant types. It is now included only for the `authorization_code` grant, as required by RFC 6749.
  - The `ignore_signature` option now logs a warning when it is set, because it turns off JWS signature verification for the listed grants.
- opentelemetry:
  - Fixed an issue where the `kong.dp.cluster_cert.expiry` metric reused the same datapoint timestamp across exports, causing monitoring systems to treat the series as stale.
- saml:
  - Hardened signature validation against XML Signature Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that names the `ID` of the element it digests and consumes, so a signature can no longer be bound to a different element than the one that provides the identity. A response whose reference URI is empty or not a same-document fragment is now rejected.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a crash that occurred when a plugin set `schema_registry.confluent.authentication.mode` to `oauth2` but omitted the `oauth2_client` record. Previously this returned a 500 from the Admin API during validation, and once saved it also crashed at runtime while fetching the schema registry OAuth2 token. The absent `oauth2_client` is now handled and falls back to the default authentication method, so a configuration without `oauth2_client` works end-to-end.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

confluent-consume: Fixed an issue where OAuth2 authentication against Confluent Cloud Schema
d `target-sr-cluster` header.

P

method and query were reported incorrectly, or could raise an error, when a request hit the error handler

C

per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.

crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`,

plane ready before the new router and plugins iterator became active. Kong now reports readiness only
re installed.

mittent 503 responses while a failover target remained healthy.

- **Konnect Only**. **Debugger**: Fixed an issue where deep copy of the worker logs stack overflowed by replacing `deep_copy` with `cycle_aware_deep_copy`.
- On shell-free (distroless) images, the pluginserver query and start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with a clear error on an unterminated quote or `${`, instead of passing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.

Clustering

- Fixed an issue where the control plane could crash while handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as a ping/pong control frame) arrived before the `basic_info` frame. The control plane now drains and responds to control frames during the handshake until the expected frame is received, instead of dereferencing a nil plugin list.
- Improved RPC connection stability during long-running calls: a data plane now cancels a timed-out RPC so a late response cannot disrupt later calls, and the connection is kept alive (within a bound) while calls are still in flight instead of being dropped as a missed heartbeat.

CLI Command

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Kong Manager

- Fixed an issue where the Export button on the Vitals Reports page did not download the report CSV.

Performance

Clustering

- Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.
- Optimized performance of clustering payload handling for version compatibility. This reduces CPU usage and transient memory pressure.

Admin API

- Improved the performance of listing workspaces with `?counter=true`. Entity counts for the whole page are now retrieved with one grouped query per entity type instead of a separate count query per entity type per workspace, while keeping the counts exact.

Core

- Reduced config update latency on hybrid data planes by notifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in parallel.

3.13.0.9

Release date 2026/08/10

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-42533.
- Applied upstream nginx security patches for CVE-2026-56434.
- 0005.
- 2055 and CVE-2026-48142.

P

gin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly
g a crafted unsigned SAML response from silently bypassing authentication under configurations that set

D

C

3

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Release date 2026/07/27

Feature

Core

- Added a Distroless Docker image variant for Kong API Gateway. The Distroless image ships only the Kong binary and its runtime dependencies, with no package managers, no shells or any other programs you would expect to find in a standard Linux distribution.

Bugfix

Plugin

- ai-mcp-oauth2:
  - Fixed an issue where token-related 401 responses omitted the protected resource metadata URL when a token was given.
- ai-mcp-proxy:
  - Fixed an issue where non-managed MCP listeners advertised unsupported SSE streams.
  - Fixed an issue where the ACL decision cache has collision.
- ai-proxy-advanced:
  - Fixed an issue where unsafe model names could construct upstream AI provider paths.
  - Fixed an issue where the configured auth header (`api-key` or `x-api-key`, for example) leaked the provider credential into access logs instead of being redacted.
  - Fixed an issue where unsafe batch IDs could cause upstream AI provider path traversal.
  - Fixed an issue where unsafe model names in native format adaptors could cause upstream AI provider path traversal.
  - Fixed an issue where the Anthropic driver dropped the `top_p`, `top_k`, and `stop` parameters when translating OpenAI-format requests. The driver now also omits `temperature`, `top_p`, and `top_k` for models that reject them (Claude Opus 4.7, Opus 4.8, and Fable), preventing upstream 400 errors.
  - Fixed Azure OpenAI responses support in deployment style.
- ai-proxy:
  - Fixed Gemini driver dropping Gemini-native fields (`cachedContent` or `safetySettings`, for example) and Vertex AI-only fields (`labels`, for example) during OpenAI-to-Gemini request transformation.
- ai-request-transformer:
  - Fixed an issue where unsafe model names could cause upstream AI provider path traversal.
- ip-restriction:
  - Fixed an issue where warn log messages didn't include the plugin name, making it difficult to identify the source of blocked requests.
- oas-validation:
  - Fixed an issue where the OAS specification cache failed to distinguish between different values of `api_spec_encoded` for the same specification content.
- openid-connect:
  - Fixed an issue where switching clients within a single request (via `client_arg`) failed to use the matching client's JWK.

e resolved when the groups claim was only available from the user info endpoint, which resulted in a `500`

C

LS certificate setup failures instead of loading their backup configuration.

ull sync from resuming.

C

r under sustained HTTPS traffic.

returned HTTP 404 when using `router_flavor=expressions` due to incorrect protocol matching

D

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped kong-redis-cluster from 1.5.7 to 1.6.0.

Performance

Core

- Improved router update performance during incremental sync by updating service data in place instead of triggering a full router rebuild when only service attributes change.

3.13.0.7

Release date 2026/06/30

Feature

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which could avoid the frequent disconnections and reconnection attempts and improve performance. Emitted a log entry telling the config payload size and the configured `cluster_max_payload` size when this happens.

Bugfix

Plugin

- **kafka-upstream, kafka-log, kafka-consume, confluent, confluent-consume**:
  - Fixed Kafka keepalive pools leaking connections across different SASL credentials and TLS verification settings.
- ai-azure-content-safety:
  - Fixed a crash (HTTP 500) when `azure_use_managed_identity` is enabled.
- ai-mcp-proxy:
  - Fixed stale tools cache after full-sync reconfigure (e.g. `deck sync`), causing `tools/list` to return empty results.
- ai-proxy-advanced:
  - Fixed an issue where observability errors occurred when `gpt-image-1.5` returned image token usage details.
- ai-proxy:
  - Fixed an issue where the Azure managed identity token was cached indefinitely and never refreshed, causing requests to fail with 401 after the token expired (roughly one hour).
- ai-request-transformer:
  - Fixed an issue where runtime template placeholders (e.g. `$(uri_captures.*)`) in `config.llm.model.*` fields were not interpolated.
- ai-response-transformer:
  - Fixed an issue where runtime template placeholders (e.g. `$(uri_captures.*)`) in `config.llm.model.*` fields were not interpolated.
- aws-lambda:
  - Fixed an issue where empty JSON array bodies (`[]`) were incorrectly converted to objects (`{}`) when using `is_proxy_integration=true` and
    ansformer plugin.

    _proxy_integration` was enabled and the Lambda function returned `null` values in `headers` or
    d to empty strings.

    revent unsupported Datakit configurations from being pushed to older data planes in hybrid mode.

    ON primitive (e.g. `false`) caused a 500 internal error.

    S verification. It allows certificate chain and hostname checks against specified CAs instead of global

    d from the wrong URI segment when `custom_base_path` was used with bare `/{param}` paths.
- opa:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed json body processing to recognize `application/json` content-type with charset, ensuring proper handling of JSON request bodies.

- openid-connect:
  - Fixed an inconsistency where `credential_claim` resolved the same claim name to a different value than `upstream_headers_claims` because it consulted the id_token before the access_token, while the upstream headers resolver consulted the access_token first. With IdPs (e.g. Okta) that set distinct `sub` values in the two tokens, `authenticated_entity.id` did not match the upstream header the plugin set on the same request.
  - Fixed an issue where Redis-backed session storage could fail when Redis connections were routed through a proxy.
- opentelemetry:
  - Fixed an issue where template 'resource_attributes' in configuration of the plugin could not work as expected for metrics.
  - Fixed an issue where the plugin crashed when DNS or balancer failures occurred during upstream retries.
- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.
- session:
  - Fixed an issue where when Postgres strategy is used for session storage, concurrent authentication requests could result in race condition and session creation collisions.

Clustering

- **Clustering**: The `/status/sync` endpoint now returns an empty stat object instead of null before the first sync has run, keeping the response shape consistent.
- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.
- Fixed an issue where DP syncing failed with large configs. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful full-sync.
- Fixed an issue where hybrid data planes retried unrecoverable CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable reconnect storms.
- Fixed an issue where incremental DP (sync v2) would not export config to fallback storage when the control plane uses periodic polling instead of notify_new_version.
- Fixed an issue where paginated full sync could keep stale pending foreign-key references across a failed resume, causing spurious validation failures.
- Fixed an issue where using Google Cloud Storage cannot use the Application Default Credentials method order when the environment variable GCP_AUTH_METHOD_ORDER is set to "adc".

Core

- **Debugger**: Fixed an issue where the default key name `apikey` of the `key-auth` and `key-auth-enc` plugins was not redacted when captured by the Debugger. This has been resolved by adding `apikey` to the list of default redacted headers.
- Fixed an issue where a failure in a `dao:*:post` hook during insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.
- Fixed an issue where cluster mutex did not timeout immediately with `no_wait = true` when node level mutex is being held by another worker.
- Fixed an issue where immediate cosocket SSL handshake errors could be reported as subsequent socket write failures.
- Fixed an issue where Kong Manager users authenticated through IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim changes, or end up with inconsistent mappings during concurrent authentication requests.
- Fixed an issue where `kong.service.set_tls_cert_key` did not update the upstream keepalive pool name. Now includes a cert fingerprint for proper connection

_INTERVAL environment variable was not correctly applied to the analytics flush interval.

_ssl_verify_depth from 1 to 5.

configuration and errored when `null` or `nil` values were passed to `access_token_keyset` or

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

Performance

Core

- Improved performance of analytics data collection by introducing a shared payload pool and reducing the default local buffer size.
- **RBAC**: Improved PostgreSQL performance when deleting Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

3.13.0.6

Release date 2026/06/11

Bugfix

Core

- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).

3.13.0.5

Release date 2026/05/28

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-40701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.
- Security: Fixed CVE-2026-6338 in core proxy request header handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header cleanup, preventing CL.0 request smuggling with crafted `Connection: Content-Length` headers on requests with a body.

Dependency

Core

- Bumped libexpat from 2.7.3 to 2.8.1 to address the issues: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-2026-41080, and CVE-2026-45186.
- Bumped OpenSSL from 3.5.5 to 3.5.6 to address the issues: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-2026-28390, and CVE-2026-31789.

3.13.0.4

Release date 2026/05/05

Bugfix

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

MCP conversion.

rsing failure.

rmat requests (gemini, anthropic, bedrock, cohere, huggingface) by forwarding an OpenAI-shaped body

riable endpoints like `$(headers.x_gcp_endpoint)`. These warnings appeared on every configuration
ed until request time.

tokens without dots) caused a 500 Internal Server Error instead of returning 401 Unauthorized.

- Fixed an issue where the `add.headers` operation lowercased the header name, causing the configured letter case to be lost when adding new headers to the request.

Core

- **Debugger**: Fixed an issue where Redis command arguments were incorrectly included in Redis spans.
- **Debugger**: Fixed an issue where the time spent during the TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side latency.
- **Debugger**: Fixed an issue where the Konnect Debugger concatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g. `unix:/<prefix>/sockets/am:tls`).
- Fixed an issue where the real client IP from Proxy Protocol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497 plain HTTP to HTTPS port) or when the client disconnected prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from `$proxy_protocol_addr` on early request termination, and added `error_page` 497 routing through `kong_error_handler`.

Clustering

- Fixed an issue where Incremental Sync (ICS) would crash and stop further sync attempts.
- Fixed clustering sync reliability issues by immediately failing pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

Dependency

Core

- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2.

3.13.0.3

Release date 2026/04/08

Bugfix

Plugin

- **kafka-consume, confluent-consume**:
  - Increased the minimum API version of FetchRequest from 0 to 4 for Kafka 3.x. No changes made for Kafka 4.0, as it is already using version 4.
- acl:
  - Fixed an issue where anonymous consumers with valid legacy ACL group credentials were rejected with 403 when `include_consumer_groups` was enabled and no enterprise consumer groups were assigned.
- ai-aws-guardrails:
  - This plugin now allows streaming of responses when `guarding_mode` is set to `INPUT` with `allow_masking` enabled.
- ai-gcp-model-armor:
  - By default, this plugin now blocks unrecognized/new filters added to GCP Model Armor.
- ai-mcp-proxy:
  - Fixed an issue where the ACL metric label value was incorrect.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Konnect since 3.13.0.0.

fined the Authorization error codes, which are different from the error codes that Kong uses.

failed during load balancer failover due to token refresh attempts in `balancer_by_lua`. Tokens are now

API was unavailable in Cohere native format.

in multiple drivers.

penAI format was broken.

non-200 responses to streaming requests was overridden.

re incorrect according to https://opentelemetry.io/docs/specs/semconv/gen-ai/gen-ai-spans.

le_id}/content batch output analytics.

- ai-semantic-prompt-guard:

  - Fixed an issue where a vectorDB error occurred during initialization or config reload.

- graphql-rate-limiting-advanced:
  - Fixed an issue where the graphql-rate-limiting-advanced plugin's API threw 500 errors when handling HTTP PUT requests.
- kafka-log:
  - Fixed an issue where cached producers could cause memory leaks.
- oas-validation:
  - Fixed an issue where swagger `formData` parameters were not properly handled.
  - Fixed an issue where `minLength` and `maxLength` constraints defined in a Swagger 2.0 parameter schema were not enforced.
  - Fixed an issue where the validator cache did not account for the `collect_all_errors` setting.
  - Fixed an issue where parameter validation errors caused a runtime crash when `collect_all_errors` was enabled.
- openid-connect:
  - Fixed an issue where the `username` and `password` were used for Redis Sentinel and no authentication was supported for Redis, causing `NOAUTH Authentication Required` errors.
  - Fixed an issue where client-provided headers could be forwarded to upstream services when the corresponding JWT claim was missing from the token. The plugin now clears client headers before processing `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or downstream.
  - Fixed DPoP verification for opaque tokens (RFC 9449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.
- opentelemetry:
  - Fixed an issue where invalid `x-b3-flags` header values caused 500 responses.
- service-protection:
  - Fixed an issue where the Service Protection plugin could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after Rate Limiting Advanced and only evaluates requests that pass rate limiting, by updating its priority from 915 to 901.

Configuration

- Added `lru_cache_size` to allow configuration of in-memory LRU cache size.

Core

- Fixed an issue where in the postinstall script that changed /etc/kong/kong.logrotate's ownership and permissions; the script now restores ownership to root:root and sets permissions to 0644.
- Fixed an issue where `$remote_addr` was not replaced with the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` was enabled on the proxy listener. Also added proper error body messages for 501 and 505 status codes.
- Fixed an issue where the Active Tracing would report incorrect `latencies.client` values due to not capturing the access end time properly. This fix ensures that the access end timestamp is always recorded regardless of Active Tracing being active or not.
- Fixed AWS STS throttling during Redis IAM authentication via token caching.
- **vault**: Fixed an issue where `kong.vault.update()` changed the secret to an empty string temporarily after changing a vault config.

Clustering

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

mers when downgrading sync protocol to v1, which could cause excessive load on the CP and lead to

K

ning non-ASCII characters.

D

C

issue in the GraphQL query syntax that caused a parsed AST error in the degraphql plugin.

P

A

- Optimized `GET /kong` endpoint to use `SELECT DISTINCT` for populating `enabled_in_cluster` instead of iterating all plugin rows.

3.13.0.2

Release date 2026/03/10

Bugfix

Clustering

- Fixed an issue where a SQL injection vulnerability existed in the clustering RPC procedure, ensuring safer SQL operations (CVE-2026-1907).

Core

- Apply Nginx patch for a man-in-the-middle upstream response injection (CVE-2026-1642)

Dependency

Core

- Bumped OpenSSL from 3.4.3 to 3.5.5 to address the issue: CVE-2025-15467.

3.13.0.1

Release date 2026/02/01

Bugfix

Core

- Fixed an issue where DP's proxy listener could not be verified because of it was disabled in CP.
- Fixed an issue where `kong health` command would fail to run when kong configuration contains vault references.
- Fixed an issue where the Redis cloud authentication feature cannot fetch a correct credential for connecting to Azure Redis, especially when using Azure Workload Identity.
- Fixed an issue where the `network.peer.name` attribute in OpenTelemetry traces showed the same hostname for all retry attempts instead of capturing the specific hostname for each attempt.

Plugin

- **confluent, confluent-consume**:
  - Fix issue where Kafka plugin failed to encode and validate message keys when using Confluent Schema Registry.
- **kafka**:
  - Fixed issue where Kafka message key deserialization failed silently, returning raw string data instead of deserialized objects.
  - Fix issue where Kafka plugin produced records with incorrect `offsetDelta` in the record package.
- **llm**:
  - Fixed an issue where we could not specify the correct dimensions for Gemini embeddings model provider.
- acl:

consumer groups from all sources, causing it to incorrectly deny access when consumer groups were set
ted_consumer_groups.

ent claim.

ls to consumers denied by tool ACL in listener mode.

error.

actively refreshed before expiration.

y or null body caused 500 errors when `is_proxy_integration` is enabled.

- datakit:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed xml_to_json node to recognize `text/xml` content-type in addition to `application/xml` for XML request body processing, ensuring RFC 7303 compliance.

- oas-validation:
  - Fixed an issue where response body buffering was not properly disabled when `validate_response_body` was set to `false`.
- opentelemetry:
  - Fixed an issue where the `http.response.status_code` attribute of the `http.server.request.count` metric was incorrectly set to `kong.response.status_code`. Now, the attribute name follows the OTel specification.
  - Fixed an issue where the `kong.upstream.status_code` field of access logs was incorrectly populated with string value instead of integer value when there was one or more retries to the upstream.

3.13.0.0

Release date 2025/12/18

Breaking Change

Admin API

- Fixed an issue where certain record/map fields with an empty-object default value were incorrectly JSON-encoded as arrays.

Feature

Core

- **active-tracing**: Added exponential backoff retry support for the websocket connections of debug sessions.
- **sandbox**: Improved protection for whitelisted modules.
- **active-tracing**: Added instrumentation for log phase operations and created a new trace for the log phase spans.
- Added a configuration option `authenticated_groups_delimiter` (available values: `,`, `;`, `|`) to `admin_gui_auth_conf` for OIDC. This option specifies the delimiter used to split group values retrieved from JWT claims. When multiple group values are concatenated in a single claim using a specific delimiter, this configuration allows multiple groups to be extracted from that single claim value
- Added `ai_mcp_reqs` to reporting metrics to count AI MCP request usage.
- Added `ai_model_usage:{"provider/model": num}` to the anonymous report to count AI usage per model.
- Added OAuth2 authentication to the Hashicorp Vault backend.
- Added support for GCP authentication methods to connect to GCP CloudSQL Postgres databases. Configurations include `pg_gcp_auth` and `pg_gcp_service_account_key`.
- Added support for the `tls_certificate_verify` global option in `kong.tools.redis` and `kong.enterprise_edition.tools.redis.v2` modules. When this option is enabled and Redis is configured to connect to a secure endpoint, the module's `ssl_verify` flag cannot be disabled.
- Added TLS certificate verification enforcement. When tls_certificate_verify option is "on", certificate verification can't be disabled by Service or Plugin entities.
- AWS ElastiCache for Redis with AWS IAM Authentication
- Azure Cache for Redis with Azure Microsoft Entra Authentication
- **core**: Added directive 'proxy_protocol_passthrough' to allow gateway keep the proxy_protocol header unmodified.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

s_certificate_verify is enabled. You will see a warning if plugins try to disable SSL verification. This

g sync backup strategy.

HashiCorp Vault integration.

Event Hooks.

thentication

y.

lugins for license enforcement. let ai request not "double-dipping" the API Requests by counting twice.

Redis `host`, `port`, and `server_name` fields in plugins using Redis configuration (such as `rate-limiting-`

orts using common Cloud Authentication methods to connect to Cloud Redis instances. This includes

ce entities cannot disable certificate verification using the `tls_verify` option anymore.

Plugin

- **AI AWS Guardrails Plugin**:
  - Introduced a new mask mode feature in the AWS Guardrails plugin that allows sensitive data to be masked instead of blocked for requests, responses or both.
- **AI Plugins**:
  - Added AI Lakera Guard plugin, to integrate with the safety API provided by https://www.lakera.ai/lakera-guard.
  - Added support for `stream_options` to request server response usage statistics when using SSE streaming response mode.
  - Added support for the Gemini Files operations, through the `llm_format: gemini` native-SDK option.
  - Added xAI provider support to the LLM plugin, enabling integration with xAI's Grok chat and image generation models.
  - Adds support for AWS Bedrock Bearer Token authentication in Kong AI plugins, allowing secure access to Bedrock models using temporary or long-lived tokens.
  - Added support for video generation with `video/v1/videos/generations` route type for multiple LLM providers.
- **AI**:
  - Added instrumentation for GenAI spans.
- **ais**:
  - Add new partials(vectordb, embeddings and model) in ai plugins configs
- ace:
  - ace_credentials can now be linked to Consumers or Consumer Groups
  - Added `operation_id` in analytics and set it to the header `X-ACE-Operation-ID`.
  - Enabled at-rest keyring encryption for sensitive fields in ACE plugin.
- acme:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `storage_config.vault.tls_verify` setting cannot be disabled.
  - Enabled at-rest keyring encryption for sensitive fields in ACME plugin.
- ai-aws-guardrails:
  - Added block reason info metrics to AWS Guardrails plugin analytics.
  - added the flag `ssl_verify` to control certificate verification when connecting to the bedrock service.
  - Enabled at-rest keyring encryption for sensitive fields in AI AWS Guardrails plugin.
- ai-azure-content-safety:
  - Added support for the global `tls_certificate_verify` option. When enabled globally via `kong.conf`, the plugin's `ssl_verify` config field cannot be set to `false`. This ensures SSL/TLS certificate verification cannot be disabled when global security policy requires it.
  - Enabled at-rest keyring encryption for sensitive fields in AI Azure Content Safety plugin.
- ai-gcp-model-armor:
  - Added block reason and processing latency metrics to GCP Model Armor plugin analytics.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

oing MCP conversion.

ersion.

ature for semantic routing.

algorithm to the AI Proxy Advanced plugin which was missed in the previous release.

proxy-advanced plugin.

load balancer. Added two new fields `max_fails` and `fail_timeout`.

  - Added support for HuggingFace's new serverless API in the AI Proxy plugin, enabling seamless integration and improved compatibility.
  - Added support for native format video generation in Bedrock and Gemini LLM drivers, allowing direct passthrough of provider-specific video generation requests without format conversion.
  - Added support for batch mode of anthropic.
  - Added support for inline batch mode of gemini
  - Added support for batch API of bedrock.
  - Introduced Alibaba Dashscope as new provider.
- ai-rag-injector:
  - Added metadata filtering and ACL (Access Control List) capabilities to the RAG plugin. This feature enables fine-grained control over document retrieval based on metadata attributes and user permissions, supporting both pgvector and Redis vector database backends.
- ai-rate-limiting-advanced:
  - added support to count cost for routes with dynamic AI models.
- ai-request-transformer:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `https_verify` setting cannot be disabled.
- ai-response-transformer:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `https_verify` setting cannot be disabled.
- ai-sanitizer:
  - Added a `skip_logging_sanitized_items` option to control whether to log the sanitized items, which may contain sensitive data.
- aws-lambda:
  - added a verbose error level logging for better debugging of AWS Lambda invocation issues.
- azure-functions:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `https_verify` flag cannot be disabled.
- basic-auth:
  - Added brute force protection with exponential backoff for failed login attempts.
- confluent-consume:
  - added new config option `tls_certificate_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `tls_certificate_verify` setting cannot be disabled.
- confluent:
  - added new config option `ssl_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.
- datadog:
  - Added a configuration option to tag the metrics with the Kong route name, or the route ID if the name is empty.
- datakit:
  - Add support for using `application/x-www-form-urlencoded` as the body encoding.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ON or lua table to XML data.

e_request and response nodes

proxy phase.

ag allows users to control certificate verification when making HTTPS requests to the configured `url`
ificate_verify` global option is enabled.

IL data to lua table and JSON format.

obal option. When this option is enabled, the plugin's `https_verify` setting cannot be disabled.

obal option. When this option is enabled, the plugin's `ssl_verify` flag cannot be disabled.

  - added the flag `ssl_verify` to control certificate verification when connecting to the server of the OCSP responder's URL and to the server of the CRL Distribution Point.

- hmac-auth:
  - Enabled at-rest keyring encryption for sensitive fields in HMAC Auth plugin.
- http-log:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` flag cannot be disabled.
  - added the flag `ssl_verify` to control certificate verification when pushing logs to the configured `http_endpoint`.
- jwt-signer:
  - added support to the `tls_certificate_verify` global option. When this option is enabled the plugin's flags related to certificate verification cannot be disabled.
  - added the flags `access_token_endpoints_ssl_verify` and `channel_token_endpoints_ssl_verify` to switch certificate verification on the related fields.
- kafka-consume:
  - added new config option `ssl_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.
- kafka-log:
  - added new config option `ssl_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.
- kafka-upstream:
  - added new config option `ssl_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.
- ldap-auth-advanced:
  - added support for the `tls_certificate_verify` global option. When this option is enabled and LDAPS is used, the plugin's `verify_ldap_host` setting cannot be disabled.
- ldap-auth:
  - added support for the `tls_certificate_verify` global option. When this option is enabled and LDAPS is used, the plugin's `verify_ldap_host` or `start_tls` setting cannot be disabled.
- mtls-auth:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` flag cannot be disabled.
  - added the flag `ssl_verify` to control certificate verification when connecting to the server of the OCSP responder's URL and to the server of the CRL Distribution Point.
- oas-validation:
  - Added support for collecting all validation errors when `collect_all_errors` is set to `true` in the plugin configuration. Note: Enabling this option with OpenAPI 3.0 will affect performance.
  - Support readOnly and writeOnly keywords for OpenAPI 3.1.x.
- opa:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

bal option. When this option is enabled the plugin's flags `ssl_verify`, `tls_client_auth_ssl_verify`, sabled.

ion_memcached_ssl_verify` to switch certificate verification when connecting to Memcached server.

/HTTP protocol to an observability backend (e.g. OpenTelemetry Collector). Please enable this feature by in the OpenTelemetry plugin.

s via OTLP/HTTP protocol to an observability backend (e.g. OpenTelemetry Collector). Please enable this meter in the OpenTelemetry plugin.

and `stream_sessions_total` metrics providing more specific information.

pound_identifier`.

- request-callout:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting for HTTPS callouts cannot be disabled.
- request-validator:
  - Provided detailed error messages for `oneOf` / `anyOf` subschemas.
- solace-consume:
  - allowed basic auth credentials to be passed from downstream clients.
- solace-log:
  - allowed basic auth credentials to be passed from downstream clients.
- solace-upstream:
  - allowed basic auth credentials to be passed from downstream clients.
- tcp-log:
  - added new config option `ssl_verify` to support verifying server certificates. Added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `ssl_verify` setting cannot be disabled.
- upstream-oauth:
  - added support for the `tls_certificate_verify` global option. When this option is enabled, the plugin's `client.ssl_verify` setting cannot be disabled.
- *datakit*: the `call` node now supports performing requests via a proxy server.

Clustering

- **Clustering**: Add a mechanism to suppress connection retry logs within 100 seconds from last error.
- Removed analytics metrics related to rate limiting and threats on the data plane side.

PDK

- Added a new PDK method - kong.service.request.set_authentication_headers()

Kong Manager

- Added support for AWS, Azure, GCP authentication providers in Redis config.
- Added support for using OAuth2 with HashiCorp Vault.

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue where the Gemini provider would not correctly return Model Armor 'Floor' blocking responses to the caller.
  - Fixed an issue where Gemini (Vertex) models didn't return JSON formatted responses when instructed.
  - Fixed an issue where Gemini with native format was not correctly reporting total tokens.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

arch Tools" and "extra_body" when calling Gemini models in OpenAI format.

, and HuggingFace models may have a 0 `completion_tokens` count with SSE streaming responses.

g model names in the request path would not be properly validated. Now returns a clear error when model

d not correctly run tool calls when combined with thinking text.

be 0 and set default to 1048576 (1M).

would not work when `log_statistics` was disabled in the logging configuration.

cept non-OpenAI format.

ot being refreshed properly.

  - Fixed an issue where PARTIAL invocationResult was not handled.

- **ai-azure-content-safety, ai-aws-guardrail**:
  - Fixed an issue where the plugins failed to decompress gzip-encoded responses, leading to errors in response handling.
- **ai-proxy, ai-proxy-advanced**:
  - Fix SSE response parsing when the response is gzip-encoded, last chunk was not processed.
- **kafka**:
  - Fixed an issue where consumed messages were not validated against their JSON schema.
  - Fixed an issue where Schema Registry didn't properly validate JSON schemas.
- **kafka-consume, confluent-consume**:
  - Added `enforce_latest_offset_reset` flag to fix incorrect `latest` offset behavior. When `false` (default), maintains backwards compatibility where `latest` acts like `earliest`. When `true`, `latest` correctly starts from end of topic. Also fixed offset commit bug when no records are consumed, preventing feedback loop with true latest behavior.
- **llm**:
  - Fixed an issue where Gemini embeddings driver did not use correct url.
  - Fixed an issue where HuggingFace embeddings driver did not handle response correctly.
  - Fixed an issue where the subrequest implemented in LLM drivers did not handle error properly.
- **response**:
  - Fixed an issue where the `kong.response.exit() didn't interrupt the execution flow of plugins in header_filter phase`. Also added a new configuration `pdk_response_exit_header_filter_early_exit` to control this behavior to avoid silent breaking changes. The current default value is 'off', and output a warning log when `kong.response.exit()` is called in header_filter phase.
- ace:
  - Fixed an issue where multiple key-auth strategies could not use the same apikey.
  - Fixed an issue where observability headers could not be set correctly in some unhappy paths.
  - Fixed an issue where the anonymous consumer was not being set properly when authentication failed.
  - Fixed an issue where users could set the `anonymous` field in the OpenID Connect configuration of ACE auth strategies, which is not supported and could lead to unexpected authentication behavior.
- acl:
  - Fixed an issue where the cache was not being invalidated for incremental sync in certain scenarios, leading to stale data being served.
- acme:
  - Fixed an issue where the plugin would not properly handle cases when a referenced key_set does not exist, now returns a clear error message instead of causing unexpected behavior.
- ai-aws-guardrails:
  - Fixed an issue where the ai-aws-guardrails metrics could not be recorded.
  - Fixed an issue where the error does not reflect the root cause when the `guardrails_version` did not match the expected pattern.
- ai-gcp-model-armor:

on) filter violations were not detected. The plugin now correctly handles both RAI-style results (matchState
ate + findings array with infoType and likelihood).

y when the global `tls_certificate_verify` configuration option is enabled.

during merging.

correctly handled.

ired: false` in the plugin schema.

ot respected.

henticated.

  - Fixed an issue where mcp proxy is not parsing default values properly.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue when using passthrough-mode, tools without tool ACL do not apply default ACL.
  - Fixed an issue where MCP server could not call upstream when proxy protocol is used.
  - Fixed an issue where failing to fetch tools cache was not handled properly.
  - Fixed an issue where forwarding client headers to upstream could not be disabled.
  - Fixed an issue where trusted ip relative headers were forwarded upstream.
  - Fixed an issue where `tools/call` could accept malformed requests and generate wrong responses.
  - Fixed an issue where path invalid error was not handled properly.
  - Fixed an issue where we could not override the upstream's scheme when converting MCP tool to RESTful API.
  - Fixed an issue where MCP server could not call upstream when self-signed certificate is used in Kong.
  - Fixed an issue where path traversal can be done with path parameter.
- ai-prompt-template:
  - Fixed an issue where non-OpenAI requests were not being processed correctly.
- ai-proxy-advanced:
  - Fixed an issue where the `max_completion_tokens` parameter was not being set correctly for O1 series models (e.g., `o1`, `o3`, `o4`, `gpt-5`).
  - Fixed an issue where the token count for Gemini Vertex embeddings API in OpenAI format was incorrect.
  - Fixed an issue where the native format option did not work correctly for non-openai formats.
  - Fixed an issue where the semantic load balancing with pgvector namespace was not functioning correctly.
  - Fixed an issue when using responses API and background mode.
  - Fixed an issue where Files content analytics extraction is not handled properly for Azure.
  - Fixed an issue where requests to Anthropic Claude models via Azure Foundry were not being processed correctly.
  - Fixed an issue where AWS Bedrock invoke command is not properly proxied.
  - Fixed an issue where the Gemini image generation model responses were not being processed correctly.
  - Fixed an issue where the token count for Gemini Vertex embeddings API in native format was incorrect.
  - Fixed balancer retry failures caused by expired DNS entries by preloading DNS for targets.
  - Fixed intermittent 500 responses from the AI Proxy Advanced plugin when using Azure OpenAI
  - Fixed missing `id` and `created` fields in certain drivers.
- ai-proxy:
  - Added dimension configuration support for Amazon Titan Embed v2 models.
  - Added tool_calls passthrough and preserved finish_reason in Huggingface driver responses.
  - Fixed an issue where `tls_certificate_verify` configuration was not respected in JSON-RPC and AWS STS calls.
  - Fixed an issue where HuggingFace embedding driver were incorrectly parsed responses from embedding API
  - Fixed an issue where extra inputs were not permitted for huggingface inference provider

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

onjunction with a logging plugin (such as file-log) resulting in missing information on the last entry of the

Bedrock returned a bad request error

by whole numbers when using Redis. This is an opt-in fix and can be enabled by setting
plugin configuration.

does not accept capture groups for deployment field

lels did not work with the semantic cache because of the polluted request format.

to first token (TTFT) metrics when hit.

onses api to be used with Azure.

- Fixed an issue where cost savings attributes `ai_proxy_cache_cost_savings` were not properly calculated when cache hits.

- ai-semantic-prompt-guard:
  - deprecate config.rules.max_request_body_size with config.max_request_body_size.
- ai-semantic-response-guard:
  - Fixed an issue where a stacktrace error occurred during initialization and teardown.
- confluent-consume:
  - Fixed an issue where the plugin would fail to connect using mTLS.
- confluent:
  - Fixed an issue where `forward_body` dropped request bodies larger than Nginx's default buffer size (16 KB). It now reads up to 1 MB and returns an error if the body can't be fully read.
- datakit:
  - Fixed implicit request node headers field to be correct type.
- file-log:
  - Fixed an issue where the configuration with leading or trailing spaces in the `path` field could cause upgrade failures.
- ip-restriction:
  - Fixed an issue where blocking an IP over TCP would log error: "function cannot be called in preread phase" (#14749)
- kafka-consume:
  - Fixed an issue where the plugin would fail to connect using mTLS.
  - Fixed an issue where the SSE connection was not terminated when there was an error in Schema Registry.
- kafka-upstream:
  - Fixed an issue where the kafka-upstream plugin fails to connect certain Kafka clusters using SCRAM-SHA-256 or SCRAM-SHA-512
  - Fixed issue where Kafka producer cached TLS certificates, causing failures when certificates were updated. Now, the plugin properly reloads updated certificates.
- key-auth-enc:
  - Fixed an issue where for incremental sync, caches may not be properly invalidated, causing stale data to be served.
- key-auth:
  - Fixed an issue where the consumer authentication cache was not isolated by realm.
- ldap-auth:
  - Fixed an issue where a failed ssl handshake with the ldap server would return 401 instead of 500.
- mocking:
  - Fixed an issue where path match pattern failed when `()[]` were in the path pattern.
- oas-validation:
  - Fixed an issue where nested references in oneOf / anyOf when they are used with a discriminator are not unfolded.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

parsed incorrectly.

ed when $ appears in the path pattern.

ssage for the token's `iss` claim did not reflect the correct token type and expected issuers.

thorization_code auth would not auto-recover if IdP was not accessible during Kong startup.

failed in non-default workspaces. The certificate lookup now explicitly specifies the plugin's workspace itialization.

er related caches may not be properly invalidated, causing stale data to be served.

timestamp claims (exp, nbf, iat) even when provided as non-numeric types.

t match the correct property in otel logs.

- Fixed an issue where the instrumentation started unexpectedly on control planes of hybird mode.

- prometheus:
  - Fixed an issue where the Prometheus plugin would not return DB connections to the connection pool, potentially leading to exhaustion of available connections under high load.
- request-callout:
  - Fix duplicated content-type headers in the callout request when body.custom is enabled and content-type header is also set in headers.
- saml:
  - Fixed an issue that caused a crash when the NameID Format was set to `Unspecified`.
- solace-log:
  - Fixed end-to-end tracing context propagation.
- solace-upstream:
  - Fixed end-to-end tracing context propagation.
- *request-callout*: Ensure that upstream headers are cleared after custom expressions are executed.

Configuration

- Fixed an issue where the restart command read configuration multiple times and failed to stop nginx.
- **balancer**: Fixed an issue where the dns query not stopped when related upstream deleted.
- **template**: Fixed an issue where duplicated “proxy_protocol on” directive in nginx-kong-stream.conf when KONG_NGINX_SPROXY_PROXY_PROTOCOL was set for ssl stream.

Core

- **active-tracing**: Fixed an issue where WebSocket connections to the control plane are not correctly closed in debug sessions.
- **active-tracing**: Fixed parent span for body filter plugin spans
- **event-hooks**: Fixed an issue where the event_hook crud events cannot be handled in traditional cluster mode.
- **Fixed a typo in certificate phase name in kong.tools.yield module.**
- Fixed an issue where `500` response status can occasionally occur during reconfiguration.
- Fixed an issue where **active-tracing** debug sessions are not reporting headers and payloads when proxy is used to connect to the telemetry endpoint.
- Fixed an issue where `ai_reqs` and `ai_model_usage` were increased even for non-ai requests.
- Fixed an issue where consumer group renaming may not be properly populated, causing stale cache to be served.
- Fixed an issue where Kong incorrectly logged upstream status codes as 000 (or empty) when HTTP/2 clients disconnected during response processing. This occurred when response buffering was enabled. Kong now correctly records the actual upstream status code even when the HTTP/2 client disconnects before receiving the complete response.
- Fixed an issue where Kong Manager failed to generate a cookie when OIDC was enabled due to a missing `password` grant type in `auth_methods`.
- Fixed an issue where migrations could fail due to missing database relations by repositioning basic-auth and key-auth plugin scripts for correct execution order.
- Fixed an issue where `otlp.prepare_logs` did not reset the `spans` field, causing unsupported data exported to OTel backends.
- Fixed an issue where plugin preparation incorrectly retained userdata values; they are now set to `nil` during preparation.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

eted when cascading delete a workspace.

ccurring when encoding traces and logs.

lthchecks.threshold is set to 100.

ike `1.1 kong/3.13.0.0-enterprise-edition`), which is not allowed by RFC 9001 and may cause issues uration option `via_header_comply_rfc` was added, when enabled, the `Via` header will not include Kong

C

cky_sessions_cookie_path was blocking configuration syncing on data planes older than version 3.11.

ause incremental sync to fail at the first sync of a DP.

n checker before cleaning up old configurations, which could lead to resource leaks.

- Fixed an issue where the prometheus metric `kong_control_plane_connected` was missing when the Data Plane side enabled incremental sync.

CLI Command

- Fixed an issue where the CLI command `kong runner` crashes when clustering cert and key are provided as content from environment variables.

PDK

- Fixed an issue where the `kong.log.serialize()` function incorrectly ommitted the `consumer_id` in the `authenticated_entity` log field.
- **log-pdk**: Fixed an issue in log-pdk where log serialization could cause a panic due to incorrect type handling in `set_serialize_value`. Strengthened validation to prevent this.

Dependency

Core

- Bumped lua-resty-healthcheck to version 3.1.1 to remove incorrect deprecation notice on active healthchecks headers.
- Bumped jq from 1.7.1 to 1.8.1.
- Bumped kong-redis-cluster from 1.5.6 to 1.5.7.
- Bumped libexpat from 2.7.1 to 2.7.3.
- Bumped libxml2 from 2.12.10 to 2.15.0.
- Bumped lua-resty-acme from 0.15.0 to 0.16.0.
- Bumped lua-resty-aws from 1.6.0 to 1.7.1.
- Bumped lua-resty-gcp from 0.0.14 to 0.0.16.
- Bumped lua-resty-openssl from 1.5.1 to 1.7.0.
- Bumped lua-resty-session from 4.1.4 to 4.1.5. Added cloud Redis authentication support.
- Bumped OpenSSL to 3.4.3 in Core dependencies.
- Bumped PCRE2 from 10.46 to 10.47.
- Replaced resty-cli with rusty-cli
- Switched lua-resty-ljsonschema dependency to Kong's maintained fork lua-resty-ljsonschema. Bumped version to kong-lua-resty-ljsonschema 1.3.1.

CLI Command

- Bumped ca-certificates (debug tool) from 2025-07-15 to 2025-11-04.
- Bumped curl (debug tool) from 8.15.0 to 8.17.0.
- Bumped nghttp2 (debug tool) from 1.66.0 to 1.68.0.

Performance

Core

- **core**: Improved performance of deleting expired rows for Postgres versions below 12.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ai-mcp-proxy:
  - Fixed an issue where converted HTTPS MCP tool calls lost the original forwarded port on the internal TLS Unix socket.
- ai-proxy-advanced:
  - Fixed a bug where a response from Anthropic could fail to decode when the client's request advertised Brotli support, since Anthropic's edge may then return a Brotli-encoded body that Kong's response decompression, which only understands gzip, can't inflate. Kong now normalizes the outgoing `Accept-Encoding` request header before proxying to any LLM provider: `gzip, identity` when the client accepts gzip, and `identity` otherwise, so a client that cannot inflate gzip is never handed a compressed body on paths where the upstream response passes through unmodified.
- ai-proxy:
  - Fixed streaming token count metrics that reported inflated totals for third-party models hosted on Vertex AI (claude-, mistral-, jamba-*), caused by incremental counts being treated as cumulative.
- jwt:
  - Fixed an issue where the plugin failed to decode standard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.
- prometheus:
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
  - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.

3.12.0.11

Release date 2026/08/18

Feature

Core

- Added a Distroless Docker image variant for Kong API Gateway. The Distroless image ships only the Kong binary and its runtime dependencies, with no package managers, no shells or any other programs you would expect to find in a standard Linux distribution.

Bugfix

PDK

- Fixed an issue on HTTP/2 connections where the request method and query were reported incorrectly, or could raise an error, when a request hit the error handler such as a 502 from an upstream connection reset.

Core

- Fixed an issue where a failed balancer creation leaked the per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.
- Fixed an issue where a healthcheck counter value of 255 crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`, `http_failures`) are now limited to 254.

plane ready before the new router and plugins iterator became active. Kong now reports readiness only are installed.

mittent 503 responses while a failover target remained healthy.

nd start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with ssing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.

C

s. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful

ull sync from resuming.

handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as frame. The control plane now drains and responds to control frames during the handshake until the plugin list.

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Plugin

- jwt-signer:
  - Fixed an issue where the plugin failed to set the signed access token header on the upstream request, when `access_token_upstream_header` (or `original_access_token_upstream_header`) had the same name as `channel_token_request_header`.
- mocking:
  - Fixed a memory leak where the plugin config cache did not use weak keys due to a misspelled `__mode` metatable field.
- oauth2-introspection:
  - Fixed an authentication bypass where a revoked or expired token stayed authorized indefinitely instead of being rejected. An authoritative `active:false` result is now also cached briefly (5 seconds).
- openid-connect:
  - Fixed an issue where the `redirect_uri` parameter was sent to the token endpoint for all grant types. It is now included only for the `authorization_code` grant, as required by RFC 6749.
  - The `ignore_signature` option now logs a warning when it is set, because it turns off JWS signature verification for the listed grants.
- saml:
  - Hardened signature validation against XML Signature Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that names the `ID` of the element it digests and consumes, so a signature can no longer be bound to a different element than the one that provides the identity. A response whose reference URI is empty or not a same-document fragment is now rejected.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a crash that occurred when a plugin set `schema_registry.confluent.authentication.mode` to `oauth2` but omitted the `oauth2_client` record. Previously this returned a 500 from the Admin API during validation, and once saved it also crashed at runtime while fetching the schema registry OAuth2 token. The absent `oauth2_client` is now handled and falls back to the default authentication method, so a configuration without `oauth2_client` works end-to-end.

Kong Manager

- Fixed an issue where the Export button on the Vitals Reports page did not download the report CSV.

Dependency

Core

- Bumped kong-redis-cluster from 1.5.7 to 1.6.0.
- Replaced resty-cli with rusty-cli

Performance

Clustering

- Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.
- Optimized performance of clustering payload handling for version compatibility. This reduces CPU usage and transient memory pressure.

C

sync by updating service data in place instead of triggering a full router rebuild when only service attributes

otifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in

A

unter=true. Entity counts for the whole page are now retrieved with one grouped query per entity type
space, while keeping the counts exact.

3

R

E

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Core

- Applied upstream nginx security patches for CVE-2026-42533.
- Applied upstream nginx security patches for CVE-2026-56434.
- Applied upstream nginx security patches for CVE-2026-60005.
- Applied upstream nginx security patches for CVE-2026-42055 and CVE-2026-48142.

Plugin

- saml:
  - Security: Fixed CVE-2026-14917 in the SAML plugin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly, and logging a warning if misconfigured. This prevents a crafted unsigned SAML response from silently bypassing authentication when `validate_assertion_signature` is set to false.

Dependency

Core

- Bumped jq from 1.8.1 to 1.8.2.

3.12.0.9

Release date 2026/07/22

Feature

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which could avoid the frequent disconnections and reconnection attempts and improve performance. Emitted a log entry telling the config payload size and the configured `cluster_max_payload` size when this happens.

Plugin

- forward-proxy:
  - Added `ca_certificates` option for per-plugin TLS verification. It allows certificate chain and hostname checks against specified CAs instead of global settings, ensuring explicit trust.
- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.

Bugfix

Plugin

- ai-proxy-advanced:
  - Fixed an issue where unsafe batch id could cause upstream AI provider path traversal.

ve format adapters could cause upstream AI provider path traversal.

nstruct upstream AI provider paths.

se upstream AI provider path traversal.

) were incorrectly converted to objects (`{}`) when using `is_proxy_integration=true` and ansformer plugin.

_proxy_integration` was enabled and the Lambda function returned `null` values in `headers` or d to empty strings.

ON primitive (e.g. `false`) caused a 500 internal error.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where warn log messages did not include the plugin name, making it difficult to identify the source of blocked requests.

- oas-validation:
  - Fixed an issue where the OAS specification cache failed to distinguish between different values of `api_spec_encoded` for the same specification content.
  - Fixed an issue where path parameters were extracted from the wrong URI segment when `custom_base_path` was used with bare `/{param}` paths.
- opa:
  - Fixed json body processing to recognize `application/json` content-type with charset, ensuring proper handling of JSON request bodies.
- openid-connect:
  - Fixed an inconsistency where `credential_claim` resolved the same claim name to a different value than `upstream_headers_claims` because it consulted the id_token before the access_token, while the upstream headers resolver consulted the access_token first. With IdPs (e.g. Okta) that set distinct `sub` values in the two tokens, `authenticated_entity.id` did not match the upstream header the plugin set on the same request.
  - Fixed an issue where switching clients within a single request (via `client_arg`) failed to use the matching client's JWK.
  - Fixed an issue where Redis-backed session storage could fail when Redis connections were routed through a proxy.
  - Fixed an issue where consumer groups could not be resolved when the groups claim was only available from the user info endpoint, which resulted in a `500` error.
- session:
  - Fixed an issue where when Postgres strategy is used for session storage, concurrent authentication requests could result in race condition and session creation collisions.
- kafka-upstream, **kafka-log**, **kafka-consume**, **confluent**, **confluent-consume**: Fixed Kafka keepalive pools leaking connections across different SASL credentials and TLS verification settings.
- kafka-upstream, **kafka-log**, **kafka-consume**, **confluent-consume**: Fixed Kafka broker returning failed connections to the keepalive pool, added SSL handshake retry, and improved error propagation.

Clustering

- **Clustering**: The `/status/sync` endpoint now returns an empty stat object instead of null before the first sync has run, keeping the response shape consistent.
- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.
- Fixed an issue where data planes retried unrecoverable TLS certificate setup failures instead of loading their backup configuration.
- Fixed an issue where hybrid data planes retried unrecoverable CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable reconnect storms.
- Fixed an issue where incremental DP (sync v2) would not export config to fallback storage when the control plane uses periodic polling instead of notify_new_version.
- Fixed an issue where paginated full sync could keep stale pending foreign-key references across a failed resume, causing spurious validation failures.

Core

- **Debugger**: Fixed an error that could occur under sustained HTTPS traffic.
- **Debugger**: Fixed an issue where the default key name `apikey` of the `key-auth` and `key-auth-enc` plugins was not redacted when captured by the Debugger. This has been resolved by adding `apikey` to the list of default redacted headers.
- Fixed an issue where a failure in a `dao:*:post` hook during insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.

diately with `no_wait = true` when node level mutex is being held by another worker.

errors could be reported as subsequent socket write failures.

hrough IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim ncurrent authentication requests.

did not update the upstream keepalive pool name. Now includes a cert fingerprint for proper connection

VAL environment variable was not correctly applied to the analytics flush interval.

returned HTTP 404 when using `router_flavor=expressions` due to incorrect protocol matching

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

C

_ssl_verify_depth from 1 to 5.

Dependency

Core

- Bumped kong-lua-resty-ljsonschema from 1.2.0 to 1.3.3.
- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

Performance

Core

- Improved performance of analytics data collection by reducing the default local buffer size.
- **RBAC**: Improved PostgreSQL performance when deleting Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

3.12.0.8

Release date 2026/06/11

Bugfix

Core

- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).

3.12.0.7

Release date 2026/05/28

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-40701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.
- Security: Fixed CVE-2026-6338 in core proxy request header handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header cleanup, preventing CL.0 request smuggling with crafted `Connection: Content-Length` headers on requests with a body.

Dependency

Core

- Bumped libexpat from 2.7.3 to 2.8.1 to address the issues: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-2026-41080, and CVE-2026-45186.
- Bumped OpenSSL from 3.5.5 to 3.5.6 to address the issues: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-2026-28390, and CVE-2026-31789.

3.12.0.6

Release date 2026/05/11

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

nts were incorrectly included in Redis spans.

e TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side

oncatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g.

ol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497
ted prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from
l added `error_page` 497 routing through `kong_error_handler`.

lling pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

Plugin

- service-protection:
  - Fixed an issue where the Service Protection plugin could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after Rate Limiting Advanced and only evaluates requests that pass rate limiting, by updating its priority from 915 to 901.

Dependency

Core

- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2.

3.12.0.5

Release date 2026/04/15

Bugfix

Configuration

- Added `lru_cache_size` to allow configuration of in-memory LRU cache size.

Plugin

- ai-mcp-proxy:
  - Fixed an issue where we didn't keep the port after MCP conversion.
- ai-proxy-advanced:
  - Fixed an issue where `id`/`created` fields were missing in multiple drivers.
- ai-proxy:
  - Fixed an issue where using ai-proxy-advanced in conjunction with a logging plugin (such as file-log) resulting in missing information on the last entry of the balancer "tries" section.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the graphql-rate-limiting-advanced plugin's API threw 500 errors when handling HTTP PUT requests.
- jwt:
  - Fixed an issue where malformed JWT tokens (e.g. tokens without dots) caused a 500 Internal Server Error instead of returning 401 Unauthorized.
- kafka-log:
  - Fixed an issue where cached producers could cause memory leaks.
- oas-validation:
  - Fixed an issue where swagger `formData` parameters were not properly handled.
  - Fixed an issue where `minLength` and `maxLength` constraints defined in a Swagger 2.0 parameter schema were not enforced.
  - Fixed an issue where nested references in `oneOf`/`anyOf` were not unfolded when used with a discriminator.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

be forwarded to upstream services when the corresponding JWT claim was missing from the token. The `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or

449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.

tected if multiple `X-Forwarded-Proto` values were provided.

h the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` was dy messages for 501 and 505 status codes.

orrect `latencies.client` values due to not capturing the access end time properly. This fix ensures that f Active Tracing being active or not.

wnership of `/etc/kong/kong.logrotate` to `kong:kong`, causing permission issues when executed by the nstall.

- **vault**: Fixed an issue where `kong.vault.update()` changed the secret to an empty string temporarily after changing vault config.

Clustering

- Fixed an issue where DP may spawn multiple sync timers when downgrading sync protocol to v1, which may cause excessive load on CP and lead to performance degradation.
- Fixed an issue where Incremental Sync (ICS) would crash and stop further sync attempts.

Kong Manager

- Fixed workspace navigation for workspace names containing non-ASCII characters.

Dependency

Core

- Bumped kong-gql from 0.2.3 to 0.2.4 to fix the null value issue in the GraphQL query syntax that caused a parsed AST error in the DeGraphQL plugin.

Performance

Core

- **core**: Improved performance of Kong core by using `ngx.var.http_*` instead of `kong.tools.http.get_header`.

Admin API

- Optimized `GET /kong` endpoint to use `SELECT DISTINCT` for populating `enabled_in_cluster` instead of iterating all plugin rows.

3.12.0.4

Release date 2026/03/11

Bugfix

Clustering

- Fixed an issue where a SQL injection vulnerability existed in the clustering RPC procedure, ensuring safer SQL operations (CVE-2026-1907).

Core

- Apply Nginx patch for a man-in-the-middle upstream response injection (CVE-2026-1642)

Dependency

Core

- Bumped OpenSSL from 3.4.1 to 3.5.5 to address the issue: CVE-2025-15467.

3.12.0.3

R

E

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

g model names in the request path would not be properly validated. Now returns a clear error when model

h incorrect `offsetDelta` in the record package.

ect dimensions for Gemini embeddings model provider.

    - Fixed an issue where users could set the `anonymous` field in the OpenID Connect configuration of ACE auth strategies, which is not supported and could lead to unexpected authentication behavior.

- ai-mcp-oauth2:
    - Fixed an issue where we didn't clear header for absent claim.
- ai-mcp-proxy:
    - Fixed an issue where path traversal can be done with path parameter.
    - Fixed an issue where PATCHing the tool caused an error.
- ai-proxy-advanced:
    - Fixed balancer retry failures caused by expired DNS entries by preloading DNS for targets.
    - Fixed excessive DNS warning logs for template variable endpoints like `$(headers.x_gcp_endpoint)`. These warnings appeared on every configuration change because template variables cannot be resolved until request time.
    - Fixed an issue where metrics were missing and v2 API was unavailable in Cohere native format.
    - Fixed an issue where GCP tokens would not be proactively refreshed before expiration.
- ai-semantic-prompt-guard:
    - Fixed an issue where a vectorDB error occurred during initialization or config reload.
- aws-lambda:
    - added a verbose error level logging for better debugging of AWS Lambda invocation issues.
    - Fixed an issue where Lambda responses with empty or null body caused 500 errors when `is_proxy_integration` is enabled.
- oas-validation:
    - Fixed an issue where response body buffering was not properly disabled when `validate_response_body` was set to `false`.
- openid-connect:
    - Fixed an issue where the `username` and `password` were used for Redis Sentinel and no authentication supported for Redis, causing `NOAUTH Authentication Required` errors.
- opentelemetry:
    - Fixed an issue where invalid `x-b3-flags` header values caused 500 responses.
    - Fixed an issue where the instrumentation started unexpectedly on control planes of hybird mode.

Core

- Fixed an issue where Kong incorrectly logged upstream status codes as 000 (or empty) when HTTP/2 clients disconnected during response processing. This occurred when response buffering was enabled. Kong now correctly records the actual upstream status code even when the HTTP/2 client disconnects before receiving the complete response.
- Fixed an issue where `kong health` command would fail to run when kong configuration contains vault references.
- Fixed an issue where the postinstall script changed kong.logrotate permissions; it now resets to 644.

3.12.0.2

R

F

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`elimiter` (available values: `,`, `;`, `|`) to `admin_gui_auth_conf` for OIDC. This option specifies the delimiter
hen multiple group values are concatenated in a single claim using a specific delimiter, this configuration
aim value

F

P

arch Tools" and "extra_body" when calling Gemini models in OpenAI format.

would not work when `log_statistics` was disabled in the logging configuration.

- ace:
  - Fixed an issue where the anonymous consumer was not being set properly when authentication failed.
  - Fixed an issue where observability headers could not be set correctly in some unhappy paths.
- ai-mcp-oauth2:
  - Fixed an issue where MCP-like request was not authenticated. Previously, we only authenticated requests that satisfied the MCP spec. As a result, the attacker can bypass this via an MCP-like request. Therefore, now we change to authenticate all the requests.
  - Fixed an issue where the oidc schema was polluted during merging.
  - Fixed an issue where resource without path was not correctly handled.
  - Fixed an issue where x-forwarded-* headers were not respected.
- ai-mcp-proxy:
  - Fixed an issue where failing to fetch tools cache was not handled properly.
  - Fixed an issue where trusted ip relative headers were forwarded upstream.
  - Fixed an issue where `tools/call` could accept malformed requests and generate wrong responses.
  - Fixed an issue where path invalid error was not handled properly.
  - Fixed an issue where we could not override the upstream's scheme when converting MCP tool to RESTful API.
- ai-proxy-advanced:
  - Fixed intermittent 500 responses from the AI Proxy Advanced plugin when using Azure OpenAI
  - Fixed an issue where Files content analytics extraction is not handled properly for Azure.
- ai-proxy:
  - Fixed an issue where cohere embedding model on Bedrock returned a bad request error
- ai-semantic-cache:
  - Fixed an issue where cost savings attributes `ai_proxy_cache_cost_savings` were not properly calculated when cache hits.
- solace-log:
  - Fixed end-to-end tracing context propagation.
- solace-upstream:
  - Fixed end-to-end tracing context propagation.

Clustering

- **balancer**: Fixed an issue where the unsupported field `sticky_sessions_cookie_path` was blocking configuration syncing on data planes older than version 3.11.

Dependency

Core

- Bumped lua-resty-healthcheck to version 3.1.1 to remove incorrect deprecation notice on active healthchecks headers.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Postgres versions below 12.

  - Fixed an issue where Bedrock ‘Nova’ models would not correctly run tool calls when combined with thinking text.
  - Fixed an issue where the Gemini provider would not correctly return Model Armor ‘Floor’ blocking responses to the caller.
  - Fixed an issue where Gemini (Vertex) models didn’t return JSON formatted responses when instructed.
  - Fixed an issue where OpenAI, OpenAI-compatible, and HuggingFace models may have a 0 `completion_tokens` count with SSE streaming responses.
- **GCP Model Armor**:
  - Fixed an issue where PARTIAL invocationResult was not handled.
  - Fixed an issue where short-lived credentials were not being refreshed properly.
- **kafka-consume, confluent-consume**:
  - Added `enforce_latest_offset_reset` flag to fix incorrect `latest` offset behavior. When `false` (default), maintains backwards compatibility where `latest` acts like `earliest`. When `true`, `latest` correctly starts from end of topic. Also fixed offset commit bug when no records are consumed, preventing feedback loop with true latest behavior.
- **llm**:
  - Fixed an issue where Gemini embeddings driver did not use correct url.
  - Fixed an issue where HuggingFace embeddings driver did not handle response correctly.
  - Fixed an issue where the subrequest implemented in LLM drivers did not handle error properly.
- acl:
  - Fixed an issue where the cache was not being invalidated for incremental sync in certain scenarios, leading to stale data being served.
- ai-aws-guardrails:
  - Fixed an issue where the ai-aws-guardrails metrics could not be recorded.
- ai-mcp-proxy:
  - Fixed an issue where MCP server could not call upstream when proxy protocol is used.
  - Fixed an issue where forwarding client headers to upstream could not be disabled.
  - Fixed an issue where MCP server could not call upstream when self-signed certificate is used in Kong.
- ai-proxy-advanced:
  - Fixed an issue where the token count for Gemini Vertex embeddings API in native format was incorrect.
  - Fixed an issue where the token count for Gemini Vertex embeddings API in OpenAI format was incorrect.
  - Fixed an issue where the native format option did not work correctly for non-openai formats.
  - Fixed an issue where the semantic load balancing with pgvector namespace was not functioning correctly.
  - Fixed an issue where AWS Bedrock invoke command is not properly proxied.
- ai-proxy:
  - Added dimension configuration support for Amazon Titan Embed v2 models.
  - Fixed integration with HuggingFace by adding support for the new serverless API, ensuring seamless compatibility.
  - Fixed an issue where HuggingFace embedding driver were incorrectly parsed responses from embedding API

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d for huggingface inference provider

by whole numbers when using Redis. This is an opt-in fix and can be enabled by setting
lugin configuration.

does not accept capture groups for deployment field

lels did not work with the semantic cache because of the polluted request format.

to first token (TTFT) metrics when hit.

ring initialization and teardown.

- confluent-consume:

  - Fixed an issue where the plugin would fail to connect using mTLS.
- datakit:
  - Fixed implicit request node headers field to be correct type.
- file-log:
  - Fixed an issue where the configuration with leading or trailing spaces in the `path` field could cause upgrade failures.
- kafka-consume:
  - Fixed an issue where the plugin would fail to connect using mTLS.
- key-auth-enc:
  - Fixed an issue where for incremental sync, caches may not be properly invalidated, causing stale data to be served.
- oas-validation:
  - Fixed an issue where parameter data extraction failed when `$` appears in the path pattern.
- openid-connect:
  - Fixed an issue where for incremental sync, consumer related caches may not be properly invalidated, causing stale data to be served.
  - Fixed an issue where the `client_credentials`/`authorization_code` auth would not auto-recover if IdP was not accessible during Kong startup.
- request-callout:
  - Fix duplicated content-type headers in the callout request when body.custom is enabled and content-type header is also set in headers.
- saml:
  - Fixed an issue that caused a crash when the NameID Format was set to `Unspecified`.

Configuration

- Fixed an issue where the restart command read configuration multiple times and failed to stop nginx.
- **balancer**: Fixed an issue where the dns query not stopped when related upstream deleted.

Core

- Fixed an issue where Kong Manager failed to generate a cookie when OIDC was enabled due to a missing `password` grant type in `auth_methods`.
- Fixed an issue where consumer group renaming may not be properly populated, causing stale cache to be served.
- **Fixed an issue where the partial entities cannot be deleted when cascading delete a workspace.**
- **event-hooks**: Fixed an issue where the event_hook crud events cannot be handled in traditional cluster mode.
- Fixed an issue where migrations could fail due to missing database relations by repositioning basic-auth and key-auth plugin scripts for correct execution order.

Clustering

- **Clustering** Fixed an issue where consumer groups may cause incremental sync to fail at the first sync of a DP.
- Fixed an issue where the prometheus metric `kong_control_plane_connected` was missing when the Data Plane side enabled incremental sync.
- h checker before cleaning up old configurations, which could lead to resource leaks.

K

de was not saving correctly in confluent-consume, kafka-consume, kafka-upstream, kafka-log, and

3

R

F

P

ugin from 950 to 960. This change is to make sure the execution sequences of the konnect-application-auth
e using the konnect-application-auth plugin and other custom plugins that have a dependency with the

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

konnect-application-auth plugin and have a priority between 950 and 960, you may need to adjust the priorities of these custom plugins accordingly or use dynamic plugin ordering.

- kafka-consume:
  - Added `typedefs.no_service` to the `kafka-consume` plugin to prevent binding to a service, as it does not proxy to one. Note that this is a breaking change. If you previously attached a kafka-consume plugin to a service, it will no longer take effect. In such cases, requests will instead be proxied to the upstream configured in the service.

Deprecation

Core

- The lua-resty-kafka module `resty.kafka` inside the Kong Gateway package is now deprecated. Developers can still use it, but it will no longer receive any updates.

Feature

Plugin

- **AI Plugins**:
  - Support relative path for tool paths in MCP plugins.
  - Added a new `endpoint_id` field for GCP Gemini options to support Model Garden.
  - GCP authentication order can now be configured using the `GCP_AUTH_METHOD_ORDER` environment variable. Setting it to `adc` allows the plugin to select Application Default Credentials (ADC) in precedence over Service Account.
- **Kafka**:
  - Supported sending failed messages to dead letter queue topics.
- **ai-mcp**:
  - Added observability support for AI MCP traffic.
  - Introduced the AI MCP plugin, enabling you to export any API to AI applications via MCP.
  - The plugin now supports using multiple tools in the same plugin instance.
  - The plugin now supports path parameters.
- **ais**:
  - Added the MemoryDB vector database strategy to LLM plugins.
- **kafka**:
  - Added support for OAuth 2.0 authorization for Confluent Schema Registry.
- **kafka-consume, confluent-consume**:
  - The plugin now supports modifying the returned content as needed.
- ace:
  - Add the `ace` plugin.
- ai-aws-guardrails:

rails plugin.

ety and compliance.

ou to evaluate an LLM and use the score as a balancer.

in plugin table.

ects the MCP traffic with OAuth2.

ng the tool.

  - Added latency and cost observability to realtime API.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Added support for Gemini Rerank in native format.
    - Exposed `input_tokens_details.cached_tokens_details.image_tokens_count` in observability metrics.
- ai-proxy:
    - Added `time_to_first_token` and `request_mode` for observability.
- ai-sanitizer:
    - Added a `block_if_detected` option to reject requests containing PII data instead of sanitizing them. When `block_if_detected` is enabled, requests with detected PII will be blocked with a 400 response containing details about the identified PII types and count.
    - Added support for sanitizing LLM responses.
- ai-semantic-response-guard:
    - Introduced the AI Semantic Response Guard plugin, enabling you to guard LLM responses against semantic content.
- aws-lambda:
    - Added support for AWS API Gateway payload v2. A new configuration field `awsgateway_compatible_payload_version` has been added to control the version of the payload.
- confluent-consume:
    - Added `websocket` mode to the `confluent-consume` plugin.
- datakit:
    - Added caching support via a new `cache` node type.
    - Added support for conditional execution via the `branch` node.
- injection-protection:
    - Added the ability to allow users to check a request path or query.
- jwt-signer:
    - Added new options `access_token_signing` and `channel_token_signing` to quickly turn on and off token signing or re-signing.
    - Added new options to support optional claim verification: `access_channel_token_(introspection_)optional_claims`. The specified claims are verified only if they are present.
    - Added new options to support claim existence verification: `access_channel_token_(introspection_)required_claims`. The specified claims must be present in the token payload.
    - Added support for additional claim validations, including `notbefore`, `issuer`, `subject`, and `audience`.
- openid-connect:
    - Added support for claim to consumer groups mapping.
    - Added support for session binding (IP, scheme, and/or User-Agent header).
- opentelemetry:
    - Added the `peer.service` attribute to the balancer span to link multiple services together. This allows for better tracing of requests that span multiple services.
- rate-limiting-advanced:
    - Added request throttling feature.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

the form of Lua expressions `$(some_lua_expression)`.

/or User-Agent header).

Solace PubSub+ event broker.

common use cases such as storing secrets in Vault and retrieving them as tokens in Datakit.

h adds Solace consumption capabilities to Kong.

mation on the Data Plane side.

PDK

- Added a new `kong.client.get_aws_vpce_id()` function for returning the VPC ID of the endpoint in the PROXY protocol v2 header PP2_SUBTYPE_AWS_VPCE_ID.
- **PDK**: Added support for calling the `kong.response.get_raw_body()` and `kong.response.set_raw_body()` PDK functions from plugin `:response()` handlers.
- **PDK Request ID**: Added support for retrieving the request ID via the `kong.request.get_id()` function in the PDK.

Core

- Added failover support for upstream targets, allowing load balancing to backup targets when primary targets are offline.
- Added `$kong_upstream_*` Nginx variables to correctly log upstream information in `log_format`.
- Added the new metric `target_id` (Target entity ID) to the Konnect Analytics to improve the observability.
- Added the `/status/timers` endpoint to the Status API for data planes, mirroring the Admin API `/timers` endpoint.
- AI MCP metrics are now reported to Konnect Analytics.
- **Analytics**: Added the `cache.status` field to collect the cache status of proxy-cache plugin.
- Kong now supports Azure authentication methods for connecting to Azure PostgreSQL databases. A new configuration option `pg_azure_auth` as well as corresponding configuration fields `pg_azure_client_id`, `pg_azure_client_secret`, and `pg_azure_tenant_id` have been added to the Kong configuration file. When `pg_azure_auth` is set to `on`, Kong will use Azure authentication methods to connect to Azure PostgreSQL databases.

Default

- **solace**: Added WebSocket transport support for `PERSISTENT` delivery mode.

Kong Manager

- Added support for failover targets in upstreams.
- **jwt-signer**: Added support for new parameters in the JWT Signer plugin.
- **key-auth, key-auth-enc**: You can now configure the TTL parameter for the Key Authentication and Key Authentication Encrypted plugins.
- **service-protection**: Revamped the UI of the Service Protection plugin.
- Updated documentation links in the Kong Manager Enterprise Edition to point to the latest resources.

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue where Structured Output did not work correctly with Anthropic Claude models.
  - Fixed an issue where structured output did not work for the Bedrock provider when SSE streaming responses.
  - Fixed an issue where Structured Output did not work correctly with Bedrock (Converse API) models.
  - Fixed an issue where `id`, `created`, and/or `finish_reason` fields were missing from or incorrect in Gemini responses.
  - Fixed an issue where Structured-Output requests were ignored.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

’t properly parse multiple `toolUse` tool calls in one turn, on some models.

ent for Gemini embeddings calls.

he namespace instead of including it in the table name to avoid truncation. This change invalidates Semantic Prompt Guard, and AI Proxy Advanced. If a user is using a very long cache TTL, cache warmup

s failed due to incorrect URL construction and response parsing.

nced generated incorrect default ports for upstream schemes, leading to 400 errors.

ken usage for AI Proxy token usage details.

    - Fixed an issue where AI Proxy and AI Proxy Advanced could produce duplicate content in the response when the SSE event was truncated.
    - Fixed an issue where AI Proxy and AI Proxy Advanced could drop content in the response when the SSE event was truncated.
    - Fixed an issue where AI Proxy and AI Proxy Advanced couldn't properly failover to a Bedrock target.
- **ais**:
    - Fixed an issue where the LLM license migration could fail if the license counter contained more than one week of data.
- **embeddings**:
    - Fixed an issue where the `text-embedding-ada-002` model would return a 400 error when the `dimensions` parameter was set.
- **kafka-log, kafka-upstream, kafka-consume**:
    - Added warnings when the strategy is SASL without a mechanism, or the mechanism is set without a SASL strategy.
- ai-aws-guardrails:
    - Fixed the plugin to work with multi-modal content.
- ai-azure-content-safety:
    - Fixed the plugin to work with multi-modal content.
- ai-llm-as-judge:
    - Fix an issue where the ai-llm-as-judge plugin didn't work with non-OpenAI provider configuration.
- ai-prompt-compressor:
    - Fixed the plugin when no model parameter is specified.
- ai-proxy-advanced:
    - Fixed an issue where the ai-retry phase was not correctly setting the namespace in the `kong.plugin.ctx`, causing the ai-proxy-advanced balancer to retry the first target more than once.
    - Fixed an issue where the Gemini provider didn't support Model Garden.
    - Fixed an issue where managed identity could be cached incorrectly.
    - Fixed an issue where Mistral models would return `Unsupported field: seed` when using some inference libraries.
    - Fixed an issue where array input wasn't being properly validated for certain providers. Note that Bedrock, Gemini Public, and Mistral providers don't support array input, as before.
    - Fixed an issue where some Titan embeddings models reported malformed requests.
    - Fixed an issue where the AI Proxy Advanced plugin's lowest latency load balancer could fail to select a target when only one target was available, leading to 500 errors.
- ai-proxy:
    - Fixed an issue where JSON array data wasn't correctly parsed.
    - Fixed an issue where the Anthropic provider failed to stream function call responses.
    - Fixed an issue where the Anthropic provider could truncate tokens in streaming responses.
    - Fixed an issue where OpenAI chat completion's `tool_choice` was not converted to Anthropic's.
    - in Gemini responses when a variable was used as the model name.
    - n OpenAI-format Gemini responses in some situations.
    - roperly handle multiple tool calls across different turns.
    - s an empty object in structured output.
    - se correctly when the frame was incomplete.
    - d the wrong `stop_reason` to Chat and Completions responses.
    - ests would panic when the ai-semantic-cache plugin was enabled.
    - ssed correctly when using Azure as the provider.
    - y handle image editing requests through the `image/v1/images/edits` route.
    - tials causing improper request balancing.
    - Fixed an issue where responses could not be redacted correctly when there were multiple redact texts of different lengths sharing the same prefix.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ai-semantic-cache:
  - Fixed an issue where the DELETE `/ai-semantic-cache` endpoint returned an incorrect 204 status for non-existent keys.
  - Fixed an issue where AI inference requests to non-OpenAI providers in the stream mode were not supported.
  - Fixed an issue where the SSE terminator could have incorrect ending characters.
  - Fixed an issue where the DELETE `/ai-semantic-cache` endpoint returned 500 errors for successful deletions when using pgvector as the vector database.
- ai-semantic-prompt-guard:
  - Fixed the deletion of guard instances and improved error handling.
- ai-semantic-response-guard:
  - Fixed the deletion of guard instances and improved error handling.
- app-dynamics:
  - Fixed an issue where response time measurements to backend services were inaccurate. The plugin now captures the full request duration, including upstream.
- aws-lambda:
  - Fixed an issue where the AWS Gateway compatible payload generated by the plugin did not include the `resource` field in some cases.
- confluent:
  - Fixed an issue where the plugin did not use `conf.cluster_name`.
- datakit:
  - Fixed an issue where an invalid plugin instance could affect other plugins.
  - Fixed plugin config validation to catch more invalid usage of the `property` node.
- exit-transformer:
  - Fixed an issue where exit-transformer affected the Status API.
- jwe-decrypt:
  - Fixed an issue where the `key_sets` cache could not be invalidated correctly.
- kafka-upstream:
  - Fixed an issue where `forward_body` dropped request bodies larger than Nginx's default buffer size (16 KB). It now reads up to 1 MB and returns an error if the body can't be fully read.
- ldap-auth-advanced:
  - Fixed a group validation issue where LDAP group names containing asterisk (*) characters were incorrectly marked as invalid during Kong Manager RBAC authentication. Group names with asterisk characters (such as `*Dev - EXAMPLE - TOP`) now properly validate and allow role mapping.
- mocking:
  - Fixed an issue where empty arrays defined in the mocking plugin schema were incorrectly returned as object types instead of array types in response bodies.
- mtls-auth:
  - Fixed an issue where a certificate with an empty DN led to a runtime exception.
- oas-validation:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

that did not conform to the configured OpenAPI specification could cause the plugin to throw an P 500 error.

g negative introspection responses.

log messages in the error logs.

er and `downstream_session_id_header` mistakenly required the `downstream_headers_claims` and

n the Prometheus metrics.

ow empty consumer identifiers when consumers didn't have a username. The plugin now falls back to e is not available, ensuring consumer identification in metrics.

- request-callout:

  - Fixed an issue where expressions could not read headers, query, and URI captures via shortcuts of the form `$(headers.some_header)`.
  - Fixed an issue where `untrusted_lua_sandbox_requires` option was not respected.
  - Fixed regression where the upstream request body would not be forwarded if `upstream.body.custom` was empty.
  - `request.by_lua` code will now run before a request is made or a cached callout is fetched. Previously, it did not run before an attempt to fetch from cache, which did not allow for cache key customization.
  - The plugin now uses additional components to generate the cache key: request consumer, consumer groups, plugin ID, route ID; callout request method, URL, query params, headers, and body.
- response-transformer-advanced:
  - Fixed a failure that occurred when Nginx gzip was enabled for an upstream.
- solace-upstream:
  - Fixed an issue where `forward_body` dropped request bodies larger than Nginx's default buffer size (16 KB). It now reads up to 1 MB and returns an error if the body can't be fully read.
- tls-metadata-headers:
  - Fixed an issue where a certificate with an empty DN led to a runtime exception.
- xml-threat-protection:
  - Fixed an issue where requests without a body were blocked.

Core

- Fixed an issue where stream/proxy listeners could unexpectedly access the router from the control plane. Stream/proxy listeners are now disabled for the control plane.
- **analytics**: Fixed an issue where multi-model tokens usage metrics were not reported to Konnect.
- Fix an issue where the CLI command and the kong process could throw warning messages about the user directive not being used when running as a non-root user.
- Fixed an issue where incorrect an delimiter in cluster events caused cache key problems, preventing Dev Portal from updating the page cache properly in hybrid deployment mode.
- Fixed an issue where results were lost when querying LMDB page by page.
- **keyring**: Fixed an issue where 'key not found' was incorrectly reported as a warning continuously.
- **postgres**: Improved error logging for PostgreSQL connection failures. **vault**: Log more details when vault callback execution fails.
- **vault**: Fixed an issue where vault config `base64_decode` caused DP to fail to start.

Clustering

- Fixed an issue where adding consumers to consumer groups could crash the data plane during incremental sync.
- Fixed an issue where control planes could consume unnecessary memory when only incremental data planes were connected.
- Fixed an issue where the `/clustering/data-planes` endpoint returned an incorrect DP hostname when incremental sync was enabled.
- Fixed an issue where the incremental sync did not work properly for the stream subsystem.
- Fixed redundant configuration exports when multiple data planes were connected concurrently by coalescing triggers and delegating export/broadcast operations to the background push loop.

A

tation in Kong Manager would fail due to `authenticated_groups` being a string.

d an unexpected error.

n API didn't include the `ttl` field in GET responses. This includes:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

PDK

- Fixed an issue where PDK returned non-empty header when requests were not proxied to upstream.

Default

- Fixed an issue where the request count was not being updated based on the `license_creation_date` of the license.
- **kafka**: Fixed an issue where the Kafka or Confluent Consume plugins couldn't consume the correct message when the consuming offset of the topic was not 0.
  kafka: Fixed an issue with parsing `ListOffset` Response version 0.

Kong Manager

- Fixed an issue where the vault picker was missing in the Request Callout plugin.

Dependency

CLI Command

- Bumped ca-certificates (debug tool) from 2025-02-25 to 2025-07-15.
- Bumped curl (debug tool) from 8.12.1 to 8.15.0.
- Bumped nghttp2 (debug tool) from 1.65.0 to 1.66.0.

Core

- Bumped kong-redis-cluster from 1.5.5 to 1.5.6. This fixes an issue where Redis connections were not reused properly.
- Bumped libexpat from 2.6.4 to 2.7.1.
- Bumped libxslt from 1.1.42 to 1.1.43.
- Bumped lua-muiltipart from 0.5.9 to 0.5.11
- Bumped lua-protobuf from 0.5.2 to 0.5.3.
- Bumped lua-resty-aws from 1.5.4 to 1.6.0.
- Bumped lua-resty-azure from 1.7.0 to 1.10.0.
- Bumped lua-resty-cookie from 0.3.0 to 0.4.1.
- Bumped lua-resty-gcp from 0.0.13 to 0.0.14.
- Bumped lua-resty-jq from 0.1.0 to 0.2.0.
- Bumped lua-resty-lmdb to version 1.6.1.
- Bumped lua-resty-session from 4.0.5 to 4.1.4.
- Bumped lua-resty-websocket to version 0.4.0.2 to solve an issue with connecting to an HTTP/1.0 proxy, and to add an enhancement for status code return.
- Bumped LuaRocks from 3.11.1 to 3.12.2.
- Bumped multipart from 0.5.9 to 0.5.10.
- Bumped PCRE2 from 10.45 to 10.46.
- Bumped snappy from 1.2.1 to 1.2.2.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

P

P

t path.

P

al metric by using internal counters instead of the `select count(*)` query through the database. If this
nts, use the command `kong migrations reinitialize-workspace-entity-counters` to re-sync the

K

Kong Manager

- **Kong Manager**: In the Confluent Consume, Kafka Consume, Kafka Upstream, Kafka Log, and Confluent plugins, setting `schema_registry.confluent.authentication.mode` or `topics.schema_registry.confluent.authentication.mode` to `none` may not be saved after submission.

3.11.0.14

Release date 2026/06/30

Feature

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which could reduce frequent disconnections and reconnection attempts and improve performance. Emitted a log entry showing the config payload size and the configured `cluster_max_payload` size when this happens.

Bugfix

Plugin

- **kafka-upstream, kafka-log, kafka-consume, confluent, confluent-consume**:
  - Fixed Kafka keepalive pools leaking connections across different SASL credentials and TLS verification settings.
- exit-transformer:
  - Fixed an issue where a response body that was a JSON primitive (e.g. `false`) caused a 500 internal error.
- oas-validation:
  - Fixed an issue where path parameters were extracted from the wrong URI segment when `custom_base_path` was used with bare `/{param}` paths.
- opa:
  - Fixed json body processing to recognize `application/json` content-type with charset, ensuring proper handling of JSON request bodies.
- openid-connect:
  - Fixed an inconsistency where `credential_claim` resolved the same claim name to a different value than `upstream_headers_claims` because it consulted the id_token before the access_token, while the upstream headers resolver consulted the access_token first. With IdPs (e.g. Okta) that set distinct `sub` values in the two tokens, `authenticated_entity.id` did not match the upstream header the plugin set on the same request.
  - Fixed an issue where Redis-backed session storage could fail when Redis connections were routed through a proxy.
- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.
- session:
  - Fixed an issue that occurs when Postgres strategy is used for session storage, concurrent authentication requests could result in race condition and session creation collisions.

Clustering

- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.

LS certificate setup failures instead of loading their backup configuration.

s. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful

able CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable

t export config to fallback storage when the control plane uses periodic polling instead of

pending foreign-key references across a failed resume, causing spurious validation failures.

C

ng insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.

diately with `no_wait = true` when node level mutex is being held by another worker.

errors could be reported as subsequent socket write failures.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where Kong Manager users authenticated through IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim changes, or end up with inconsistent mappings during concurrent authentication requests.
- Fixed an issue where `kong.service.set_tls_cert_key` did not update the upstream keepalive pool name. Now includes a cert fingerprint for proper connection isolation.
- Fixed an issue where the KONG_ANALYTICS_FLUSH_INTERVAL environment variable was not correctly applied to the analytics flush interval.
- Fixed Kafka broker returning failed connections to the keepalive pool, added SSL handshake retry, and improved error propagation.

Dependency

Core

- Bumped kong-lua-resty-ljsonschema from 1.2.0 to 1.3.3.
- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

Performance

Core

- Improved performance of analytics data collection by reducing the default local buffer size.
- **RBAC**: Improved PostgreSQL performance when deleting Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

3.11.0.13

Release date 2026/06/11

Bugfix

Core

- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).

3.11.0.12

Release date 2026/05/28

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-40701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.
- Security: Fixed CVE-2026-6338 in core proxy request header handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header cleanup, preventing CL.0 request smuggling with crafted `Connection: Content-Length` headers on requests with a body.

Dependency

Core

: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-

es: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-

3

R

E

P

) were incorrectly converted to objects ({}) when using `is_proxy_integration=true` and
ansformer plugin.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where a 500 error occurred when `is_proxy_integration` was enabled and the Lambda function returned `null` values in `headers` or `multiValueHeaders`. Null values are now converted to empty strings.

3.11.0.10

Release date 2026/04/27

Bugfix

Core

- **Debugger**: Fixed an issue where Redis command arguments were incorrectly included in Redis spans.
- **Debugger**: Fixed an issue where the time spent during the TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side latency.
- **Debugger**: Fixed an issue where the Konnect Debugger concatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g. `unix:/<prefix>/sockets/am:tls`).
- Fixed an issue where the real client IP from Proxy Protocol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497 plain HTTP to HTTPS port) or when the client disconnected prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from `$proxy_protocol_addr` on early request termination, and added `error_page` 497 routing through `kong_error_handler`.

Clustering

- Fixed clustering sync reliability issues by immediately failing pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

Plugin

- forward-proxy:
  - Added `ca_certificates` option for per-plugin TLS verification. It allows certificate chain and hostname checks against specified CAs instead of global settings, ensuring explicit trust.
- service-protection:
  - Fixed an issue where the Service Protection plugin could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after Rate Limiting Advanced and only evaluates requests that pass rate limiting, by updating its priority from 915 to 901.

Dependency

Core

- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2

3.11.0.9

Release date 2026/04/15

Bugfix

Configuration

- Added `lru_cache_size` to allow configuration of in-memory LRU cache size.

C

tected if multiple `X-Forwarded-Proto` values were provided.

h the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` was
dy messages for 501 and 505 status codes.

orrect `latencies.client` values due to not capturing the access end time properly. This fix ensures that
f Active Tracing being active or not.

wnership of `/etc/kong/kong.logrotate` to `kong:kong`, causing permission issues when executed by the
nstall.

ged the secret to an empty string temporarily after changing vault config.

C

when downgrading sync protocol to v1, which may cause excessive load on CP and lead to performance

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where Incremental Sync (ICS) would crash and stop further sync attempts.

Plugin

- graphql-rate-limiting-advanced:
  - Fixed an issue where the graphql-rate-limiting-advanced plugin's API threw 500 errors when handling HTTP PUT requests.
- jwt:
  - Fixed an issue where malformed JWT tokens (e.g. tokens without dots) caused a 500 Internal Server Error instead of returning 401 Unauthorized.
- oas-validation:
  - Fixed an issue where `minLength` and `maxLength` constraints defined in a Swagger 2.0 parameter schema were not enforced.
  - Fixed an issue where swagger `formData` parameters were not properly handled.
- openid-connect:
  - Fixed an issue where client-provided headers could be forwarded to upstream services when the corresponding JWT claim was missing from the token. The plugin now clears client headers before processing `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or downstream.
  - Fixed DPoP verification for opaque tokens (RFC 9449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.

Kong Manager

- Fixed workspace navigation for workspace names containing non-ASCII characters.

Dependency

Core

- Bumped kong-gql from 0.2.3 to 0.2.4 to fix the null value issue in the GraphQL query syntax that caused a parsed AST error in the DeGraphQL plugin.

Performance

Core

- **core**: Improved performance of Kong core by using `ngx.var.http_*` instead of `kong.tools.http.get_header`.

Admin API

- Optimized `GET /kong` endpoint to use `SELECT DISTINCT` for populating `enabled_in_cluster` instead of iterating all plugin rows.

3.11.0.8

Release date 2026/03/12

Bugfix

Clustering

- Fixed an issue where a SQL injection vulnerability existed in the clustering RPC procedure, ensuring safer SQL operations (CVE-2026-1907).

C

onse injection (CVE-2026-1642)

I

C

e: CVE-2025-15467.

3

R

P

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- **AI Plugins**:
  - Fixed an issue where Gemini (Vertex) models didn't return JSON formatted responses when instructed.
  - Fixed an issue where OpenAI, OpenAI-compatible, and HuggingFace models may have a 0 `completion_tokens` count with SSE streaming responses.
  - Fixed an issue where Bedrock requests with missing model names in the request path would not be properly validated. Now returns a clear error when model name is required in the path but not provided.
- **kafka**:
  - Fix issue where Kafka plugin produced records with incorrect `offsetDelta` in the record package.
- **llm**:
  - Fixed an issue where Gemini embeddings driver did not use correct url.
  - Fixed an issue where HuggingFace embeddings driver did not handle response correctly.
- ai-aws-guardrails:
  - Fixed an issue where the ai-aws-guardrails metrics could not be recorded.
- ai-proxy-advanced:
  - Fixed balancer retry failures caused by expired DNS entries by preloading DNS for targets.
  - Fixed an issue where the token count for Gemini Vertex embeddings API in native format was incorrect.
  - Fixed an issue where the token count for Gemini Vertex embeddings API in OpenAI format was incorrect.
  - Fixed excessive DNS warning logs for template variable endpoints like `$(headers.x_gcp_endpoint)`. These warnings appeared on every configuration change because template variables cannot be resolved until request time.
  - Fixed intermittent 500 responses from the AI Proxy Advanced plugin when using Azure OpenAI
  - Fixed an issue where the native format option did not work correctly for non-openai formats.
  - Fixed an issue where Files content analytics extraction is not handled properly for Azure.
  - Fixed an issue where AWS Bedrock invoke command is not properly proxied.
  - Fixed missing `id` and `created` fields in certain drivers.
  - Fixed an issue where the `max_completion_tokens` parameter was not being set correctly for O1 series models (e.g., `o1`, `o3`, `o4`, `gpt-5`).
- ai-proxy:
  - Added dimension configuration support for Amazon Titan Embed v2 models.
  - Fixed an issue where using ai-proxy-advanced in conjunction with a logging plugin (such as file-log) resulting in missing information on the last entry of the balancer "tries" section.
- ai-semantic-cache:
  - Fixed an issue where Cohere and Huggingface models did not work with the semantic cache because of the polluted request format.
- aws-lambda:
  - added a verbose error level logging for better debugging of AWS Lambda invocation issues.
- datakit:

d usage of the `property` node.

g or trailing spaces in the `path` field could cause upgrade failures.

ed from non-default workspaces.

not properly disabled when `validate_response_body` was set to `false`.

nyOf when they are used with a discriminator are not unfolded.

were used for Redis Sentinel and no authentication supported for Redis, causing `NOAUTH Authentication`

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where invalid `x-b3-flags` header values caused 500 responses.
  - Fixed an issue where the instrumentation started unexpectedly on control planes of hybird mode.
- saml:
  - Fixed an issue that caused a crash when the NameID Format was set to `Unspecified`.

Core

- Fixed an issue where Kong Manager failed to generate a cookie when OIDC was enabled due to a missing `password` grant type in `auth_methods`.
- **Clustering** Fixed an issue where consumer groups may cause incremental sync to fail at the first sync of a DP.
- Fixed an issue where Kong incorrectly logged upstream status codes as 000 (or empty) when HTTP/2 clients disconnected during response processing. This occurred when response buffering was enabled. Kong now correctly records the actual upstream status code even when the HTTP/2 client disconnects before receiving the complete response.
- Fixed an issue where `kong health` command would fail to run when kong configuration contains vault references.
- Fixed an issue where migrations could fail due to missing database relations by repositioning basic-auth and key-auth plugin scripts for correct execution order.
- Fixed an issue where the postinstall script changed kong.logrotate permissions; it now resets to 644.

Clustering

- **balancer**: Fixed an issue where the unsupported field `sticky_sessions_cookie_path` was blocking configuration syncing on data planes older than version 3.11.
- Fixed an issue where the prometheus metric `kong_control_plane_connected` was missing when the Data Plane side enabled incremental sync.

Dependency

Core

- Bumped lua-resty-healthcheck to version 3.1.1 to remove incorrect deprecation notice on active healthchecks headers.
- Bumped libexpat from 2.7.1 to 2.7.3.

Performance

Core

- **core**: Improved performance of deleting expired rows for Postgres versions below 12.

3.11.0.6

Release date 2025/11/03

Bugfix

Configuration

- **balancer**: Fixed an issue where the dns query not stopped when related upstream deleted.

Core

up renaming may not be properly populated, causing stale data to be served.

vents cannot be handled in traditional cluster mode.

P

incorrect `latest` offset behavior. When `false` (default), maintains backwards compatibility where `latest` tarts from end of topic. Also fixed offset commit bug when no records are consumed, preventing feedback

er were incorrectly parsed responses from embedding API

may not be properly invalidated, causing stale data to be served.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- openid-connect:
  - Fixed an issue where for incremental sync, consumer related caches may not be properly invalidated, causing stale data to be served.
  - Fixed an issue where the `client_credentials/authorization_code` auth would not auto-recover if IdP was not accessible during Kong startup.

Clustering

- Fixed an issue where the data plane did not stop the health checker before cleaning up old configurations, which could lead to resource leaks.

Kong Manager

- **Confluent/Kafka plugins**: Fixed issues where Kafka plugins did not work when configured via Kong Manager.

3.11.0.5

Release date 2025/10/23

Bugfix

Plugin

- **llm**:
  - Fixed an issue where the subrequest implemented in LLM drivers did not handle error properly.
- acl:
  - Fixed an issue where the cache was not being invalidated for incremental sync in certain scenarios, leading to stale data being served.
- ai-proxy:
  - Fixed an issue where OpenAI chat completion's tool_choice was not converted to Anthropic's.
  - Fixed an issue where the `model` field was incorrect in Gemini responses when a variable was used as the model name.
  - Fixed an issue where `model` field was missing in OpenAI format response from Gemini provider in some situations.
  - Fixed integration with HuggingFace by adding support for the new serverless API, ensuring seamless compatibility.
  - Fixed an issue where extra inputs were not permitted for huggingface inference provider
- ai-rate-limiting-advanced:
  - Fixed an issue where the plugin decreased requests by whole numbers when using Redis. This is an opt-in fix and can be enabled by setting `decrease_by_fractions_in_redis` to true in the plugin configuration.
- ai-request-transformer:
  - Fixed an issue where ai-request-transformer plugin does not accept capture groups for deployment field
- ai-sanitizer:
  - Fixed an issue where responses could not be redacted correctly when there were multiple redact texts of different lengths sharing the same prefix.
- ai-semantic-cache:
  - Fixed an issue where the DELETE /ai-semantic-cache returned 500 even deletion was successful, when using pgvector as vectordb.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

che with non-existent key returned incorrect status 204.

OpenAI providers in the stream mode were not supported.

e payload generated by the plugin did not include the `resource` field in some cases.

ect using mTLS.

ect type.

ld affect other plugins.

be invalidated correctly.

- kafka-consume:
  - Fixed an issue where the plugin would fail to connect using mTLS.
- ldap-auth-advanced:
  - Fixed group validation issue where LDAP group names containing asterisk (*) characters were incorrectly marked as invalid during Kong Manager RBAC authentication. Group names with asterisk characters (such as "Dev - EXAMPLE - TOP") now properly validate and allow role mapping.
- oas-validation:
  - Fixed an issue where parameter data extraction failed when `$` appears in the path pattern.
- response-transformer-advanced:
  - Fixed an issue where the failure occurred when Nginx gzip was enabled for upstream.

Configuration

- Fixed an issue where the restart command read configuration multiple times and failed to stop nginx.

Core

- **Fixed an issue where the partial entities cannot be deleted when cascading delete a workspace.**
- **analytics**: multi-model tokens usage metrics were not reported to konnect

Clustering

- Fixed an issue where `/clustering/data-planes` endpoint returns incorrect DP hostname when incremental sync was enabled.
- Fixed an issue where adding consumers to consumer groups could crash the data plane during incremental sync.

Admin API

- Fixed an issue where enabling `openid-connect` authentication in Kong Manager would fail due to `authenticated_groups` being a string.

Kong Manager

- Fixed an issue where admins with custom role saw 'restricted access' banner when trying to create a new role.

3.11.0.4

Release date 2025/09/30

Bugfix

Plugin

- ai-proxy:
  - Fixed an issue when empty array in structured output was encoded as empty object.

3.11.0.3

R

F

P

_AUTH_METHOD_ORDER environment variable. By configuring it to be "adc" allows plugin to select
ce over Service Account.

F

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- **AI Plugins**:
  - Fixed an issue Structured Output did not work correctly with Anthropic Claude models.
  - Fixed an issue Structured Output did not work correctly with Bedrock (Converse API) models.
  - Fixed an issue where `id`, `created`, and/or `finish_reason` fields were missing from or incorrect in Gemini responses.
  - Fixed an issue where Structured-Output requests were ignored.
  - Fixed an issue where the Dimensionality was not sent for Gemini embeddings calls.
- **ai-driver**:
  - Fixed an issue where AI Proxy and AI Proxy Advanced generated incorrect default ports for upstream schemes, leading to 400 errors.
- **embeddings**:
  - Fixed an issue where the `text-embedding-ada-002` model would return an 400 error when the `dimensions` parameter was set.
- ai-aws-guardrails:
  - Fixed the plugin to work with multi-modal content.
- ai-azure-content-safety:
  - Fixed the plugin to work with multi-modal content.
- ai-proxy-advanced:
  - Fixed an issue where Mistral models would return `Unsupported field: seed` when using some inference libraries.
  - Skip unknown cached details key from o11y observation.
  - Fixed an issue where array input is not recognized as valid request for some providers. Bedrock, Gemini Public and Mistral provider don't accept array input as before.
  - Fixed an issue where some Titan embeddings model reported malformed request.
- ai-proxy:
  - Fixed an issue where the Anthropic provider mapped the wrong stop_reason to Chat and Completions responses.
  - Fixed an issue where JSON array data is not correctly parsed.
  - Fixed an issue with Azure Managed Identity credentials causing improper request balancing.
  - Fixed an issue where AWS Bedrock did not properly handle image editing requests through the `image/v1/images/edits` route.
- mocking:
  - Fixed an issue where an empty array set in the mocking plugin schema with object type. It should return an array type instead of an object type in the response body.
- oauth2-introspection:
  - Fixed an issue where authentication failures did not log messages in the error logs.
- prometheus:
  - Fixed an issue where Prometheus metrics would show empty consumer identifiers when consumers don't have a username. The plugin now falls back to using the consumer's custom_id when username is not available, ensuring consumer identification in metrics.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

uld not be forwarded if `upstream.body.custom` was empty.

sage for AI Proxy token usage details

r not support model garden

caused cache key problems, preventing portal from updating page cache properly in hybrid deployment

DB page by page.

caused DP to fail to start.

roperly for the stream subsystem.

Kong Manager

- Resolved a security issue in the Kong Manager UI.

Dependency

Core

- Bumped lua-muiltipart from 0.5.9 to 0.5.11
- Bumped lua-resty-gcp from 0.0.13 to 0.0.14.

Performance

Plugin

- prometheus:
  - Optimized fetching of the `kong_db_entities_total` metric by using internal counters instead of `select count(*)` query through the database. If this metric is found to be get out of sync with the real row counts, please use the command `kong migrations reinitialize-workspace-entity-counters` to re-sync the counts.

3.11.0.2

Release date 2025/07/28

Bugfix

Plugin

- **Semantic Plugins**:
  - Fixed an issue where Gemini Vertex AI embeddings failed due to incorrect URL construction and response parsing.
- ai-proxy-advanced:
  - Fixed an issue where ai-retry phase was not correctly setting the namespace in the kong.plugin.ctx, causing ai-proxy-advanced balancer retry first target more than once.
  - Fixed an issue where managed identity may not be cached properly.
- ai-proxy:
  - Fixed an issue where aws stream parser didn't parse correctly when the frame was incomplete.
  - Fixed an issue where AWS Bedrock streaming requests would panic when the ai-semantic-cache plugin was enabled.
  - Fixed an issue where resource was not being passed correctly when using Azure as provider.
- request-callout:
  - Fixed an issue where `untrusted_lua_sandbox_requires` option was not respected.
  - `request.by_lua` code will now run before a request is made or a cached callout is fetched. Previously, it did not run before an attempt to fetch from cache, which did not allow for cache key customization.
  - The plugin now uses additional components to generate the cache key: request consumer, consumer groups, plugin ID, route ID; callout request method, URL, aders, query, and URI captures via shortcuts of the form `$(headers.some_header)`.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

an't properly failover to a Bedrock target.

ight produce duplicate content in the response when the SSE event was truncated.

ight drop content in the response when the SSE event was truncated.

- Fixed an issue where the llm license migration could fail if the license counter contained more than one week of data.

- ai-semantic-cache:
  - Fixed an issue where SSE terminator may not have correct ending characters.
- request-callout:
  - Fixed an issue where `untrusted_lua_sandbox_requires` option was not respected.

Kong Manager

- Fixed an issue where the vault picker was missing in the Request Callout plugin.

Dependency

Core

- Bumped luarocks from 3.11.1 to 3.12.2. This fixes the error `main function has more than 65536 constants`, which was preventing rocks from being published or installed.
- **lua-resty-lmdb**: updated to version 1.6.1.

3.11.0.0

Release date 2025/07/03

Deprecation

Plugin

- ai-proxy, ai-proxy-advanced: Deprecated the `preserve` route_type. You are encouraged to use new route_types added in version 3.11.x.x and onwards.

Feature

Plugin

- **AI Plugins**:
  - Added new config field genai_category ‘text/embeddings’ and new route_type ‘llm/v1/embeddings’
- **Solace Upstream (beta)**:
  - Added a new plugin which allows to transform requests into Solace messages in a Solace queue or topic.
- **ai**:
  - Added support for transforming, introspecting, and collecting metrics for image and audio generation requests, Responses API, and Realtime API. Added support for proxying Files, Batches, and Assistants API.
  - add support for the `huggingface` LLM Native format in the ai related plugins.
  - added `model.options.bedrock.performance_config_latency` config parameter, to allow administrators to enforce performanceConfig ‘latency’ for all AWS Bedrock requests.
  - Added support for the `cohere` LLM format in the ai related plugins. This allows users can directly use the `cohere` rerank API.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ze schema field to clarify relation to the request body size limit.

t requests, for AWS Bedrock requests.

erand, converse, converse-stream, retrieveAndGenerate, and retrieveAndGenerate-stream.

d responses to/from AI LLM.

nation in requests before they are proxied by the AI Proxy or AI Proxy Advanced plugin.

te Limiting Advanced plugin. This allows users to specify a ratelimiting namespace for the plugin, Similar
ng-advanced plugin.

    - Added support for sending messages with dynamic keys to determine partitions.
- datakit:
    - Added new datakit plugin
- graphql-rate-limiting-advanced:
    - Added support for passing all downstream headers to GraphQL upstream servers in introspection requests.
- kafka-consume:
    - Added WebSocket support to the kafka-consume plugin for consuming Kafka messages.
- kafka-log:
    - Added support for Kafka 4.0. **kafka-upstream**: Added support for Kafka 4.0.
    - Added support for Schema Registry integration with Confluent Schema Registry for AVRO and JSON schemas.
    - Added support for sending messages with dynamic keys to determine partitions.
- kafka-upstream:
    - Added support for sending messages with dynamic keys to determine partitions.
- oas-validation:
    - Added support for validating `multipart/form-data` requests.
- opentelemetry:
    - Added a new configuration field `sampling_strategy` to the plugin. The field allowed you to specify the sampling strategies for OTLP `traces`. Set `parent_drop_probability_fallback` if you want parent-based sampling when the parent span contains a `false` sampled flag, and fallback to probability-based sampling otherwise. Set `parent_probability_fallback` if you want parent-based sampling when the parent span contains a valid sampled flag (`true` or `false`), and fallback to probability-based sampling otherwise. The default value is `parent_drop_probability_fallback` and keeps the instrumentation, sampling and exporting behaviour as before.
- prometheus:
    - added `consumer` label for ai metrics and added metrics for ai-rag-injector plugin.
- request-callout:
    - Marked the `auth_password` as an `encrypted` field.
    - The plugin now logs the request URL, response code, and request latency (in milliseconds).
    - The plugin now sends a custom User-Agent header if one isn't provided. The default value is `kong/<kong_version>/request-callout`.
- request-validator:
    - Added support for specifying JSON schema draft versions.
- Fixed an issue where the `ai-prompt-decorator` plugin prompt field was too short.

Configuration

- Added a configuration option `vault_secrets_lazy_load` to control how vault secrets are loaded. When enabled, plugin options stored as vault secrets are loaded only when needed. This can save memory and reduce startup time but may increase latency the first time a secret is accessed or after it expires. The default value is `off`, preserving the behavior of previous releases.

ide_konnect_cta that controls the visibility of the Konnect call-to-action in the Admin GUI.

P

) function for returning non-normalized forwarded_path.

ding A128KW, A192KW, A256KW, ECDH-ES+A128KW, ECDH-ES+A192KW, ECDH-ES+A256KW,

C

_sans. This allows to specify additional entries (either DNS names or URIs) for Subject Alternative Names

ault backend.

tech preview) Active Tracing feature

d incremental_sync were enabled in anonymous reports.

- Added the sticky-sessions load-balancer algorithm.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- **ai**: Change sales counter sync per hour instead of per week.
- **Conjur Vault**: Added support for CyberArk Conjur Vault.
- **Core**: Provided more granular and valuable latency metrics in Kong Gateway, aligning with our Active Tracing measurements.
- Created internal JSON Object Signing and Encryption (JOSE) library to improve performance, features and security of several plugins.
- Logged license model_hours exceeded warning when LLM model usage exceeded the limit.
- Schema map values can now assume null values.
- **vault**: Added support to decode base64 secrets before using them.

Kong Manager

- Added a feature to persist the configuration format preference.
- Added a new UI for the Request Callout plugin.
- Improved the Route configuration form for a better user experience.

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue where the Gemini provider could not use Anthropic 'rawPredict' endpoint models hosted in Vertex.
  - Fixed unable to use Titan Text Embeddings models.
- **ollama**:
  - Fixed an issue where 'tools' and 'RAG' decoration did not work for Ollama (llama2) provider.
- ai-aws-guardrails:
  - Fixed an issue where the plugin did not support inspecting responses in non-stream mode.
- ai-prompt-decorator:
  - Fixed an issue where the plugin would miss the model, temperature, and other user-defined fields.
- ai-proxy-advanced:
  - Add `tried_targets` field in serialized analytics logs for record of all tried ai targets.
  - Fix consistent-hashing algorithm not using correct value to hash.
  - Fixed an issue where the stale semantic key vector may not be refreshed after the plugin config is updated.
  - Fixed an issue where AI Proxy Advanced can't failover from other provider to Bedrock.
- ai-proxy:
  - Fixed an issue where latency metric was not implemented for streaming responses.
  - Fixed an issue where SSE terminator may not have correct ending characters.
  - Fixed an issue where the response body for observability may be larger than the real one because of the stale data.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

logged.

hen using AWS Bedrock inference profile.

emini provider.

e groups (e.g., `$(group1)/$(group2)`) failed to extract expected matches.

gin might panic when use redis strategy and sync_rate is set to 0.

correct ending characters.

lation on those plugins that contain a function name that does not comply with AWS Lambda's

- cors:
  - Fixed an issue where requests with empty `origin` headers would cause empty reply from server.
- degraphql:
  - Fixed an issue where the degraphql handle type Boolean was not being assigned correctly in the degraphql router.
- forward-proxy:
  - Marked the `auth_password` in the `forward_proxy` plugin as an `encrypted` field.
- header-cert-auth:
  - Fixed an issue where Header Cert Authentication plugin failed to validate revocation using OCSP when the downstream connection wasn't an SSL connection.
- jwt-signer:
  - Fixed an issue where data planes didn't use the keys passed from the control plane to sign/re-sign.
- jwt:
  - Fixed an issue where the WWW-Authenticate header used an incorrect delimiter, now using a comma as specified by RFC 7235.
- key-auth:
  - Fixed an issue where region was not permitted to be null for remote identity realms.
  - Fixed an issue where external consumers could not be used with traditional Kong deployments, such as with KIC.
- ldap-auth-advanced:
  - Fixed an issue that caused browsers to automatically pop up dialog boxes when authentication failed while `ldap-auth-advanced` was enabled in the Kong Manager.
- mocking:
  - Fixed an issue where an empty array set in the mocking plugin returned an object type instead of an array type in the response body.
- mtls-auth:
  - Fixed an issue where uselss interface is called when doing the OCSP client cert verification.
- oas-validation:
  - Fixed an issue where the plugin throws an error for responses without a Content-Type header.
  - Fixed an issue where query parameters with explode=false couldn't be validated.
  - Fixed an issue where the plugin raises "path not found error" when include_base_path is set to true and the server url is "/".
- openid-connect:
  - Fixed an issue where the OIDC plugin caused the third-party IDP to throw an error during logout attempts if the session had already been invalidated. Added the `client_id` to the logout URL to ensure the logout request is sent to the correct client, preventing such errors.
  - Fixed an issue where caused IdP to report invalid redirect_uri errors when `config.redirect_uri` was not configured and the uri path contained spaces.
- prometheus:
  - Fixed an issue where AI latency histogram might miss some calculation.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`ig_hash` might not work correctly for incremental sync.

`ose the db_entities_total` metric.

`ailable to response by_lua` code

would be accepted.

ccept explicit null values for removal of fields

body customizations were not performed when an empty request body was provided; now, an empty JSON request.

`eout when callouts.request.body.custom` is null and `callouts.request.headers.forward` is true.

`varded to upstream when upstream.body.forward` is false.

`by_lua` would apply to all subsequent callouts.

`query` will now correctly replace those in the callout URL.

- request-validator:
  - Fixed an issue where multipart/form-data content type was rejected.
- upstream-timeout:
  - Fixed an issue where `read_timeout`, `write_timeout`, and `connect_timeout` were set to 0, causing a runtime error. After this release, any existing upstream-timeout plugin with these fields set to 0 will automatically update them to the default value of 60000.
- AI Azure Content Safety: Fixed an issue where Blocklist breaches are not correctly parsed.
- Blocked plugins to execute retry logic. Also improve testing funtions
- Fixed an issue where AI Proxy and AI Proxy Advanced would use corrupted plugin config.
- Fixed an issue where an external Python plugin cannot receive the updated value for its referenceable configuration fields.
- Fixed an issue where some of ai metrics was missed in analytics
- Fixed an issue where the rate limiting plugins can't handle decimal numbers when using Redis strategy.

Core

- Fixed an issue where `ca_certificate` cache was not invalidated when incremental sync was enabled.
- Fixed an issue where upstream connection pooling failed when pool names exceeded 32 characters by applying a patch from upstream OpenResty.
- Fixed several issues that `kong start` and `kong stop` command throw error when the configuration contains vault reference and a prefix directory exists.
- Reverted removal of `translate_backwards` from plugins' metaschema in order to maintain backward compatibility.
- Added a new configuration, `route_match_calculation`, which included bug fixes for the `traditional_compatible` and the `expressions` router flavors. The default value `original` retained the current `3.x` router matching behavior without changes. The value `strict` enforced the router matching behavior with corrected calculation as follows:
  1. The weight (priority point) of a route was incorrectly downgraded.
  2. A route of HTTPS-only protocol with SNIs incorrectly captured requests over HTTP routes.
  3. A route of TLS-only protocol with SNIs incorrectly captured requests over TCP or UDP routes.
- **AI**: Fixed an issue where the password for the pgvector strategy was not being set correctly in the database.
- Fix issue where schema library would fail with a nil reference if configurations are set via both deprecated and new names with diverging values
- Fixed an issue where a change to a Partial in a custom workspace caused a communication issue between CP and DP on Incremental Config Sync mode.
- Fixed an issue where crud event was triggered multiple times by event_hooks.
- Fixed an issue where error logs were excessive when changing routes.
- Fixed an issue where full configuration sync caused data plane to stop proxying when incremental config sync is enabled.
- Fixed an issue where modifying x-forwarded-for header before access phase may not take effect
- Fixed an issue where new custom plugin creation during a full sync with incremental enabled would cause inconsistency. It now fails and reinitiating the sync in such case.
- -> Fixed an issue where newly spawned workers used outdated router data because the `init` phase was skipped.
- Fixed an issue where Pgvector index failed when using special characters in the name.
- Fixed an issue where Plugins were not exported correctly when using Partials in a custom workspace in Hybrid Mode.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

t including connection and handshake times.

orkspace correctly during batch updates.

d during incremental sync.

r rebuilding might be excessively noisy.

led due to token not being refreshed under certain conditions.

l with incorrect permission when running kong cli command with root privileges.

gged.

y status API is not accurate on the control plane.

int returned a validation error when a plugin was linked to a partial containing a vault key.

y calculated, now it should be more accurate.

lation errors on `rbac_role_entities_pkey` while using the `deck sync` command.

- Fixed an issue where validation incorrectly passed for mis-matched deprecated and new fields if the new field value was false.

- Fixed an issue where validation required all of `timeout` fields (`connect_timeout`, `read_timeout`, `send_timeout`) to have the same value. In reality only `connect_timeout` has to have the same value since that is the value used for generating the `timeout` field in the response if it is missing in the request.
- **kafka**: Fixed an issue where the Kafka SCRAM authentication did not send the server nonce.

Default

- Fixed an issue where adding the `hash_subject` and `store_metadata` fields to the `portal_session_conf` in the Dev Portal was not working as expected.

Clustering

- Fixed an issue where CP may send sync notifications too frequently when incremental sync is enabled.
- Fixed an issue where data plane (DP) might receive incorrect data if the control plane's (CP) configuration version was older than the DP's version.
- Fixed an issue where dataplane nodes sometimes did not recover from sync failures, leading to recursive retries and failures.
- Fixed an issue where debug level logs for incremental sync were insufficient, making debugging more difficult.
- Fixed an issue where events mechanism of clustering might be initialized repeatedly.
- Fixed an issue where LMDB operation failures during incremental sync were not reported.
- Fixed an issue where RPC calls miss the retry mechanism in the clustering system for resilience against transient network issues.
- Fixed an issue where some logs are missing when incremental sync is enabled on the Data Plane side.
- -> Fixed an issue where sometimes the paginated sync incorrectly reports "history lost" and fails.
- Fixed an issue where the Control Plane (CP) would send duplicate sync notifications when configuration changes occurred.
- Fixed an issue where the control plane might not send RPC calls to the data plane correctly in some corner cases.
- Fixed an issue where the delta coalescing logic on the CP side might work inefficiently.
- Fixed an issue where the RPC framework might handle connections incorrectly on the data plane.
- Fixed an issue where updating an entity in a non-default workspace during incremental sync may not have been applied correctly.
- Fixed an issue where validation might not report error message correctly when incremental sync was enabled.
- Fixed an issue where with small chance DP might repeatedly full sync when incremental sync is enabled.

Admin API

- Fixed an issue where deleting an RBAC user would also delete a non-default role with the same name.
- Fixed an issue where the Admin API returned a 500 error instead of a 401 error when an empty string was provided for the `Kong-Admin-Token` header.
- Fixed an issue where the data plane (DP) may report healthy before it is actually ready to accept traffic.
- Fixed an issue where the field `user_token_ident` was not being disallowed for update in the Admin API.
- Visiting kconfig.js from the Kong Manager UI no longer triggers warnings for vitals and portal deprecation.

Performance

- Fixed an issue where rate-limiting library could cause deadlock with Postgres.

C

shes if using off strategy.

K

various UI-related issues.

D

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped luarocks from 3.11.1 to 3.12.1. This fixes the error `main function has more than 65536 constants`, which was preventing rocks from being published or installed.

Default

- **Wasm**: removed ngx_wasm_module from default builds.

Performance

Core

- Improved the performance of string splitting functions in Kong's core.
- Improved performance by removing the n+1 query problem for plugins. Plugins are now fetched in bulk with plugins_partials and partials.
- Optimized query of the default workspace by directly accessing LMDB, improving performance.

Plugin

- ai-proxy:
  - Implemented a faster SSE parser.
- jwt:
  - refactored plugin code to be more performant (measured to be at least three times faster).
- oas-validation:
  - Improved performance for OpenAPI 3.1.
- openid-connect:
  - improved the performance of signature verification.
- rate-limiting-advanced:
  - Limited the length of the bucket identifier to prevent using strings longer than 256 characters for cache indexing, which could lead to high memory consumption in high-traffic scenarios.

Clustering

- Bumped page size for cluster sync to improve performance of full syncs.
- Improved RPC message queue responsiveness.

Known Issues

Plugin

- If any AI Gateway plugin has been enabled in a self-managed Kong Gateway deployment for more than a week, upgrades from 3.10 versions to 3.11.0.0 will fail due to a license migration issue. This does not affect Konnect deployments. A fix will be provided in 3.11.0.1.

  See breaking changes in 3.11 for a temporary workaround.

Core

RM64 Kong Gateway Docker images:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

would keep blocking certificate issuance. Retries are now rejected only while the backoff timestamp is

- ai-proxy:
  - Fixed streaming token count metrics for third-party models hosted on Vertex AI (claude-, *mistral-*, jamba-*) that reported inflated totals because incremental counts were treated as cumulative.
- degraphql:
  - Fixed an issue where the plugin router did not refresh after an incremental sync update on a Data Plane, leaving routes stale until the next full config push.
- oas-validation:
  - Fixed an issue where YAML 1.1 `null` values were parsed incorrectly.
  - Fixed an issue where the OAS specification cache failed to distinguish between different values of `api_spec_encoded` for the same specification content.
- openid-connect:
  - Fixed an issue where disabling `verify_signature` gave no warning, even though it also skips signature verification for bearer tokens from clients. The plugin now logs a warning when `verify_signature` is `false` and `auth_methods` includes `bearer`. It logs a notice instead when `bearer` is not enabled.
- request-callout:
  - Fixed an issue where a callout that failed and then succeeded on retry still returned the earlier failed response. The plugin now returns the response from the successful retry.
- kafka-consume, **confluent-consume**: Fixed an issue where the consumer group subscription declared protocol version 1 but carried the version 0 layout, so a topic-rewriting proxy rejected it.

Clustering

- Fixed an issue where a data plane failed to load config updates when a CA certificate expired. The data plane now accepts the config and logs a warning.
- Fixed an issue where the control plane sent incremental sync v2 notifications to a data plane that had fallen back to legacy sync v1, logging a misleading error.
- Fixed an issue where the data plane router rebuild could falsely abort with a concurrent-change error when the router spanned more than one page, leaving routes stale until the next config push.

Core

- Fixed an issue where Kong API Gateway skipped the WebSocket `ws_close` phase when it could not proxy the request.
- Fixed an issue where Kong API Gateway in DB-less mode could fail to detect configuration changes during reconfiguration, leaving the router or plugins iterator stale.

Dependency

Core

- Bumped libexpat to 2.8.4.
- Bumped libxml2 to 2.15.4.
- Bumped msgpack-c to 7.0.2.
- Bumped OpenSSL from 3.5.7 to 3.5.8.
- Bumped PCRE2 to 10.48.

Performance

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

incremental sync enabled under some circumstances.

P

ssary hash computation. Enabling the plugin now adds much less latency and CPU overhead to requests.

3

R

F

C

- Added a Distroless Docker image variant for Kong API Gateway. The Distroless image ships only the Kong binary and its runtime dependencies, with no package managers, no shells or any other programs you would expect to find in a standard Linux distribution.

Bugfix

Clustering

- **Clustering**: Improved RPC connection stability during long-running calls: a data plane now cancels a timed-out RPC so a late response cannot disrupt later calls, and the connection is kept alive (within a bound) while calls are still in flight instead of being dropped as a missed heartbeat.
- Fixed an issue where heavy packet loss could prevent a full sync from resuming.
- Fixed an issue where incremental sync delta coalescing merged non-adjacent deltas for the same entity. This could drop an entity's earlier `create` delta and keep only a later update, reordering it after a delta that already referenced it (for example, a plugin instance referencing a cloned plugin by name), causing validation to fail with `plugin '<name>' not enabled`. Coalescing now only merges successive deltas of the same entity, preserving the causal order the data plane relies on.
- Fixed an issue where the control plane could crash while handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as a ping/pong control frame) arrived before the `basic_info` frame. The control plane now drains and responds to control frames during the handshake until the expected frame is received, instead of dereferencing a nil plugin list.
- Fixed an issue where the delta coalescing logic on the CP side might work inefficiently.
- Fixed an issue where, with plugin streaming enabled, a single incremental sync validation failure would wipe out all plugin subschemas because the currently loaded plugins were not correctly excluded from the subschema unload.

PDK

- Fixed an issue on HTTP/2 connections where the request method and query were reported incorrectly, or could raise an error, when a request hit the error handler such as a 502 from an upstream connection reset.

Core

- Fixed an issue where a failed balancer creation leaked the per-upstream create lock, so every later creation for the same upstream stalled for 30 seconds.
- Fixed an issue where a healthcheck counter value of 255 crashed health checker creation. Healthcheck counters (`successes`, `tcp_failures`, `timeouts`, `http_failures`) are now limited to 254.
- Fixed an issue where `/status/ready` could report a data plane as `ready` before the new router and plugins iterator became active. Kong now reports readiness only after plugin configuration completes and the live objects are installed.
- On shell-free (distroless) images, the pluginserver query and start commands now expand `$KONG_PREFIX` / `${KONG_PREFIX}` from the environment and fail fast with a clear error on an unterminated quote or `${`, instead of passing the literal `$KONG_PREFIX` to the pluginserver or building a best-effort argv.

CLI Command

- Hardened stale nginx PID detection to survive PID reuse. On Linux, `kong start` now confirms a live PID actually belongs to nginx by reading `/proc/<pid>/cmdline`, so a reused PID from an ungraceful exit no longer blocks a restart.

Plugin

- ip-restriction:
  - Fixed an issue where warn log messages did not include the plugin name, making it difficult to identify the source of blocked requests.
- jwt-signer:
  - Fixed an issue where the plugin failed to set the signed access token header on the upstream request, when `access_token_upstream_header` (or
    he same name as `channel_token_request_header`.

    ndard Base64 secrets that contained `+` or `/` when `config.secret_is_base64` was enabled.

    e did not use weak keys due to a misspelled `__mode` metatable field.

    g negative introspection responses.

    expired token stayed authorized indefinitely instead of being rejected. An authoritative `active:false`

    was sent to the token endpoint for all grant types. It is now included only for the `authorization_code`

  - The `ignore_signature` option now logs a warning when it is set, because it turns off JWS signature verification for the listed grants.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- prometheus:
  - Fixed an issue where `kong_nginx_requests_total` and `kong_nginx_connections_total` duplicated the `http` values under the `stream` subsystem. They are now exported once under `http`.
  - Histogram series are now emitted grouped by label set (all buckets in ascending `le` order, then `_count`, then `_sum`) so the output follows the OpenMetrics interleaving rule. Previously samples were grouped by suffix, which caused strict consumers such as Google Managed Prometheus to drop points.
- saml:
  - Hardened signature validation against XML Signature Wrapping. The plugin now checks that the signature `Reference URI` is a same-document fragment that names the `ID` of the element it digests and consumes, so a signature can no longer be bound to a different element than the one that provides the identity. A response whose reference URI is empty or not a same-document fragment is now rejected.
- kafka-upstream, **kafka-log**, **confluent**, **kafka-consume**, **confluent-consume**: Fixed a permanent failure that started when a broker answered an `ApiVersions` request with an error code, an empty API key set, or a malformed frame. The client cached that result and every later request failed with `ProduceRequest API version not negotiated; broker may be unreachable` until the node restarted, even after the broker recovered. The client now refuses an unusable `ApiVersions` response, keeps the previous negotiation, and retries the negotiation for a topic whose metadata is already cached.

Kong Manager

- Fixed an issue where the Export button on the Vitals Reports page did not download the report CSV.

Dependency

Core

- Replaced resty-cli with rusty-cli

Performance

Clustering

- Improved data plane stability when applying a large configuration sync from the control plane, reducing the chance of a worker restart while the update is being processed.

Admin API

- Improved the performance of listing workspaces with `?counter=true`. Entity counts for the whole page are now retrieved with one grouped query per entity type instead of a separate count query per entity type per workspace, while keeping the counts exact.

Core

- Reduced config update latency on hybrid data planes by notifying the stream subsystem before applying the update in the HTTP subsystem, so both rebuild in parallel.

3.10.0.17

Release date 2026/08/10

Bugfix

Core

2533.

6434.

0005.

2055 and CVE-2026-48142.

P

gin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly
g a crafted unsigned SAML response from silently bypassing authentication under configurations that set

D

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped jq from 1.8.1 to 1.8.2.

3.10.0.16

Release date 2026/07/08

Bugfix

Core

- **Debugger**: Fixed an issue where the default key name `apikey` of the `key-auth` and `key-auth-enc` plugins was not redacted when captured by the Debugger. This has been resolved by adding `apikey` to the list of default redacted headers.
- **router**: Fixed an issue where WebSocket routes (`ws`/`wss`) returned HTTP 404 when using `router_flavor=expressions` due to incorrect protocol matching expressions being generated.

Clustering

- Fixed an issue where the control plane could crash while handshaking with a data plane on the legacy clustering endpoint if a non-binary WebSocket frame (such as a ping/pong control frame) arrived before the `basic_info` frame. The control plane now drains and responds to control frames during the handshake until the expected frame is received, instead of dereferencing a nil plugin list.

Plugin

- openid-connect:
  - Fixed an issue where switching clients within a single request (via `client_arg`) failed to use the matching client's JWK.

Performance

Clustering

- Improved performance of clustering payload handling for version compatibility, reducing CPU usage and transient memory pressure.

3.10.0.15

Release date 2026/06/30

Bugfix

Clustering

- Fixed an issue where a config backup exported by a data plane could not be re-imported if it contained non-workspaceable entities such as `ca_certificates` or `oic_issuers`. The export incorrectly included a `ws_id` field for those entities, which the declarative config schema rejects as an unknown field.
- Fixed an issue where data planes retried unrecoverable TLS certificate setup failures instead of loading their backup configuration.
- Fixed an issue where hybrid data planes retried unrecoverable CP connection failures and ignored Retry-After delays on 429/503 responses, preventing avoidable reconnect storms.
- Fixed an issue where paginated full sync could keep stale pending foreign-key references across a failed resume, causing spurious validation failures.

Core

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ng insert/update/upsert was silently swallowed, causing the DAO to return `nil` with no error.

errors could be reported as subsequent socket write failures.

mediately with `no_wait = true` when node level mutex was being held by another worker.

VAL environment variable was not correctly applied to the analytics flush interval.

P

confluent-consume:

leak connections across different SASL credentials and TLS verification settings.

esolved the same claim name to a different value than `upstream_headers_claims` because it consulted the ream headers resolver consulted the `access_token` first. With IdPs (e.g. Okta) that set distinct `sub` values not match the upstream header the plugin set on the same request.

- Fixed an issue where concurrent authentication requests could cause race conditions and session creation collisions when using the Postgres strategy for session storage.

Configuration

- Increased the default `proxy_ssl_verify_depth` and `lua_ssl_verify_depth` from 1 to 5.

Dependency

Core

- Bumped kong-redis-cluster from 1.5.7 to 1.6.0.
- Bumped lua-resty-websocket from version 0.4.0.2 to 0.5.0 to solve an issue when handling protocol upgrade failure.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

Performance

Core

- Improved performance of analytics data collection by reducing the default local buffer size.
- Improved router update performance during incremental sync by updating service data in place instead of triggering a full router rebuild when only service attributes change.
- **RBAC**: Improved PostgreSQL performance when deleting Admin API entities by adding an index used to clean up `rbac_role_entities` permissions.

3.10.0.14

Release date 2026/06/11

Bugfix

Core

- Applied upstream nginx security patches for limiting the maximum number of headers (CVE-2026-49975).

3.10.0.13

Release date 2026/06/08

Bugfix

Clustering

- Fixed an issue where DP syncing failed with large configs. Added yielding to prevent CPU stall, and set Konnect mode RPC timeout to 30 seconds for successful full-sync.
- Fixed an issue where incremental DP (sync v2) would not export config to fallback storage when the control plane used periodic polling instead of `notify_new_version`.

Core

did not update the upstream keepalive pool name. It now includes a cert fingerprint for proper connection

P

nections to the keepalive pool, added SSL handshake retry, and improved error propagation.

3

R

E

C

0701, CVE-2026-40460, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Security: Fixed CVE-2026-6338 in core proxy request header handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header cleanup, preventing CL.0 request smuggling with crafted `Connection: Content-Length` headers on requests with a body.

Dependency

Core

- Bumped libexpat from 2.7.3 to 2.8.1 to address the issues: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-2026-41080, and CVE-2026-45186.
- Bumped OpenSSL from 3.5.5 to 3.5.6 to address the issues: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-2026-28390, and CVE-2026-31789.

3.10.0.11

Release date 2026/05/14

Feature

CLI Command

- Added a `--lts_314_compatibility` option to the `check` command to perform configuration compatibility checks for upgrading to version 3.14.x.x.

Clustering

- Added a safeguard to prevent the CP or DP from sending payloads larger than the configured `cluster_max_payload` size to each other, which could avoid the frequent disconnections and reconnection attempts and improve performance. Emitted a log entry telling the config payload size and the configured `cluster_max_payload` size when this happens.

Bugfix

Core

- **Debugger**: Fixed an issue where Redis command arguments were incorrectly included in Redis spans.
- **Debugger**: Fixed an issue where the time spent during the TLS handshake was incorrectly added to Kong internal latency. This fix moved it to the client side latency.
- **Debugger**: Fixed an issue where the Konnect Debugger concatenated `nil` and errored when accessing Kong Gateway via a Unix socket (e.g. `unix:/<prefix>/sockets/am:tls`).
- Fixed an issue where Kong Manager users authenticated through IDPs such as OIDC or LDAP could retain stale RBAC groups or IDP-sourced roles after claim changes, or end up with inconsistent mappings during concurrent authentication requests.
- Fixed an issue where the real client IP from Proxy Protocol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497 plain HTTP to HTTPS port) or when the client disconnected prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from `$proxy_protocol_addr` on early request termination, and added `error_page` 497 routing through `kong_error_handler`.

Clustering

- Fixed an issue where Incremental Sync (ICS) would crash and stop further sync attempts.
- Fixed clustering sync reliability issues by immediately failing pending sync v2 RPC callbacks on disconnect with a `connection closed` error.

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

t to `null` for remote identity realms.

cation/json content-type with charset, ensuring proper handling of JSON request bodies.

could fail when Redis connections were routed through a proxy.

allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.

D

C

- Bumped kong-lua-resty-ljsonschema from 1.2.0 to 1.3.3.
- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2.

3.10.0.10

Release date 2026/04/09

Feature

Plugin

- kafka-log and **kafka-upstream**: Added support for Kafka 4.0 to fix the Confluent deprecation.

Bugfix

Core

- **core**: Resolved an issue where HTTPS was incorrectly detected if multiple `X-Forwarded-Proto` values were provided.
- Fixed an issue where in the postinstall script that changed `/etc/kong/kong.logrotate`'s ownership and permissions. The script now restores ownership to `root:root` and sets permissions to 0644.
- Fixed an issue where `$remote_addr` was not replaced with the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` was enabled on the proxy listener. Also added proper error body messages for 501 and 505 status codes.
- Fixed an issue where the Active Tracing would report incorrect `latencies.client` values due to not capturing the access end time properly. This fix ensures that the access end timestamp is always recorded regardless of Active Tracing being active or not.
- **vault**: Fixed an issue where `kong.vault.update()` changed the secret to an empty string temporarily after changing vault config.

Clustering

- Fixed an issue where the DP could spawn multiple sync timers when downgrading sync protocol to v1, which could cause excessive load on the CP and lead to performance degradation.

Plugin

- **kafka**:
  - Fix issue where Kafka plugins produced records with incorrect `offsetDelta` in the record package.
- **kafka-consume, confluent-consume**:
  - Increased the minimum API version of FetchRequest from 0 to 4 for Kafka 3.x. No changes made for Kafka 4.0, as it is already using version 4.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the graphql-rate-limiting-advanced plugin's API threw 500 errors when handling HTTP PUT request.
- kafka-log:
  - Fixed an issue where certificates could not be loaded from non-default workspaces.
- oas-validation:
  - Fixed an issue where `minLength` and `maxLength` constraints defined in a Swagger 2.0 parameter schema were not enforced.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

be forwarded to upstream services when the corresponding JWT claim was missing from the token. The `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or

449 Section 6.2) where Kong failed to correctly parse nested `cnf.jkt` claims from introspection responses.

could count requests already rejected by Rate Limiting Advanced. Service Protection now executes after ts that pass rate limiting, by updating its priority from 915 to 901.

D

where the Kafka Consume and Confluent Consume plugins couldn't consume the correct message when an issue of parsing ListOffset Response version 0.

K

- Fixed workspace navigation for workspace names containing non-ASCII characters.

Dependency

Core

- Bumped kong-gql from 0.2.3 to 0.2.4 to fix the null value issue in the GraphQL query syntax that causes a parsed AST error in the degraphql plugin.

Performance

Core

- **core**: Improved performance of Kong core by using ngx.var.http_* instead of kong.tools.http.get_header.

Admin API

- Optimized `GET /kong` endpoint to use `SELECT DISTINCT` for populating `enabled_in_cluster` instead of iterating all plugin rows.

3.10.0.9

Release date 2026/03/12

Bugfix

Clustering

- Fixed an issue where a SQL injection vulnerability existed in the clustering RPC procedure, ensuring safer SQL operations (CVE-2026-1907).

Core

- Apply Nginx patch for a man-in-the-middle upstream response injection (CVE-2026-1642)

Dependency

Core

- Bumped OpenSSL from 3.4.1 to 3.5.5 to address the issue: CVE-2025-15467.

3.10.0.8

Release date 2026/02/11

Bugfix

Plugin

- aws-lambda:
  - added a verbose error level logging for better debugging of AWS Lambda invocation issues.
- oas-validation:

not properly disabled when `validate_response_body` was set to `false`.

were used for Redis Sentinel and no authentication supported for Redis, causing `NOAUTH Authentication`

alues caused 500 responses.

expectedly on control planes of hybird mode.

ersions.

mand throw error when the configuration contains vault reference and a prefix directory exists.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where Kong incorrectly logged upstream status codes as 000 (or empty) when HTTP/2 clients disconnected during response processing. This occurred when response buffering was enabled. Kong now correctly records the actual upstream status code even when the HTTP/2 client disconnects before receiving the complete response.
- Fixed an issue where `kong health` command would fail to run when kong configuration contains vault references.

Configuration

- Added `lru_cache_size` to allow configuration of in-memory LRU cache size.

Clustering

- Fixed redundant configuration exports when multiple data planes connect concurrently by coalescing triggers and delegating export/broadcast to the background push loop.
- Fixed an issue where control planes may consume unnecessary memory when only incremental data planes are connected.

Performance

Plugin

- oas-validation:
  - Improved performance for OpenAPI 3.1.

3.10.0.7

Release date 2025/12/09

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue where OpenAI, OpenAI-compatible, and HuggingFace models may have a 0 `completion_tokens` count with SSE streaming responses.
- **AI Semantic Plugins**:
  - Fixed an issue by using a separate column to store namespace instead of including it in the table name to avoid truncation. This change invalidates previous caches created AI Semantic Cache, AI Semantic Prompt Guard and AI Proxy Advanced, if user is using a very long cache TTL, another cache warmup is required after this change.
- **ai-driver**:
  - Fixed an issue where AI Proxy and AI Proxy Advanced generated incorrect default ports for upstream schemes, leading to 400 errors.
- **llm**:
  - Fixed an issue where the subrequest implemented in LLM drivers did not handle error properly.
- acl:
  - Fixed an issue where the cache was not being invalidated for incremental sync in certain scenarios, leading to stale data being served.
- ai-proxy:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

port for the new serverless API, ensuring seamless compatibility.

er were incorrectly parsed responses from embedding API

d for huggingface inference provider

by whole numbers when using Redis. This is an opt-in fix and can be enabled by setting
lugin configuration.

does not accept capture groups for deployment field

g or trailing spaces in the `path` field could cause upgrade failures.

may not be properly invalidated, causing stale data to be served.

- oas-validation:
  - Fixed an issue where nested references in oneOf / anyOf when they are used with a discriminator are not unfolded.
- openid-connect:
  - Fixed an issue where for incremental sync, consumer related caches may not be properly invalidated, causing stale data to be served.
  - Fixed an issue where the `client_credentials/authorization_code` auth would not auto-recover if IdP was not accessible during Kong startup.
  - Fixed an issue where the OIDC plugin caused the third-party IDP to throw an error during logout attempts if the session had already been invalidated. Added the `client_id` to the logout URL to ensure the logout request is sent to the correct client, preventing such errors.
- response-transformer-advanced:
  - Fixed an issue where the failure occurred when Nginx gzip was enabled for upstream.

Core

- Fixed an issue where Kong Manager failed to generate a cookie when OIDC was enabled due to a missing `password` grant type in `auth_methods`.
- Fixed an issue where for incremental sync, consumer group renaming may not be properly populated, causing stale data to be served.
- **event-hooks**: Fixed an issue where the event_hook crud events cannot be handled in traditional cluster mode.
- Fixed an issue where migrations could fail due to missing database relations by repositioning basic-auth and key-auth plugin scripts for correct execution order.

Configuration

- **balancer**: Fixed an issue where the dns query not stopped when related upstream deleted.

Clustering

- **Clustering** Fixed an issue where consumer groups may cause incremental sync to fail at the first sync of a DP.
- Fixed an issue where the prometheus metric `kong_control_plane_connected` was missing when the Data Plane side enabled incremental sync.
- Fixed an issue where the data plane did not stop the health checker before cleaning up old configurations, which could lead to resource leaks.

Dependency

Core

- Bumped lua-resty-healthcheck to version 3.1.1 to remove incorrect deprecation notice on active healthchecks headers.
- Bumped libexpat from 2.7.1 to 2.7.3.
- Bumped PCRE2 from 10.45 to 10.47.

Performance

Core

- **core**: Improved performance of deleting expired rows for Postgres versions below 12.

3.10.0.6

R

F

C

`_sans`. This allows to specify additional entries (either DNS names or URIs) for Subject Alternative Names

F

P

2 model would return an 400 error when the `dimensions` parameter was set.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Added `enforce_latest_offset_reset` flag to fix incorrect `latest` offset behavior. When `false` (default), maintains backwards compatibility where `latest` acts like `earliest`. When `true`, `latest` correctly starts from end of topic. Also fixed offset commit bug when no records are consumed, preventing feedback loop with true latest behavior.

- ai-proxy-advanced:
    - Fixed an issue where AI Proxy Advanced can't failover from other provider to Bedrock.
    - Fixed model name escape or bedrock from request
- ai-proxy:
    - Fixed an issue where OpenAI chat completion's tool_choice was not converted to Anthropic's.
    - Fixed an issue where JSON array data is not correctly parsed.
    - Fixed an issue with Azure Managed Identity credentials causing improper request balancing.
- aws-lambda:
    - Fixed an issue where the AWS Gateway compatible payload generated by the plugin did not include the `resource` field in some cases.
- confluent-consume:
    - Fixed an issue where the plugin would fail to connect using mTLS.
- jwe-decrypt:
    - Fixed an issue where the key_sets cache could not be invalidated correctly.
- kafka-consume:
    - Fixed an issue where the plugin would fail to connect using mTLS.
- ldap-auth-advanced:
    - Fixed group validation issue where LDAP group names containing asterisk (*) characters were incorrectly marked as invalid during Kong Manager RBAC authentication. Group names with asterisk characters (such as "Dev - EXAMPLE - TOP") now properly validate and allow role mapping.
- prometheus:
    - Fixed an issue where Prometheus metrics would show empty consumer identifiers when consumers don't have a username. The plugin now falls back to using the consumer's custom_id when username is not available, ensuring consumer identification in metrics.

Configuration

- Fixed an issue where the restart command read configuration multiple times and failed to stop nginx.

Core

- **Fixed an issue where the partial entities cannot be deleted when cascading delete a workspace.**
- Fixed an issue where results were lost when querying LMDB page by page.

Clustering

- Fixed an issue where `/clustering/data-planes` endpoint returns incorrect DP hostname when incremental sync was enabled.
- Fixed an issue where the incremental sync did not work properly for the stream subsystem.

ps could crash the data plane during incremental sync.

A

tation in Kong Manager would fail due to `authenticated_groups` being a string.

K

ted access' banner when trying to create a new role

3

R

P

K

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Resolved a security issue in the Kong Manager UI.

Performance

Plugin

- prometheus:
  - Optimized fetching of the `kong_db_entities_total` metric by using internal counters instead of `select count(*)` query through the database. If this metric is found to be get out of sync with the real row counts, please use the command `kong migrations reinitialize-workspace-entity-counters` to re-sync the counts.

3.10.0.4

Release date 2025/08/07

Feature

Plugin

- Fixed an issue where the `ai-prompt-decorator` plugin prompt field was too short.

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue where the Gemini provider could not use Anthropic 'rawPredict' endpoint models hosted in Vertex.
- **Semantic Plugins**:
  - Fixed an issue where Gemini Vertex AI embeddings failed due to incorrect URL construction and response parsing.
- ai-proxy-advanced:
  - Fixed an issue where ai-retry phase was not correctly setting the namespace in the kong.plugin.ctx, causing ai-proxy-advanced balancer retry first target more than once.
  - Fix consistent-hashing algorithm not using correct value to hash.
- ai-proxy:
  - Fixed an issue where aws stream parser didn't parse correctly when the frame was incomplete.
  - Fixed an issue where AWS Bedrock streaming requests would panic when the ai-semantic-cache plugin was enabled.
  - Fixed an issue where model name did not escape when using AWS Bedrock inference profile.
  - Fixed an issue where resource was not being passed correctly when using Azure as provider.
- ai-rate-limiting-advanced:
  - Fixed an issue where AI rate limiting advanced plugin might panic when use redis strategy and sync_rate is set to 0.
- ai-semantic-cache:
  - correct ending characters.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - lugin failed to validate revocation using OCSP when the downstream connection wasn't an SSL
  - s passed from the control plane to sign/re-sign.
  - king plugin schema with object type. It should return an array type instead of an object type in the response
  - n doing the OCSP client cert verification.
  - log messages in the error logs.

- request-callout:
  - Fixed an issue where `untrusted_lua_sandbox_requires` option was not respected.
  - `request.by_lua` code will now run before a request is made or a cached callout is fetched. Previously, it did not run before an attempt to fetch from cache, which did not allow for cache key customization.
  - The plugin now uses additional components to generate the cache key: request consumer, consumer groups, plugin ID, route ID; callout request method, URL, query params, headers, and body.
  - Fixed an issue where expressions could not read headers, query, and URI captures via shortcuts of the form `$(headers.some_header)`.
  - Fixed an issue where the client request body is forwarded to upstream when `upstream.body.forward` is false.
- Fixed an issue where AI Proxy and AI Proxy Advanced can't properly failover to a Bedrock target.
- AI Azure Content Safety: Fixed an issue where Blocklist breaches are not correctly parsed.
- Fixed an issue where the rate limiting plugins can't handle decimal numbers when using Redis strategy.

Core

- Fixed an issue where the Active Tracing total time was not including connection and handshake times.
- Fixed an issue where the LMDB database file was created with incorrect permission when running kong cli command with root privileges.
- **kafka**: Fixed an issue where the Kafka SCRAM authentication did not send the server nonce.
- Fixed an issue where the /schemas/plugins/validate endpoint returned a validation error when a plugin was linked to a partial containing a vault key.
- Fixed an issue where the Lua VM memory size returned by status API is not accurate on the control plane.

Dependency

Core

- Bumped LuaRocks from 3.11.1 to 3.12.2.
- **lua-resty-lmdb**: updated to version 1.6.1.

Performance

Core

- Improved performance by removing the n+1 query problem for plugins. Plugins are now fetched in bulk with plugins_partials and partials.

3.10.0.3

Release date 2025/07/06

Feature

Core

- Added support for reporting whether `new_dns_client` and `incremental_sync` were enabled in anonymous reports.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

did not work for Ollama (llama2) provider.

del, temperature, and other user-defined fields.

may not be refreshed after the plugin config is updated.

    - Fixed an issue where large request payload was not logged.
    - Fixed an issue where SSE terminator may not have correct ending characters.
    - Fixed an issue where the response body for observability may be larger than the real one because of the stale data.
    - Fixed an issue where patterns using multiple capture groups (e.g., `$(group1)/$(group2)`) failed to extract expected matches.
    - Fixed an issue where AI Proxy returns 403 using gemini provider.
- ai-semantic-cache:
    - Fixed an issue where SSE terminator may not have correct ending characters.
- key-auth:
    - Fixed an issue where external consumers could not be used with traditional Kong deployments, such as with KIC.
- mocking:
    - Fixed an issue where an empty array set in the mocking plugin returned an object type instead of an array type in the response body.
- oas-validation:
    - Fixed an issue where the plugin throws an error for responses without a Content-Type header.
- prometheus:
    - Fixed an issue where AI latency histogram might miss some calculation.
- Fixed an issue where some of ai metrics was missed in analytics

Core

- Added a new configuration, `route_match_calculation`, which included bug fixes for the `traditional_compatible` and the `expressions` router flavors. The default value `original` retained the current `3.x` router matching behavior without changes. The value `strict` enforced the router matching behavior with corrected calculation as follows:
    1. The weight (priority point) of a route was incorrectly downgraded.
    2. A route of HTTPS-only protocol with SNIs incorrectly captured requests over HTTP routes.
    3. A route of TLS-only protocol with SNIs incorrectly captured requests over TCP or UDP routes.
- Fixed an issue where new custom plugin creation during a full sync with incremental enabled would cause inconsistency. It now fails and reinitiating the sync in such case.
- Fixed an issue where Pgvector index failed when using special characters in the name.
- Fixed an issue where the IAM Authentication for RDS failed due to token not being refreshed under certain conditions.
- Fixed an issue where error logs were excessive when changing routes.
- -> Fixed an issue where newly spawned workers used outdated router data because the `init` phase was skipped.
- Fixed an issue where the send request time was incorrectly calculated, now it should be more accurate.
- Fixed an issue where users encountered duplicate key violation errors on `rbac_role_entities_pkey` while using the `deck sync` command.
- Fixed an issue where the admin API might not fetch the workspace correctly during batch updates.

Clustering

ht be initialized repeatedly.

erate correct deltas for non-default workspaces.

onnections incorrectly on the data plane.

orrectly reports “history lost” and fails.

in the clustering system for resilience against transient network issues.

recover from sync failures, leading to recursive retries and failures.

workspace during incremental sync may not have been applied correctly.

C calls to the data plane correctly in some corner cases.

remental sync were not reported.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

shes if using off strategy.

Dependency

Core

- Bumped luarocks from 3.11.1 to 3.12.1.

Performance

Clustering

- Bumped page size for cluster sync to improve performance of full syncs.
- Improved RPC message queue responsiveness.

3.10.0.2

Release date 2025/05/20

Feature

Configuration

- Added an optional configuration parameter, `admin_gui_hide_konnect_cta`, which controls the visibility of the Konnect call-to-action in Kong Manager.

Core

- Schema map values can now assume null values. This fixes an issue where values in custom schemas wouldn't accept explicit null values for the removal of fields.

PDK

- Added a new `kong.request.get_raw_forwarded_path()` function for returning the non-normalized `forwarded_path`. This fixes an issue with the OpenID Connect plugin, which was normalizing the path when it shouldn't.

Bugfix

Core

- Applied a patch from upstream OpenResty to fix an issue where upstream connection pooling failed when pool names exceeded 32 characters.
- Fixed an issue where the delta type was not being validated during incremental sync.
- Fixed an issue where the error logs generated during router rebuilds could be excessively noisy.
- Fixed an issue where log lines could be incorrectly logged.
- Fixed an issue where a full configuration sync caused the data plane to stop proxying when incremental config sync was enabled.

Performance

- Fixed an issue where the rate limiting library could become deadlocked with Postgres.
- Optimized the querying of the default workspace by directly accessing LMDB, improving performance.

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d `redirect_uri` errors when `config.redirect_uri` was not configured and the URI path contained

de, and request latency (in milliseconds).

ilable to response `by_lua` code.

`by_lua` would apply to all subsequent callouts.

would be accepted.

`query` now correctly replace those in the callout URL.

cept explicit null values for removal of fields.

  - Fixed an issue where callout and upstream request body customizations weren't performed when an empty request body was provided. Now, an empty JSON body is used and `Content-Type: application/json` is added to the request.
  - Fixed an issue where the Request Callout plugin failed with a timeout when `callouts.request.body.custom` was null and `callouts.request.headers.forward` was set to `true`.
- session:
  - Fixed an issue where boolean configuration fields `hash_subject` (default `false`) and `store_metadata` (default `false`) stored the session's metadata in the database. This also resolves an issue with Dev Portal, where adding these fields to `portal_session_conf` wasn't working as expected.

Admin API

- Fixed an issue where the data plane (DP) could report a healthy status before it was actually ready to accept traffic.

Clustering

- Fixed an issue where debug level logs for incremental sync were insufficient, making debugging more difficult.
- Fixed an issue where some logs were missing when incremental sync was enabled on the data plane side.
- Fixed an issue where the data plane could repeatedly trigger a full sync when incremental sync was enabled.

3.10.0.1

Release date 2025/04/15

Feature

Kong Manager

- Added a new UI for the Request Callout plugin.

Bugfix

Core

- Fixed an issue where `ca_certificate` cache was not invalidated when incremental sync was enabled.
- **AI**: Fixed an issue where the password for the pgvector strategy was not being set correctly in the database.
- Fix issue where schema library would fail with a nil reference if configurations are set via both deprecated and new names with diverging values
- Fixed an issue where validation required all of `timeout` fields (`connect_timeout`, `read_timeout`, `send_timeout`) to have the same value. In reality only `connect_timeout` has to have the same value since that is the value used for generating the `timeout` field in the response if it is missing in the request.

Plugin

- prometheus:
  - Fixed an issue where the metric `data_plane_config_hash` might not work correctly for incremental sync.
- Fixed an issue where AI Proxy and AI Proxy Advanced would use corrupted plugin config.

Clustering

rect data if the control plane's (CP) configuration version was older than the DP's version.

frequently when incremental sync is enabled.

duplicate sync notifications when configuration changes occurred.

ssage correctly when incremental sync was enabled.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

m affects connection pooling in certain circumstances. This issue impacts transaction handling and uest rates and increased latencies. Versions 3.10.0.0 and 3.10.0.1 are both affected. To resolve this ater.

Breaking Change

Plugin

- **AI Plugins**:
  - Changed the serialized log key of AI metrics from `ai.ai-proxy` to `ai.proxy` to avoid conflicts with metrics generated from plugins other than AI Proxy and AI Proxy Advanced. If you are using logging plugins (for example, File Log, HTTP Log, etc.), you will have to update metrics pipeline configurations to reflect this change.
- **kong.service.request.clear_query_arg**:
  - Changed the encoding of spaces in query arguments from `+` to `%20` as a short-term solution to an issue that some users are reporting. While the `+` character is the correct encoding of space in querystrings, Kong uses `%20` in many other APIs (inherited from Nginx / OpenResty).
- ai-rate-limiting-advanced:
  - `window_size` and `limit` now require an array of numbers instead of a single number. If you configured the plugin before 3.10 and use `kong migrations` to upgrade to 3.10, it will be automatically migrated to use the array.
- openid-connect:
  - Fixed an issue where forbidden requests were redirected to `unauthorized_redirect_uri` if configured. After the fix, forbidden requests will be redirected to `forbidden_redirect_uri` if configured.

Core

- Free mode is no longer available. Starting Kong without a license will now function the same as Kong with an expired license.

Deprecation

Plugin

- **AI Plugins**:
  - Deprecated `preserve` mode in `config.route_type`. Use `config.llm_format` instead. The `preserve` mode setting will be removed in a future release.

Feature

Core

- Added a new configuration parameter `admin_gui_csp_header` to Gateway, which controls the Content-Security-Policy (CSP) header served with Admin GUI (Kong Manager). This defaults to `"off"`, and you can opt-in by setting it to `"on"`.
- Added a new field `x5t` to the entity `keys`, letting you use a X.509 Certificate Thumbprint to identify the key.
- Backported the `balancer.set_upstream_tls` feature from the OpenResty upstream openresty/lua-resty-core#460.
- The upstream URI variable is now refreshed when the proxy pass balancer is recreated.
- Added a new core entity to Kong Gateway: partials. Partials enable users to define shared configuration for Redis.
- Added external consumer support for Konnect.
- **ai**: Added an AI Gateway sales counter for license reporting.
- **ai**: Added support for `pgvector` database in the `ai` related plugins.

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ock providers to embeddings. They can be used by the ai-proxy-advanced, ai-semantic-cache, ai-semantic-

me roles in AWS.

er, and for Google GenAI SDKs for Gemini provider.

g the lowest-usage load balancing strategy.

lows setting apriority group for each upstream model.

ic routing.

- Added the `failover_criteria` configuration option, which allows retrying requests to the next upstream server in case of failure.

- ai-rag-injector:
  - Added a new plugin which allows automatically injecting documents to simplify building RAG pipelines.
- ai-rate-limiting-advanced:
  - Added support for allowing multiple rate limits for the same providers.
- ai-sanitizer:
  - Added a new plugin that can sanitize the PII information in requests before the requests are proxied by the AI Proxy or AI Proxy Advanced plugin.
- confluent:
  - Added support for message manipulation with the new configuration field `message_by_lua_functions`.
  - Added support for sending messages to multiple topics with `topics_query_arg`, and enabled topic allowlisting with `allowed_topics`.
- cors:
  - Added an option to skip returning the Access-Control-Allow-Origin response header when requests don't have the Origin header.
- json-threat-protection:
  - Added the schema field `allow_duplicate_object_entry_name` to allow or disallow duplicate object keys in JSON payloads. When set to `false`, the plugin will reject JSON payloads with duplicate object keys. The default value is `true`, which is same as the previous behavior.
- kafka-upstream:
  - Added support for message manipulation with the new configuration field `message_by_lua_functions`.
  - Added support for sending messages to multiple topics with `topics_query_arg`, and enabled topic allowlisting with `allowed_topics`.
- oas-validation:
  - Added support for `oneOf`, `anyOf`, `allOf`, and `not` keywords.
  - Added support for the `discriminator` keyword in OpenAPI specs.
- opentelemetry:
  - This plugin now supports instana headers in propagation.
  - This plugin now supports variable resource attributes.
- prometheus:
  - Added gauge to expose connectivity state to the control plane.
  - Added the capability to enable or disable exporting of Proxy-Wasm metrics.
- request-callout:
  - Added the `request-callout` plugin, which provides complex request augmentation and internal authentication.
- session:
  - Added two boolean configuration fields `hash_subject` (default `false`) and `store_metadata` (default `false`) to store the session's metadata in the database.
- kafka-consume Added the `kafka-consume` plugin, which adds Kafka consumption capabilities to Kong.

P

set_scheme was called

ms: A128GCM, A192GCM, A128CBC-HS256, A192CBC-HS384, A256CBC-HS512.

C

ne side.

de deployments. Instead of sending the entire entity config to data planes on each config update, onfiguration to data planes.

D

loper's related session while changing the password.

A

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Updated `/license/report` endpoint to include counts for Kafka consumption, Confluent Kafka consumption, and Confluent production.

Kong Manager

- Add Redis shared configuration support in Plugins.
- Kong Manager now returns to the previous page upon canceling plugin editing.
- Kong Manager now shows the scope option in gray when it can't be changed.

Bugfix

Core

- Added a patch for `kong.resty.set_next_upstream()` to control the next upstream retry logic on the Lua side.
- Fixed an issue where a GET request to the Admin API root `/` path would return a 500 server error.
- Fixed an issue where a valid declarative config with certificate or SNI entities couldn't be loaded in DB-less mode.
- Fixed an issue where consistent hashing did not correctly handle hyphenated-Pascal-case headers, leading to uneven distribution of requests across upstream targets.
- Fixed an issue where `POST /config?flatten_errors=1` could return a JSON object instead of an empty array.
- Fixed an issue where `POST /config?flatten_errors=1` could not return a proper response if the input contained duplicate consumer credentials.
- Fixed an issue where `socket_path` permissions were not correctly set to `755` when the umask setting did not give enough permissions.
- Fixed an issue where targets couldn't be removed from the DNS query if they were deleted or updated via the Admin API.
- Fixed an issue where the error reason wasn't thrown when parsing the certificate from vault.
- Fixed an issue where the new DNS client did not correctly handle the timeout option in resolv.conf.
- Fixed an issue where the schema library would error with a nil reference if an entity checker referred to a nonexistent field.
- Fixed an issue where the `tls_verify`, `tls_verify_depth`, and `ca_certificates` properties of a service were not included in the upstream keepalive pool name.
- Fixed potential connection leaks when the data plane failed to connect to the control plane.
- Added an optional configuration parameter `admin_gui_csp_header_value` to Gateway, which controls the value of the Content-Security-Policy (CSP) header served with Admin GUI (Kong Manager).
- Added support for the new Ollama streaming content type in the AI driver.
- **Analytics**: Fixed an issue where `trace_id` did not honor the value extracted during tracing headers propagation.
- Fixed an issue where a certificate entity configured with a vault reference occasionally didn't get refreshed on time when initialized with an invalid string.
- Fixed an issue where a false error log was generated when a DELETE request with `Content-Type: application/json` and no body was made.
- Fixed an issue where a mismatch between If-Match in requests and ETag in responses would result in a bad case in the response phase.
- Fixed an issue where a newly spawned worker couldn't use RDS IAM authentication when an old worker was decommissioned.
- Fixed an issue where DNS answers with TTL=0 were incorrectly cached indefinitely in the new DNS client.
- Fixed an issue where event hooks sometimes ignored events, caused by the normalized table not including values of type number or boolean.
- Fixed an issue where Kong could have connection leaks when failing to connect to an upstream by websocket.

Kong AI Gateway.

re access phase may not take effect

he keys entity were not encrypted when keyring was enabled.

e latest.

P

uld be empty.

an anonymous consumer was configured but did not exist.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where the ai-proxy-advanced plugin identity running failed in retry scenarios.
  - Fixed an issue where the ai-proxy-advanced plugin failed to failover between providers of different formats.
- ai-proxy:
  - Fixed a bug in the Azure provider where `model.options.upstream_path` overrides would always return a 404 response.
  - Fixed a bug where response streaming in Gemini and Bedrock providers was returning whole chat responses in one chunk.
  - Fixed a bug where Azure streaming responses would be missing individual tokens.
  - Fixed a bug with the Gemini provider, where multimodal requests (in OpenAI format) would not transform properly.
  - Fixed an incorrect error thrown when trying to log streaming responses.
  - Fixed an issue where Gemini streaming responses were getting truncated and/or missing tokens.
  - Fixed preserve mode.
  - Fixed tool calls not working in streaming mode for Bedrock and Gemini providers.
- ai-semantic-cache:
  - Fixed an issue where the Refresh header wasn't properly sent to the client.
  - Fixed issue where the SSE body may have extra trailing.
- ai-semantic-prompt-guard:
  - Fixed an issue where Kong Gateway was not able to reconfigure the plugin when using DB-less mode.
- app-dynamics:
  - Fixed a segmentation fault caused by a missing destructor call on process exit.
- aws-lambda:
  - Fixed an issue that occurred when `is_proxy_integration` was enabled, where Kong's response could behave incorrectly when the response was changed after the execution of the AWS Lambda plugin. The Content-Length header in the lambda function response is now ignored by the AWS Lambda plugin.
- file-log:
  - Fixed an issue where an error would occur when there were spaces at the beginning or end of a path.
- forward-proxy:
  - Fixed an issue where the `upstream_status` field was empty in logs when using the `forward-proxy` plugin.
- jq:
  - Fixed an issue where jq did not work properly with proxy-cache-advanced.
- json-threat-protection:
  - This plugin now accurately supports proxying for non-`POST/PUT/PATCH` requests.
- jwt-signer:
  - Fixed an issue where the jwt-signer plugin failed to upsert jwks if the jwks contains extra custom fields.
- ldap-auth-advanced:

the first null character.

nge.

caused an assertion failure.

as accidentally added to the `pre-function` schema.

_rate not being set if the `strategy` was `local`.

osed to be sent to the upstream were lost instead.

- service-protection:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Enhanced robustness for user misconfigurations. The following use cases are now handled:
        - RLA and service-protection are configured on the same service.
        - There is no service but the service-protection plugin is enabled with global scope.
    - Fixed an issue where the runtime failed due to `sync_rate` not being set if the `strategy` was `local`.
- grpc-web and **grpc-gateway**: Fixed a bug where the `TE` (transfer-encoding) header would not be sent to the upstream gRPC servers when `grpc-web` or `grpc-gateweay` are in use.
- Fixed an issue where templates weren't being resolved correctly.
- The plugins now support nested fields.

Configuration

- Fixed an issue where the `db_resurrect_ttl` configuration didn't take effect.

Admin API

- Fixed error caused by duplicate `Content-Type`.
- Fixed an issue where Admin API Enterprise-only entities were not writable when a license expired but was still in the grace period.
- Fixed an issue where the "meta" field was not validated when creating or updating a portal developer.

PDK

- Users can now use a backslash to escape dots in logging plugins' `custom_fields_by_lua` key strings, preventing dots from creating nested tables.

Default

- Created connection pools for each `host`, `port`, `username`, `ssl` combination to fix the following issues:

Kong Manager

- Fixed an issue where creating `jwt-credential` with special algorithms (`PS256`, `PS384`, `PS512`, and `EdDSA`) couldn't populate `rsa_public_key` in the Kong Manager.
- Fixed an issue where editing an upstream would not remove the values of some fields (`client certificate`, `tags`, `timeouts`, and `host_header`, etc) in the Kong Manager.
- Fixed an issue where the license expiration date was calculated incorrectly.
- Fixed an issue where the lists in the UI would flicker under some circumstances.

Dependency

Core

- Bumped atc-router from v1.6.2 to v1.7.1. This release contains upgraded dependencies and a new interface for validating expressions.
- Bumped Kong Nginx Module from 0.15.0 to 0.15.1.
- Bumped libexpat from 2.6.2 to 2.6.4 to fix a crash in the XML_ResumeParser function caused by XML_StopParser stopping an uninitialized parser.
- Bumped lua-kong-nginx-module from 0.13.0 to 0.14.0.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

PCRE2Project/pcre2/blob/pcre2-10.45/NEWS).

D

9ef25a540865ee6740

C

a CA Certificate Store to 2025-02-25, and `nghttp2` to 1.65.0.

Performance

Core

- Improved performance of trace ID size lookup.
- Reduced the LMDB storage space by optimizing the key format.

PDK

- Refined PDK usage for better performance.

Plugin

- oas-validation:
  - Improved performance on OpenAPI 3.0.
- openid-connect:
  - Removed issuer discovery from schema to improve performance upon plugin initialization or updating. The issuer discovery will only be triggerd by client requests.

Known Issues

Plugin

- **Confluent Consume and Kafka Consume plugins**:
  - An error message appears in the logs about a missing cluster name, even when the name is specified.
- **Vault Auth**:
  - The Vault Auth plugin doesn't clear its cache when incremental sync is turned on. This means that deleted secrets will remain in the cache, and can still be accessed by the plugin.
- ai-proxy:
  - Some active tracing latency values are incorrectly reported as having zero length when using the AI Proxy plugin.
- kafka-consume:
  - Kong Gateway allows you to configure the Kafka Consume plugin without authentication settings, but authentication must be configured for the plugin to work.

    If authentication is not configured, or if the authentication strategy is missing, the plugin will fail with a generic authentication error.

Core

- The Brotli module is missing from all of the following ARM64 Kong Gateway Docker images:
  - RHEL 9
  - Debian 12
  - Amazon Linux 2
  - Amazon Linux 2023
- When running in incremental sync mode (`incremental_sync=on`), Kong Gateway can't apply configuration deltas to the stream subsystem. This issue affects
  nabled alongside stream proxying (`stream_listen`). As a workaround for this issue, set

m affects connection pooling in certain circumstances. This issue impacts transaction handling and
uest rates and increased latencies. Versions 3.10.0.0 and 3.10.0.1 are both affected. To resolve this
ater.

3

R

P

P

) function for returning non-normalized `forwarded_path`.

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Added support for reporting whether `new_dns_client` was enabled in anonymous reports.

Bugfix

Core

- Added a new configuration, `route_match_calculation`, which included bug fixes for the `traditional_compatible` and the `expressions` router flavors. The default value `original` retained the current `3.x` router matching behavior without changes. The value `strict` enforced the router matching behavior with corrected calculation as follows:
    1. The weight (priority point) of a route was incorrectly downgraded.
    2. A route of HTTPS-only protocol with SNIs incorrectly captured requests over HTTP routes.
    3. A route of TLS-only protocol with SNIs incorrectly captured requests over TCP or UDP routes.
- -> Fixed an issue where newly spawned workers used outdated router data because the `init` phase was skipped.
- Fixed an issue where users encountered duplicate key violation errors on `rbac_role_entities_pkey` while using the `deck sync` command.
- Fixed an issue where adding the `hash_subject` and `store_metadata` fields to the `portal_session_conf` in the Dev Portal was not working as expected.

Plugin

- ldap-auth-advanced:
    - Fixed an issue where binary string was truncated at the first null character.
- mocking:
    - Fixed an issue where an empty array set in the mocking plugin returned an object type instead of an array type in the response body.
- oas-validation:
    - Fixed an issue where the plugin throws an error for responses without a Content-Type header.
- openid-connect:
    - Fixed an issue where caused IdP to report invalid redirect_uri errors when `config.redirect_uri` was not configured and the uri path contained spaces.
- Fixed an issue where AI Proxy and AI Proxy Advanced would use corrupted plugin config.

Performance

- Fixed an issue where rate-limiting library could cause deadlock with Postgres.

Dependency

Core

- Bumped luarocks from 3.11.1 to 3.12.1.

3.9.1.1

Release date 2025/03/20

Bugfix

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

y and supported nested fields.

some cases.

tor call on process exit.

C

re access phase may not take effect

- Fixed an issue where DNS answers with TTL=0 were incorrectly cached indefinitely in the new DNS client.
- Fixed an issue where Konnect analytics were missing for Kong AI Gateway.

3.9.1.0

Release date 2025/03/11

Feature

Plugin

- session:
  - Added two boolean configuration fields `hash_subject` (default `false`) and `store_metadata` (default `false`) to store session's metadata in the database.

Core

- Added a new feature to invalidate the admin's or the developer's related session while changing the password.

Bugfix

Core

- Fixed an issue where A mismatch between If-Match in request and ETag in response would result in bad case in the response phase.
- **Vault**: Updated the AWS Vault supported regions list to the latest.
- Added support for the new Ollama streaming content type in AI driver.

Plugin

- ai-proxy:
  - Fixed Gemini streaming responses getting truncated and/or missing tokens.
  - Fixed incorrect error thrown when trying to log streaming responses.
  - Fixed tool calls not working in streaming mode for Bedrock and Gemini providers.
- ai-semantic-prompt-guard:
  - Fixed an issue where the plugin was not able to reconfigure the plugin when using DB-less mode.

3.9.0.1

Release date 2025/01/28

Bugfix

Plugin

- **AI Plugins**:
  - Reverted the analytics container key from "proxy" to "ai-proxy" to align with previous versions.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`tions.upstream_path` overrides would always return 404.

ld be missing individual tokens.

nd Bedrock providers was returning whole chat responses in one chunk.

format) would not transform properly, when using the Gemini provider.

ransfer-encoding) header would not be sent to the upstream gRPC servers when `grpc-web` or `grpc-`

handle hyphenated-Pascal-case headers, leading to uneven distribution of requests across upstream targets.

reference may not get refreshed on time when initial with an invalid string.

Core

- Bumped libexpat from 2.6.2 to 2.6.4 to fix a crash in the XML_ResumeParser function caused by XML_StopParser stopping an uninitialized parser.
- Bumped lua-kong-nginx-module from 0.13.1 to 0.13.2.

3.9.0.0

Release date 2024/12/12

Deprecation

Core

- `node_id` in configuration has been deprecated.

Plugin

- Fix an issue where running the “kong migration” command will fail when upgrading to 3.8 version, which is caused by an incomplete Redis configuration related SQL.

Feature

Plugin

- ai-proxy-advanced:
  - Added support for streaming responses to the AI Proxy Advanced plugin.
- ai-proxy:
  - Disabled HTTP/2 ALPN handshake for connections on routes configured with AI-proxy.
- ai-rate-limiting-advanced:
  - Added support for Huggingface provider to the AI Rate Limiting Advanced plugin.
- ai-semantic-cache:
  - Added `ignore_tool` configuration option to discard tool role prompts from the input text.
  - Plugin can now be enabled on Consumer Groups.
- injection-protection:
  - Added the `injection-protection` plugin that supports blocking requests based on regex patterns.
- jwt-signer:
  - Supported `/jwt-signer/jwks` endpoint in dbless mode
- openid-connect:
  - Allowed `http_proxy_authorization` and `https_proxy_authorization` to be referenceable.
  - Added the `introspection_post_args_client_headers` config option, allowing you to pass client headers as introspection POST body arguments.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

maximal capacity to 6000

_name to support specifying an independent shared memory for storing locks.

way to Envoy Proxy.

ms with the new configuration field `compound_identifier`.

cation

request rate limiting.

- ai-semantic-cache, **ai-semantic-prompt-guard**, **ai-proxy-advanced**: Made the `embeddings.model.name` config field a free text entry, enabling use of a self-hosted (or otherwise compatible) model.

Clustering

- Added a remote procedure call (RPC) framework for Hybrid mode deployments.

Core

- **Core**: Added Ada dependency - WHATWG-compliant and fast URL parser.
- Addded a new LLM driver for interfacing with the Hugging Face inference API. The driver supports both serverless and dedicated LLM instances hosted by Hugging Face for conversational and text generation tasks.
- **Core**: Added `tls.disable_http2_alpn()` function needed patch for disabling HTTP/2 ALPN when tls handshake.
- Improved the output of the request debugger:
  - Now the resolution of field `total_time` is microseconds.
  - A new field `total_time_without_upstream` on the top level shows the latency only introduced by Kong.
- **proxy-wasm**: Added support for Wasm filters to be configured via the /plugins admin API
- Added a new feature for Kong Manager that supports multiple domains, enabling dynamic cross-origin access for Admin API requests.
- Added a configuration parameter `admin_gui_auth_login_attempts_ttl` (default to `604800`) to allow users to specify a custom duration to wait before they can try login again if they have exceeded the maximum login attempts. This is only meaningful when `admin_gui_auth_login_attempts` is a positive number.
- let the embedding driver cache the embeddings for a given model in the current request
- Added an option for GitHub Actions to build nginx/OpenResty with debug symbols.

Admin API

- **Admin API**: Added support for official YAML media-type (application/yaml) to /config endpoint.
- Added the ability to remove the consumer list from the return value for consumer groups Admin API `/consumer_groups/:consumer_groups` when `list_consumers=false`.
- Entity counts in `/license/report` were retrieved with `select count` instead of `workspace_entity_counters` table on db mode.
- Entity counts in `/workspaces?counter` and `/workspace/<workspace>/meta` were retrieved with `select count` instead of `workspace_entity_counters` table on db mode.
- `/license/report` could retrive entity counts under db-less mode.
- `/workspaces?counter` and `/workspace/<workspace>/meta` could retrieve entity counts under db-less mode.
- Added a feature to allow updating the `belong_workspace` field of an admin via the Admin API and Kong Manager.

CLI Command

- Add the `kong drain` CLI command to make the `/status/ready` endpoint return `503 Service Unavailable` response.

PDK

- Added `kong.service.request.clear_query_arg(name)` to PDK.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

the tracing PDK

age when failing to delete a service.

if the `Content-Type` in the request/response body included parameters (e.g., `application/json;` fined in `api_spec` did not include parameters.

was not propagated to the caller.

  - Fixed an issue where the *ai-prompt-guard* plugin could fail when handling requests with multiple models.
- ai-proxy-advanced:
  - Fixed an issue where lowest-usage and lowest-latency strategy did not update data points correctly.
- ai-proxy:
  - Fixed a bug where tools (function) calls to Anthropic would return empty results.
  - Fixed a bug where tools (function) calls to Bedrock would return empty results.
  - Fixed a bug where Bedrock Guardrail config was ignored.
  - Fixed a bug where tools (function) calls to Cohere would return empty results.
  - Fixed a bug where Gemini provider would return an error if content safety failed in AI Proxy.
  - Fixed a bug where tools (function) calls to Gemini (or via Vertex) would return empty results.
  - Fixed an issue where AI Transformer plugins always returned a 404 error when using 'Google One' Gemini subscriptions.
  - Fixed issue where multi-modal requests is blocked on azure provider.
- ai-rate-limiting-advanced:
  - Updated the error message for rate limit exceeded to include AI-related information.
  - Fixed an issue where the plugin yielded an error when incrementing the rate limit counters in non-yieldable phases.
  - Fixed an issue where the plugin may fail to authenticate to Redis correctly with vault-referenced redis configuration.
- ai-semantic-cache:
  - Fixed the exact matching to catch everything including embeddings.
  - Fixed an issue where the ai-semantic-cache plugin put the wrong type value in the metrics when using the prometheus plugin.
  - Fixed an issue where the plugin failed when handling requests with multiple models.
- ai-semantic-prompt-guard:
  - Fixed an issue where requests with multiple models caused failures.
- app-dynamics:
  - Fixed an issue where the `snapshot` of the fields upstream, service, route and consumer was missing in the AppDynamics plugin.
- aws-lambda:
  - Fixed an issue in proxy integration mode that caused internal server error when the `multiValueHeaders` is null.
- degraphql:
  - Fixed an issue where the degraphql routes were updated from the control plane but not updated in the degraphql router on the data plane.
- exit-transformer:
  - Fixed an issue where the exit-transformer could not take effect on invalid non-admin requests.
- graphql-rate-limiting-advanced:
  - Fixed an issue where the plugin may fail to authenticate to Redis correctly with vault-referenced redis configuration.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

sequences, non-ASCII characters, and object entry names in JSON Strings was incorrect; now using UTF-

es were incorrectly interpreted as 0 in some environments (e.g., ARM64-based):

printed.

- kafka-log:

  - Fixed an issue where the plugin cannot function correctly when it is configured in a non-default workspace with certificate_id.
  - Reduced noisy logs from kafka-log and counters.
- key-auth:
  - Fixed to retain order of query arguments when hiding the credentials.
- oas-validation:
  - Fixed an issue where the error message was omitted if `notify_only_request_body_validation_failure` or `notify_only_response_body_validation_failure` was set to `false`.
  - Fixed an issue where the `include_base_path` did not work when multiple servers were provided.
- openid-connect:
  - Fixed an `500` error caused by JSON `null` from the request body when parsing bearer tokens or client IDs.
  - Fixed an issue where the configured Redis database was ignored.
  - Fixed an issue where the `token_cache_key_include_scope` feature was not considering scopes defined via `config.scopes` to generate the cache key.
- rate-limiting-advanced:
  - Fixed an issue where counters of the overriding consumer groups didn't fetched when the window_size is different and the workspace is non-default.
  - Fixed an issue where a warn log was printed when event_hooks was disabled.
  - Fixed an issue where multiple plugin instances sharing the same namespace enforced consumer groups and different `window_sizes` were used in the consumer group overriding configs, then the rate limiting of some consumer groups would fall back to local strategy. Now every plugin instance sharing the same namespace can set different `window_size`.
  - Fixed an issue where the plugin may fail to authenticate to Redis correctly with vault-referenced redis configuration.
  - Fixed an issue where RLA stores long expiration time items cause `no memory` errors.
- rate-limiting:
  - Fix a bug where the return values from `get_redis_connection()` are mistaken.
  - Fixed an issue that caused an HTTP 500 error when `hide_client_headers` is set to `true` and the request exceeds the rate limit.
- request-validator:
  - Fixed an issue where requests get rejected when defining an object parameter with form style and exploded.
- Fixed an bug that AI semantic cache can't use request provided models
- ai-proxy-advanced, **ai-semantic-prompt-guard**: Fixed an issue where stale plugin config was not updated in dbless and hybrid mode.
- Fixed an issue where the ai-semantic-cache plugin would abort in stream mode when another plugin enable the buffering proxy mode.
- ai-request-transformer, **ai-response-transformer**: Fixed an issue where Azure Managed Identity did not work for AI Transformer Plugins.

Clustering

- **Clustering**: Adjust error log levels for control plane connections.
- Fixed an issue where EventHooks is not working in Data Planes.
- Fixed the clustering compatibility logic for the RDS assume role and custom STS endpoint features backport.

ction was not closed promptly during reconnection.

A

correctly when using form-urlencoded requests.

ved in certain cases when they were empty.

C

ze in rare cases.

as otherwise it may runtime crash.

used an error warning on startup.

quest API does not refresh body buffer when `ngx.req.set_body_data` is used in balancer phase

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue where the workspace id was not included in the plugin config in the plugins iterator.
- Fixed a 500 error triggered by unhandled nil fields during schema validation.
- **Vault**: Fixed an issue where array-like configuration fields cannot contain vault reference.
- **Vault**: Fixed an issue where updating a vault entity in a non-default workspace will not take effect.
- **Vault**: Fixed an issue where vault reference in kong configuration cannot be dereferenced when both http and stream subsystems are enabled.
- **proxy-wasm:** Added a check that prevents Kong from starting when the database contains invalid Wasm filters.
- Fixed an issue where the `kong.request.enable_buffering` can not be used when downstream uses HTTP/2.
- Fixed an issue where paginated results of `audit_requests` fetched via the `next` field were incorrect when `before` and `after` filters were applied.
- Fixed an issue where event_hooks added during runtime didn't function until restart.
- Fixed an issue where using Hashicorp Vault AppRole authentication with a secret ID file would fail to read the secret ID.
- Fixed an issue where RBAC authorization could be enabled via `enforce_rbac` in DB-less mode. RBAC authorization should be disabled in DB-less mode.
- Fixed an issue where massive routes insertion causes crashing and 500.

PDK

- Line up the `kong.log.inspect` function to log at `notice` level as documented in the PDK documentation (used to be `debug`).
- Fixed an issue where the `retries` error message incorrectly referred to the port.

Kong Manager

- Fixed an issue where the content in the header and footer were not center aligned when enabled.
- Fixed an issue where Kong Manager was not displaying the overview page when there is a workspace with the name "portal" (case-insensitive).
- Fixed an issue where Kong Manager was not redirecting users to the previous page after cancelling the plugin creation.
- Fixed an issue where the username does not allow special characters.

Dependency

Core

- Add Ubuntu 24.04 (Noble Numbat) to build
- Bumped the bundled `datakit` Wasm filter to `0.3.1`
- Updated the default base for RPM Dockerfile from UBI 8 to UBI 9.
- Bumped lua-kong-nginx-module from 0.11.0 to 0.13.1 to fix the upstream cert chain issue and enable the new API for retrieving SSL pointer.
- Bumped lua-resty-aws to 1.5.4, to fix a bug inside region prefix generating
- Bumped lua-resty-events to 0.3.1. Optimized the memory usage.
- Updated lua-resty-ljsonschema to 1.2.0. Fixed UTF-8 string length calculation and added support for `null` in `enum` types.
- Bumped lua-resty-lmdb to 1.6.0. Allowing page_size to be 1.

eter to allow overriding page size from caller side.

c88c3ddecd0eb5e25d

owth with session handling in TLSv1.3 and other CVEs

to `5s`. We added a new option `lock_timeout` to make it configurable.
`ime_out = 0`. We fix it to `timeout = 0`. This would improve perf as there is no need for each instance to

mponent (e.g. Kong Gateway) for better debuggability.

d issue

image.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Core

- The Brotli module is missing from all of the following ARM64 Kong Gateway Docker images:
  - RHEL 9
  - Debian 12
  - Amazon Linux 2
  - Amazon Linux 2023

3.8.1.2

Release date 2025/07/02

Feature

PDK

- Added a new `kong.request.get_raw_forwarded_path()` function for returning non-normalized `forwarded_path`.

Core

- Added support for reporting whether `new_dns_client` was enabled in anonymous reports.

Bugfix

Core

- Added a new configuration, `route_match_calculation`, which included bug fixes for the `traditional_compatible` and the `expressions` router flavors. The default value `original` retained the current `3.x` router matching behavior without changes. The value `strict` enforced the router matching behavior with corrected calculation as follows:
  1. The weight (priority point) of a route was incorrectly downgraded.
  2. A route of HTTPS-only protocol with SNIs incorrectly captured requests over HTTP routes.
  3. A route of TLS-only protocol with SNIs incorrectly captured requests over TCP or UDP routes.
- Fixed an issue where newly spawned workers used outdated router data because the `init` phase was skipped.
- Fixed an issue where users encountered duplicate key violation errors on `rbac_role_entities_pkey` while using the `deck sync` command.

Plugin

- mocking:
  - Fixed an issue where an empty array set in the mocking plugin returned an object type instead of an array type in the response body.
- oas-validation:
  - Fixed an issue where the plugin throws an error for responses without a Content-Type header.
- openid-connect:
  - Fixed an `500` error caused by JSON `null` from the request body when parsing bearer tokens or client IDs.
  - Fixed an issue where caused IdP to report invalid redirect_uri errors when `config.redirect_uri` was not configured and the uri path contained spaces.
- rate-limiting-advanced Fixed an issue where RLA stores long expiration time items cause `no memory` errors.

P

dlock with Postgres.

D

C

3

R

D

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fix an issue where running the “kong migration” command will fail when upgrading to 3.8 version, which is caused by an incomplete Redis configuration related SQL.

Feature

Plugin

- session:
  - Added two boolean configuration fields `hash_subject` (default `false`) and `store_metadata` (default `false`) to store session’s metadata in the database.

Core

- Added an option for GitHub Actions to build nginx/OpenResty with debug symbols.
- Added a new feature to invalidate the admin’s or the developer’s related session while changing the password.

Bugfix

Core

- Fixed an issue where consistent hashing did not correctly handle hyphenated-Pascal-case headers, leading to uneven distribution of requests across upstream targets.
- Fixed an issue that certificate entity configured with vault reference may not get refreshed on time when initial with an invalid string.
- Fixed an issue where A mismatch between If-Match in request and ETag in response would result in bad case in the response phase.
- **Vault**: Updated the AWS Vault supported regions list to the latest.
- Fixed an issue where adding the `hash_subject` and `store_metadata` fields to the `portal_session_conf` in the Dev Portal was not working as expected.

Plugin

- app-dynamics:
  - Fixed segmentation fault caused by missing destructor call on process exit.
- ldap-auth-advanced:
  - Fixed an issue where binary string was truncated at the first null character.
- proxy-cache-advanced:
  - Fixed an issue where the `kong.plugins.proxy-cache-advanced.migrations` module was not being loaded when upgrading to `3.8.x.y`. This issue was introduced in `3.8.0.0` and Kong refuses to start if `redis.timeout` and `redis.connect_timeout` are set to different values.
- rate-limiting-advanced:
  - Fixed an issue where the `kong.plugins.rate-limiting-advanced.migrations` module was not being loaded when upgrading to `3.8.x.y`. This issue was introduced in `3.8.0.0` and Kong refuses to start if `redis.timeout` and `redis.connect_timeout` are set to different values.

Dependency

Core

- Bumped libexpat from 2.6.2 to 2.6.4 to fix a crash in the XML_ResumeParser function caused by XML_StopParser stopping an uninitialized parser.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

maximal capacity to 6000

- **ai-transformers**:
  - Fixed a bug where the correct LLM error message was not propagated to the caller.
- ai-proxy-advanced:
  - Fixed an issue where lowest-usage and lowest-latency strategy did not update data points correctly.
- ai-proxy:
  - Fixed an issue where AI Transformer plugins always returned a 404 error when using 'Google One' Gemini subscriptions.
  - Fixed issue where multi-modal requests is blocked on azure provider.
- ai-rate-limiting-advanced:
  - Fixed an issue where the plugin yielded an error when incrementing the rate limit counters in non-yieldable phases.
- ai-semantic-cache:
  - Fixed an issue where the ai-semantic-cache plugin put the wrong type value in the metrics when using the prometheus plugin.
- degraphql:
  - Fixed an issue where the degraphql routes were updated from the control plane but not updated in the degraphql router on the data plane.
- json-threat-protection:
  - Fixed an issue where the length counting of escape sequences, non-ASCII characters, and object entry names in JSON Strings was incorrect; now using UTF-8 character count instead of bytes.
  - Fixed an issue where certain default parameter values were incorrectly interpreted as 0 in some environments (e.g., ARM64-based):
    - `max_container_depth`
    - `max_object_entry_count`
    - `max_object_entry_name_length`
    - `max_array_element_count`
    - `max_string_value_length`
- rate-limiting-advanced:
  - Fixed an issue where a warn log was printed when event_hooks was disabled.
- rate-limiting:
  - Fixed an issue that caused an HTTP 500 error when `hide_client_headers` is set to `true` and the request exceeds the rate limit.
- Fixed an bug that AI semantic cache can't use request provided models
- ai-proxy-advanced, **ai-semantic-prompt-guard**: Fixed an issue where stale plugin config was not updated in dbless and hybrid mode.
- Fixed an issue where the ai-semantic-cache plugin would abort in stream mode when another plugin enable the buffering proxy mode.

Admin API

- Fix for querying admin API entities with empty tags

Core

- **Vault**: Fixed an issue where updating a vault entity in a non-default workspace will not take effect.

C

me role and custom STS endpoint features backport.

K

ners.

h different case letters, does not render the correct overview page.

D

C

fix an issue where the upstream cert chain wasn't properly set

prefix generating

d issue

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

3.8.0.0

Release date 2024/09/11

Deprecation

Core

- Debian 10, CentOS 7, and RHEL 7 reached their End of Life (EOL) dates on June 30, 2024. As of version 3.8.0.0 onward, Kong is not building installation packages or Docker images for these operating systems. Kong is no longer providing official support for any Kong version running on these systems.

PDK

- The shared configuration for Redis `kong/enterprise_edition/redis/init.lua` was deprecated in favor of `kong/enterprise_edition/tools/redis/v2/init.lua`

Plugin

- ai-rate-limiting-advanced:
  - Switched to sentinel_nodes and cluster_nodes for redis configuration.
  - Deprecated timeout config field in redis config in favor of connect_/send_/read_timeout (timeout field will be removed in 4.0).
- graphql-proxy-cache-advanced:
  - Switched to sentinel_nodes and cluster_nodes for redis configuration.
  - Deprecated timeout config field in redis config in favor of connect_/send_/read_timeout (timeout field will be removed in 4.0).
- graphql-rate-limiting-advanced:
  - Deprecated timeout config field in redis config in favor of connect_/send_/read_timeout (timeout field will be removed in 4.0).
  - Switched to sentinel_nodes and cluster_nodes for redis configuration.
- openid-connect:
  - Standardized Redis configuration across plugins. The Redis configuration now follows a common schema shared with other plugins.
- proxy-cache-advanced:
  - Deprecated timeout config field in redis config in favor of connect_/send_/read_timeout (timeout field will be removed in 4.0).
  - Switched to sentinel_nodes and cluster_nodes for redis configuration.
- rate-limiting-advanced:
  - Deprecated timeout config field in redis config in favor of connect_/send_/read_timeout (timeout field will be removed in 4.0).
  - Switched to sentinel_nodes and cluster_nodes for redis configuration.
- saml:
  - Standardized Redis configuration across plugins. The Redis configuration now follows a common schema shared with other plugins.

Feature

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`groups` to support using authenticated groups even when an authenticated consumer already exists.

les in addition to `user`.

s advanced load balancing between LLM services.

e upstream model auth parameter or header from the caller's request.

    - Allowed mistral provider to use mistral.ai managed service by omitting upstream_url
    - Added a new response header X-Kong-LLM-Model that displays the name of the language model used in the AI-Proxy plugin.
- ai-rate-limiting-advanced:
    - Add the cost strategy to AI rate Limiting plugin.
    - Added the `bedrock` and `gemini` providers to the providers list in the `ai-rate-limiting-advanced` plugin.
    - Add the stats when reaching limit and exiting AI rate Limiting plugin.
    - Added Redis cluster_max_redirections configuration option.
- ai-semantic-cache:
    - Introduced AI Semantic Caching plugin, enabling you to configure an embeddings-based caching system for Large Language Model responses.
- ai-semantic-prompt-guard:
    - Added the `ai-semantic-prompt-guard` plugin that supports semantic similarity-based prompt guarding.
- app-dynamics:
    - Added new ANALYTICS_ENABLE flag and collected more snapshot userdata in runtime.
- aws-lambda:
    - A new configuration field `empty_arrays_mode` is now added to control whether Kong should send `[]` empty arrays (returned by Lambda function) as `[]` empty arrays or `{}` empty objects in JSON responses.`
    - Added support for a configurable STS endpoint with the new configuration field `aws_sts_endpoint_url`.
- confluent:
    - Added the `confluent` plugin which allows to interface with Confluent.
- graphql-proxy-cache-advanced:
    - Added Redis cluster_max_redirections configuration option.
- graphql-rate-limiting-advanced:
    - Added Redis cluster_max_redirections configuration option.
- header-cert-auth:
    - Added a new plugin for header-based certificate authentication.
- json-threat-protection:
    - Added JSON threat protection plugin. Validates JSON nesting depth, array elements, object entries, key length, and string length. Logs or terminates violating requests.
- jwt-signer:
    - Supported `/jwt-signer/jwks/:jwt_signer_jwks` endpoint in dbless mode.
- ldap-auth-advanced:
    - Supported decoding an empty sequence or set represented in long form length
- oas-validation:

alue when the path parameter name contains hyphen characters.

ss.

lt with new fields `cluster_cache_strategy` and `cluster_cache_redis`. When configured, the plugin across nodes configured to use the same Redis Database.

n option.

n option.

- request-transformer:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where renamed query parameters, url-encoded body parameters, and json body parameters were not handled properly when target name is the same as the source name in the request.

- standard-webhooks:
  - Added standard webhooks plugin.
- upstream-oauth:
  - Added the Upstream OAuth plugin, enabling Kong to obtain an OAuth2 token to consume an upstream API.
- AI plugins: retrieved latency data and pushed it to logs and metrics.
- Kong AI Gateway (AI Proxy and associated plugin family) now supports all AWS Bedrock “Converse API” models.
- Kong AI Gateway (AI Proxy and associated plugin family) now supports the Google Gemini “chat” (generateContent) interface.
- Added support for json_body rename in response-transformer plugin

Core

- **prometheus**: Added `ai_requests_total`, `ai_cost_total` and `ai_tokens_total` metrics in the Prometheus plugin to start counting AI usage.
- Added a new configuration `concurrency_limit`(integer, default to 1) for Queue to specify the number of delivery timers. Note that setting `concurrency_limit` to `-1` means no limit at all, and each HTTP log entry would create an individual timer for sending.
- Append gateway info to upstream `Via` header like `1.1 kong/3.8.0`, and optionally to response `Via` header if it is present in the `headers` config of “kong.conf”, like `2 kong/3.8.0`, according to `RFC7230` and `RFC9110`.
- Starting from this version, a new DNS client library has been implemented and added into Kong, which is disabled by default. The new DNS client library has the following changes - Introduced global caching for DNS records across workers, significantly reducing the query load on DNS servers. - Introduced observable statistics for the new DNS client, and a new Status API `/status/dns` to retrieve them. - Simplified the logic and make it more standardized
- **analytics**: send AI analytics about latency and caching to Konnect.
- **analytics**: Added support for also sending cache data of AI analytics to Konnect
- Added connection support via Redis Proxy (e.g. Envoy Redis proxy or Twemproxy) via configuration field `connection_is_proxied`.
- Added support for AWS IAM role assuming in AWS IAM Database Authentication, with new configuration fields: “pg_iam_auth_assume_role_arn”, “pg_iam_auth_role_session_name”, “pg_ro_iam_auth_assume_role_arn”, and “pg_ro_iam_auth_role_session_name.”
- Added keyring encryption support to license database entity payloads.
- Added support for a configurable STS endpoint for RDS IAM Authentication, with new configuration fields: `pg_iam_auth_sts_endpoint_url` and `pg_ro_iam_auth_sts_endpoint_url`.
- Added support for a configurable STS endpoint for AWS Vault. This can either be configured by `vault_aws_sts_endpoint_url` as a global configuration, or `sts_endpoint_url` on a custom AWS vault entity.
- Added two configurations, `admin_gui_auth_change_password_attempts` (default value `0`) and `admin_gui_auth_change_password_ttl` (default value `86400`), to limit the number of password change attempts.
- Added a new sub-command `status` to the `kong debug` CLI tool.

Admin API

- Added support for brackets syntax for map fields configuration via the Admin API

PDK

`max_allowed_file_size` is `0`, `get_raw_body` will return the entire body, but the size of this body will still

body to read from buffered file

: `kong.telemetry.log` to generate log entries to be reported via the OpenTelemetry plugin.

C

ed

K

onally creating SNIs while creating a certificate.

admins that prevent the operation.

the plugin detail page.

- Added UI components for building the vault reference easily while configuring referenceable fields for plugins.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Bugfix

Plugin

- **AI Plugins**:
  - Fixed an issue for multi-modal inputs are not properly validated and calculated.
- **AI-Transformers**:
  - Fixed a bug where cloud identity authentication was not used in `ai-request-transformer` and `ai-response-transformer` plugins.
- **OpenTelemetry / Zipkin**:
  - remove redundant deprecation warnings
- acme:
  - Fixed an issue of DP reporting that deprecated config fields are used when configuration from CP is pushed
  - Fixed an issue where username and password were not accepted as valid authentication methods.
- ai-prompt-guard:
  - Fixed an issue when `allow_all_conversation_history` is set to false, the first user request is selected instead of the last one.
- ai-proxy:
  - Fixed a bug where certain Azure models would return partial tokens/words when in response-streaming mode.
  - Fixed a bug where Cohere and Anthropic providers don't read the `model` parameter properly from the caller's request body.
  - Fixed a bug where using "OpenAI Function" inference requests would log a request error, and then hang until timeout.
  - Fixed a bug where AI Proxy would still allow callers to specify their own model, ignoring the plugin-configured model name.
  - Fixed a bug where AI Proxy would not take precedence of the plugin's configured model tuning options, over those in the user's LLM request.
  - Fixed a bug where setting OpenAI SDK model parameter "null" caused analytics to not be written to the logging plugin(s).
  - Fixed issue when response is gzipped even if client doesn't accept.
  - Resolved a bug where the object constructor would set data on the class instead of the instance
- ai-rate-limiting-advanced:
  - Edit the logic for the window ajustement and fix missing passing window to shm
- ai-semantic-cache:
  - Fix the `ai-semantic-caching` plugin with a condition for calculating latencies when no embeddings, add deep copy for the request table and fix countback.
- aws-lambda:
  - Fixed an issue that the plugin does not work with multiValueHeaders defined in proxy integration and legacy empty_arrays_mode.
  - Fixed an issue that the `version` field is not set in the request payload when `awsgateway_compatible` is enabled.
- basic-auth:
  - Fix an issue of realm field not recognized for older kong versions (before 3.6)

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

we explicitly set the `generator` to `null`.

`Origin` header was not sent when `conf.origins` has multiple entries but includes `*`.

e not handled correctly when converting query parameters.

status 400 and error information in the body instead of status 500.

- Fix an issue where the plugin doesn't include port information in the HTTP host header when sending requests to the log server.

- jwt:
  - Add WWW-Authenticate headers to 401 responses.
- key-auth-enc:
  - Added WWW-Authenticate headers to all 401 responses.
- key-auth:
  - Fix an issue of realm field not recognized for older kong versions (before 3.7)
- ldap-auth-advanced:
  - Added WWW-Authenticate headers to all 401 response.
- ldap-auth:
  - Add WWW-Authenticate headers to all 401 responses.
- oas-validation:
  - Fixed an issue where parameter serialization does not behave the same as in the OpenAPI specification
  - Fixed a bug where the non-string primitive types passed via URL query were unexpectedly cast to string when OpenAPI spec is v3.1.0.
- oauth2-introspection:
  - Fixed an issue where the consumer's cache cannot be invalidated when oauth2-introspection uses `client_id` as `consumer_by`.
- oauth2:
  - Add WWW-Authenticate headers to all 401 responses and realm option.
- openid-connect:
  - Fixed a bug where anonymous consumers may be cached as nil under a certain condition.
  - Updated the rediscovery to use a short lifetime (5s) if the last discovery failed.
  - Fixed an issue where using_pseudo_issuer does not work when patching.
- opentelemetry:
  - Fixed an issue where migration fails when upgrading from below version 3.3 to 3.7.
  - Improved accuracy of sampling decisions.
- prometheus:
  - Fixed an issue where CP/DP compatibility check was missing for the new configuration field `ai_metrics`.
  - Improved error logging when having inconsistent labels count.
- proxy-cache-advanced:
  - Fixed a bug where the Age header was not being updated correctly when serving cached requests
- proxy-cache:
  - Fixed an issue where the Age header was not being updated correctly when serving cached responses.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

sumer group overriding config is different from the `window_size` in the default config, the rate limiting of gy.

ig fields are used when configuration from CP is pushed

cked when the request body is buffered to a temporary file.

quests when param_schema is $ref schema.

rameter_validation to determine whether to enable Content-Type parameters validation.

- Fixed an issue of DP reporting that deprecated config fields are used when configuration from CP is pushed

- statsd:
  - Fixed an issue where the exported workspace was always `default` when the workspace identifier was set to the workspace name.
- tls-metadata-headers:
  - Fixed an issue where intermediate certificates details were not added to request headers.
- Fixed certain AI plugins cannot be applied per consumer or per service.
- Fixed a bug where Azure Managed-Identity tokens would never rotate in case of a network failure when authenticating.
- Fixed a Redis schema issue where `connect_timeout`, `read_timeout`, `send_timeout` were reset to `null` if the deprecated `timeout` is `null`.
- rate-limiting-advanced Fixed an issue where the sync timer may stop working due to race condition.

Admin API

- Fixed an issue where validation of the certificate schema failed if the `snis` field was present in the request body.
- Fixed an issue where resetting the token was allowed while disabling rbac_token_enabled.
- The `application-registration` plugin will be hidden from `available_plugins` when the Dev Portal is disabled.
- Fixed an issue where the field `is_default` should be immutable when updating the rbac_roles.
- Fixed an issue where the license report returns 500 when non-required fields are not specified in the Lambda and Kafka plugins.
- Returns a detailed error message when failed to cascade delete a workspace caused by admins associated.

Clustering

- Fixed an issue where hybrid mode not working if the forward proxy password contains special character(#). Note that the `proxy_server` configuration parameter still needs to be url-encoded.

CLI Command

- Fixed an issue where some debug level error logs were not being displayed by the CLI.
- Fixed an issue where `db_import` fails when there are licenses in declarative YAML.

Core

- Fixed an issue where ‘read’ was not always passed to Postgres read-only database operations.
- Deprecated shorthand fields don’t take precedence over replacement fields when both are specified.
- Fixed an issue where `lua-nginx-module` context was cleared when `ngx.send_header()` triggered `filter_finalize` openresty/lua-nginx-module#2323.
- Changed the way deprecated shorthand fields are used with new fields. If the new field contains null it allows for deprecated field to overwrite it if both are present in the request.
- Fixed an issue where unnecessary uninitialized variable error log is reported when 400 bad requests were received.
- Fixed an issue where the URI captures are unavailable when the first capture group is absent.
- Fixed an issue where the priority field can be set in a traditional mode route When ‘router_flavor’ is configured as ‘expressions’.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

override the global level `proxy_ssl_verify`.

a sni is updated.

erwritten during upgrade. When upgrading, set the environment variable
o avoid any interactive prompts and enable fully automatic upgrades.

during `resurrect_ttl` time and could not be fetched by other workers.

he `notice` level instead of `warn`.

y can not be set correctly in requests to upstream as Host header when retries to upstream happen.

from enabling `log_statistics` upon providers not supporting statistics. Accordingly, the default of
atabase migration is added as well for disabling `log_statistics` if it has already been enabled upon

of the Kong prefix.

o describe deprecated fields. If both fields are sent in the request and their values mismatch - the request

- Reverted DNS client to original behaviour of ignoring ADDITIONAL SECTION in DNS responses.

- Shortened names of internal Unix sockets to avoid exceeding the socket name limit.
- Built-in RBAC roles for admins (`admin` under the default workspace and `workspace-admin` under non-default workspaces) now disallow CRUD actions to `/groups` and `/groups/*` endpoints.
- Fixed an issue where luarocks-admin was not available in /usr/local/bin.
- Fixed an issue where running Kong CLI commands with database configurations containing Hashicorp Vault references would fail to execute.
- Fixed an issue where the stale license expiry warning continued to be logged even if the license was updated.
- License expiry warnings are no longer logged and license info is removed from /metrics in Konnect.
- Fixed an issue where the CPs won't trigger a configuration push after a keyring recovery.

PDK

- **PDK**: Fixed a bug that log serializer will log `upstream_status` as nil in the requests that contains subrequest
- **Vault**: Reference ending with slash when parsed should not return a key.
- Fixed an issue that pdk.log.serialize() will throw an error when JSON entity set by serialize_value contains json.null

Configuration

- Re-enabled the Lua DNS resolver from proxy-wasm by default.
- The behavior of the configuration option `analytics_flush_interval` has changed for saving memory resources by flushing analytics messages more frequently. It now controls the maximum time interval between two flushes of analytics messages to the configured backend, which means that if there are enough (less than `analytics_buffer_size_limit`) messages have already been buffered, the flush will happen before the configured interval. Previously, Kong always tries to flush messages after the configured interval, regardless of the number of messages in the buffer.
- Fixed an issue where `debug_listen` incorrectly used the SSL-related configuration of `status_listen`.

Kong Manager

- Fixed an issue where dynamic ordering was configurable for plugins scoped by consumers and/or consumer groups. These plugins does not support dynamic ordering.
- Removed redundant data previously saved in browser's local storage.
- Fixed issues with `cluster_addresses` and `sentinel_addresses` fields for plugins that support Redis clusters.
- Fixed an issue where the overview page for Dev Portal was not correctly rendered.
- Fixed an issue where user info was not refreshed after the active admin was updated.

Dependency

Core

- Bumped lua-protobuf 0.5.2
- Bumped lua-resty-acme to 0.15.0 to support username/password auth with redis.
- Bumped lua-resty-aws to 1.5.3 to fix a bug related to STS regional endpoint.
- Bumped lua-resty-healthcheck from 3.0.1 to 3.1.0 to fix an issue that was causing high memory usage

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ream (lmdb 0.9.33), which resolved numerous race conditions and fixed a cursor issue.

uding a potential use-after-free issue.

88a91c22f23981db35

ce of the LuaJIT hash computation.

e release (nothing important)

x set to `/`.

n, which would improve the latency significantly.

socket keepalive and allow client_id to be set for the kafka client.

- bump lua-resty-cookie to 0.3.0
- Bumped libxml2 to 2.12.9.
- Bumped libxslt to 1.1.42.
- Bumped `lua-resty-azure` to `1.6.0` to support more Azure authentication methods.
- Bumped luaexpat to 1.5.2.
- Bumped msgpack-c to 6.1.0.
- Bumped `kong-redis-cluster` to `1.5.4`, fixing the following issues.
    1. Fixed an issue where Kong Gateway cannot recover if partial or all pods were restared with new IPs in Kubernetes environment.
    2. Fixed a memory leak issue where master nodes cache expanded infinitely upon refresh.
    3. Fixed an issue where multiple cluster instances were accidently flushed.

Performance

Core

- Removed unnecessary DNS client initialization
- Improved latency performance when gzipping/gunzipping large data (such as CP/DP config data).
- Improved the performance of Konnect Analytics by fetching Rate Limiting context more efficiently.
- Improved the performance of Konnect Analytics by optimizing the buffering mechanism.

Plugin

- rate-limiting-advanced:
    - Improved that timer spikes do not occur when there is network instability with the central data store.

Feature

Core

- Bumped lua-resty-events to 0.3.0 to fix an issue that was preventing the configuration from being updated to the latest version

Known Issues

Core

- The Brotli module is missing from all of the following ARM64 Kong Gateway Docker images:
    - RHEL 9
    - Debian 12
    - Amazon Linux 2
    - Amazon Linux 2023

3.7.1.5

Release date 2025/04/10

F

P

ect (default false) and store_metadata (default false) to store session’s metadata in the database.

C

loper’s related session while changing the password.

F

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed segmentation fault caused by missing destructor call on process exit.

- ldap-auth-advanced:
  - Fixed an issue where binary string was truncated at the first null character.

Core

- **Vault**: Updated the AWS Vault supported regions list to the latest.
- Fixed an issue where adding the `hash_subject` and `store_metadata` fields to the `portal_session_conf` in the Dev Portal was not working as expected.

3.7.1.4

Release date 2025/02/25

Feature

Core

- Added an option for GitHub Actions to build nginx/OpenResty with debug symbols.

Bugfix

Core

- Fixed an issue that certificate entity configured with vault reference may not get refreshed on time when initial with an invalid string.

Dependency

Core

- Bumped libexpat from 2.6.2 to 2.6.4 to fix a crash in the XML_ResumeParser function caused by XML_StopParser stopping an uninitialized parser.
- Bumped lua-kong-nginx-module from 0.11.0 to 0.11.2.
- Bumped libxml2 to 2.12.9 for CVE-2024-40896

3.7.1.3

Release date 2024/11/26

Feature

Plugin

- aws-lambda:
  - Added support for a configurable STS endpoint with the new configuration field `aws_sts_endpoint_url`.

Core

- Added support for AWS IAM role assuming in AWS IAM Database Authentication, with new configuration fields: “pg_iam_auth_assume_role_arn”, sume_role_arn”, and “pg_ro_iam_auth_role_session_name.”

IAM Authentication, with new configuration fields: `pg_iam_auth_sts_endpoint_url` and

Vault. This can either be configured by `vault_aws_sts_endpoint_url` as a global configuration, or

E

P

rn partial tokens/words when in response-streaming mode.

don’t read the `model` parameter properly from the caller’s request body.

nce requests would log a request error, and then hang until timeout.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Fixed a bug where AI Proxy would still allow callers to specify their own model, ignoring the plugin-configured model name.
    - Fixed a bug where AI Proxy would not take precedence of the plugin's configured model tuning options, over those in the user's LLM request.
    - Fixed a bug where setting OpenAI SDK model parameter "null" caused analytics to not be written to the logging plugin(s).
- rate-limiting-advanced:
    - Fixed an issue where if the `window_size` in the consumer group overriding config is different from the `window_size` in the default config, the rate limiting of that consumer group would fall back to local strategy.
    - Fixed an issue where the sync timer may stop working due to race condition.

Core

- The kong.logrotate configuration file will no longer be overwritten during upgrade. When upgrading, set the environment variable `DEBIAN_FRONTEND=noninteractive` on Debian/Ubuntu to avoid any interactive prompts and enable fully automatic upgrades.
- **Vault**: Fixed an issue where updating a vault entity in a non-default workspace will not take effect.
- Fixed an issue where the Vault secret cache got refreshed during `resurrect_ttl` time and could not be fetched by other workers.
- Moved internal Unix sockets to a subdirectory (`sockets`) of the Kong prefix.
- Shortened names of internal Unix sockets to avoid exceeding the socket name limit.
- Fixed an issue where luarocks-admin was not available in /usr/local/bin.

Dependency

Core

- Bumped lua-resty-aws to 1.5.3 to fix a bug related to STS regional endpoint.
- Bumped lua-resty-azure to 1.6.1 to fix a GET request build issue
- Made the RPM package relocatable with the default prefix set to `/`.

3.7.1.2

Release date 2024/07/09

Deprecation

Core

- Debian 10, CentOS 7, and RHEL 7 reached their End of Life (EOL) dates on June 30, 2024. As of this patch, Kong is not building Kong Gateway 3.7.x installation packages or Docker images for these operating systems. Kong is no longer providing official support for any Kong version running on these systems.

Feature

Plugin

- aws-lambda:

ow added to control whether Kong should send `[]` empty arrays (returned by Lambda function) as `[]`
es.`

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

was unavailable because the official documentation was removed after the 3.4.x.

Release date 2024/06/22

Bugfix

Core

- Reverted DNS client to original behaviour of ignoring ADDITIONAL SECTION in DNS responses.

3.7.1.0

Release date 2024/06/18

Bugfix

Plugin

- ai-proxy:
  - Resolved a bug where the object constructor would set data on the class instead of the instance
- ai-rate-limiting-advanced:
  - Edit the logic for the window ajustement and fix missing passing window to shm
- basic-auth:
  - Fix an issue of realm field not recognized for older kong versions (before 3.6)
- key-auth:
  - Fix an issue of realm field not recognized for older kong versions (before 3.7)
- openid-connect:
  - Fixed a bug where anonymous consumers may be cached as nil under a certain condition.
- request-validator:
  - Fix an issue where the plugin may fail to handle requests when param_schema is $ref schema.
  - Added a new configuration field `content_type_parameter_validation` to determine whether to enable Content-Type parameters validation.

Core

- Fixed an issue where the priority field can be set in a traditional mode route When 'router_flavor' is configured as 'expressions'.
- fix a bug that the `host_header` attribute of upstream entity can not be set correctly in requests to upstream as Host header when retries to upstream happen.
- Built-in RBAC roles for admins (`admin` under the default workspace and `workspace-admin` under non-default workspaces) now disallow CRUD actions to `/groups` and `/groups/*` endpoints.

Dependency

Core

- Bumped lua-resty-events to 0.2.1

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ai-proxy:
  - To support the new messages API of `Anthropic`, the upstream path of the `Anthropic` for `llm/v1/chat` route type has changed from `/v1/complete` to `/v1/messages`.

Core

- "**Hashicorp Vault**: Starting from this version, a string fully made of spaces cannot be specified as the `role_id` or `secret_id` value in the Hashicorp Vault entity with Approle authentication method. "**Hashicorp Vault**: Starting from this version, at least one of `secret_id` and `secret_id_file` must be specified in the Hashicorp Vault entity with Approle authentication method.
- Removed the Granular Tracing feature, and configurations like `tracing = on` are not available any longer. You should now use OpenTelemetry Instrumentation instead.

Feature

Core

- Added `events:ai:response_tokens`, `events:ai:prompt_tokens` and `events:ai:requests` to the anonymous report to start counting AI usage
- Added support for debugging with EmmyLuaDebugger. This feature is a tech preview and not officially supported by Kong Inc. for now.
- Improved config handling when the CP runs with the router set to the `expressions` flavor:
  - If mixed config is detected and a lower DP is attached to the CP, no config will be sent at all
  - If the expression is invalid on the CP, no config will be sent at all
  - If the expression is invalid on a lower DP, it will be sent to the DP and DP validation will catch this and communicate back to the CP (this could result in partial config application)
- The route entity now supports the following fields when the `router_flavor` is `expressions`: `methods`, `hosts`, `paths`, `headers`, `snis`, `sources`, `destinations`, and `regex_priority`. The meaning of these fields are consistent with the traditional route entity.
- Kong Manager now supports creating and editing Expressions routes with an interactive in-browser editor with syntax highlighting and autocompletion features for Kong's Expressions language.
- Kong Manager now groups the parameters to provide a better user experience while configuring plugins. Meanwhile, several issues with the plugin form page were fixed.
- **Analytics**: Add `latencies.receive_ms` and `websocket` fields
- **Analytics**: `latencies.kong_gateway_ms` no longer includes receive time/latency
- **Analytics**: Add `sse` boolean field to payload, which is set to `true` for Server-Sent Event requests/responses.
- When authenticating Kong Manager with IDPs (e.g., OIDC, LDAP), the source of an RBAC role will be stored in its `role_source` field, which enables the existing roles with a source of `idp` to be removed upon new logins after IDP role mapping has changed. This also allows users to change a role's source between `local` and `idp` via the Admin API manually.

Plugin

- **OpenTelemetry, Zipkin**:
  - The propagation module has been reworked. The new options allow better control over the configuration of tracing headers propagation.
- ai-azure-content-safety:
  - Adds a new plugin that allows the Kong administrator to enforce that all AI-Proxy requests must be introspected with the Azure Content Safety service.

    The plugin enables configurable thresholds for the different moderation categories, and reports audit results into the Kong log serializer for reporting

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

s to 500 for the allow and deny parameters.

ses back to the client on supported providers.

config for `graphql-proxy-cache-advanced` plugin.

ervices

wks. For example, to autmatically rotate `access_token_jwks_uri`, you can set the config

s) to the upstream request header by specifying the names of the upstream request header with `original_access_token_upstream_header` and `original_channel_token_upstream_header`. And `access_token_upstream_header`,

`channel_token_upstream_header`, `original_access_token_upstream_header`, and `original_channel_token_upstream_header` should not have the same value.

- mocking:
  - Add the `custom_base_path` field to specifiy a custom base path. It will be used with the `deck file namespace` feature
- mtls-auth:
  - Add `default_consumer` option that allows a default consumer to be used when the client certificate is valid but does not match any existing consumers.
- oas-validation:
  - Add a new field `api_spec_encoded` to indicate whether the `api_spec` is URI-Encoded.
  - Add the `custom_base_path` field to specifiy a custom base path. It will be used with the `deck file namespace` feature
  - Supported OpenAPI Specification v3.1.0. The plugin now switches to a new JSONSchema validator when the specification version is v3.1.0.
- openid-connect:
  - Added support for DPoP (Demonstrating Proof-of-Possession) tokens validation. The feature is available by enabling `proof_of_possession_dpop`
  - Add support for JWT Secured Authorization Requests (JAR) on Authorization and Pushed Authorization (PAR) endpoints, see: `config.require_signed_request_object`
  - Add support for JARM response modes: `query.jwt`, `form_post.jwt`, `fragment.jwt`, `jwt`
- prometheus:
  - Added workspace label to Prometheus plugin metrics.
- AI Proxy now reads most prompt tuning parameters from the client, while the plugin config parameters under `model_options` are now just defaults. This fixes support for using the respective provider's native SDK.
- AI Proxy now has a `preserve` option for `route_type`, where the requests and responses are passed directly to the upstream LLM. This is to enable compatibility with any and all models and SDKs that may be used when calling the AI services.
- Addded support for EdDSA algorithms in JWT plugin
- Added support for ES512, PS256, PS384, PS512 algorithms in JWT plugin
- Introduced the new ai-rate-limiting-advanced plugin that allow to implement a rate limit by AI provider.
- Added support for Managed Identity authentication when using the Azure provider with AI Proxy.
- Support pseudo json value in add_claims and set_claims for JWT-Signer. We can achieve the goal of passing multiple values to a key by passing a JSON string as the value. And add add_access_token_claims, set_access_token_claims, add_channel_token_claims, set_channel_token_claims for individually adding claims to access tokens and channel tokens. Additionally, add remove_access_token_claims and remove_channel_token_claims to support the removal of claims.

Configuration

- TLSv1.1 and lower versions are disabled by default in OpenSSL 3.x.
- Introduced `nginx_wasm_main_shm_kv` configuration parameter, which enables Wasm filters to use the Proxy-Wasm operations `get_shared_data` and `set_shared_data` without namespaced keys.
- **Schema**: Added a deprecation field attribute to identify deprecated fields
- Added the `wasm_filters` configuration parameter for enabling individual filters

P

zer

A

lters.

filtered by request_timestamp.

sorted by request_timestamp descending

P

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- acme:
  - Fixed an issue where the certificate was not successfully renewed during ACME renewal.
  - Fixed migration of redis configuration.
  - fix a bug where the wrong error log is printed, regarding private keys.
- ai-proxy:
  - Fixed the bug that the `route_type` `/llm/v1/chat` didn't include the analytics in the responses.
- aws-lambda:
  - Fixed an issue where the latency attributed to AWS Lambda API requests was counted as part of the latency in Kong.
- degraphql:
  - Fixed an issue where GraphQL variables were not being correctly parsed and coerced into their defined types.
- jwt:
  - Fixed an issue where the plugin would fail when using invalid public keys for ES384 and ES512 algorithms.
- ldap-auth-advanced:
  - fix an issue where if the credential is encoded with no username kong will throw an error and return 500
  - fix an issue where an exception will be thrown when ldap search fails
- opentelemetry:
  - Fixed an OTEL sampling mode Lua panic bug, which happened when the `http_response_header_for_traceid` option was enabled.
- rate-limiting-advanced:
  - Refactored `kong/tools/public/rate-limiting` to keep the original interfaces unchanged (backward compatibility) and extend a new interface `new_instance` to provide isolation between different plugins. If you are using custom Rate Limiting plugins based on this library, please update the initialization code to the new format like 'local ratelimiting = require("kong.tools.public.rate-limiting").new_instance("custom-plugin-name")'. The old interface will be removed in the upcoming major release.
  - Fixed an issue where RLA and other similar plugins using the `rate-limiting` library, when used together, would interfere with each other and thus fail to synchronize counter data to the central data store
  - Falling back to local strategy if sync_rate = 0 when redis goes down
  - The plugin now creates counter syncing timers when being executed instead of being created to reduce some meaningless error logs
  - Print error log when multiple plugins with the same namespace have different configurations
  - fix an issue where if `sync_rate` is changed from a value greater than `0` to `0`, the namespace will be cleared unexpectedly
  - fix some timer-related issues where the counter syncing timer can't be created or destroyed properly
- rate-limiting:
  - Fixed migration of redis configuration.
- response-ratelimiting:
  - Fixed migration of redis configuration.
- Added WWW-Authenticate headers to all 401 responses in the Key Auth plugin.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ate graphql router with better error handling

lator, **XML Threat Protection**: priorities have been updated to prevent collisions between plugins. The lugins remained unchanged.

C

s low, Kong would fail to start as the `lua-resty-timer-ng` exhausted the available `worker_connections`. r-ng library from `[512, 2048]` to `[256, 1024]` to fix this bug.

could not return a proper response if the input included duplicate upstream targets.

for options timeout, and use a default value of 2 seconds instead.

entity configured with a vault reference may not get refreshed on time.

- Fixed the missing router section for the output of the request-debugging.

- Fixed an issue in the internal caching logic where mutexes could get never unlocked.
- Fixed an issue where the router didn't work correctly when the route's configuration changed.
- Fixed an issue where SNI-based routing didn't work using `tls_passthrough` and the `traditional_compatible` router flavor.
- Fixed a bug that `X-Kong-Upstream-Status` didn't appear in the response headers even if it was set in the `headers` parameter in the `kong.conf` file when the response was hit and returned by the Proxy Cache plugin.
- Fixed vault initialization by postponing vault reference resolving on init_worker
- Fixed a bug that allowed vault secrets to refresh even when they had no TTL set.
- **Vault**: do not use incorrect (default) workspace identifier when retrieving vault entity by prefix
- **Core**: Fixed unexpected table nil panic in the balancer's stop_healthchecks function
- Use `-1` as the worker ID of privileged agent to avoid access issues.
- Fix an issue where external plugins using the protobuf-based protocol would fail to call the `kong.Service.SetUpstream` method with an error `bad argument #2 to 'encode' (table expected, got boolean)`.
- Reverted the hard-coded limitation of the `ngx.read_body()` API in OpenResty upstreams' new versions when downstream connections are in HTTP/2 or HTTP/3 stream modes.
- Each Kong cache instance now utilizes its own cluster event channel. This approach isolates cache invalidation events and reducing the generation of unnecessary worker events.
- Updated telemetry collection for AI Plugins to allow multiple plugins data to be set for the same request.
- Improved the user experience in Kong Manager by fixing various UI-related issues.
- **Core**: Disable analytics in stream module to avoid unnecessary error logs.
- Fix a problem that a new DP cannot resolve the license required Vault reference after the first configuration push.
- Fixed an issue where DP was unable to resolve license required Vault reference when loading an existing lmdb.
- Fixing an issue where users were not allowed to start Kong Gateway if `admin_gui_auth_conf.scope` is missing `"openid"` or `"offline_access"` when `admin_gui_auth` is set to `openid-connect`. Kong Gateway will now print warning logs only if `"openid"` is missing from `admin_gui_auth_conf.scope`.

PDK

- **PDK:** Fixed `kong.request.get_forwarded_port` to always return a number, which was caused by an incorrectly stored string value in `ngx.ctx.host_port`.
- The value of `latencies.kong` in the log serializer payload no longer includes the response receive time, so it now has the same value as the `X-Kong-Proxy-Latency` response header. Response receive time is recorded in the new `latencies.receive` metric, so if desired, the old value can be calculated as `latencies.kong + latencies.receive`. **Note:** this also affects payloads from all logging plugins that use the log serializer: `file-log`, `tcp-log`, `udp-log`,`http-log`, `syslog`, and `loggly`, e.g. descriptions of JSON objects for the HTTP Log Plugin's log format.
- **Tracing**: enhanced robustness of trace ID parsing

Configuration

- Fixed the default value in kong.conf.default documentation from 1000 to 10000 for the `upstream_keepalive_max_requests` option.
- Fixed an issue where an external plugin (Go, Javascript, or Python) would fail to apply a change to the plugin config via the Admin API.
- Disabled usage of the Lua DNS resolver from proxy-wasm by default.
- Set security level of gRPC's TLS to 0 when `ssl_cipher_suite` is set to `old`.

A

ST `/schemas/vaults/validate` was conflicting with the endpoint `/schemas/vaults/:name` which only

dmins associated with a workspace based on their assigned RBAC roles. It has been fixed to return admins

C

0s even if `--db-timeout` was not explicitly passed in CLI arguments.

nore the `lua_ssl_trusted_certificate` configuration option.

C

ts Manager

- Adjust clustering compatible check related to HCV kube auth path

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Adjusted a clustering compatible check related to Hashicorp Vault Approle authentication.
- Fixed a problem where event_hooks were prematurely validated in hybrid mode. The fix delays the validation of event_hooks to the point where event_hooks are emitted.

Kong Manager

- Fixed an issue where the “Add Role” button was visible when authenticating with an IDP. It is now hidden when Kong Manager is set to authenticate with an IDP.
- Corrected the documentation link shown on the RBAC user form page.

Dependency

Core

- Added package `tzdata` to DEB Docker image for convenient timezone setting.
- Bumped atc-router from v1.6.0 to v1.6.2
- Bumped libexpat to 2.6.2
- Bumped lua-kong-nginx-module from 0.8.0 to 0.11.0
- Bumped lua-protobuf to 0.5.1
- Bumped lua-resty-acme to 0.13.0
- Bumped lua-resty-aws from 1.3.6 to 1.4.1
- Bumped lua-resty-http to 0.17.2.
- Bumped lua-resty-lmdb from 1.4.1 to 1.4.2
- Bumped lua-resty-openssl from 1.2.0 to 1.3.1
- Bumped lua-resty-timer-ng to 0.2.7
- Bumped LuaRocks from 3.9.2 to 3.11.0
- Bumped `ngx_wasm_module` to `91d447ffd0e9bb08f11cc69d1aa9128ec36b4526`
- Bumped PCRE from the legacy libpcre 8.45 to libpcre2 10.43
- Bumped penlight to 1.14.0
- Bumped `V8` version to `12.0.267.17`
- Bumped `Wasmtime` version to `19.0.0`
- Improved the robustness of lua-cjson when handling unexpected input.
- Updated `kong-lua-resty-kafka` to `0.18`.
- Updated submodule kong-openid-connect to 2.7.1
- Updated `lua-resty-luasocket` to `1.1.2` for fixing luasocket#427.
- Updated lua-resty-mail to 1.1.0
- Updated OpenSSL FIPS-provider to 3.0.9

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

P

P

- opentelemetry.

- Increased queue max batch size to 200.

Performance

- Improved proxy performance by refactoring internal hooking mechanism.
- Sped up the router matching when the `router_flavor` is `traditional_compatible` or `expressions`.
- Speeded up tracing mechanism.

Known Issues

Core

- The Brotli module is missing from all of the following ARM64 Kong Gateway Docker images:
  - RHEL 9
  - Debian 12
  - Amazon Linux 2
  - Amazon Linux 2023

3.6.1.8

Release date 2024/10/11

Feature

Plugin

- aws-lambda:
  - Added support for a configurable STS endpoint with the new configuration field `aws_sts_endpoint_url`.

Core

- Added support for AWS IAM role assuming in AWS IAM Database Authentication, with new configuration fields: “pg_iam_auth_assume_role_arn”, “pg_iam_auth_role_session_name”, “pg_ro_iam_auth_assume_role_arn”, and “pg_ro_iam_auth_role_session_name.”
- Added support for a configurable STS endpoint for RDS IAM Authentication, with new configuration fields: `pg_iam_auth_sts_endpoint_url` and `pg_ro_iam_auth_sts_endpoint_url`.
- Added support for a configurable STS endpoint for AWS Vault. This can either be configured by `vault_aws_sts_endpoint_url` as a global configuration, or `sts_endpoint_url` on a custom AWS vault entity.

Bugfix

Core

- The kong.logrotate configuration file will no longer be overwritten during upgrade. When upgrading, set the environment variable `DEBIAN_FRONTEND=noninteractive` on Debian/Ubuntu to avoid any interactive prompts and enable fully automatic upgrades.
- **Vault**: Fixed an issue where updating a vault entity in a non-default workspace will not take effect.
- Fixed an issue where the Vault secret cache got refreshed during `resurrect_ttl` time and could not be fetched by other workers.

of the Kong prefix.

ling the socket name limit.

/usr/local/bin.

P

n ldap search fails

a concatenation error.

w_size in the consumer group overriding config is different from the window_size in the default config,
o local strategy.

er may stop working due to race condition.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Dependency

Core

- Bumped lua-resty-aws to 1.5.3 to fix a bug related to STS regional endpoint.
- Made the RPM package relocatable with the default prefix set to `/`.

3.6.1.7

Release date 2024/07/09

Deprecation

Core

- Debian 10, CentOS 7, and RHEL 7 reached their End of Life (EOL) dates on June 30, 2024. As of this patch, Kong is not building Kong Gateway 3.6.x installation packages or Docker images for these operating systems. Kong is no longer providing official support for any Kong version running on these systems.

Feature

Plugin

- aws-lambda:
  - A new configuration field `empty_arrays_mode` is now added to control whether Kong should send `[]` empty arrays (returned by Lambda function) as `[]` empty arrays or `{}` empty objects in JSON responses.`

Dependency

Core

- Bumped lua-resty-events to 0.3.0
- Bumped lua-resty-healthcheck from 3.1.0

3.6.1.6

Release date 2024/06/22

Bugfix

Core

- Reverted DNS client to original behaviour of ignoring ADDITIONAL SECTION in DNS responses.

3.6.1.5

Release date 2024/06/18

Feature

A

lters.

filtered by request_timestamp.

sorted by request_timestamp descending

E

C

60s even if `--db-timeout` was not explicitly passed in CLI arguments.

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- acme:
  - Fixed migration of redis configuration.
- basic-auth:
  - Fix an issue of realm field not recognized for older kong versions (before 3.6)
- openid-connect:
  - Fixed a bug where anonymous consumers may be cached as nil under a certain condition.
- rate-limiting:
  - Fixed migration of redis configuration.
- request-validator:
  - Fix an issue where the plugin may fail to handle requests when param_schema is $ref schema.
  - Added a new configuration field `content_type_parameter_validation` to determine whether to enable Content-Type parameters validation.
- response-ratelimiting:
  - Fixed migration of redis configuration.

Core

- fix a bug that the `host_header` attribute of upstream entity can not be set correctly in requests to upstream as Host header when retries to upstream happen.
- Built-in RBAC roles for admins (`admin` under the default workspace and `workspace-admin` under non-default workspaces) now disallow CRUD actions to `/groups` and `/groups/*` endpoints.
- **Vitals**: Fixed a bug that each data plane connecting to the control plane would trigger the control plane to create a redundant table rotater timer.

Admin API

- The `/<workspace>/admins` endpoint was used to return admins associated with a workspace based on their assigned RBAC roles. It has been fixed to return admins according to the workspace they belong to.

Kong Manager

- Fixed an issue where the Dev Portal documentation link was unavailable because the official documentation was removed after the 3.4.x.

Dependency

Core

- Bumped lua-resty-azure from 1.4.1 to 1.5.0, to refine some error logging.
- Bumped lua-resty-events to 0.2.1
- Bumped lua-resty-healthcheck from 3.0.1 to 3.0.2, to reduce active healthcheck timer usage.
- Improve the robustness of lua-cjson when handling unexpected input.

Performance

P

occur when there is network instability with the central data store.

3

R

F

P

lt consumer to be used when the client certificate is valid but does not match any existing consumers.

F

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

PDK

- **PDK:** fix kong.request.get_forwarded_port to always return a number which was caused by an incorrectly stored string value in ngx.ctx.host_port.

Core

- Fixed a problem that in hybrid DP mode a certificate entity configured with vault reference may not get refreshed on time
- fix vault initialization by postponing vault reference resolving on init_worker

Clustering

- Fixed a problem where event_hooks were prematurely validated in hybrid mode. The fix delays the validation of event_hooks to the point where event_hooks are emitted.

Plugin

- rate-limiting-advanced:
  - Refactored `kong/tools/public/rate-limiting` to keep the original interfaces unchanged (backward compatibility) and extend a new interface `new_instance` to provide isolation between different plugins. If you are using custom Rate Limiting plugins based on this library, please update the initialization code to the new format like 'local ratelimiting = require("kong.tools.public.rate-limiting").new_instance("custom-plugin-name")'. The old interface will be removed in the upcoming major release.
- oas-validation, **WebSocket Size Limit**, **WebSocket Validator**, **XML Threat Protection**: priorities have been updated to prevent collisions between plugins. The relative priority (and the order of execution) of bundled plugins remained unchanged.

Dependency

Core

- Bump lua-protobuf to 0.5.1

3.6.1.3

Release date 2024/04/16

Bugfix

Plugin

- opentelemetry:
  - Improved robustness of parsing for short trace IDs.

Kong Manager

- Fixed an issue where admin account profile page returning 404 error if the `admin_gui_path` was not a slash.

3.6.1.2

Release date 2024/04/08

F

P

ether the `api_spec` is URI-Encoded.

F

P

sfully renewed during ACME renewal.

being correctly parsed and coerced into their defined types.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- rate-limiting-advanced:
  - Fixed an issue where RLA and other similar plugins using the `rate-limiting` library, when used together, would interfere with each other and thus fail to synchronize counter data to the central data store

Configuration

- Fix an issue where an external plugin (Go, Javascript, or Python) would fail to apply a change to the plugin config via the Admin API.

Core

- update file permission of kong.logrotate to 644
- **Vault**: do not use incorrect (default) workspace identifier when retrieving vault entity by prefix
- Fix a problem that a new DP cannot resolve the license required Vault reference after the first configuration push.
- Fixing an issue where users were not allowed to start Kong Gateway if `admin_gui_auth_conf.scope` is missing `"openid"` or `"offline_access"` when `admin_gui_auth` is set to `openid-connect`. Kong Gateway will now print warning logs only if `"openid"` is missing from `admin_gui_auth_conf.scope`.

Clustering

- Adjust clustering compatible check related to AWS Secrets Manager

Kong Manager

- fixed the display of the remaining days of license expireation date
- Fix an issue that setting up Developer Portal configuration `Developer Meta Fields` contains characters outside of the Latin1 range, admins are not able to login to Kong Manager.
- change the type of rbac token for the RBAC user to `password`

Dependency

Core

- Bumped lua-resty-openssl to 1.2.1
- Bumped PCRE from the legacy libpcre 8.45 to libpcre2 10.43
- Bump `kong-lua-resty-kafka` to `0.18`.
- Bumped lua-kong-nginx-module to 0.8.1
- Bump `lua-resty-luasocket` to `1.1.2` for fixing luasocket#427.

3.6.1.1

Release date 2024/03/05

Bugfix

Core

t-debugging

PI in OpenResty upstreams' new versions when downstream connections are in HTTP/2 or HTTP/3 stream

C

orp Vault Approle authentication.

P

nc_rate = 0 when redis goes down

ncing timers when being executed instead of being created to reduce some meaningless error logs

changed from a value greater than `0` to `0`, the namespace will be cleared unexpectedly

e the counter syncing timer can't be created or destroyed properly

K

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fix an issue where custom plugins were missing from the plugin select page.
- Fix an issue where the service was not prefilled in the route form while using Expressions router.

3.6.1.0

Release date 2024/02/26

Feature

Configuration

- now TLSv1.1 and lower is by default disabled in OpenSSL 3.x

Bugfix

Core

- Fix a bug where the ulimit setting (open files) is low Kong will fail to start as the lua-resty-timer-ng exhausts the available worker_connections. Decrease the concurrency range of the lua-resty-timer-ng library from [512, 2048] to [256, 1024] to fix this bug.

Plugin

- ldap-auth-advanced:
  - fix an issue where if the credential is encoded with no username kong will throw an error and return 500
- opentelemetry:
  - fix otel sampling mode lua panic bug when http_response_header_for_traceid option enable

Configuration

- Set security level of gRPC's TLS to 0 when ssl_cipher_suite is set to old

Clustering

- Adjust clustering compatible check related to HCV kube auth path

Performance

Plugin

- opentelemetry:
  - increase queue max batch size to 200

3.6.0.0

Release date 2024/02/12

Breaking Change

P

quest URI and only use `routeprefix` configuration field to construct request path when requesting Azure

`application/json`.

orrect the integration between the SAML plugin and other consumer-based plugins

C

ed nginx.conf directives, the prefix for Wasm `shm_kv` nginx.conf directives was changed from

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- In OpenSSL 3.2, the default SSL/TLS security level has been changed from 1 to 2. Which means security level set to 112 bits of security. As a result RSA, DSA and DH keys shorter than 2048 bits and ECC keys shorter than 224 bits are prohibited. In addition to the level 1 exclusions any cipher suite using RC4 is also prohibited. SSL version 3 is also not allowed. Compression is disabled.

Admin API

- The listing endpoints for consumer groups (`/consumer_groups`) and consumers (`/consumers`) now respond with paginated results. The JSON key for the list has been changed to `data` instead of `consumer_groups` or `consumers`.

Deprecation

Plugin

- acme:
  - Standardize redis configuration across plugins. The redis configuration right now follows common schema that is shared across other plugins.
- rate-limiting:
  - Standardize redis configuration across plugins. The redis configuration right now follows common schema that is shared across other plugins.
- response-ratelimiting:
  - Standardize redis configuration across plugins. The redis configuration right now follows common schema that is shared across other plugins.

Feature

Plugin

- acl:
  - Add support for consumer-groups
- ip-restriction:
  - add support for consumer group scoping
- ldap-auth-advanced:
  - support decoding non-standard asn1 integer and enumerated encoded with redundant leading padding
- openid-connect:
  - configurations `scopes`, `login_redirect_uri`, `logout_redirect_uri` can now be referenced as a secret in the Kong Vault
  - extend `token_post_args_client` to support injection from headers
  - add support for explicit proof key for code exchange (PKCE).
  - add support for pushed authorization requests (PAR).
- proxy-cache-advanced:
  - add support for consumer group scoping
- proxy-cache:
  - add support for consumer group scoping

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

es prepending and appending llm/v1/chat messages onto consumer LLM requests, for prompt tuning.

/or block LLM requests based on pattern matching.

onsumers and array of LLM prompt templates, with variable substitutions.

d integration with various AI provider Large Language Models.

- Introduced the new ai-request-transformer plugin that enables passing mid-flight consumer requests to an LLM for transformation or sanitization.

- Introduced the new ai-response-transformer plugin that enables passing mid-flight upstream responses to an LLM for transformation or sanitization.
- Tracing Sampling Rate can now be set via the `config.sampling_rate` property of the OpenTelemetry plugin instead of it just being a global setting for the gateway.
- Add CONTROLLER_CERTIFICATE_FILE and CONTROLLER_CERTIFICATE_DIR env config for AppDynamics plugin to use self-signed certificate
- Support the `tls_client_auth` and `self_signed_tls_client_auth` auth methods in the OpenID Connect plugin, allowing to do mTLS Client Authentication with the IdP.
- rate-limiting-advanced Enhance the resolution of RLA sliding window weight

Core

- Adds telemetry collection for AI Proxy, AI Request Transformer, and AI Response Transformer, pertaining to model and provider usage.
- add ngx_brotli module to kong prebuild nginx
- Allow primary key passed as a full entity to DAO functions.
- Build deb packages for Debian 12. The debian variant of kong docker image is built using Debian 12 now.
- The expressions route now supports the `!` (not) operator, which allows creating routes like `!(http.path ^= "/a")` and `!(http.path == "/a" || http.path == "/b")`
- Add `source` property to log serializer, indicating the response is generated by `kong` or `upstream`.
- Ensure Kong-owned directories are cleaned up after an uninstall using the system's package manager.
- Support `http.path.segments.len` and `http.path.segments.*` fields in the expressions router which allows matching incoming (normalized) request path by individual segment or ranges of segments, plus checking the total number of segments.
- `net.src.*` and `net.dst.*` match fields are now accessible in HTTP routes defined using expressions.
- Extend support for getting and setting Gateway values via proxy-wasm properties in the `kong.*` namespace.
- add the `examples` field to the metaschema
- Add new `upstream_status` and `source` properties to analytics pusher.
- add the `consumer_groups` support for analytics
- HashiCorp Vault backend now supports using Approle authentication method
- Allow using RBAC token to authenticate while using group mapping feature (e.g., OIDC, LDAP) with Kong Manager, and also fix some issue with the group mapping feature.
- Use the value provided by the new Request ID feature for all request ID fields, for better consistency
- Exclude dot keys like `a.b.c` from both audit requests and audit objects, and otherwise exclude singular key like `password` recursively.

Admin API

- add gateway edition to the root endpoint of the admin api
- Enable `status_listen` on `127.0.0.1:8007` by default
- Make fips enablement status responding to license conf changes. Also, introduces a new endpoint `/fips-status` to show its current status.

Clustering

he control plane API.

nts. Now Dataplanes can act as importer and exporter at the same time, and Kong will try to control the

fig reload failures such as invalid configuration or transient errors to the control-plane.

connection error.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d but the Admin API is not enabled

ermediate configuration

ed to `off`

on block

), wiping the content if tag mismatch to avoid compatibility issues during minor version upgrade.

- The default value of dns_no_sync option has been changed to `off`

PDK

- Increase the precision of JSON number encoding from 14 to 16 decimals

CLI Command

- Automatically reinitialize the workspace entity counters after executing the cli change migrations commands.

Kong Manager

- Added support for creating/editing the route-by-header plugin from the UI.
- Added an onboarding flow to make it easier for new customers to start using Kong Gateway.
- Now the summary section has a new design in both workspaces page and overview page.

Bugfix

Plugin

- datadog:
  - Fix a bug that datadog plugin is not triggered for serviceless routes. In this fix, datadog plugin is always triggered, and the value of tag `name`(service_name) is set as an empty value.
- forward-proxy:
  - Fixed the issue where request payload is being discarded when payload exceeded the `client_body_buffer_size`.
- jwt-signer:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- ldap-auth-advanced:
  - fix some cache-related issues which cause groups_required to not work properly and unexpected return codes after a non-200 response
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- mocking:
  - Fix an issue where valid recursive schemas are always rejected.
  - Fix an issue where the plugin failed to return the mock response when `resposnes` contains `default` or wildcard codes like 2XX.
- oas-validation:
  - Fixed an issue that the plugin throws a runtime error while validating parameters with AnyType schema and style keyword defined.
  - Fixed an issue that the cookie parameters are not being validated.
  - Fixed an issue that the nullable keyword did not take effect.
  - Fixed an issue where the request path could not matched when containing regex escape characters.
  - Fixed an issue that the URI component escaped characters were incorrectly unescaped.
- oauth2-introspection:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ong.client.authenticate function

version of `kong.request.get_forwarded_path()` instead of `ngx.var.request_uri` (especially when

erinfo from the `userinfo_load` function

ong.client.authenticate function

extra_jwks_uris contain the same uri

iration time checking

ions/001_035_to_050.lua that blocks migration from OSS to EE. This is a breaking change for
0.5.0.

- rate-limiting:

  - fix to provide better accuracy in counters when sync_rate is used with the redis policy.
  - fix an issuer where all counters are synced to the same DB at the same rate.
- saml:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- Add missing WWW-Authenticate headers to 401 response in basic auth plugin.
- Enhance error responses for authentication failures in the Admin API
- forward-proxy fallback to the non-streaming proxy when the request body has already been read
- oas-validation Fix a bug where the plugin throws a runtime error caused by the ref parameter schema not being dereferenced.
- Expose metrics for serviceless routes
- Mark the `authorization_value` in the `oauth2-introspection` plugin as an encrypted field
- Mark the `introspection_headers_values` in the `openid-connect` plugin as an encrypted and referenceable field
- Fix typo in jwe-decrypt error message
- check if `sync_rate` is `nil` when calling the RLA phase `configure()`
- Skip sync with DB or Redis if `sync_rate` is `nil` or `null`.
- mtls-auth print notice log if revocation check fails with revocation_check_mode = IGNORE_CA_ERROR
- request-validator The Request Validator plugin now validates the request body schema when json is the suffix value in the request content type's subtype, for example `application/merge-patch+json`.
- rate-limiting-advanced Check the error of queries in the redis pipeline
- Provide better error messages in the route-transformer-advanced plugin
- validate private and public key for keys entity

Core

- prevent ca to be deleted when it's still referenced by other entities and invalidate the related ca store caches when a ca cert is updated.
- Now cookie names are validated against RFC 6265, which allows more characters than the previous validation.
- Remove nulls only if the schema has transformations definitions. Improve performance as most schemas does not define transformations.
- Fix a bug that the error_handler can not provide the meaningful response body when the internal error code 494 is triggered.
- Header value matching (`http.headers.*`) in `expressions` router flavor are now case sensitive. This change does not affect on `traditional_compatible` mode where header value match are always performed ignoring the case.
- print error message correctly when plugin fails
- fix ldoc intermittent failure caused by LuaJIT error.
- use NGX_WASM_MODULE_BRANCH environment variable to set ngx_wasm_module repository branch when building Kong.
- Eliminate asynchronous timer in syncQuery() to prevent hang risk
- **tracing:** Fixed an issue where a DNS query failure would cause a tracing failure.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ve stricter validation. Previously they share the same validation schema which means admin can configure eam routes. This is no longer allowed.

eam dns queries (in addition to cosocket ones)

r thrown when a filter triggers re-entrancy of the access handler.

s to all workspaces.

ing #7077 #7101

plane resilience

when secrets cannot be fetched

ugging when using the filter

ang risk

vers. Those logs cannot be suppressed due to the limitation of OpenResty. We choose to remove the socket

- Fix an issue where the IAM auth token was not refreshed when the underlying AWS credential expired.

- Print Redis's 'timeout' warning message only if it explicitly set. Use the default timeout value if it is not set.

Clustering

- Fix a bug causing data-plane status updates to fail when an empty PING frame is received from a data-plane
- Fix an issue where the dataplane's log serializer output has workspace name under Hybrid mode
- reduce message push error log when cluster_telemetry_endpoint config is disabled
- Return `-1` as worker id for privileged agent in the Clustering analytics.

Configuration

- fix error data loss caused by weakly typed of function in declarative_config_flattened function
- respect custom `proxy_access_log`

PDK

- response.set_header support header argument with table array of string
- Fix an issue that when using kong.response.exit, the Transfer-Encoding header set by user is not removed
- **Plugin Server**: fix an issue where every request causes a new plugin instance to be created

Admin API

- Fix an issue where the `/rbac/roles/:role/endpoints` endpoint did not accept `actions` as an array.
- The workspace listing API only shows workspaces that the current user has endpoints associated with
- Fix an issue where HTTP 500 errors were returned when paginating and sorting by timestamp fields (e.g., `created_at`).
- Fix an issue where unique violation errors were reported while trying to update the user_token with the same value on the same RBAC user.
- Ensure the `/developers/:developer` endpoint only accepts `roles` as arrays.
- disallow admins or RBAC users to update their own roles

CLI Command

- Do not reinitialize workspace entity counters when migrating from CE to EE.

Portal

- Implement relative URLs for portal root path redirection to prevent erroneous redirections to incorrect domains or protocols

Kong Manager

- Fix issues with Admin GUI authentication using OpenID Connect, including session, response_mode, and RP-initiated logout.
- Corrected UI descriptions under Teams when mapping roles from external sources (e.g., OIDC, LDAP).
- Kong Manager now supports operating keys scoped to a specific keyset without permissions on the `/keys/*` endpoint.
- via OpenID Connect.

D

C

may sometimes cause incorrect logic

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped lua-resty-lmdb from 1.3.0 to 1.4.1
- Bumped lua-resty-timer-ng from 0.2.5 to 0.2.6
- Bump `ngx_wasm_module` to `a7087a37f0d423707366a694630f1e09f4c21728`
- Bumped OpenResty from 1.21.4.2 to 1.25.3.1
- Bumped OpenSSL from 3.1.4 to 3.2.1
- Bump resty-openssl from 0.8.25 to 1.2.0
- Bump `Wasmtime` version to `14.0.3`
- Bumped ngx_brotli to master branch, and disabled it on rhel7 rhel9-arm64 and amazonlinux-2023-arm64 due to toolchain issues
- Bumped lua-resty-healthcheck from 1.6.3 to 3.0.0
- bump submodule kong-openid-connect to 2.7.0
- Bump kong-redis-cluster to '1.5.2'
- Bump kong-redis-cluster to '1.5.3'
- bump jq to 1.7.1
- bump luasec to 1.3.2
- bump OpenSSL to 3.1.4
- bump lua-resty-aws to 1.3.6

Performance

Core

- Reuse match context between requests to avoid frequent memory allocation/deallocation

Performance

- Bumped the concurrency range of the lua-resty-timer-ng library from [32, 256] to [512, 2048].
- Cooperatively yield when building statistics of routes to reduce the impact to proxy path latency.

Configuration

- Bump `dns_stale_ttl` default to 1 hour so stale DNS record can be used for longer time in case of resolver downtime.
- Bumped default values of `nginx_http_keepalive_requests` and `upstream_keepalive_max_requests` to `10000`. These changes are optimized to work better in systems with high throughput. In a low-throughput setting, these new settings may have visible effects in loadbalancing - it can take more requests to start using all the upstreams than before.
- Bump `dns_stale_ttl` default to 1 hour so stale DNS record can be used for longer time in case of resolver downtime.

PDK

- Performance optimization to avoid unnecessary creations and garbage-collections of spans

K

C

I64 Kong Gateway Docker images:

3

R

D

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Debian 10, CentOS 7, and RHEL 7 reached their End of Life (EOL) dates on June 30, 2024. As of this patch, Kong is not building Kong Gateway 3.5.x installation packages or Docker images for these operating systems. Kong is no longer providing official support for any Kong version running on these systems.

Feature

Plugin

- aws-lambda:
  - A new configuration field `empty_arrays_mode` is now added to control whether Kong should send `[]` empty arrays (returned by Lambda function) as `[]` empty arrays or `{}` empty objects in JSON responses.`

3.5.0.6

Release date 2024/06/22

Bugfix

Core

- Reverted DNS client to original behaviour of ignoring ADDITIONAL SECTION in DNS responses.

3.5.0.5

Release date 2024/06/18

Feature

Admin API

- Add LHS brackets filtering to search fields
- **Audit Log:** Add request_timestamp to audit_objects.
- **Audit Log**: Add before / after aliases for LHS Brackets filters.
- **Audit Log:** Allow audit_requests and audit_objects to be filtered by request_timestamp.

Bugfix

Core

- fix a bug that the `host_header` attribute of upstream entity can not be set correctly in requests to upstream as Host header when retries to upstream happen.
- Built-in RBAC roles for admins (`admin` under the default workspace and `workspace-admin` under non-default workspaces) now disallow CRUD actions to `/groups` and `/groups/*` endpoints.

Admin API

- The `/<workspace>/admins` endpoint was used to return admins associated with a workspace based on their assigned RBAC roles. It has been fixed to return admins according to the workspace they belong to.
- The workspace listing API only shows workspaces that the current user has endpoints associated with

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Performance

Plugin

- rate-limiting-advanced Improved that timer spikes do not occur when there is network instability with the central data store.

3.5.0.4

Release date 2024/05/20

Breaking Change

Core

- In OpenSSL 3.2, the default SSL/TLS security level has been changed from 1 to 2. Which means security level set to 112 bits of security. As a result RSA, DSA and DH keys shorter than 2048 bits and ECC keys shorter than 224 bits are prohibited. In addition to the level 1 exclusions any cipher suite using RC4 is also prohibited. SSL version 3 is also not allowed. Compression is disabled.

Feature

Admin API

- add gateway edition to the root endpoint of the admin api
- **Audit Log:** change default ordering of audit_requests to sorted by request_timestamp descending

Configuration

- now TLSv1.1 and lower is by default disabled in OpenSSL 3.x

Core

- The expressions route now supports the `!` (not) operator, which allows creating routes like `!(http.path =^ "/a")` and `!(http.path == "/a" || http.path == "/b")`
- Support `http.path.segments.len` and `http.path.segments.*` fields in the expressions router which allows matching incoming (normalized) request path by individual segment or ranges of segments, plus checking the total number of segments.
- `net.src.*` and `net.dst.*` match fields are now accessible in HTTP routes defined using expressions.
- HashiCorp Vault backend now supports using Approle authentication method
- Allow using RBAC token to authenticate while using group mapping feature (e.g., OIDC, LDAP) with Kong Manager, and also fix some issue with the group mapping feature.

Clustering

- Resilience support for homogeneous Dataplane deployments. Now Dataplanes can act as importer and exporter at the same time, and Kong will try to control the concurrency when export the config.

Plugin

- ldap-auth-advanced:

umerated encoded with redundant leading padding

lt consumer to be used when the client certificate is valid but does not match any existing consumers.

ether the `api_spec` is URI-Encoded.

E

C

s router flavor are now case sensitive. This change does not affect on `traditional_compatible` mode
the case.

y configured with vault reference may not get refreshed on time

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fix the missing router section for the output of the request-debugging
- fix vault initialization by postponing vault reference resolving on init_worker
- **Vault**: do not use incorrect (default) workspace identifier when retrieving vault entity by prefix
- Expressions route in `http` and `stream` subsystem now have stricter validation. Previously they share the same validation schema which means admin can configure expressions route using fields like `http.path` even for stream routes. This is no longer allowed.
- Fixed an rbac issue that required adding missing endpoints to all workspaces.
- fix a bug where workload identity does not work for dataplane resilience
- Fix a problem that a new DP cannot resolve the license required Vault reference after the first configuration push.
- Fix a bug that GCP backend vault hides the error message when secrets cannot be fetched
- Fix an issue where external pluginservers would not start automatically with Kong

Plugin

- acme:
  - Fixed an issue where the certificate was not successfully renewed during ACME renewal.
- degraphql:
  - Fixed an issue where GraphQL variables were not being correctly parsed and coerced into their defined types.
- jwt-signer:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- ldap-auth-advanced:
  - fix some cache-related issues which cause groups_required to not work properly and unexpected return codes after a non-200 response
  - fix an issue where if the credential is encoded with no username kong will throw an error and return 500
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- oas-validation:
  - Fixed an issue that the cookie parameters are not being validated.
- oauth2-introspection:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- openid-connect:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- opentelemetry:
  - fix otel sampling mode lua panic bug when http_response_header_for_traceid option enable
- rate-limiting-advanced:
  - Refactored `kong/tools/public/rate-limiting` to keep the original interfaces unchanged (backward compatibility) and extend a new interface `new_instance` to provide isolation between different plugins. If you are using custom Rate Limiting plugins based on this library, please update the initialization code to the new format like 'local ratelimiting = require("kong.tools.public.rate-limiting").new_instance("custom-plugin-name")'. The old
lease.
s using the `rate-limiting` library, when used together, would interfere with each other and thus fail to
redis goes down
n being executed instead of being created to reduce some meaningless error logs
value greater than `0` to `0`, the namespace will be cleared unexpectedly
cing timer can't be created or destroyed properly
ong.client.authenticate` function
the request body has already been read
d-connect` plugin as an encrypted and referenceable field
lator**, **XML Threat Protection**: priorities have been updated to prevent collisions between plugins. The relative priority (and the order of execution) of bundled plugins remained unchanged.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

PDK

- **PDK:** fix kong.request.get_forwarded_port to always return a number which was caused by an incorrectly stored string value in ngx.ctx.host_port.
- **OpenTelemetry**: Improved robustness of parsing for short trace IDs.

Configuration

- Fix an issue where an external plugin (Go, Javascript, or Python) would fail to apply a change to the plugin config via the Admin API.
- Set security level of gRPC's TLS to 0 when ssl_cipher_suite is set to old

Clustering

- Adjust clustering compatible check related to AWS Secrets Manager
- Adjust clustering compatible check related to HCV kube auth path
- Fixed a problem where event_hooks were prematurely validated in hybrid mode. The fix delays the validation of event_hooks to the point where event_hooks are emitted.
- reduce message push error log when cluster_telemetry_endpoint config is disabled

Admin API

- Fix an issue where HTTP 500 errors were returned when paginating and sorting by timestamp fields (e.g., `created_at`).
- disallow admins or RBAC users to update their own roles

Portal

- Implement relative URLs for portal root path redirection to prevent erroneous redirections to incorrect domains or protocols

Kong Manager

- Fixed an issue where the remaining days for the license expiration date was displayed inconsistently on the workspaces page and in the top tip.
- Fixed an issue where setting the Developer Portal configuration "Developer Meta Field" to contain characters outside the Latin1 range prevented admin from logging into Kong Manager.
- change the type of rbac token for the RBAC user to `password`
- Fixed an issue where admin account profile page returning 404 error if the `admin_gui_path` was not a slash.

Dependency

Core

- Bumped atc-router from 1.2.0 to 1.6.0
- Bump lua-protobuf to 0.5.1
- Bumped lua-resty-openssl to 1.2.1
- Bumped OpenSSL from 3.1.4 to 3.2.0

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ected input.

et#427.

P

C

memory allocation/deallocation

Configuration

- Bumped default values of `nginx_http_keepalive_requests` and `upstream_keepalive_max_requests` to `10000`.

Plugin

- opentelemetry:
  - increase queue max batch size to 200

3.5.0.3

Release date 2024/01/26

Breaking Change

Admin API

- The listing endpoints for consumer groups (`/consumer_groups`) and consumers (`/consumers`) now respond with paginated results. The JSON key for the list has been changed to `data` instead of `consumer_groups` or `consumers`.

Feature

Core

- Build deb packages for Debian 12. The debian variant of kong docker image is built using Debian 12 now.

Kong Manager

- added pagination support for nested consumer list and consumer group list.

Bugfix

Kong Manager

- fixed an issue where dynamic ordering dropdown list does not show custom plugins.
- fixed an issue targets page shows 404 if the workspace is non-default.
- fixed an issue where the role of the current workspace can't be created by `workspace-super-admin`.

Dependency

Core

- Bump kong-redis-cluster to '1.5.3'

3.5.0.2

Release date 2023/12/21

Breaking Change

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

orrect the integration between the SAML plugin and other consumer-based plugins

ed to `off`

ion from headers

_uri, `logout_redirect_uri` can now be referenced as a secret in the Kong Vault

Bugfix

Core

- fix ldoc intermittent failure caused by LuaJIT error.
- Dismiss confusing debug log from Redis tool of rate limiting #7077 #7101
- fix the missing workspace_id in the output of request debugging when using the filter
- Eliminate asynchronous timer in syncQuery() to prevent hang risk
- Fixed critical level logs when starting external plugin servers. Those logs cannot be suppressed due to the limitation of OpenResty. We choose to remove the socket availibilty detection feature.

Plugin

- forward-proxy:
  - Fixed the issue where request payload is being discarded when payload exceeded the `client_body_buffer_size`.
- mocking:
  - Fix an issue where valid recursive schemas are always rejected.
- oas-validation:
  - Fixed an issue that the plugin throws a runtime error while validating parameters with AnyType schema and style keyword defined.
  - Fixed an issue that the nullable keyword did not take effect.
  - Fixed an issue that the URI component escaped characters were incorrectly unescaped.
- openid-connect:
  - Fix logout uri suffix detection by using normalized version of `kong.request.get_forwarded_path()` instead of `ngx.var.request_uri` (especially when passing query strings to logout)
  - update time when calculating token expire
- rate-limiting:
  - fix an issuer where all counters are synced to the same DB at the same rate.
- oas-validation Fix a bug where the plugin throws a runtime error caused by the ref parameter schema not being dereferenced.
- Mark the `authorization_value` in the `oauth2-introspection` plugin as an encrypted field
- Fix typo in jwe-decrypt error message

Configuration

- respect custom `proxy_access_log`

Clustering

- Fix an issue where the dataplane's log serializer output has workspace name under Hybrid mode

P

new plugin instance to be created

A

while trying to update the user_token with the same value on the same RBAC user.

D

C

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Configuration

- Bump `dns_stale_ttl` default to 1 hour so stale DNS record can be used for longer time in case of resolver downtime.

3.5.0.1

Release date 2023/11/14

Bugfix

Kong Manager

- Fix the issue where some values in config cards were not displayed correctly.

3.5.0.0

Release date 2023/11/08

Breaking Change

Plugin

- graphql-rate-limiting-advanced:
  - Fix a bug in the schema validation which prevents from using redis in cluster mode
- session:
  - a new configuration field `read_body_for_logout` was added with a default value of `false`, that changes behavior of `logout_post_arg` in a way that it is not anymore considered if the `read_body_for_logout` is not explicitly set to `true`. This is to avoid session plugin from reading request bodies by default on e.g. `POST` request for logout detection.

Deprecation

Configuration

- Removed support for Developer Portal and Vitals, which were deprecated in Kong 3.4.

Feature

Plugin

- cors:
  - Support the `Access-Control-Request-Private-Network` header in crossing-origin pre-light requests
- mocking:
  - Introduces a new property `include_base_path` to indicate whether to include the base path when performing the path match evaluation.
- oas-validation:
  - Introduces a new property `include_base_path` to indicate whether to include the base path when performing the path match evaluation.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

h when set to true, we destory the session (delete the user's session cookie) when the request is
ve the session.

, the plugin instance will not discover configuration from the issuer.

e, which allows Kong to inject datadog headers into the headers of requests forwarding to upstream.

n

hrown when the administrator login successfully and then retrieves the session

of token for introspection and revocation with `introspection_token_param_name` and
`revocation_token_param_name` respectively.

Core

- Add a new endpoint `/schemas/vaults/:name` to retrieve the schema of a vault.
- rename `privileged_agent` to `dedicated_config_processing. Enable` dedicated_config_processing` by default
- Support observing the time consumed by some components in the given request.
- Plugins can now implement `Plugin:configure(configs)` function that is called whenever there is a change in plugin entities. An array of current plugin configurations is passed to the function, or `nil` in case there is no active configurations for the plugin.
- Add a request-aware table able to detect accesses from different requests.
- A unique Request ID is now populated in the error log, access log, error templates, log serializer, and in a new X-Kong-Request-Id header (configurable for upstream/downstream using the `headers` and `headers_upstream` configuration options).
- Add support for optional Wasm filter configuration schemas
- Support JSON in Wasm filter configuration
- aws vault backend use credential provider chain and support role assuming
- Allow OSS features to continue working with an expired license and configured Kong Enterprise features to continue operating in read-only mode. Kong Gateway now logs a daily critical message when a license is expired and within the 30 days grace period.
- Add troubleshooting tool
- add analytics_debug option to output requests to logs.
- **OpenID Connect:** Added support for mTLS proof of possession. The feature is available by enabling `proof_of_possession_mtls`

Clustering

- **Clustering**: Allow configuring DP metadata labels for on-premise CP Gateway
- Add cluster_fallback_export_s3_config option to config s3 config backup `putObject` request

PDK

- add support for Azure's KeyVault Secrets Engine.

CLI Command

- New kong command `kong debug COMMAND [OPTIONS]`
- Add troubleshooting lua scripts

Admin API

- Add counters such as routes, plugins, licenses, deployment info, etc. to the report component. Also, add a checksum and timestamp to the output.
- Support for workspace search by name.

Bugfix

PDK

e:

ving Vault references fail

uest
ntations
g them
planes

guration has changed

et_raw_body()` is called multiple times in a request lifecycle.

end before their children due to different precision of their timestamps

the kong.log.serialize function.

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fix an issue that the TTL of the key-auth plugin didnt work in DB-less and Hybrid mode.
- Fix a problem that abnormal socket connection will be reused when querying Postgres database.
- Fix upstream ssl failure when plugins use response handler
- Fix an issue that protocol `tls_passthrough` can not work with expressions flavor
- fix the building failure when applying patches
- Vault references can be used in Dbless mode in declarative config
- Properly warmup Vault caches on init
- Vault resurrect time is respected in case a vault secret is deleted from a vault
- update vitals prometheus grafana dashboard
- Fix a keyring issue where a kong node fails to send keyring material when using cluster strategy
- Fix a bug that will cause a failure of sending tracing data to datadog when value of x-datadog-parent-id header in requests is a short dec string
- Enforce Content Security Policy (CSP) headers while serving static resources via Dev Portal and Kong Manager
- fix rbac retrieve group roles with the group name that type is number.
- Allow to specify azure_vault config options in the `kong.conf` file.
- Correctly invalidate caches based on names and ids for Consumer Groups
- Apply Nginx patch for detecting HTTP/2 stream reset attacks early (CVE-2023-44487)
- Hardcode part settings of `admin_gui_auth_conf` while `admin_gui_auth` is `openid-connect`

Plugin

- aws-lambda:
  - let plugin-level proxy take effect on EKS IRSA credential provider
- mocking:
  - Fix the issue that path parameter cannot match non-ascii characters.
- oas-validation:
  - Fix an issue where a null pointer exception may occur in some scenarios when configuration notify_only_request_validation_failure is true
  - Fix the issue that path parameter cannot match non-ascii characters.
  - Fix an issue where valid recursive schemas are always rejected.
- openid-connect:
  - Fix issue on token revocation on logout where the code was revoking refresh token when it was supposed to revoke access token when using the discovered revocation endpoint.
  - Fix the issue where `using_pseudo_issuer` does not work.
- opentelemetry:
  - fix an issue that resulted in invalid parent IDs in the propagated tracing headers

nt IDs when `balancer` instrumentation was enabled

gured, users now receive a 500 error instead of being redirected endlessly

es to ‘info’

g TLS connection

elated fields

g revocation check

Admin API

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- oas-validation Fix an issue where non `application/json` content-types are being rejected even though the request body is not required.
- Require a license to use Dynamic Plugin Ordering

Configuration

- The default value of `dns_no_sync` option has been changed to `on`
- Fix an issue that remove FIPS from free mode. Add a check of FIPS state and license type in validate_fips. If no license with FIPS `on` will throw an error and exit.
- lazily enable FIPS mode after a valid license is received and only emit a warning instead of blocking Kong to start.

Admin API

- Fix a bug that when an entity is deleted, the rbac_role_entities records of its cascaded entities are not deleted.
- Fix an issue that made it possible to create colliding routes in different workspaces when using `application/x-www-form-urlencoded` as content type in the admin API
- optimize the performance of querying plugins when access application_services/application_instances endpoint.
- Fix an issue where users cannot completely delete a developer by email via Admin API.

Portal

- sanitize developer name in portal email
- Support boolean token in portal email template and fix 500 error

Clustering

- Fix an issue where the dataplane hostname is `nil` in Vitals under Hybrid mode

Kong Manager

- Fix an issue where the input fields for cert_alt and key_alt in the certificate form do not accept multi-line content.
- Fix an issue that Kong Manager ‘Invite Admin’ button missing on Teams page if no admin created on DB initialization with RBAC disabled

Dependency

Core

- Bumped lua-resty-healthcheck from 1.6.2 to 1.6.3
- Bumped OpenResty from 1.21.4.1 to 1.21.4.2
- Bumped resty.openssl from 0.8.23 to 0.8.25
- Bumped lua-resty-aws from 1.3.1 to 1.3.2
- Bumped lua-resty-aws from 1.3.2 to 1.3.5
- Fix incorrect LuaJIT register allocation for IR_*LOAD on ARM64
- Fix LDP/STP fusing for unaligned accesses on ARM64

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

C

P

gin from 2.5.5 to 2.5.7.

Performance

Core

- refactor workspace id and name retrieval
- workspaces.get_workspace() now tries to get workspace from cache instead of querying database directly

Configuration

- Bumped the default value of `upstream_keepalive_pool_size` to `512` and `upstream_keepalive_max_requests` to `1000`

Plugin

- rate-limiting-advanced to use the new Plugin:configure for building namespaces without looping through all the plugins

3.4.3.29

Release date 2026/08/10

Bugfix

Core

- Applied upstream nginx security patches for CVE-2026-42533.
- Applied upstream nginx security patches for CVE-2026-56434.
- Applied upstream nginx security patches for CVE-2026-60005.
- Applied upstream nginx security patches for CVE-2026-42055 and CVE-2026-48142.

Plugin

- saml:
  - Security: Fixed CVE-2026-14917 in the SAML plugin by always validating the `samlp:Response` signature when `idp_certificate` is configured correctly (and logging a warning if misconfigured), preventing a crafted unsigned SAML response from silently bypassing authentication under configurations that set `validate_assertion_signature` to false.

Dependency

Core

- Bumped jq from 1.8.1 to 1.8.2.
- Bumped OpenSSL from 3.5.6 to 3.5.7.

3.4.3.28

Release date 2026/06/11

Bugfix

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

maximum number of headers (CVE-2026-49975).

0701, CVE-2026-42934, CVE-2026-42946, CVE-2026-42945, and CVE-2026-9256.

ader handling by preserving inbound `Content-Length` headers during hop-by-hop Connection header `Connection: Content-Length` headers on requests with a body.

Core

- Bumped libexpat from 2.7.3 to 2.8.1 to address the issues: CVE-2026-25210, CVE-2026-24515, CVE-2026-32778, CVE-2026-32777, CVE-2026-32776, CVE-2026-41080, and CVE-2026-45186.
- Bumped OpenSSL from 3.5.5 to 3.5.6 to address the issues: CVE-2026-31790, CVE-2026-2673, CVE-2026-28387, CVE-2026-28388, CVE-2026-28389, CVE-2026-28390, and CVE-2026-31789.

3.4.3.26

Release date 2026/05/11

Bugfix

Core

- Fixed an issue where the real client IP from Proxy Protocol was not correctly reflected in access logs and logging plugins when nginx rejected requests early (497 plain HTTP to HTTPS port) or when the client disconnected prematurely during header parsing. Added an nginx patch to resolve `$remote_addr` from `$proxy_protocol_addr` on early request termination, and added `error_page` 497 routing through `kong_error_handler`.

Plugin

- request-validator:
  - Added `array_length_compat` config option to allow legacy Draft 4 schemas to use `minLength`/`maxLength` keywords for array length validation.

Kong Manager

- Fixed workspace list and routing not working correctly when workspace count exceeds 1000.

Dependency

Core

- Bumped kong-lua-resty-ljsonschema from 1.2.0 to 1.3.3.
- Bumped lua-resty-healthcheck from 3.1.1 to 3.1.2.

3.4.3.25

Release date 2026/04/09

Bugfix

Core

- Fixed an issue where `$remote_addr` was not replaced with the proxy protocol source address for early nginx error responses (501, 505) when `proxy_protocol` is enabled on the proxy listener. Also added proper error body messages for 501 and 505 status codes.
- **vault**: Fixed an issue where `kong.vault.update()` changed the secret to an empty string temporarily after changing a vault config.

Plugin

anced plugin's API threw 500 errors when handling HTTP PUT requests.

be forwarded to upstream services when the corresponding JWT claim was missing from the token. The `upstream_headers_names`, ensuring that only verified JWT claim values are sent to upstream or

K

ining non-ASCII characters.

P

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Removed issuer discovery from schema to improve performance upon plugin initialization or updating. The issuer discovery will only be triggerd by client requests.

3.4.3.24

Release date 2026/03/11

Bugfix

Core

- Apply Nginx patch for a man-in-the-middle upstream response injection (CVE-2026-1642)

Dependency

Core

- Bumped OpenSSL from 3.2.1 to 3.5.5 to address the issue: CVE-2025-15467.

3.4.3.23

Release date 2026/01/07

Bugfix

Plugin

- kafka-upstream:
  - Fixed issue where Kafka producer cached TLS certificates, causing failures when certificates were updated. Now, the plugin properly reloads updated certificates.
- opentelemetry:
  - Fixed an issue where the instrumentation started unexpectedly on control planes of hybird mode.

Dependency

Core

- Bumped lua-resty-healthcheck to version 3.1.1 to remove incorrect deprecation notice on active healthchecks headers.

Performance

Core

- **core**: Improved performance of deleting expired rows for Postgres versions below 12.

3.4.3.22

Release date 2025/11/24

B

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

tion multiple times and failed to stop nginx.

C

y occur during reconfiguration.

P

thorization_code auth would not auto-recover if IdP was not accessible during Kong startup.

inx gzip was enabled for upstream.

- openid-connect Updated the rediscovery to use a short lifetime (5s) if the last discovery failed.

Clustering

- Fixed an issue where the data plane did not stop the health checker before cleaning up old configurations, which could lead to resource leaks.

Dependency

Core

- Bumped libexpat from 2.7.1 to 2.7.3.
- Bumped lua-resty-ljsonschema to 1.2.0. Fixed UTF-8 string length calculation and added support for `null` in `enum` types.

Performance

Core

- Improved the performance of retrieving workspace entity counts.

3.4.3.21

Release date 2025/09/05

Bugfix

Core

- Fixed a bug where the health checker could fail to initialize in rare cases.
- Fixed an issue where running Kong CLI commands with database configurations containing Hashicorp Vault references would fail to execute.
- **kafka**: Fixed an issue where the Kafka SCRAM authentication did not send the server nonce.
- Fixed an issue where the Lua VM memory size returned by status API is not accurate on the control plane.
- fixed an issue where utils.random_string() returned multiple values

Plugin

- ldap-auth-advanced:
  - Fixed an issue where an empty sequence or set represented in long form length couldn't be decoded.
- mocking:
  - Fixed an issue where an empty array set in the mocking plugin schema with object type. It should return an array type instead of an object type in the response body.
- oauth2-introspection:
  - Fixed an issue where authentication failures did not log messages in the error logs.

Kong Manager

en editing basic-auth credentials, now allows empty passwords.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- openid-connect:
  - Fixed an `500` error caused by receiving a JSON `null` from the request body when parsing bearer tokens or client IDs.

Dependency

Core

- Bumped luarocks from 3.11.1 to 3.12.1. This fixes the error `main function has more than 65536 constants`, which was preventing rocks from being published or installed.

3.4.3.19

Release date 2025/06/10

Bugfix

Configuration

- Fixed an issue where `debug_listen` incorrectly used the SSL-related configuration of `status_listen`.

Core

- Added a new configuration, `route_match_calculation`, which included bug fixes for the `traditional_compatible` router flavor. The default value `original` retained the current `3.x` router matching behavior without changes. The value `strict` enforced the router matching behavior with corrected calculation as follows:
  1. The weight (priority point) of a route was incorrectly downgraded.
  2. A route of HTTPS-only protocol with SNIs incorrectly captured requests over HTTP routes.
  3. A route of TLS-only protocol with SNIs incorrectly captured requests over TCP or UDP routes.

3.4.3.18

Release date 2025/04/29

Feature

PDK

- Added a new `kong.request.get_raw_forwarded_path()` function for returning a non-normalized `forwarded_path`.

Bugfix

Core

- Fixed an issue where the detail page failed to render when a certificate or CA certificate was configured with a Vault reference.
- **Clustering** : You can now configure Data Plane metadata labels for a self-managed Gateway Control Plane.

Plugin

- openid-connect:
  - Fixed an issue which caused IdPs to report invalid `redirect_uri` errors when `config.redirect_uri` was not configured and the URI path contained spaces.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

`ash_subject` (default `false`) and `store_metadata` (default `false`) stored the session's metadata in the
al, where adding these fields to `portal_session_conf` wasn't working as expected.

D

C

e worker process crash caused by a segmentation fault.

3

R

F

Plugin

- session:
  - Added two boolean configuration fields `hash_subject` (default `false`) and `store_metadata` (default `false`) to store session's metadata in the database.

Core

- Added an option for GitHub Actions to build nginx/OpenResty with debug symbols.
- Added a new feature to invalidate the admin's or the developer's related session while changing the password.

Bugfix

Plugin

- app-dynamics:
  - Fixed segmentation fault caused by missing destructor call on process exit.
- ldap-auth-advanced:
  - Fixed an issue where binary string was truncated at the first null character.

Core

- **Vault**: Updated the AWS Vault supported regions list to the latest.

Dependency

Core

- Bumped libexpat from 2.6.2 to 2.6.4 to fix a crash in the XML_ResumeParser function caused by XML_StopParser stopping an uninitialized parser.
- Bumped lua-resty-events to 0.3.0
- Bumped lua-resty-healthcheck to 3.1.0

3.4.3.16

Release date 2025/01/16

Dependency

Core

- Bumped libxml2 to 2.11.9 for CVE-2024-40896

3.4.3.15

Release date 2025/01/10

Bugfix

Core

reference may not get refreshed on time when initial with an invalid string.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

n the plugin config in the plugins iterator.

- fix vault initialization by postponing vault reference resolving on init_worker
- Fixed an issue where using Hashicorp Vault AppRole authentication with a secret ID file would fail to read the secret ID.

Plugin

- graphql-rate-limiting-advanced:
  - Fixed an issue where the plugin may fail to authenticate to Redis correctly with vault-referenced redis configuration.
- mtls-auth:
  - Fixed an issue where a 500 error occurs when the configuration changes with the mTLS plugin enabled.
- rate-limiting-advanced:
  - Fixed an issue where counters of the overriding consumer groups didn't fetched when the window_size is different and the workspace is non-default.
  - Fixed an issue where multiple plugin instances sharing the same namespace enforced consumer groups and different `window_sizes` were used in the consumer group overriding configs, then the rate limiting of some consumer groups would fall back to local strategy. Now every plugin instance sharing the same namespace can set different `window_size`.
  - Fixed an issue where the plugin may fail to authenticate to Redis correctly with vault-referenced redis configuration.
  - Fixed an issue where RLA stores long expiration time items cause `no memory` errors.

3.4.3.13

Release date 2024/11/15

Feature

Plugin

- aws-lambda:
  - Added support for a configurable STS endpoint with the new configuration field `aws_sts_endpoint_url`.
- rate-limiting-advanced:
  - Enhance the resolution of RLA sliding window weight

Core

- Added support for AWS IAM role assuming in AWS IAM Database Authentication, with new configuration fields: "pg_iam_auth_assume_role_arn", "pg_iam_auth_role_session_name", "pg_ro_iam_auth_assume_role_arn", and "pg_ro_iam_auth_role_session_name."
- Added support for a configurable STS endpoint for RDS IAM Authentication, with new configuration fields: `pg_iam_auth_sts_endpoint_url` and `pg_ro_iam_auth_sts_endpoint_url`.
- Added support for a configurable STS endpoint for AWS Vault. This can either be configured by `vault_aws_sts_endpoint_url` as a global configuration, or `sts_endpoint_url` on a custom AWS vault entity.

Bugfix

Core

during `resurrect_ttl` time and could not be fetched by other workers.

of the Kong prefix.

ling the socket name limit.

/usr/local/bin.

e of rate-limiting related headers are not integer

when the underlying AWS credential expired.

P

a concatenation error.

ing due to race condition.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Dependency

Core

- Bumped `LPEG` from `1.0.2` to `1.1.0` to keep the version consistent accross all active branches. The version bump includes fixes like UTF-8 ranges, Larger limit for rules and matches, accumulator capture, etc.
- Bumped lua-resty-aws to 1.5.3 to fix a bug related to STS regional endpoint.
- Bumped lua-resty-azure to 1.6.1 to fix a GET request build issue
- Made the RPM package relocatable with the default prefix set to `/`.

3.4.3.12

Release date 2024/08/08

Feature

Core

- Backported image signing and provenance generation to 3.4.

Bugfix

Core

- The kong.logrotate configuration file will no longer be overwritten during upgrade. This change will present an additional prompt for debian users upgrading via apt and .deb packages. To accept the defaults provided by Kong in the package use the following command `DEBIAN_FRONTEND=noninteractive apt upgrade kong-enterprise-edition_3.4.3.11_arm64.deb` depending on your architecture and the version upgrading to.
- Fixed a bug where a new data plane couldn't resolve a Vault reference after the first configuration push. This was happening due to issues with license pre-loading.

Plugin

- ldap-auth-advanced:
  - Fixed an issue where an exception will be thrown when ldap search fails
- rate-limiting-advanced:
  - Fixed an issue where if the `window_size` in the consumer group overriding config is different from the `window_size` in the default config, the rate limiting of that consumer group would fall back to local strategy.

Dependency

Core

- Made the RPM package relocatable.

3.4.3.11

Release date 2024/06/22

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Core

- Bumped lua-resty-events to 0.2.1

3.4.3.9

Release date 2024/06/08

Feature

Admin API

- Add LHS brackets filtering to search fields
- **Audit Log:** Add request_timestamp to audit_objects.
- **Audit Log**: Add before / after aliases for LHS Brackets filters.
- **Audit Log:** Allow audit_requests and audit_objects to be filtered by request_timestamp.

Bugfix

Core

- Fixed an issue where cluster_cert or cluster_ca_cert is inserted into lua_ssl_trusted_certificate before being base64 decoded.
- fix a bug that the `host_header` attribute of upstream entity can not be set correctly in requests to upstream as Host header when retries to upstream happen.
- Built-in RBAC roles for admins (`admin` under the default workspace and `workspace-admin` under non-default workspaces) now disallow CRUD actions to `/groups` and `/groups/*` endpoints.
- **Vitals**: Fixed a bug that each data plane connecting to the control plane would trigger the control plane to create a redundant table rotater timer.

Admin API

- The workspace listing API only shows workspaces that the current user has endpoints associated with

Plugin

- openid-connect:
  - Fixed a bug where anonymous consumers may be cached as nil under a certain condition.

Dependency

Core

- Bumped lua-resty-azure from 1.4.1 to 1.5.0, to refine some error logging.
- Bumped lua-resty-healthcheck from 1.6.4 to 1.6.5, to reduce active healthcheck timer usage.

Performance

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

is network instability with the central data store.

3

R

P

A

sorted by request_timestamp descending

P

A

- Fix an issue where HTTP 500 errors were returned when paginating and sorting by timestamp fields (e.g., `created_at`).

Plugin

- rate-limiting-advanced:
  - Refactored `kong/tools/public/rate-limiting` to keep the original interfaces unchanged (backward compatibility) and extend a new interface `new_instance` to provide isolation between different plugins. If you are using custom Rate Limiting plugins based on this library, please update the initialization code to the new format like 'local ratelimiting = require("kong.tools.public.rate-limiting").new_instance("custom-plugin-name")'. The old interface will be removed in the upcoming major release.
- oas-validation, **WebSocket Size Limit**, **WebSocket Validator**, **XML Threat Protection**: priorities have been updated to prevent collisions between plugins. The relative priority (and the order of execution) of bundled plugins remained unchanged.

Dependency

Core

- Improve the robustness of lua-cjson when handling unexpected input.
- Bumped `kong-lua-resty-kafka` to `0.19` for supporting TCP socket keepalive.

3.4.3.7

Release date 2024/04/23

Bugfix

PDK

- **PDK:** fix kong.request.get_forwarded_port to always return a number which was caused by an incorrectly stored string value in ngx.ctx.host_port.

Core

- Fixed a problem that in hybrid DP mode a certificate entity configured with vault reference may not get refreshed on time

Clustering

- Fix an issue that delay validate of event_hooks to avoid unregistered event_hooks in hybrid mode

Dependency

Core

- Bump lua-protobuf to 0.5.1

3.4.3.6

Release date 2024/04/15

Feature

P

ether the `api_spec` is URI-Encoded.

K

E

P

sfully renewed during ACME renewal.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue where GraphQL variables were not being correctly parsed and coerced into their defined types.

- rate-limiting-advanced:
  - Fixed an issue where RLA and other similar plugins using the `rate-limiting` library, when used together, would interfere with each other and thus fail to synchronize counter data to the central data store

Configuration

- Fix an issue where an external plugin (Go, Javascript, or Python) would fail to apply a change to the plugin config via the Admin API.

PDK

- **OpenTelemetry**: Improved robustness of parsing for short trace IDs.

Kong Manager

- Fixed an issue where logging in fails when the Developer Portal configuration “Developer Meta Field” contains characters outside the Latin1 range.
- Fixed an issue where admin account profile page returns 404 error if `admin_gui_path` is not a slash.

Dependency

Core

- Bumped lua-kong-nginx-module to 0.8.1
- Bump `lua-resty-luasocket` to `1.1.2` for fixing luasocket#427.

3.4.3.5

Release date 2024/03/21

Breaking Change

Core

- In OpenSSL 3.2, the default SSL/TLS security level has been changed from 1 to 2. Which means security level set to 112 bits of security. As a result RSA, DSA and DH keys shorter than 2048 bits and ECC keys shorter than 224 bits are prohibited. In addition to the level 1 exclusions any cipher suite using RC4 is also prohibited. SSL version 3 is also not allowed. Compression is disabled.

Feature

Core

- Add a new endpoint `/schemas/vaults/:name` to retrieve the schema of a vault.
- The expressions route now supports the `!` (not) operator, which allows creating routes like `!(http.path =^ "/a")` and `!(http.path == "/a" || http.path == "/b")`
- Support observing the time consumed by some components in the given request.
- Plugins can now implement `Plugin:configure(configs)` function that is called whenever there is a change in plugin entities. An array of current plugin configurations is passed to the function, or `nil` in case there is no active configurations for the plugin.

ents.* fields in the expressions router which allows matching incoming (normalized) request path by the total number of segments.

le in HTTP routes defined using expressions.

ort role assuming

thentication method

license and configured Kong Enterprise features to continue operating in read-only mode. Kong Gateway d and within the 30 days grace period.

up mapping feature (e.g., OIDC, LDAP) with Kong Manager, and also fix some issue with the group

L 3.x

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- add support for Azure's KeyVault Secrets Engine.

Plugin

- cors:
  - Support the `Access-Control-Request-Private-Network` header in crossing-origin pre-light requests
- mtls-auth:
  - Add `default_consumer` option that allows a default consumer to be used when the client certificate is valid but does not match any existing consumers.

Bugfix

Core

- Header value matching (`http.headers.*`) in `expressions` router flavor are now case sensitive. This change does not affect on `traditional_compatible` mode where header value match are always performed ignoring the case.
- update file permission of kong.logrotate to 644
- **Vault**: do not use incorrect (default) workspace identifier when retrieving vault entity by prefix
- Expressions route in `http` and `stream` subsystem now have stricter validation. Previously they share the same validation schema which means admin can configure expressions route using fields like `http.path` even for stream routes. This is no longer allowed.
- Allow to specify azure_vault config options in the `kong.conf` file.

Plugin

- forward-proxy:
  - fallback to the non-streaming proxy when the request body has already been read
- jwt-signer:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- ldap-auth-advanced:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- oauth2-introspection:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- openid-connect:
  - support for consumer group scoping by using pdk `kong.client.authenticate` function
- opentelemetry:
  - fix otel sampling mode lua panic bug when http_response_header_for_traceid option enable
- rate-limiting-advanced:
  - Falling back to local strategy if sync_rate = 0 when redis goes down
  - The plugin now creates counter syncing timers when being executed instead of being created to reduce some meaningless error logs

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

value greater than `0` to `0`, the namespace will be cleared unexpectedly

cing timer can't be created or destroyed properly

ong.client.authenticate` function

d-connect` plugin as an encrypted and referenceable field

C

ite is set to old

C

dpoint config is disabled

A

- Fix a bug that when an entity is deleted, the rbac_role_entities records of its cascaded entities are not deleted.

Kong Manager

- fixed the display of the remaining days of license expireation date
- Conceal the user token input field while editing an RBAC user.

Dependency

Core

- Bumped atc-router from 1.2.0 to 1.6.0
- Bumped lua-resty-openssl to 1.2.1
- Bump `kong-lua-resty-kafka` to `0.18`.

Performance

Core

- Reuse match context between requests to avoid frequent memory allocation/deallocation

Configuration

- Bumped default values of `nginx_http_keepalive_requests` and `upstream_keepalive_max_requests` to `10000`.

Plugin

- opentelemetry:
  - increase queue max batch size to 200

3.4.3.4

Release date 2024/02/10

Feature

Clustering

- Resilience support for homogeneous Dataplane deployments. Now Dataplanes can act as importer and exporter at the same time, and Kong will try to control the concurrency when export the config.

Core

- Adds support for namespaced authentication and user defined auth path when using HCV vault on Kubernetes.

Bugfix

Configuration

declarative_config_flattened function

C

plane resilience

when secrets cannot be fetched

ttp.status_code when the request was not proxied to an upstream.

P

required to not work properly and unexpected return codes after a non-200 response

no username kong will throw an error and return 500

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Dependency

Core

- Bumped OpenSSL from 3.1.4 to 3.2.1
- Bump resty-openssl from 0.8.25 to 1.2.0
- bump lua-resty-aws to 1.3.6

3.4.3.3

Release date 2024/01/17

Feature

Admin API

- add gateway edition to the root endpoint of the admin api

Core

- Build deb packages for Debian 12. The debian variant of kong docker image is built using Debian 12 now.

Plugin

- Add CONTROLLER_CERTIFICATE_FILE and CONTROLLER_CERTIFICATE_DIR env config for AppDynamics plugin to use self-signed certificate

Bugfix

Core

- Fixed an rbac issue that required adding missing endpoints to all workspaces.

Plugin

- oas-validation:
  - Fixed an issue that the cookie parameters are not being validated.

Portal

- Implement relative URLs for portal root path redirection to prevent erroneous redirections to incorrect domains or protocols

Admin API

- disallow admins or RBAC users to update their own roles

Kong Manager

- fixed an issue dynamic ordering dropdown list does not show custom plugins.

reated by the role `workspace-super-admin`'s admin.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- ldap-auth-advanced:

- support decoding non-standard asn1 integer and enumerated encoded with redundant leading padding

Bugfix

Admin API

- Optimize the performance of querying plugins when accessing the application_services/application_instances endpoints.

Kong Manager

- Fix an issue where clicking the spec upload input doesn't trigger file selection.
- Fix an issue where some services are missing from the Dev Portal's application list in Kong Manager.

3.4.3.1

Release date 2023/12/15

Breaking Change

Plugin

- saml:
  - adjust the priority of the SAML plugin to 1010 to correct the integration between the SAML plugin and other consumer-based plugins

Feature

Plugin

- openid-connect:
  - configurations `scopes`, `login_redirect_uri`, `logout_redirect_uri` can now be referenced as a secret in the Kong Vault
  - extend `token_post_args_client` to support injection from headers
- the AWS-Lambda plugin has been refactored by using `lua-resty-aws` as an underlying AWS library. The refactor simplifies the AWS-Lambda plugin code base and adding support for multiple IAM authenticating scenarios.
- Fix when the Dev portal OIDC is enabled, a 500 error is thrown when the administrator login successfully and then retrieves the session

Core

- A unique Request ID is now populated in the error log, access log, error templates, log serializer, and in a new X-Kong-Request-Id header (configurable for upstream/downstream using the `headers` and `headers_upstream` configuration options).

CLI Command

- Add troubleshooting lua scripts

Configuration

- The default value of `dns_no_sync` option has been changed to `off`

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

dential provider

arded when payload exceeded the `client_body_buffer_size`.

-ascii characters.

caused by the ref parameter schema not being dereferenced.

- Fix an issue where valid recursive schemas are always rejected.

  - Fixed an issue that the plugin throws a runtime error while validating parameters with AnyType schema and style keyword defined.
  - Fixed an issue that the nullable keyword did not take effect.
  - Fixed an issue that the URI component escaped characters were incorrectly unescaped.
  - Fix the issue that path parameter cannot match non-ascii characters.
- openid-connect:
  - update time when calculating token expire
- rate-limiting:
  - fix an issuer where all counters are synced to the same DB at the same rate.
- tcp-log:
  - fix an issue of unnecessary handshakes when reusing TLS connection
- Cache the AWS lambda service by those lambda service related fields
- Mark the `authorization_value` in the `oauth2-introspection` plugin as an encrypted field
- Fix typo in jwe-decrypt error message

PDK

- Fix a bug related to data interference between requests in the kong.log.serialize function.
- **Plugin Server**: fix an issue where every request causes a new plugin instance to be created

Core

- print error message correctly when plugin fails
- fix ldoc intermittent failure caused by LuaJIT error.
- Fix Vault's try function to avoid using semaphore in non-yieldable phases.
- Vault references can be used in Dbless mode in declarative config
- Correctly invalidate caches based on names and ids for Consumer Groups
- Eliminate asynchronous timer in syncQuery() to prevent hang risk
- Fixed critical level logs when starting external plugin servers. Those logs cannot be suppressed due to the limitation of OpenResty. We choose to remove the socket availibilty detection feature.

Configuration

- respect custom `proxy_access_log`

Clustering

- Fix an issue where the dataplane's log serializer output has workspace name under Hybrid mode
- Fix an issue where the dataplane hostname is `nil` in Vitals under Hybrid mode

A

while trying to update the user_token with the same value on the same RBAC user.

K

r services under non-default workspaces.

ewer version.

D

C

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bump lua-resty-healthcheck from 1.6.2 to 1.6.3
- Bumped lua-resty-aws from 1.2.3 to 1.3.0
- Bumped lua-resty-aws from 1.3.2 to 1.3.5
- Bump lua-kong-nginx-module from 0.6.0 to 0.8.0
- bump jq to 1.7
- bump luasec to 1.3.2

CLI Command

- Backport troubleshooting tools to 3.4
- Update included curl to 8.4.0 & nghttp2 1.57.0

Performance

Configuration

- Bump `dns_stale_ttl` default to 1 hour so stale DNS record can be used for longer time in case of resolver downtime.

3.4.2.0

Release date 2023/11/10

Feature

Admin API

- Add counters such as routes, plugins, licenses, deployment info, etc. to the report component. Also, add a checksum and timestamp to the output.

Bugfix

Core

- Apply Nginx patch for detecting HTTP/2 stream reset attacks early (CVE-2023-44487)

Plugin

- openid-connect:
  - Fix the issue where `using_pseudo_issuer` does not work.
- opentelemetry:
  - fix an issue that resulted in traces with invalid parent IDs when `balancer` instrumentation was enabled

Configuration

- The default value of `dns_no_sync` option has been changed to `on`

K

the exact name or ID under certain circumstances while configuring a route.

D

C

3

R

B

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Plugin

- saml:
  - Reduce severity of ‘session was not found’ messages to ‘info’

Core

- Apply Nginx patch for detecting HTTP/2 stream reset attacks early (CVE-2023-44487)

Dependency

Core

- bump libxml2 from 2.10.3 to 2.11.5

3.4.1.0

Release date 2023/09/28

Breaking Change

Plugin

- graphql-rate-limiting-advanced:
  - Fix a bug in the schema validation which prevents from using redis in cluster mode

Feature

Core

- Support HTTP query parameters in expression routes.

Plugin

- openid-connect:
  - New field `unauthorized_destroy_session`, which when set to true, we destory the session (delete the user’s session cookie) when the request is unauthorized. Default to true. Set to false to preserve the session.
  - New field `using_pseudo_issuer`. When set to true, the plugin instance will not discover configuration from the issuer.
- opentelemetry:
  - A new value is added to the parameter `header_type`, which allows Kong to inject datadog headers into the headers of requests forwarding to upstream.

Bugfix

PDK

- Fix several issues in Vault and refactor the Vault code base:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Re-enable negative caching
  - Reimplement the kong.vault.try function
  - Remove references from rotation in case their configuration has changed

- Tracing: fix an issue that resulted in some parent spans to end before their children due to different precision of their timestamps

Plugin

- openid-connect:
  - Fix issue on token revocation on logout where the code was revoking refresh token when it was supposed to revoke access token when using the discovered revocation endpoint.
- opentelemetry:
  - fix an issue that resulted in invalid parent IDs in the propagated tracing headers
  - fix an issue that resulted in invalid parent IDs in the propagated tracing headers
- saml:
  - When the redis session storage is incorrectly configured, users now receive a 500 error instead of being redirected endlessly
- mtls-auth should not cache the network failure when doing revocation check
- allow the ‘start’ field be a past time

Core

- Fix a problem that abnormal socket connection will be reused when querying Postgres database.
- Fix upstream ssl failure when plugins use response handler
- Fix an issue that protocol `tls_passthrough` can not work with expressions flavor
- Fix an issue that the TTL of the key-auth plugin didnt work in DB-less and Hybrid mode.
- Fix a problem that abnormal socket connection will be reused when querying Postgres database.
- Fix upstream ssl failure when plugins use response handler
- Fix an issue that protocol `tls_passthrough` can not work with expressions flavor
- Fix a keyring issue where a kong node fails to send keyring material when using cluster strategy
- Fix a bug that will cause a failure of sending tracing data to datadog when value of x-datadog-parent-id header in requests is a short dec string
- fix rbac retrieve group roles with the group name that type is number.
- Fixed critical level logs when starting external plugin servers. Those logs cannot be suppressed due to the limitation of OpenResty. We choose to remove the socket availibilty detection feature.

Dependency

Core

- Fix incorrect LuaJIT LDP/STP fusion on ARM64 which may sometimes cause incorrect logic
- Fix incorrect LuaJIT LDP/STP fusion on ARM64 which may sometimes cause incorrect logic

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ets you delete a workspace and all of its entities in one request.

roups, you can apply different configurations to select groups of consumers. The following plugins can

  - Request Transformer and Request Transformer Advanced

    - Response Transformer and Response Transformer Advanced

  See the documentation for consumer groups to learn more.

- Added a new `ttl` option to vault configurations, allowing users to define the interval at which references are automatically re-fetched from the configured vault.

  See the documentation for secrets rotation to learn more.

- The workspace name now appears in the logging payload.
- **Beta feature:** Introduced the beta of WebAssembly (`proxy-wasm`).#11218

  This release integrates `Kong/ngx-wasm-module`into Kong Gateway.

- The `/schemas` endpoint now returns additional information about cross-field validation as part of the schema. This should help tools that use the Admin API to perform better client-side validation.
- Enabled the `expressions` and `traditional_compatible` router flavors in the stream subsystem.#11071
- The upstream `host_header` and router `preserve_host` configuration parameters now work in stream TLS proxy.#11244
- In DB-less mode, the declarative schema is now fully initialized at startup instead of on-demand in the request path. This is most evident in decreased response latency when updating configuration via the `/config` API endpoint.#10932
- Tracing: Added the new attribute `http.route` to HTTP request spans.#10981
- Tracing: Added the span attribute `net.peer.name`, which records the upstream hostname if it's available in `balancer_data.hostname`. Thanks @backjo for contributing this change.#10723
- The default value of `lmdb_map_size` config has been bumped to `2048m`from `128m` to accommodate most commonly deployed config sizes in DB-less and hybrid modes.#11047
- The default value of `cluster_max_payload` config has been bumped to `16m`from `4m` to accommodate most commonly deployed config sizes in hybrid mode.#11090
- Removed Kong branding from the kong HTML error template.#11150

Plugin

- graphql-rate-limiting-advanced:
    - The `host` field of this plugin now accepts Kong upstream targets.
- ip-restriction:
    - Added support for the `tcp`, `tls`, `grpc`, and `grpcs` protocols.

      Thanks @scrudge for contributing this change.#10245
- kafka-log:
    - The Kafka Log plugin now supports the `custom_fields_by_lua` configuration for dynamic modification of log fields using Lua code.
- openid-connect:
    - This plugin now supports the error reason header. This header can be turned off by setting `expose_error_code` to `false`.
    - OpenID Connect now supports adding scope to the token cache key by setting `token_cache_key_include_scope` to `true`.
- opentelemetry:
    - Introduced support for the AWS X-Ray propagation header. The field `header_type`now accepts the `aws` value to handle this specific propagation header.#11075

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

can be stored as a secret in a vault.#11220

s during scraping. #10949#11040#11065

n failures.

mproved.

mproved. [#10840](https: `max_batch_size`, `max_entries`, and `max_bytes` are now declared as `integer`

mproved. [#10840](https: `initial_retry_delay` and `max_retry_delay` must now be numbers greater than

K

- Enhanced the user experience of editing pages for entities with a refined look and feel.

- Simplified the user path by removing the configuration pages for nested entities.

Bugfix

Core

- Fixed a potential memory leak and reconnection problem which could occur when telemetry breaks down due to any exceptions in its `send` thread.
- Telemetry: Fixed issues that broke the telemetry websocket:
  - Fixed an issue that caused the telemetry websocket to be blocked by latency while flushing Vitals to database. By using a queue as a buffer, the process of receiving Vitals data from the data plane is now decoupled from the process of flushing Vitals to the database on the control plane.
  - Fixed an issue that broke the telemetry websocket in Konnect mode due to unexpected payloads when the counter of requests equals zero.
- Fixed an issue where you could receive an empty `request_id` when generating audit data.
- Fixed an error that occurred when the header `x-datadog-parent-id` wasn't passed to Kong Gateway.
- Fixed a queueing-related issue that broke event hooks in 3.3.0.0.
- Updated the datafile library to make the SAML plugin work when Kong Gateway is controlled by systemd.
- Fixed an issue where a workspace couldn't attach to the cache's consumer well.
- Fixed a LuaJIT crash on Arm64 and enabled LuaJIT on M1.
- Fixed an issue where the license couldn't load when pulling `KONG_LICENSE_DATA` from a vault.
- Declarative config now performs proper uniqueness checks against its inputs. Previously, it would silently drop entries with conflicting primary/endpoint keys, or accept conflicting unique fields silently.#11199
- Fixed a bug where a worker consuming dynamic log level setting events used the wrong reference for notice logging.#10897
- Added a `User=` specification to the systemd unit definition so that Kong Gateway can be controlled by systemd again.#11066
- Fixed a bug that caused the sampling rate to be applied to individual spans, producing split traces.#11135
- Fixed a bug that caused the router to fail in `traditional_compatible` mode when a route with multiple paths and no service was created.#11158
- Fixed an issue where the `expressions` router couldn't work correctly when `route.protocols` is set to `grpc` or `grpcs`.#11082
- Fixed an issue where the `expressions` router couldn't configure HTTPS redirection.#11166
- Made the `kong vault get` CLI command work in DB-less mode by injecting the necessary directives into the Kong CLI `nginx.conf`.#11127#11291
- Fixed an issue where a crashing Go plugin server process would cause subsequent requests proxied through Kong Gateway to execute Go plugins with inconsistent configurations. The issue only affects scenarios where the same Go plugin is applied to different route or service entities.#11306

dev-portal

- Fixed an issue on portal documentation pages, where disabling the Application Registration plugin didn't remove the **Register** button from a service.
- Fixed an issue with viewing OAS docs in the in the Dev Portal, where the UI would hang when attempting to expand an API.

Admin API

- Fixed an issue that caused `POST /config?flatten_errors=1` to throw an exception and return a 500 error under certain circumstances.#10896
- Fixed an issue where `/schemas/plugins/validate` endpoint failed to validate valid plugin configuration when the key of `custom_fields_by_lua` contained dot

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

hen operating in DB-less mode or on the data plane.#10995

uld fail to be encoded.

sages couldn't be unframed correctly.#10836

OR, then the CRL revocation failure will be ignored.
ways do CRL revocation check with this CRL file.
rtificate in chain error if the client only sent a leaf certificate.

    - `http_timeout` wasn't correctly set.
  - If `revocation_check_mode=IGNORE_CA_ERROR`, then the CRL revocation failure will be ignored.
  - Once a CRL is added into the store, it will always do CRL revocation check with this CRL file.
  - OCSP verification failed with `no issuer certificate in chain` error if the client only sent a leaf certificate.
  - `http_timeout` wasn't correctly set.
  - Optimized CRL revocation verification.
  - Fixed an issue that would cause an unexpected error when `skip_consumer_lookup` is enabled and `authenticated_group_by` is set to `null`.
- acme:
  - Fixed an issue where the sanity test didn't work with `kong` storage in hybrid mode.#10852
- mocking:
  - Fixed an issue where the plugin threw an error when the arbitrary elements were defined in the path node.
- oas-validation:
  - Fixed an issue where the plugin was unable to pass the validation even if path parameter was valid.
  - Fixed an issue where the plugin always validated the request body even if the method spec had no `requestBody` defined.
  - Fixed an issue where the comparison between large absolute value numbers could be incorrect due to the number being converted to exponential notation.
- oauth2-introspection:
  - Fixed an issue where the plugin failed when processing a request with JSON that is not a table.
- openid-connect:
  - Changed some log levels from `notice` to `error` for better visibility.
  - Correctly set the right table key on `log` and `message`.
  - If an invalid opaque token is provided but verification fails, the plugin now prints the correct error.
- rate-limiting-advanced:
  - Fixed an issue that impacted the accuracy with the `redis` policy. Thanks @giovanibrioni for contributing this change.#10559
- request-validator:
  - Optimized the response message for invalid requests.
- zipkin:
  - Fixed an issue where traces weren't being generated correctly when instrumentations were enabled.#10983
- response-transformer and **Request Transformer Advanced**: Fixed an issue where the plugin wouldn't transform the response body when the upstream returned a Content-Type with a `+json` suffix as the subtype.
- kafka-log and **Kafka Upstream**: Fixed an issue where the plugin could lose connection to a broker when the broker leadership changed.

Kong Manager

- Fixed an issue where Kong Manager didn't get the latest config when the Enterprise license was posted via the Admin API.

Manager was integrated with the Portal GUI.

lle `invalid credentials` when providing the wrong username.

`space access` while the `admin_auth` is set to `openid-connect`.

n't work for `/services/<service-name-or-id>/application_instances`.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped `lua-resty-openssl` from 0.8.20 to 0.8.23#10837#11099
- Bumped `kong-lapis` from 1.8.3.1 to 1.14.0.2#10841
- Bumped `lua-resty-events` from 0.1.4 to 0.2.0#10883#11083#11214
- Bumped `lua-resty-session` from 4.0.3 to 4.0.4#11011
- Bumped `OpenSSL` from 1.1.1t to 3.1.1#10180#11140
- Bumped `pgmoon` from 1.16.0 to 1.16.2 (Kong's fork)#11181#11229
- Bumped `atc-router` from 1.0.5 to 1.2.0#10100#11071
- Bumped `lua-resty-lmdb` from 1.1.0 to 1.3.0#11227

Breaking Change

Core

- **Cassandra DB support removed:** Cassandra DB support has been removed. It is no longer supported as a data store for Kong Gateway. #10931.
- **Alpine support removed:** Alpine packages and Docker images based on Alpine are no longer supported. Starting with Kong Gateway 3.4.0.0, Kong is not building new Alpine images or packages.#10926
- **Ubuntu 18.04 support removed** : Support for running Kong Gateway on Ubuntu 18.04 ("Bionic") is now deprecated, as Standard Support for Ubuntu 18.04 has ended as of June 2023. Starting with Kong Gateway 3.4.0.0, Kong is not building new Ubuntu 18.04 images or packages, and Kong will not test package installation on Ubuntu 18.04.

  If you need to install Kong Gateway on Ubuntu 18.04, see the documentation for previous versions.
- Amazon Linux 2022 artifacts are renamed to Amazon Linux 2023, based on AWS's own renaming.
- LMDB encryption has been disabled. The option `declarative_config_encryption_mode` has been removed from `kong.conf`.
- The `/consumer_groups/:id/overrides` endpoint is deprecated in favor of a more generic plugin scoping mechanism. See the new consumer groups entity.
- Renamed the configuration property `admin_api_uri` to `admin_gui_api_url`. The old `admin_api_uri` property is considered deprecated and will be fully removed in a future version of Kong Gateway.
- The RHEL8 Docker image provided by Kong is replaced with the RHEL9 Docker image. The RHEL8 packages are still available from our package repository.

Known Issues

Core

- Some referenceable configuration fields, such as the `http_endpoint` field of the `http-log` plugin and the `endpoint` field of the `opentelemetry` plugin, do not accept reference values due to incorrect field validation.
- When adding new plugins to the existing installation (either manually or via the extension of `bundled` plugins), the `kong migrations finish` or `kong migrations up` must be run with the `-f` flag to forcefully upgrade the plugin schemas.

3.3.1.1

Release date 2023/10/12

Bugfix

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

e propagated tracing headers

gured, users now receive a 500 error instead of being redirected endlessly

C

used when querying Postgres database.

ng material when using cluster strategy

acks early (CVE-2023-44487)

P

- Tracing: fix an issue that resulted in some parent spans to end before their children due to different precision of their timestamps

Dependency

Core

- Fix incorrect LuaJIT LDP/STP fusion on ARM64 which may sometimes cause incorrect logic

3.3.1.0

Release date 2023/07/03

Deprecation

Core

- **Alpine deprecation reminder:** Kong has announced our intent to remove support for Alpine images and packages later this year. These images and packages are available in 3.2 and will continue to be available in 3.3. We will stop building Alpine images and packages in Kong Gateway 3.4.
- **Cassandra deprecation and removal reminder:** Using Cassandra as a backend database for Kong Gateway is deprecated. It is planned for removal with Kong Gateway 3.4.

Bugfix

Core

- Fixed a bug that causes `POST /config?flatten_errors=1` to throw an exception and return a 500 error under certain circumstances.
- Fixed a bug that would cause an error when the header `x-datadog-parent-id` is not passed to Kong.
- Fixed a queueing-related bug that meant the `event_hooks` did not fire and led to errors in the logs.
- Updated the datafile library that meant when Kong was started with systemd, the SAML plugin did not load.
- Fixed a bug that the anonymous report can't be silenced by setting `anonymous_reports=false`.
- Fixed a Jenkins issue where `kong/kong-gateway:3.3.0.0-alpine` was missing `resty.dns.resolver` patch.
- Fixed an issue addressing occasional issues attaching a workspace with the cache's consumer well.

Plugin

- Fixed an issue with the Oauth 2.0 Introspection plugin where a request with JSON that is not a table failed.:

3.3.0.0

Release date 2023/05/19

Feature

Core

- When using the data plane resilience feature, the server-side certificate of the backend Amazon S3 or GCP Cloud Storage service will now be validated if it goes through HTTPS.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ne backend server's certificate is now validated if it goes through HTTPS.

authentication to connect to the Amazon RDS (PostgreSQL) database.

I for the navbar, sidebar, and all entity lists.
ssions router is enabled.
d in the Kong Gateway service form.

for Kong Gateway's Docker images.

ompliant with the `Accept` header value.#10366

ers, URI arguments, and POST arguments that are parsed by default can now be configured with the
eaders, `lua_max_resp_headers`, `lua_max_uri_args`, and `lua_max_post_args`.#10443

- Added PostgreSQL triggers on the core entites and entities in bundled plugins to delete expired rows in an efficient and timely manner.#10389
- Added support for configurable node IDs.#10385
- Request and response buffering options are now enabled for incoming HTTP 2.0 requests.

  Thanks @PidgeyBE for contributing this change. #10204 #10595
- Added `KONG_UPSTREAM_DNS_TIME` to `ngx.ctx` to record the time it takes for DNS resolution when Kong proxies to an upstream.#10355
- Dynamic log levels now have a default timeout of 60 seconds.#10288

kong-gateway-with-konnect

- You can now configure labels for data planesto provide metadata information for Konnect.#10471
- Sending analytics to Konnect from Kong Gateway DB-less mode is now supported.

Admin API

- Added a new `updated_at` field for the following entities: `ca_certificates`, `certificates`, `consumers`, `targets`, `upstreams`, `plugins`, `workspaces`, `clustering_data_planes`, `consumer_group_consumers`, `consumer_group_plugins`, `consumer_groups`, `credentials`, `document_objects`, `event_hooks`, `files`, `group_rbac_roles`, `groups`, `keyring_meta`, `legacy_files`, `login_attempts`, `parameters`, `rbac_role_endpoints`, `rbac_role_entities`, `rbac_roles`, `rbac_users`, and `snis`.#10400
- The `/upstreams/<upstream>/health?balancer_health=1` endpoint always shows the balancer health through a new attribute: `balancer_health`. This always returns `HEALTHY` or `UNHEALTHY`, reporting the true state of the balancer, even if the overall upstream health status is `HEALTHCHECKS_OFF`. This is useful for debugging.#5885
- **Beta** : OpenAPI specs are now available for the Kong Gateway Admin API: Kong Gateway Admin API - Enterprise spec

status-api

- The `status_listen` server has been enhanced with the addition of the`/status/ready` API for monitoring Kong Gateway's health. This endpoint provides a `200` response upon receiving a `GET` request, but only if a valid, non-empty configuration is loaded and Kong Gateway is prepared to process user requests.

  Load balancers frequently utilize this functionality to ascertain Kong Gateway's availability to distribute incoming requests. #10610#10787
- **Beta** : An OpenAPI spec is now available for the Kong Gateway Status API.

PDK

- The PDK now supports getting a plugin's ID with `kong.plugin.get_id`.#9903
- Tracing module: Renamed spans to simplify filtering on tracing backends. See `kong.tracing` for details. #10577

Plugin

- **Proxy Cache Advanced**:
  - Added wildcard and parameter match support for `content_type`.
  - Added the configuration parameter `ignore_uri_case` to allow handling the cache key URI as lowercase.#10453
- acme:
  - This plugin now supports configuring an `account_key` in `keys` and `key_sets`.#9746

for Redis storage, which defaults to an empty string for backwards compatibility.#10562

to support scheme configuration on the lambda service API endpoint.#9799

able.#10484

ption for the `Content-Type` header to support log collectors that require that character set

ets you add extra claims to JWT.

Datadog traces.10531

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Added the `header_type` field. Previously, the `header_type` was hardcoded to `preserve`. Now it can be set to one of the following values: `preserve`, `ignore`, `b3`, `b3-single`,`w3c`, `jaeger`, or `ot`.#10620
  - Added the new span attribute `http.client_ip` to capture the client IP when behind a proxy.#10723
  - Added the `http_response_header_for_traceid` configuration parameter. Setting a string value in this field sets a corresponding header in the response.#10379
- proxy-cache:
  - Added the configuration parameter `ignore_uri_case` to allow handling the cache key URI as lowercase.#10453
- request-transformer-advanced:
  - The plugin now honors the following Kong Gateway configuration parameters: `untrusted_lua`, `untrusted_lua_sandbox_requires`, `untrusted_lua_sandbox_environment`. These parameters apply to advanced templates (Lua expressions).
- request-validator:
  - Errors are now logged for validation failures.
- zipkin and **OpenTelemetry**: These plugins now convert `traceid` in HTTP response headers to hex format.#10534

Bugfix

Core

- The Kong Enterprise systemd unit was incorrectly renamed to `kong.service` in 3.2.x.x versions. It has now been reverted back to `kong-enterprise-edition.service` to keep consistent with previous releases.
- Fixed an issue where Kong Gateway failed to generate a keyring when RBAC was enabled.
- Fixed `lua_ssl_verify_depth` in FIPS mode to match the same depth of normal mode.
- Removed the email field from the developer registration response.
- Websocket requests now generate balancer spans when tracing is enabled.
- Fixed an issue where management of licenses via the `/licenses/` endpoint would fail if the current license is not valid.
- Resolved an issue with the plugin iterator where sorting would become mixed up when dynamic reordering was applied. This fix ensures proper sorting behavior in all scenarios.
- Kong Manager:
  - Fixed an issue where changing the vault name in Kong Manager would throw an error.
  - Fixed an issue with tabs, where vertical tab content became blank when selecting a tab that is currently active.
  - Fixed an issue where the `/register` route occasionally jumped to `/login` instead.
  - Removed the **Custom Identifier** field from the StatsD plugin. This field appeared in Kong Manager under Metrics, but the field doesn't exist in the plugin's schema.
- Fixed an issue where the upstream keepalive pool had a CRC32 collision.#9856
- Hybrid mode:
  - Fixed an issue where the control plane didn't downgrade configuration for the AWS Lambda and Zipkin plugins for older versions of data planes.#10346
  - Fixed an issue where the control plane didn't rename fields correctly for the Session plugin for older versions of data planes.#10352
- Fixed an issue where validation of regex routes was occasionally skipped when the old-fashioned config style was used for DB-less Kong Gateway.#10348
- Fixed an issue where tracing could cause unexpected behavior.#10364

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d use the wrong status code when Kong Gateway changed the status code from the upstream in the

ed record did not propagate the error correctly.#10449

nt Kong Gateway from restarting in Docker containers if it was not cleanly stopped.#10468

outer sources or destinations led to `invalid order function for sorting` errors.#10514

by frequent DNS queries.#10691

12

er caused a deadlock.#10561

ming propagation headers to be handled incorrectly and only affect some spans.#10655
ans from being created for OpenResty HTTP client requests.#10680
ed precision of the balancer span start and end times.#10681
ce one of every 100 requests) instead of the previous 1 (trace all requests). Tracing all requests causes unnecessary resource drain for most production systems.#10774

- Fixed an issue with vault references, which caused Kong Gateway to error out when trying to stop.#10775
- Fixed an issue where vault configuration stayed sticky and cached even when configurations were changed.#10776
- Fixed the following PostgreSQL TTL clean-up timer issues:
  - Timers will now only run on traditional and control plane nodes that have enabled the Admin API.#10405
  - Kong Gateway now runs a batch delete loop on each TTL-enabled table with a number of `50.000` rows per batch.#10407
  - The cleanup job now runs every 5 minutes instead of every 60 seconds.#10389
  - Kong Gateway now deletes expired rows based on the database server-side timestamp to avoid potential problems caused by the differences in clock time between Kong Gateway and the database server.#10389
- Fixed an issue where an empty value for the URI argument `custom_id` crashed the `/consumer` API.#10475

kong-gateway-with-konnect

- The standard expired license notification no longer appears in logs for data planes running in Konnect mode (`konnect_mode=on`), as it does not apply to them.
- New license alert behavior for data planes running in Konnect mode:
  - If there are at least 16 days left before expiration, no alerts are issued.
  - If the license expires within 16 days, a warning level alert is issued every day.
  - If the license is expired, a critical level alert is issued every day.

PDK

- `request.get_uri_captures` now returns the unnamed part tagged as an array for jsonification.#10390
- Fixed an issue for tracing PDK where the sampling rate didn't work.#10485

Plugin

- **Forward Proxy**:
  - Fixed an issue which caused the wrong `latencies.proxy` to be used in the logging plugins. This plugin now evaluates `ctx.WAITING_TIME` in the forward proxy instead of doing it in the subsequent phase.
- **StatsD Advanced**:
  - Changed the plugin's name to `statsd-advanced` instead of `statsd`.
- **gRPC Gateway**:
  - Fixed an issue where having a `null` value in the JSON payload caused an uncaught exception to be thrown during `pb.encode`.#10687
  - Fixed an issue where empty arrays in JSON were incorrectly encoded as `"{}"`. They are now encoded as `"[]"` to comply with standards.#10790
- ldap-auth-advanced:
  - The plugin now performs authentication before authorization, and returns a 403 HTTP code when a user isn't in the authorized groups.
  - The plugin now supports setting the groups to an empty array when groups are not empty.
- oauth2:
  - Fixed an issue where the OAuth2 token was being cached as `nil` if the wrong service was accessed first.#10522
  - This plugin now prevents an authorization code created by one plugin instance from being exchanged for an access token created by a different plugin instance.#10011

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

't take effect.

ncorrectly resulting in the wrong hierarchy being rendered on tracing backends.#10663

or when Redis Cluster is down.

nts broadcast the wrong data in traditional cluster mode.

yncs.

the plugin to not return the `uri-captures`.#10390

be proxied with incorrect query parameters.10539

  - The plugin now honors the value of the `untrusted_lua` configuration parameter.#10327

- request-validator:
  - Fixed an issue where the validation function for the `allowed_content_types` parameter was too strict, making it impossible to use media types that contained a `-` character.
- jwe-decrypt, **OAS Validation**, and **Vault Authentication**: Added the missing schema field `protocols` for `jwe-decrypt`, `oas-validation`, and `vault-auth`.

Dependency

Core

- Updated the datafile library dependency to fix the following issues:
  - Kong Gateway didn't work when installed on a read-only file system.
  - Kong Gateway didn't work when started from systemd.
- Bumped `lua-resty-session` from 4.0.2 to 4.0.3#10338
- Bumped `lua-protobuf` from 0.3.3 to 0.5.0#10137#10790
- Bumped `lua-resty-timer-ng` from 0.2.3 to 0.2.5#10419#10664
- Bumped `lua-resty-openssl` from 0.8.17 to 0.8.20#10463#10476
- Bumped `lua-resty-http` from 0.17.0.beta.1 to 0.17.1#10547
- Bumped `lua-resty-aws` from 1.1.2 to 1.2.2
- Bumped `lua-resty-gcp` from 0.0.11 to 0.0.12
- Bumped `LuaSec` from 1.2.0 to 1.3.1#10528
- Bumped `lua-resty-acme` from 0.10.1 to 0.11.0#10562
- Bumped `lua-resty-events` from 0.1.3 to 0.1.4#10634
- Bumped `lua-kong-nginx-module` from 0.5.1 to 0.6.0#10288
- Bumped `lua-resty-lmdb` from 1.0.0 to 1.1.0#10766
- Bumped `kong-openid-connect` from 2.5.4 to 2.5.5

Breaking Change

Core

- **Alpine deprecation reminder:** Kong has announced our intent to remove support for Alpine images and packages later this year. These images and packages are still available in 3.3. We will stop building Alpine images and packages in Kong Gateway 3.4.
- **Cassandra deprecation and removal reminder:** Using Cassandra as a backend database for Kong Gateway is deprecated. It is planned for removal with Kong Gateway 3.4.
- The `traditional_compat` router mode has been made more compatible with the behavior of `traditional` mode by splitting routes with multiple paths into multiple `atc` routes with separate priorities. Since the introduction of the new router in Kong Gateway 3.0, `traditional_compat` mode assigned only one priority to each route, even if different prefix path lengths and regular expressions were mixed in a route. This was not how multiple paths were handled in the`traditional` router and the behavior has now been changed so that a separate priority value is assigned to each path in a route.#10615
- **Tracing** : `tracing_sampling_rate` now defaults to 0.01 (trace one of every 100 requests) instead of the previous 1 (trace all requests). Tracing all requests causes unnecessary resource drain for most production systems.#10774

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

g Gateway's version.

ode, the plugin now considers it to be an error and retries according to the retry configuration. Previously, causing the log entries to be dropped.#10172

The standard queue parameter set is available to control queuing behavior.#10753

ueue has been renamed to `kong.tools.queue` and the API was changed. If your custom plugin uses

, and Datadog

The queuing system has been reworked, causing some plugin parameters to not function as expected anymore. If you use queues in these plugins, new parameters must be configured. See each plugin's documentation for details.

- pre-function and **Post-function**: `kong.cache` now points to a cache instance that is dedicated to the Serverless Functions plugins. It does not provide access to the global Kong Gateway cache. Access to certain fields in `kong.conf` has also been restricted.#10417

Known Issues

Core

- Due to known issues, Kong recommends not enabling page-level LMDB encryption in versions 3.0.x-3.3.x.

  Don't set `declarative_config_encryption_mode`; leave it at its default value of `off`. Continue relying on disk-level encryption to encrypt the configuration on disk.

- When sending an invalid configuration to the `/config` endpoint while running in DB-less mode and with `flatten_errors=1` set, Kong Gateway incorrectly returns a 500. This should be a 400 because the configuration is invalid.

- When the OpenID Connect (OIDC) plugin is configured to reference HashiCorp Vault in the `config.client_secret` field (for example, `{vault://hcv/clientSecret}`), it does not look up the secret correctly.

3.2.2.5

Release date 2023/10/12

Bugfix

Core

- Applied Nginx patch for early detection of HTTP/2 stream reset attacks. This change is in direct response to the identified vulnerability CVE-2023-44487.
- Fixed a keyring issue where Kong Gateway nodes would fail to send keyring data when using the cluster strategy.
- Fixed an issue where an abnormal socket connection would be incorrectly reused when querying the PostgreSQL database.
- Added a `User=` specification to the systemd unit definition, enabling Kong Gateway to be controlled by systemd again.#11066

Plugin

- **mTLS Authentication**:
  - Fixed an issue that caused the plugin to cache network failures when running certificate revocation checks.
- saml:
  - Users will now receive a 500 error instead of being endlessly redirected when the Redis session storage is incorrectly configured.

Dependency

Core

- Bumped `libxml2` from 2.10.2 to 2.11.5

3.2.2.4

R

E

C

ork again when Kong is controlled by systemd.

lenced by setting `anonymous_reports=false`.

would cause subsequent requests proxied through Kong to execute Go plugins with inconsistent
he same Go plugin is applied to different route or service entities.

P

e.

on fails, print the correct error.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- rate-limiting-advanced:
  - The control plane no longer attempts to create namespace or synchronize counters with Redis.
- rate-limiting:
  - The redis rate limiting strategy now returns an error when Redis Cluster is down.
- response-transformer-advanced:
  - Does not load response body when `if_status` does not match.

Kong Manager

- Fixed an issue where the Zipkin plugin prevented users from editing the `static_tags` configuration.
- Fixed an issue where the unavailable Datadog Tracing plugin displayed on the plugin installation page.
- Fixed an issue where some metrics were missing from the StatsD plugin.
- Fixed an issue where locale files were not found when using a non-default `admin_gui_path` configuration.
- Fixed an issue where endpoint permissions for application instances did not work as expected.
- Fixed an issue where some icons were shown as unreadable symbols and characters.
- Fixed an issue where users were redirected to pages under the default workspace when clicking links for services or routes of entities residing in other workspaces.
- Fixed an issue that failed to redirect OpenID Connect in Kong Manager if it was provided with an incorrect username.

Dependency

Core

- `lua-resty-kafka` is bumped from 0.15 to 0.16
- Bumped `OpenSSL` from 1.1.1t to 3.1.1

Breaking Change

Core

- **Ubuntu 18.04 support removed** : Support for running Kong Gateway on Ubuntu 18.04 (“Bionic”) is now deprecated, as Standard Support for Ubuntu 18.04 has ended as of June 2023. Starting with Kong Gateway 3.2.2.4, Kong is not building new Ubuntu 18.04 images or packages, and Kong will not test package installation on Ubuntu 18.04.
- Amazon Linux 2022 artifacts are renamed to Amazon Linux 2023, based on AWS’s own renaming.
- CentOS packages are now removed from the release and are no longer supported in future versions.

3.2.2.3

Release date 2023/06/07

Deprecation

Core

intent to remove support for Alpine images and packages later this year. These images and packages are
We will stop building Alpine images and packages in Kong Gateway 3.4.

rors=1 was set and an invalid config was sent to the endpoint, a 500 error was incorrectly returned.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed the OpenResty `ngx.print` chunk encoding duplicate free buffer issue that led to the corruption of chunk-encoded response data.#10816#10824
- Fixed the UDP socket leak in `resty.dns.client` caused by frequent DNS queries.#10691

Plugin

- rate-limiting-advanced:
  - Fixed the log flooding issue caused by low `sync_rate` settings.

3.2.2.1

Release date 2023/04/03

Deprecation

Core

- **Alpine deprecation reminder:** Kong has announced our intent to remove support for Alpine images and packages later this year. These images and packages are available in 3.2 and will continue to be available in 3.3. We will stop building Alpine images and packages in Kong Gateway 3.4.

Bugfix

Core

- Fixed the Dynatrace implementation. Due to a build system issue, Kong Gateway 3.2.x packages prior to 3.2.2.1 didn't contain the debug symbols that Dynatrace requires.

3.2.2.0

Release date 2023/03/22

Bugfix

Core

- In Kong 3.2.1.0 and 3.2.1.1, `alpine` and `ubuntu` ARM64 artifacts incorrectly handled HTTP/2 requests, causing the protocol to fail. These artifacts have been removed.
- Added the default logrotate file `/etc/logrotate.d/kong-enterprise-edition`. This file was missing in all 3.x versions of Kong Gateway prior to this release.

Plugin

- saml:
  - The SAML plugin now works on read-only file systems.
  - The SAML plugin can now handle the field `session_auth_ttl` (removed since 3.2.0.0).
- Datadog Tracing plugin: We found some late-breaking issues with the Datadog Tracing plugin and elected to remove it from the 3.2 release. We plan to add the plugin back with the issues fixed in a later release.

Known Issues

C

ease triggers a `Public key for kong-enterprise-edition-3.2.1.0.rhel7.amd64.rpm is not`
ned with a different (rotated) key from the metadata service, which triggers the error in yum. To avoid this

3

R

D

C

ne images and packages later this year. These images and packages are available in 3.2 and will continue to
nd packages in Kong Gateway 3.4.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Feature

Core

- Changed the underlying operating system (OS) for our convenience Docker tags (for example, `latest`, `3.2.1.0`, `3.2`) from Debian to Ubuntu.
- When `router_flavor` is set to`traditional_compatible`, Kong Gateway verifies routes created using the expression router instead of the traditional router to ensure created routes are compatible.#9987
- In DB-less mode, the `/config` API endpoint can now flatten all schema validation errors into a single array using the optional `flatten_errors` query parameter.#10161
- The upstream entity now has a new load balancing algorithm option: `latency`. This algorithm chooses a target based on the response latency of each target from prior requests.#9787
- The Nginx `charset` directive can now be configured with Nginx directive injections. Set it in Kong Gateway's configuration with `nginx_http_charset`#10111
- The services upstream TLS configuration is now extended to the stream subsystem.#9947
- Added the new configuration parameter `ssl_session_cache_size`, which lets you set the Nginx directive `ssl_session_cache`. This configuration parameter defaults to `10m`. Thanks Michael Kotten for contributing this change.#10021
- `status_listen` now supports HTTP2. #9919
- The shared Redis connector now supports username + password authentication for cluster connections, improving on the existing single-node connection support. This automatically applies to all plugins using the shared Redis configuration.
- **FIPS Support**:
  - The OpenID Connect, Key Authentication - Encrypted, and JWT Signer plugins are now FIPS 140-2 compliant. If you are migrating from Kong Gateway 3.1 to 3.2 in FIPS mode and are using the `key-auth-enc` plugin, you should send PATCH or POST requests to all existing `key-auth-enc` credentials to re-hash them in SHA256.
  - FIPS-compliant Kong Gateway packages now support PostgreSQL SSL connections.

Plugin

- **Improved Plugin Documentation**:
  - Split the plugin compatibility table into a technical compatibility page.
  - Updated the plugin compatibility information for more clarity on supported network protocols and on entity scopes.
  - Revised docs for the following plugins to include examples:
    - CORS
    - File Log
    - HTTP Log
    - JWT Signer
    - Key Auth
    - OpenID Connect
    - Rate Limiting Advanced
    - SAML
    - StatsD
  - CORS
  - File Log
  - HTTP Log

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ntifies a particular plugin entity.#10077:

ocol_version, which lets you select the IMDS protocol version. This option defaults to `v1` and can be set

- canary:

    - Added a default value for the `start` field in the canary plugin. If not set, the start time defaults to the current timestamp.

- http-log:
    - The `headers` configuration parameter is now referenceable, which means it can be securely stored in a vault.#9948
- opa:
    - This plugin can now handle custom messages from the OPA server.
- opentelemetry:
    - This plugin can now be scoped to individual services, routes, and consumers.#10096
- statsd:
    - Added the `tag_style` configuration parameter, which allows the plugin to send metrics with tags. The parameter defaults to `nil`, which means that no tags are added to the metrics.#10118
- zipkin:
    - Added support for setting the durations of Kong phases as span tags through the configuration property `phase_duration_flavor`.#9891
- session, **OpenID Connect**, and **SAML**: These plugins now use `lua-resty-session` v4.0.0.

  This update includes new session functionalities such as configuring audiences to manage multiple sessions in a single cookie, global timeout, and persistent cookies.

  Due to this update, there are also a number of deprecated and removed parameters in these plugins. See the invidividual plugin documentation for the full list of changed parameters in each plugin.

    - Session changelog
    - OpenID Connect changelog
    - SAML changelog
- session, **OpenID Connect**, and **SAML**: Session changelog
- session, **OpenID Connect**, and **SAML**: OpenID Connect changelog
- session, **OpenID Connect**, and **SAML**: SAML changelog
- graphql-rate-limiting-advanced and **Rate Limiting Advanced**: In hybrid and DB-less modes, these plugins now support `sync_rate = -1` with any strategy, including the default `cluster` strategy.

Bugfix

Core

- Added back PostgreSQL `FLOOR` function when calculating `ttl`, so `ttl` is always returned as a whole integer.#9960
- Exposed PostreSQL connection pool configuration.#9603
- **Nginx template** : The default charset is no longer added to the `Content-Type` response header when the upstream response doesn't contain it.#9905
- Fixed an issue where, after a valid declarative configuration was loaded, the configuration hash was incorrectly set to the value `00000000000000000000000000000000`.#9911
- Updated the batch queues module so that queues no longer grow without bounds if their consumers fail to process the entries. Instead, old batches are now dropped and an error is logged.#10247
- Fixed an issue where `X-Kong-Upstream-Status` couldn't be emitted when a response was buffered.#10056

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

4

tly from environment variables and vault references.10132

figuration for the AWS Lambda and Zipkin plugins for older versions of data planes.#10346

x routes could be skipped when using a configuration format older than `3.0`.#10348

plane and the control plane didn't support telemetry port 8006.

ther nodes in a cluster.

dd rate limiting policies to consumer groups.

- Fixed an issue where workspace admins in one workspace would have admin rights in other workspaces. Workspace admins are now correctly restricted to their own workspaces.
- Fixed a role precedence issue with RBAC. RBAC rules involving deny (negative) rules now correctly take precedence over allow (non-negative) roles.

Plugin

- **Key Authentication Encrypted**:
  - Fixed the `ttl` parameter. You can now set `ttl` for an encrypted key.
  - Fixed an issue where this plugin didn't accept tags.
- jwt:
  - This plugin now denies requests that have different tokens in the JWT token search locations.

    Thanks Jackson 'Che-Chun' Kuo from Latacora for reporting this issue.#9946
- mocking:
  - Fixed UUID pattern matching.
- oauth2:
  - `refresh_token_ttl` is now limited to a range between `0` and `100000000` by the schema validator. Previously, numbers that were too large caused requests to fail.#10068
- openid-connect:
  - Fixed an issue where it was not possible to specify an anonymous consumer by name.
  - Fixed an issue where the `authorization_cookie_httponly` and `session_cookie_httponly` parameters would always be set to `true`, even if they were configured as `false`.
- opentelemetry:
  - Fixed non-compliances to specification:
    - For `http.uri` in spans, the field is now the full HTTP URI. #10036
    - `http.status_code` is now present on spans for requests that have a status code. #10160
    - `http.flavor` is now a string value, not a double. #10160
  - For `http.uri` in spans, the field is now the full HTTP URI. #10036
  - `http.status_code` is now present on spans for requests that have a status code. #10160
  - `http.flavor` is now a string value, not a double. #10160
  - Fixed an issue with getting the traces of other formats, where the trace ID reported and propagated could be of incorrect length. This caused traces originating from Kong Gateway to incorrectly connect with the target service, causing Kong Gateway and the target service to submit separate traces.#10332
- rate-limiting-advanced:
  - Matched the plugin's behavior to the Rate Limiting plugin. When an `HTTP 429` status code was returned, rate limiting related headers were missed from the PDK module `kong.response.exit()`. This made the plugin incompatible with other Kong components like the Exit Transformer plugin.
- response-transformer:
  - Fixed an issue where the `allow.json` configuration parameter couldn't use nested JSON object and array syntax.
- saml:

ly parameter would always be set to `true`, even if it was configured as `false`.

io overrode the route-specific ratio.#9877

ngs with decimals were not processed correctly.

hese plugins' batch queue processing, where metrics would be published multiple times. This caused a limit.#10052 #10044

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bumped `openssl` from 1.1.1q to 1.1.1t
- `libyaml` is no longer built with Kong Gateway. System `libyaml` is used instead.
- Bumped `luarocks` from 3.9.1 to 3.9.2#9942
- Bumped `atc-router` from 1.0.1 to 1.0.5#9925#10143#10208
- Bumped `lua-resty-openssl` from 0.8.15 to 0.8.17#9583#10144
- Bumped `lua-kong-nginx-module` from 0.5.0 to 0.5.1#10181
- Bumped `lua-resty-session` from 3.10 to 4.0.0#10199#10230
- Bumped `libxml` from 2.10.2 to 2.10.3 to resolve CVE-2022-40303 and CVE-2022-40304

Breaking Change

Core

- The default PostgreSQL SSL version has been bumped to TLS 1.2. In `kong.conf`:
  - The default `pg_ssl_version` is now `tlsv1_2`.
  - Constrained the valid values of this configuration option to only accept the following: `tlsv1_1`, `tlsv1_2`, `tlsv1_3` or `any`.

  This mirrors the setting `ssl_min_protocol_version` in PostgreSQL 12.x and onward. See the PostgreSQL documentation for more information about that parameter.

  To use the default setting in `kong.conf`, verify that your Postgres server supports TLS 1.2 or higher versions, or set the TLS version yourself. TLS versions lower than `tlsv1_2` are already deprecated and considered insecure from PostgreSQL 12.x onward.
- Added the `allow_debug_header` configuration property to `kong.conf` to constrain the `Kong-Debug` header for debugging. This option defaults to `off`.

  If you were previously relying on the `Kong-Debug` header to provide debugging information, set `allow_debug_header: on` to continue doing so.
- **JWT plugin** (`jwt`)
  - The JWT plugin now denies any request that has different tokens in the JWT token search locations.[#9946](https: The JWT plugin now denies any request that has different tokens in the JWT token search locations.#9946
- Sessions library upgrade #10199:
  - The `lua-resty-session` library has been upgraded to v4.0.0. This version includes a full rewrite of the session library, and is not backwards compatible. This library is used by the following plugins: **Session**, **OpenID Connect**, and **SAML**. This also affects any session configuration that uses the Session or OpenID Connect plugin in the background, including sessions for Kong Manager and Dev Portal.
    All existing sessions are invalidated when upgrading to this version. For sessions to work as expected in this version, all nodes must run Kong Gateway 3.2.x or later. For that reason, we recommend that during upgrades, proxy nodes with mixed versions run for as little time as possible. During that time, the invalid sessions could cause failures and partial downtime.
  - Parameters:
    - The new parameter `idling_timeout`, which replaces `cookie_lifetime`, now has a default value of 900. Unless configured differently, sessions expire after 900 seconds (15 minutes) of idling.
    - The new parameter `absolute_timeout` has a default value of 86400. Unless configured differently, sessions expire after 86400 seconds (24 hours).
    - Many session parameters have been renamed or removed. Although your configuration will continue to work as previously configured, we recommend adjusting your configuration to avoid future unexpected behavior. Refer to the upgrade guide for 3.2 for all session configuration changes and guidance on how to convert your existing session configuration.

3.1.1.6

R

E

C

n reset attacks. This change is in direct response to the identified vulnerability CVE-2023-44487.

D

C

3

R

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Feature

Core

- The Redis strategy of Rate Limiting now catches connection failures.
- Added the parameter `admin_auto_create` for automatically creating a Kong admin.
- Kong Manager supports the `POST` response method for OIDC based authentication

Bugfix

Core

- Fixed an issue with the plugin iterator where sorting would become mixed up when dynamic reordering was applied. This fix ensures proper sorting behavior in all scenarios.
- Fixed an issue where `resty.dns.client` leaked UDP sockets.
- Fixed a bug where setting `anonymous_reports=false` would not silence anonymous reports.
- Fixed an issue with hybrid mode where vitals and analytics could not communicate through the cluster telemetry endpoint.
- Fixed the HTTP2 request handle in ARM artifacts.
- Fixed the OpenResty `ngx.print` chunk encoding duplicate free buffer issue that led to the corruption of chunk-encoded response data. #10816#10824
- Fixed an issue where a crashing Go plugin server process would cause subsequent requests proxied through Kong to execute Go plugins with inconsistent configurations. The issue only affects scenarios where the same Go plugin is applied to different route or service entities.
- Fixed the Dynatrace implementation.

Plugin

- oauth2:
  - Fixed a bug that `refresh_token` could be shared across instances.
- rate-limiting-advanced:
  - Fixed an issue where the control plane was trying to sync the rate-limiting-advanced counters with Redis.
  - Fixed an issue where the `rl cluster_events` broadcasted the wrong data in traditional cluster mode.
- request-transformer-advanced:
  - Fixed an issue that was causing some requests to be proxied with the wrong query parameters.
- response-transformer-advanced:
  - Fixed an issue where large decimals were rounded when the plugin was being used.

Dependency

Core

- Bumped `OpenSSL` from 1.1.1t to 3.1.1

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

3

R

F

C

on`admin_auto_create` to enable or disable automatic admin creation. This option is `true` by default.

F

C

- Fixed the UDP socket leak in `resty.dns.client` caused by frequent DNS queries.#10691
- Hybrid mode: Fixed an issue where Vitals/Analytics couldn't communicate through the cluster telemetry endpoint.
- Fixed an issue where `alpine` and `ubuntu` ARM64 artifacts incorrectly handled HTTP/2 requests, causing the protocol to fail.
- Fixed the OpenResty `ngx.print` chunk encoding duplicate free buffer issue that led to the corruption of chunk-encoded response data.#10816#10824
- Fixed the Dynatrace implementation. Due to a build system issue, Kong Gateway 3.1.x packages prior to 3.1.1.4 didn't contain the debug symbols that Dynatrace requires.

Plugin

- request-transformer-advanced:
  - Fixed an issue that was causing some requests to be proxied with the wrong query parameters.

Kong Manager

- Fixed configuration fields for the StatsD plugin:
  - Added missing metric fields: `consumer_identifier`, `service_identifier`, and `workspace_identifier`.
  - Removed the non-existent `custom_identifier` field.
- Fixed an issue where the `Copy JSON` for a plugin didn't copy the full plugin configuration.
- Fixed an issue where the Zipkin plugin didn't allow the addition of `static_tags` through the Kong Manager UI.
- Added missing default values to the Vault configuration page.
- Fixed the broken Konnect link in free mode banners.
- OIDC authentication issues:
  - The `/auth` endpoint, used by Kong Manager for OIDC authentication, now correctly supports the HTTP POST method.
  - Fixed an issue with OIDC authentication in Kong Manager, where the default roles (`workspace-super-admin`, `workspace-read-only`, `workspace-portal-admin`, and `workspace-admin`) were missing from any newly created workspace.
  - Fixed an issue where users with newly registered Dev Portal accounts created through OIDC were unable to log into Dev Portal until the Kong Gateway container was restarted. This happened when `by_username_ignore_case` was set to `true`, which incorrectly caused consumers to always load from cache.

3.1.1.3

Release date 2023/01/30

Bugfix

Core

- Fixed the accidental removal of the `ca-certificates` dependency from packages and images. This prevented SSL connections from using common root certificate authorities.

3.1.1.2

Release date 2023/01/24

Deprecation

C

nt is deprecated. Use one of the following endpoints from the Vitals API instead:: :

e_name}/vitals/status_codes/by_consumer instead
_name}/vitals/status_codes/by_service instead
e_name}/vitals/nodes instead

F

C

al `fields` query parameter on the `/files` endpoint. This parameter lets you specify which file object fields

fy routes created using the Expression router instead of the traditional router to ensure created routes are

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- `kong migrations up` now reports routes that are incompatible with the 3.0 router and stops the migration progress so that admins have a chance to adjust them.:

Bugfix

Core

- Fixed an issue where regexes generated in inso would not work in Kong Gateway.:
- Bumped `atc-router` to `1.0.2` to address the potential worker crash issue.#9927:

hybrid-mode

- Fixed an issue where Vitals data was not showing up after a license was deployed using the `/licenses` endpoint. Kong Gateway now triggers an event that allows the Vitals subsystem to be reinitialized during license preload.:
- Fixed an issue where the forward proxy between data planes and the control plane didn't support the telemetry port `8006`.:
- Reverted the removal of WebSocket protocol support for configuration sync. Backwards compatibility with 2.8.x.x data planes has been restored. #10067:

Plugin

- **mTLS Authentication**:
  - Fixed an issue where the plugin used the old route caches after routes were updated.
- oas-validation:
  - Added the OAS Validation plugin back into the bundled plugins list. The plugin is now available by default with no extra configuration necessary through `kong.conf`.
  - Fixed an issue where the plugin returned the wrong error message when failing to get the path schema spec.
  - Fixed a `500` error that occurred when the response body schema had no content field.
- rate-limiting-advanced:
  - Fixed an issue with the `local` strategy, which was not working correctly when `window_size` was set to `fixed`, and the cache would expire while the window was still valid.
- datadog,**OpenTelemetry**, and **StatsD**: Fixed an issue in these plugins' batch queue processing, where metrics would be published multiple times. This caused a memory leak, where memory usage would grow without limit.

Kong Manager

- Fixed an issue where Kong Manager would occasionally log out while redirecting to other pages or refreshing the page when OpenID Connect was used as the authentication method.:
- Fixed an issue where `404 Not Found` errors were triggered while updating the service, route, or consumer bound to a scoped plugin.:
- Fixed an issue where admins with the permission `['create'] /services/*/plugins` couldn't create plugins under a service.:
- Fixed an issue where viewing a consumer group in any workspace other than `default` would cause a `404 Not Found` error.:
- Fixed issues with the plugin list:
  - Added missing icons and categories for the TLS Handshake Modifier and TLS Metadata Headers plugins.
  - Removed entries for the following deprecated plugins: Kubernetes Sidecar Injector, Collector, and Upstream TLS.
  - Removed Apache OpenWhisk plugin from Kong Manager. This plugin must be installed manually via LuaRocks.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - `keyring_vault_auth_method`
  - `keyring_vault_kube_role`
  - `keyring_vault_kube_api_token_file`

- FIPS 140-2 packages:
  - Kong Gateway Enterprise now provides FIPS 140-2 compliant packages for Red Hat Enterprise 8 and Ubuntu 22.04.
  - Kong Gateway FIPS distributions now support TLS connections to the PostgreSQL database.
- You can now delete consumer group configurations without deleting the group or the consumers in it.
- **Kong Manager** :
  - You can now configure the base path for Kong Manager, for example: `localhost:8445/manager`. This allows you to proxy all traffic through Kong Gateway. For example, you can proxy both API and Kong Manager traffic from one port. In addition, using the new Kong Manager base path allows you to add plugins to control access to Kong Manager. For more information, see Enable Kong Manager.
  - You can now create consumer groups in Kong Manager. This allows you to define any number of rate limiting tiers and apply them to subsets of consumers instead of managing each consumer individually. For more information, see Create Consumer Groups in Kong Manager.
  - You can now add `key-auth-enc` credentials to a consumer.
  - OpenID Connect plugin: More authorization variables have been added to the **Authorization** tab.
  - The Kong Manager overview tab has been optimized for performance.
  - You can now configure vaults for managing secrets through Kong Manager. Use the new Vaults menu to set up and manage any vaults that Kong Gateway supports. See the Vault Backends referencesfor descriptions of all the configuration options.
  - Added support for interfacing with dynamic plugin ordering.
  - Added the ability to view details about certificates.
  - Added tooltips to plugin UI with field descriptions.
  - Added support for persisting the page size of lists across pages and provided more options for page sizes.
- Allow `kong.conf` SSL properties to be stored in vaults or environment variables. Allow such properties to be configured directly as content or base64 encoded content.#9253
- Added support for full entity transformations in schemas.#9431
- The schema `map` type field can now be marked as referenceable.#9611
- Added support for dynamically changing the log level.#9744
- Added support for the `keys` and `key-sets` entities. These are used for managing asymmetric keys in various formats (JWK, PEM). For more information, see Key management.#9737

hybrid-mode

- Data plane node IDs will now persist across restarts.#9067
- Added HTTP CONNECT forward proxy support for hybrid mode connections. New configuration options `cluster_use_proxy`, `proxy_server` and `proxy_server_ssl_verify` are added. For more information, see CP/DP Communication through a Forward Proxy.#9758#9773

Performance

- Increase the default value of `lua_regex_cache_max_entries`. A warning will be thrown when there are too many regex routes and `router_flavor` is `traditional`.#9624
- Add batch queue into the Datadog and StatsD plugins to reduce timer usage.#9521

os-support

- Kong Gateway now supports Amazon Linux 2022 with Enterprise packages.
- Kong Gateway now supports Ubuntu 22.04 with both open-source and Enterprise packages.

P

e to support setting the Distinguished Name (DN) list hints of the accepted CA certificates.#9768

P

plugin handles the headers`X-Real-IP`, `X-Forwarded-For`, `X-Forwarded-Proto`, `X-Forwarded-Host`, and

the chain to those headers. This is the default setting.
as if the the Kong Gateway was not a proxy.
g Gateway was the originating client.

nd will ignore headers from the last hop in the chain if they are not from clients with trusted IPs.

  - `append`: append information from this hop in the chain to those headers. This is the default setting.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - `transparent`: leave the headers unchanged, as if the the Kong Gateway was not a proxy.
    - `delete`: remove all the headers, as if the Kong Gateway was the originating client.

- **Proxy Cache Advanced**:
    - Added support for integrating with Redis clusters through the `config.redis.cluster_addresses` configuration property.
- **mTLS Authentication**:
    - Added the `config.send_ca_dn` configuration parameter to support sending CA DNs in the `CertificateRequest` message during SSL handshakes.
    - Added the `allow_partial_chain` configuration parameter to allow certificate verification with only an intermediate certificate.
- **Authentication plugins**:
    - The `anonymous` field can now be configured as the username of the consumer. This field allows you to configure a string to use as an "anonymous" consumer if authentication fails.
- acme:
    - Added support for Redis SSL, through configuration properties`config.storage_config.redis.ssl`, `config.storage_config.redis.ssl_verify`, and `config.storage_config.redis.ssl_server_name`.#9626
- app-dynamics:
    - Integrate Kong Gateway with the AppDynamics APM Platform.
- aws-lambda:
    - Added `requestContext` field into `awsgateway_compatible` input data#9380
- jwe-decrypt:
    - Allows you to decrypt an inbound token (JWE) in a request.
- mocking:
    - Added the `included_status_codes` and `random_status_code` fields. These allow you to configure the HTTP status codes for the plugin.
    - The plugin now lets you auto-generate a random response based on the schema definition without defining examples.
    - You can now control behavior or obtain a specific response by sending behavioral headers: `X-Kong-Mocking-Delay`, `X-Kong-Mocking-Example-Id`, and `X-Kong-Mocking-Status-Code`.
    - This plugin now supports:
        - MIME types priority match
        - All HTTP codes
        - `$ref`
    - MIME types priority match
    - All HTTP codes
    - `$ref`
- oas-validation:
    - Validate HTTP requests and responses based on an OpenAPI 3.0 or Swagger API Specification.
- opa:

field. When this field is set to true, the regex capture groups captured on the Kong Gateway route's path
nput to OPA.

that could be stored in vaults.#9611

the API.

er to count `429` or not in sliding window mode.

imited requests can now be customized. Thanks, @utix! #8930

and arrays when transforming a JSON payload.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- request-validator:
  - The plugin now supports the `charset` option for the`config.allowed_content_types` parameter.
- response-ratelimiting:
  - Added support for Redis SSL through configuration properties`redis_ssl` (can be set to `true` or `false`), `ssl_verify`, and `ssl_server_name`. Thanks, @dominikkukacka! #8595
- route-transformer-advanced:
  - Added the `config.escape_path` configuration parameter, which lets you escape the transformed path.
- saml:
  - Provides SAML v2.0 authentication and authorization between a service provider (Kong Gateway) and an identity provider (IdP).
- session:
  - Added new config `cookie_persistent`, which allows the browser to persist cookies even if the browser is closed. This defaults to `false` which means cookies are not persisted across browser restarts. Thanks @tschaumefor this contribution! #8187
- vault-auth:
  - Added support for KV Secrets Engine v2.
- xml-threat-protection:
  - This new plugin allows you to reduce the risk of XML attacks by checking the structure of XML payloads. This validates maximum complexity (depth of the tree), maximum size of elements and attributes.
- zipkin:
  - Added the `response_header_for_traceid` field in Zipkin plugin. The plugin sets the corresponding header in the response if the field is specified with a string value.#9173
- WebSocket service/route support was added for logging plugins: http-log
- WebSocket service/route support was added for logging plugins: file-log
- WebSocket service/route support was added for logging plugins: udp-log
- WebSocket service/route support was added for logging plugins: tcp-log
- WebSocket service/route support was added for logging plugins: loggly
- WebSocket service/route support was added for logging plugins: syslog
- WebSocket service/route support was added for logging plugins: kafka-log

Bugfix

Core

- Fixed an issue where the RBAC token was not re-hashed after an update on the `user_token` field.
- Fixed an issue where `admin_gui_auth_conf` wouldn't accept a JSON-formatted value, and was therefore unable to use vault references to secrets.
- Fixed an issue where Admin GUI logs were not stored in the correct log file.
- Fixed an issue where Kong Gateway was unable to start in free Enterprise mode while using vaults.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

h checks, and checking their status via the `upstreams/<upstream>/health` endpoint results in the status
`m>/health` endpoint was incorrectly reporting targets with `weight=0` as `HEALTHY`, and the health check was

`200` when the database is down.

ane to the data plane using the Admin API `/licenses` endpoint.

ion would fail when the license entity was not processed first.

eway redirects `ws`requests to `wss` for `wss`-only routes for parity with HTTP/HTTPS.

was occasionally unusable.
Kong Manager.
n the suggestion list when there were many items present.
n Kong Manager.
- Fixed an issue where admins with permissions to interact with scoped entities, such as routes and services, couldn't perform operations as expected.

  - Fixed an issue where admins with the `/admins` permission were forced to log out after signing in.
  - Fixed a performance issue where admins with a large number of workspace permissions caused Kong Manager to load slowly.

- Fixed an issue where external plugins crashing with unhandled exceptions would cause high CPU utilization after the automatic restart.#9384
- Added `use_srv_name` options to upstream for balancer.#9430
- Fixed an issue in `header_filter` instrumentation where the span was not correctly created.#9434
- Fixed an issue in router building in `traditional_compatible` mode. When the field contained an empty table, the generated expression was invalid.#9451
- Fixed an issue in router rebuilding where when the `paths` field is invalid, the router's mutex is not released properly.#9480
- Fixed an issue where `kong docker-start` would fail if `KONG_PREFIX` was set to a relative path.#9337
- Fixed an issue with error-handling and process cleanup in `kong start`.#9337
- Fixed issue with prefix path normalization.#9760
- Increased the maximum request argument number of the Admin API from 100 to 1000. The Admin API now returns a `400` error if request parameters reach the limitation instead of truncating any parameters over the limit.#9510
- Paging size parameter is now propagated to next page if specified in current request.#9503

hybrid-mode

- Fixed a race condition that could cause configuration push events to be dropped when the first data plane connection was established with a control plane worker.#9616

cli

- Fixed slow CLI performance due to pending timer jobs.#9536

PDK

- Added support for `kong.request.get_uri_captures`(`kong.request.getUriCaptures`)#9512
- Fixed parameter type of `kong.service.request.set_raw_body`(`kong.service.request.setRawBody`), return type of`kong.service.response.get_raw_body`(`kong.service.request.getRawBody`), and body parameter type of `kong.response.exit` to bytes. Note that the old version of the go PDK is incompatible after this change.#9526

Plugin

- **Proxy Cache Advanced**:
  - The plugin now catches the error when Kong Gateway connects to Redis SSL port `6379` with `config.ssl=false`.
- aws-lambda:
  - Fixed an issue that was causing inability to read environment variables in ECS environment.#9460
  - Specifying a null value for the `isBase64Encoded` field in lambda output now results in a more obvious error log entry with a `502` code.#9598
- azure-functions:
  - Fixed an issue where calls made by this plugin would fail in the following situations:
    - The plugin was associated with a route that had no service.
    - The route's associated service had a `path` value.#9177

service.

77

include `queue_size` and `flush_timeout`.#9789

and not working with wildcards. The `;q=` (q-factor weighting) of `accept` headers is now supported.

in.

was not configured to `w3c` correctly.#9457

eue to avoid data race.#9504

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Fixed an issue that the `parent_id` was not set on the span when propagating w3c traceparent.#9628

- rate-limiting-advanced:
  - The plugin now ensures that shared dict TTL is higher than `config.sync_rate`, otherwise Kong Gateway would lose all request counters in shared dict.
- request-termination:
  - The plugin no longer allows setting `status_code` to `null`.#9400
- request-transformer:
  - Fixed a bug when header renaming would override the existing header and cause unpredictable results.#9442
- response-transformer:
  - Fixed the bug that the plugin would break when receiving an unexpected body.#9463
- zipkin:
  - Fixed an issue where Zipkin plugin couldn't parse OT baggage headers due to an invalid OT baggage pattern.#9280
- Added the missing `protocols` field to the following plugin schemas: Azure Functions (`azure-functions`)
- Added the missing `protocols` field to the following plugin schemas: gRPC Gateway (`grpc-gateway`)
- Added the missing `protocols` field to the following plugin schemas: gRPC Web (`grpc-web`)
- Added the missing `protocols` field to the following plugin schemas: Serverless pre-function (`pre-function`)
- Added the missing `protocols` field to the following plugin schemas: Prometheus (`prometheus`)
- Added the missing `protocols` field to the following plugin schemas: Proxy Caching (`proxy-cache`)
- Added the missing `protocols` field to the following plugin schemas: Request Transformer (`request-transformer`)
- Added the missing `protocols` field to the following plugin schemas: Session (`session`)
- Added the missing `protocols` field to the following plugin schemas: Zipkin (`zipkin`)

Known Issues

Core

- With Dynamic log levels, if you set log-level to `alert` you will still see `info` and `error` entries in the logs.

Breaking Change

hybrid-mode

- The legacy hybrid configuration protocol has been removed in favor of the wRPC protocol introduced in 3.0.0.0. Rolling upgrades from 2.8.x.y to 3.1.0.0 are not supported. Operators must upgrade to 3.0.x.x before they can perform a rolling upgrade to 3.1.0.0. For more information, see Upgrade Kong Gateway 3.1.x.#9740

3.0.1.0

Release date 2022/11/02

Feature

P

nfiguration are now referenceable, which means they can be stored as secrets in a vault.

E

C

ateway Docker image. Previously, the version was pinned to 3.10, which was creating outdated `alpine`

The code was previously using `ngx.config.prefix()` to determine the listening socket path to provide to
x was started with a relative path prefix. This meant that you couldn't start 3.0.x with the same default

shiCorp Vault. By default, Kong passes secrets to the Nginx using environment variables when using `kong
ong start`, so the secrets were not available at initialization. #9478:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed the Amazon Linux RPM installation instructions.:

Kong Manager

- Removed the endpoint `all_routes` from configurable RBAC endpoint permissions. This endpoint was erroneously appearing in the endpoints list, and didn't configure anything.:
- Fixed an issue that allowed unauthorized IDP users to log in to Kong Manager. These users had no access to any resources in Kong Manager, but were able to go beyond the login screen.:
- Fixed an issue where, in an environment with a valid Enterprise license, admins with no access to the `default` workspace would see a message prompting them to upgrade to Kong Enterprise.:
- Fixed pagination issues with Kong Manager tables.:
- Fixed broken `Learn more` links.:
- Fixed an issue with group to role mapping, where it didn't support group names with spaces.:
- Fixed the Cross Site Scripting (XSS) security vulnerability in the Kong Manager UI.:
- Fixed an RBAC issue where permissions applied to specific endpoints (for example, an individual service or route) were not reflected in the Kong Manager UI.:
- Removed New Relic from Kong Manager. Previously, `VUE_APP_NEW_RELIC_LICENSE_KEY` and`VUE_APP_SEGMENT_WRITE_KEY` were being exposed in Kong Manager with invalid values.:
- Removed the action dropdown menu on service and route pages for read-only users.:
- Fixed the **Edit Configuration** button for Dev Portal applications.:
- Fixed an RBAC issue where the roles page listed deleted roles.:
- Fixed an issue where the orphaned roles would remain after deleting a workspace and cause the **Teams** > **Admins** page to break.:
- Added the missing **Copy JSON** button for plugin configuration.:
- Fixed an issue where the **New Workspace** button on the global workspace dashboard wasn't clickable on the first page load.:
- Removed the ability to add multiple documents per service from the UI. Each service only supports one document, so the UI now reflects that.:
- The Upstream Timeout plugin now has an icon and is part of the Traffic Control category.:
- Fixed an error that would occur when attempting to delete ACL credentials from the consumer credentials list. This happened because the name of the plugin, `acl`, and its endpoint, `/acls`, don't match.:
- Fixed a caching issue with Dev Portal, where enabling or disabling the Dev Portal for a workspace wouldn't change the Kong Manager menu.:

3.0.0.0

Release date 2022/09/09

Feature

Core

- Kong Gateway now supports dynamic plugin ordering. You can change a plugin's static priority by specifying the order in which plugins run. This lets you run plugins such as `rate-limiting` before authentication plugins.
- Kong Gateway now offers a FIPS package. The package replaces the primary library, OpenSSL, with BoringSSL, which at its core uses the FIPS 140-2 compliant

supported in Ubuntu 20.04.

rently compatible with SSL connections to PostgreSQL.

ionality. Websockets are a type of persistent connection that works on top of HTTP.

ket connections, where plugins only ran during the initial connection phase instead of for each frame. Now, affic by implementing plugins that target WebSocket frames.

ocket Validator
feature)
ng.websocket.upstream

development guide.

esign and improved user experience.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

Notable changes:

  - Reworked workspace dashboards, both for specific workspaces and at the multi-workspace level.
  - License metrics now appear at the top of overview pages.
  - Restructured the layout and navigation to make workspace selection a secondary concern.
  - Grayed out portal buttons when you don't have permissions.
  - Added license level to phone home metrics.
  - Added more tooltips.

- Secrets management is now generally available.

  - Added GCP integration support for the secrets manager. GCP is now available as a vault backend.
  - The `/vaults-beta` entity has been deprecated and replaced with the `/vaults` entity.#8871#9217

- Kong Gateway now provides slim and UBI images. Slim images are docker containers built with a minimal set of installed packages to run Kong Gateway. From 3.0 onward, Kong Docker images will only contain software required to run the Gateway. This ensures that false positive vulnerabilities don't get flagged during security scanning.

  If you want to retain or add other dependencies, you can build custom Kong Docker images.

- The base OS for our convenience docker tags (for example, `latest`, `3.0.0.0`, `3.0`) has switched from Alpine to Debian.

- Added key recovery for keyring encryption. This exposes a new endpoint for the Admin API, `/keyring/recover`, and requires `keyring_recovery_public_key` to be set in `kong.conf`.

- You can now encrypt declarative configuration files on data planes in DB-less and hybrid modes using AES-256-GCM or chacha20-poly1305 encryption algorithms.

  Set your desired encryption mode with the `declarative_config_encryption_mode` configuration parameter.

- This release introduces a new router implementation: `atc-router`. This router is written in Rust, a powerful routing language that can handle complex routing requirements. The new router can be used in traditional-compatible mode, or use the new expression-based language.

  With the new router, we have:

  - Reduced router rebuild time when changing Kong's configuration
  - Increased runtime performance when routing requests
  - Reduced P99 latency from 1.5s to 0.1s with 10,000 routes

  Learn more about the router:

  - Configure routes using expressions
  - Router Expressions Language reference
  - #8938

- Implemented delayed response in stream mode.#6878

- Added `cache_key` on target entity for uniqueness detection.#8179

- Introduced the tracing API, which is compatible with OpenTelemetry API specs, and adds built-in instrumentations.

  The tracing API is intended to be used with a external exporter plugin. Built-in instrumentation types and sampling rate are configurable through the`opentelemetry_tracing` and `opentelemetry_tracing_sampling_rate` options.#8724

- Added `path`, `uri_capture`, and `query_arg` options to upstream `hash_on`for load balancing.#8701

- Introduced Unix domain socket-based `lua-resty-events` to replace shared memory-based `lua-resty-worker-events`.#8890

- Introduced the `table_name` field for entities. This field lets you specify a table name. Previously, the name was deduced by the entity `name` attribute.#9182

- Added `headers` on active health checks for upstreams.#8255

- were not needed. Now when a target is removed or updated, the DNS record associated with it is removed

- code.#8902

- an shutdown by detecting and removing dangling Unix sockets in the prefix directory.#9254

- tes the migration status in a JSON file.

- ns_order.

- ers on hybrid mode control plane nodes anymore. #8452.

- t for the plugin server.#8912

- g `additional_section` by default.#8895

- mplementation. It doesn't fetch all headers every time it's called.#8716

- balancer on data planes.#8519,#8671

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Made configuration loading code more cooperative by yielding.#8888
- Use the LuaJIT encoder instead of JSON to serialize values faster in LMDB.#8942
- Made inflating and JSON decoding non-concurrent, which avoids blocking and makes data plane reloads faster.#8959
- Stopped duplication of some events.#9082
- Improved performance of configuration hash calculation by using `string.buffer` and `tablepool`.#9073
- Reduced cache usage in DB-less mode by not using the Kong cache for routes and services in LMDB.#8972

Admin API

- Added a new `/timers` Admin API endpoint to get timer statistics and worker info.#8912#8999
- The `/` endpoint now includes plugin priority.#8821

hybrid-mode

- Added wRPC protocol support. Configuration synchronization now happens over wRPC. wRPC is an RPC protocol that encodes with ProtoBuf and transports with WebSocket.#8357
  - To keep compatibility with earlier versions, added support for the control plane to fall back to the previous protocol to support older data planes.#8834
  - Added support to negotiate services supported with wRPC protocol. We will support more services in the future.#8926
- Declarative configuration exports now happen inside a transaction in PostgreSQL.#8586

Plugin

- **mTLS Authentication**:
  - Introduced certificate revocation list (CRL) and OCSP server support with the following parameters: `http_proxy_host`, `http_proxy_port`, `https_proxy_host`, and `https_proxy_port`.
- acme:
  - Added the `allow_any_domain` field. It defaults to false and if set to true, the gateway will ignore the `domains` field.#9047
- aws-lambda:
  - Added support for cross-account invocation through the `aws_assume_role_arn` and`aws_role_session_name` configuration parameters.#8900
  - The plugin now accepts string type `statusCode` as a valid return when working in proxy integration mode.#8765
  - The plugin now separates AWS credential cache by the IAM role ARN.#8907
- degraphql:
  - The GraphQL server path is now configurable with the `graphql_server_path` configuration parameter.
- kafka-upstream:
  - Added support for the `SCRAM-SHA-512` authentication mechanism.
- ldap-auth-advanced:
  - This plugin now allows authorization based on group membership. The new configuration parameter, `groups_required`, is an array of string elements that indicates the groups that users must belong to for the request to be authorized.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

d.

pa_input: When enabled, include the raw body as a string in the OPA input at input.request.http.body
ize.

on_body_in_opa_input: When enabled and content-type is application/json, the parsed JSON will be
arsed_body.

ream_current_connections were merged into to nginx_hconnections_total (or

d into http_requests_total.

sumer label will be empty. If the per_consumer config is true, the consumer label will be filled.

ed with Kong

- statsd:
  - **Newly open-sourced plugin capabilities** : All capabilities of the StatsD Advanced plugin are now bundled in the StatsD plugin.#9046
- zipkin:
  - Added support for including the HTTP path in the span name with the`http_span_name` configuration parameter.#8150
  - Added support for socket connect and send/read timeouts through the `connect_timeout`, `send_timeout`, and `read_timeout` configuration parameters. This can help mitigate`ngx.timer` saturation when upstream collectors are unavailable or slow.#8735
- Starting with version 3.0, all bundled plugin versions are the same as the Kong Gateway version.#8772:

  Plugin documentation now refers to the Kong Gateway version instead of the individual plugin version.
- New plugins:
  - opentelemetry: Export tracing instrumentations to any OTLP/HTTP compatible backend.`opentelemetry_tracing` configuration must be enabled to collect the core tracing spans of Kong Gateway.#8826
  - **TLS Handshake Modifier**: Make certificates available to other plugins acting on the same request.
  - **TLS Metadata Headers**: Proxy TLS client certificate metadata to upstream services via an HTTP headers.
  - **WebSocket Size Limit**: Allows operators to specify a maximum size for incoming WebSocket messages.
  - **WebSocket Validator**: Validate individual WebSocket messages against a user-specified schema before proxying them.
- Collector (`collector`): The deprecated Collector plugin has been removed.

Configuration

- You can now configure `openresty_path` to allow developers and operators to specify the OpenResty installation to use when running Kong Gateway, instead of using the system-installed OpenResty.#8412
- Added `ipv6only` to listen options `admin_listen`, `proxy_listen`, and `stream_listen`.#9225
- Added `so_keepalive` to listen options `admin_listen`, `proxy_listen`, and `stream_listen`.#9225
- Add LMDB DB-less configuration persistence and removed the JSON-based configuration cache for faster startup time.#8670
- `nginx_events_worker_connections=auto` now has a lower bound of 1024.#9276
- `nginx_main_worker_rlimit_nofile=auto` now has a lower bound of 1024.#9276

PDK

- Added new PDK function: `kong.request.get_start_time()`. This function returns the request start time, in Unix epoch milliseconds.#8688
- The function `kong.db.*.cache_key()` now falls back to `.id` if nothing from `cache_key` is found.#8553

Bugfix

Core

- Fixed an issue with keyring encryption, where the control plane would crash if any errors occurred during the initialization of the keyring module.
- Fixed an issue where the keyring module was not decrypting keys after a soft reload.
- Fixed pagination issues:
  - Fixed a consumer pagination issue.
  - Fixed an issue that appeared when loading the second page while iterating over a foreign key field using the DAO.#9255

arting a control plane.

he data plane.
t in the telemetry request query parameter.

viously, a dashboard with no request data and an existing service would still prompt users to add a service.
tion of metrics not supported by the Datadog plugin.
on in Kong Manager. Previously, fields that were supposed to accept decimals would only accept whole

re-function plugin configuration when the updated value contained a comma (,).
ge now correctly shows the service display name. Previously, it showed the service ID.
ate, the page wouldn't return to the certificate view.
service URL on the service overview page.
dashboard pages would not update the Dev Portal URL.

ua functions added through Kong Manager.
y for the `config.origins` field.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

        - The Datadog plugin now accepts an array for the `tags` field. Previously, it was incorrectly expecting a string.
    - Fixed an `HTTP 500` error that occurred when sorting routes by the **Hosts** column, then clicking **Next** on a paginated listing.
    - Fixed an issue that prevented developer role assignments from displaying in Kong Manager. When viewing a role under the Permissions tab in the Dev Portal section, the list of developers wouldn't update when a new developer was added. Kong Manager was constructing the wrong URL when retrieving Dev Portal assignees.
    - Fixed an issue where admins couldn't switch workspaces if they didn't have an roles in the default workspace.
    - Fixed a display issue with Dev Portal settings in Kong Manager.
    - Improved the error that appeared when trying to view admin roles without permissions for the resource. Instead of displaying `404 workspace not found`, the error now informs the user that they don't have access to view roles.

- Fixed an issue where the data plane would reload and lose its license after an Nginx reload.
- Fixed issues in dependencies:
    - `kong-gql`: Fixed variable definitions to handle non-nullable/list-type variables correctly.
    - `lua-resty-openssl-aux-module`: Fixed an issue with getting `SSL_CTX` from a request.
- The schema validator now correctly converts `null` from declarative configurations to `nil`.#8483
- Kong now reschedules router and plugin iterator timers only after finishing the previous execution, avoiding unnecessary concurrent executions.#8567
- External plugins now handle returned JSON with null member correctly.#8611
- Fixed an issue where the address of an environment variable could change but the code didn't check that it was fixed after init.#8581
- Fixed an issue where the Go plugin server instance would not be updated after a restart.#8547
- Fixed an issue on trying to reschedule the DNS resolving timer when Kong was being reloaded.#8702
- The private stream API has been rewritten to allow for larger message payloads.#8641
- Fixed an issue that the client certificate sent to the upstream was not updated when using the `PATCH` method.#8934
- Fixed an issue where the control plane and wRPC module interaction would cause Kong to crash when calling `export_deflated_reconfigure_payload` without a `pcall`.#8668
- Moved all `.proto` files to `/usr/local/kong/include` and ordered by priority.#8914
- Fixed an issue that caused unexpected 404 errors when creating or updating configs with invalid options.#8831
- Fixed an issue that caused crashes when calling some PDK APIs.#8604
- Fixed an issue that caused crashes when go PDK calls returned arrays.#8891
- Plugin servers now shutdown gracefully when Kong exits.#8923
- CLI now prompts with `[y/n]` instead of `[Y/n]`, as it does not take `y` as default.#9114
- Improved the error message that appears when Kong can't connect to Cassandra on init.#8847
- Fixed an issue where the Vault subschema wasn't loaded in the `off` strategy.#9174
- The schema now runs select transformations before `process_auto_fields`.#9049
- Fixed an issue where Kong Gateway would use too many timers to keep track of upstreams when `worker_consistency = eventual`.#8694,#8858
- Fixed an issue where it wasn't possible to set target status using only a hostname for targets set only by their hostname.#8797
- Fixed an issue where cache entries of some entities were not being properly invalidated after a cascade delete.#9261
- Running `kong start` when Kong Gateway is already running no longer overwrites the existing `.kong_env` file #9254

A

P

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

tatus.#8690

and Access-Control-Allow-Methods headers with OPTIONS requests.

ect base64 encoding.

host header.

rs.

ar.uri.#8558

- Fixed the handling of boolean fields from URI arguments.#9180

- acme:
  - The default value of the `auth_method` configuration parameter is now set to `token`.#8565
  - Added a cache for `domains_matcher`.#9048
- aws-lambda:
  - Removed the deprecated `proxy_scheme` field from the plugin's schema.#8566
  - Changed the path from `request_uri` to `upstream_uri` to fix an issue where the URI could not follow a rule defined by the Request Transformer plugin.#9058 #9129
- http-log:
  - Log output is now restricted to the workspace the plugin is running in. Previously, the plugin could log requests from outside of its workspace.
- ldap-auth-advanced:
  - Fixed an issue where Kong Manager LDAP authentication failed when `base_dn` was the domain root.
- ldap-auth:
  - Refactored ASN.1 parser using OpenSSL API through FFI.#8663
- mocking:
  - Fixed an issue where `204` responses were not handled correctly and you would see the following error:`"No examples exist in API specification for this resource"`.
  - `204` response specs now support empty content elements.
- openid-connect:
  - Fixed an issue with `kong_oauth2` consumer mapping.
- pre-function:
  - Fixed a problem that could cause a crash.#9269
- rate-limiting-advanced:
  - Fixed error handling when calling `get_window` and added more buffer on the window reserve.
  - Fixed error handling for plugin strategy configuration when in hybrid or DB-less mode and strategy is set to `cluster`.
- rate-limiting:
  - Fixed a PostgreSQL deadlock issue that occurred when the `cluster` policy was used with two or more metrics (for example, `second` and `day`.)#8968
- syslog:
  - The `conf.facility` default value is now set to `user`.#8564
- zipkin:
  - Fixed the balancer spans' duration to include the connection time from Nginx to the upstream.#8848
  - Corrected the calculation of the header filter start time.#9230
  - Made the plugin compatible with the latest Jaeger header spec, which makes `parent_id` optional.#8352

orting based on their name.#8957

tter when a plugin instance loses the `instances_id` in an event handler.#8652

og for its log file instead of `proxy_error_log`.#8583

role before setting a value in cache at startup. #9060

to `enabled: false` and that service had a route with an enabled plugin, any new data planes would

n the new yielding config loading code.#8188

ead of an exit when plugin throws a runtime exception in the access phase.#8599

- `kong.tools.uri.normalize()` now escapes reserved and unreserved characters more accurately.#8140

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- RFC3987 validation on route paths was removed, allowing operators to create a route with an invalid path URI like `/something|` which can not match any incoming request. This validation will be added back in a future release.

Dependency

Core

- Bumped `openresty` from 1.19.9.1 to 1.21.4.1#8850
- Bumped `pgmoon` from 1.13.0 to 1.15.0#8908#8429
- Bumped `openssl` from 1.1.1n to 1.1.1q#9074#8544#8752#8994
- Bumped `resty.openssl` from 0.8.8 to 0.8.10#8592#8753#9023
- Bumped `inspect` from 3.1.2 to 3.1.3#8589
- Bumped `resty.acme` from 0.7.2 to 0.8.1#8680#9165
- Bumped `luarocks` from 3.8.0 to 3.9.1#8700#9204
- Bumped `luasec` from 1.0.2 to 1.2.0#8754#8754
- Bumped `resty.healthcheck` from 1.5.0 to 1.6.1#8755#9018#9150
- Bumped `resty.cassandra` from 1.5.1 to 1.5.2#8845
- Bumped `penlight` from 1.12.0 to 1.13.1#9206
- Bumped `lua-resty-mlcache` from 2.5.0 to 2.6.0#9287
- Bumped `lodash` for Dev Portal from 4.17.11 to 4.17.21
- Bumped `lodash` for Kong Manager from 4.17.15 to 4.17.21

Breaking Change

Plugin

- **Deprecated** :
  - The StatsD Advanced plugin has been deprecated and will be removed in 4.0. All capabilities are now available in the StatsD plugin.
- acl:
  - Removed the deprecated `blacklist` and `whitelist` configuration parameters. #8560
- acme:
  - The default value of the `auth_method` configuration parameter is now `token`.
- aws-lambda:
  - The AWS region is now required. You can set it through the plugin configuration with the `aws_region` field parameter, or with environment variables.
  - The plugin now allows `host` and `aws_region` fields to be set at the same time, and always applies the SigV4 signature.#8082
- http-log:
  - The `headers` field now only takes a single string per header name, where it previously took an array of values.#6992

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

nx context (`ngx.ctx.authenticated_jwt_token`). Custom plugins which depend on that value being set
red context instead (`kong.ctx.shared.authenticated_jwt_token`) before upgrading to 3.0.

guration parameter from the Serverless Functions plugins' schemas. Use the `config.access` phase

lt.

en collecting metrics.

ong_upstream_latency_ms, `kong_kong_latency_ms`, and `session_duration_ms` (stream).

rders of different magnitudes. Separate these buckets to reduce memory overhead.

  - `kong_bandwidth` to `kong_bandwidth_bytes`.
  - Removed the following metric: `http_consumer_status`
  - New metrics:
    - `session_duration_ms`: monitoring stream connections.
    - `node_info`: Single gauge set to 1 that outputs the node's ID and Kong Gateway version.
  - `session_duration_ms`: monitoring stream connections.
  - `node_info`: Single gauge set to 1 that outputs the node's ID and Kong Gateway version.
  - `http_requests_total` has a new label, `source`. It can be set to `exit`, `error`, or `service`.
  - All memory metrics have a new label: `node_id`.
  - The following metric names were adjusted to add units to standardize where possible:
    - `http_status` to `http_requests_total`.
    - `latency` to `kong_request_latency_ms` (HTTP), `kong_upstream_latency_ms`, `kong_kong_latency_ms`, and `session_duration_ms` (stream).

    Kong latency and upstream latency can operate at orders of different magnitudes. Separate these buckets to reduce memory overhead.
    - `kong_bandwidth` to `kong_bandwidth_bytes`.
    - `nginx_http_current_connections` and `nginx_stream_current_connections` were merged into to `nginx_connections_total`.
    - `request_count` and `consumer_status` were merged into `http_requests_total`.

    If the `per_consumer` config is set to `false`, the `consumer` label will be empty. If the `per_consumer` config is `true`, the `consumer` label will be filled.
  - `nginx_http_current_connections` and `nginx_stream_current_connections` were merged into to `nginx_connections_total`.
  - `request_count` and `consumer_status` were merged into `http_requests_total`.

    If the `per_consumer` config is set to `false`, the `consumer` label will be empty. If the `per_consumer` config is `true`, the `consumer` label will be filled.
  - Updated the Grafana dashboard that comes packaged with Kong#8712
  - The plugin doesn't export status codes, latencies, bandwidth and upstream health check metrics by default. They can still be turned on manually by setting `status_code_metrics`,`lantency_metrics`, `bandwidth_metrics` and `upstream_health_metrics` respectively.#9028

- proxy-cache:
  - These plugins don't store response data in `ngx.ctx.proxy_cache_hit` anymore. Logging plugins that need the response data must now read it from `kong.ctx.shared.proxy_cache_hit`.#8607
- rate-limiting:
  - The default policy is now local for all deployment modes.#9344
- statsd:
  - Any metric name that is related to a service now has a `service.` prefix: `kong.service.<service_identifier>.request.count`.
    - The metric `kong.<service_identifier>.request.status.<status>` has been renamed to `kong.service.<service_identifier>.status.<status>`.
    - The metric `kong.<service_identifier>.user.<consumer_identifier>.request.status.<status>` has been renamed to `kong.service.<service_identifier>.user.<consumer_identifier>.status.<status>`.
  - The metric `kong.<service_identifier>.request.status.<status>` has been renamed to `kong.service.<service_identifier>.status.<status>`.
  - The metric `kong.<service_identifier>.user.<consumer_identifier>.request.status.<status>` has been renamed to `kong.service.<service_identifier>.user.<consumer_identifier>.status.<status>`.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

cs `status_count` and `status_count_per_user` has been removed.

oading order is explicit. Loading them in a hash-like table is no longer supported.#8988

VERSION` ("x.y.z" format) field in their `handler.lua` file, otherwise the plugin will fail to load.#8836

was removed in favor of the PDK function `kong.log.serialize`. Upgrade your plugins to use the

moved. If your custom plugins still use the old (`0.x era`) schemas, you are now forced to upgrade

m `1007` to `1705`

ged from `1001` to `1100`

rom `13` to `20`

ed from `1005` to `1500`

`ache-advanced` changed from `100` to `99`

- Updated the priority for some plugins.: `hmac-auth` changed from `1000` to `1030`
- Updated the priority for some plugins.: `jwt` changed from `1005` to `1450`
- Updated the priority for some plugins.: `jwt-signer` changed from `999` to `1020`.
- Updated the priority for some plugins.: `key-auth` changed from `1003` to `1250`
- Updated the priority for some plugins.: `key-auth-advanced` changed from `1003` to `1250`
- Updated the priority for some plugins.: `ldap-auth` changed from `1002` to `1200`
- Updated the priority for some plugins.: `ldap-auth-advanced` changed from `1002` to `1200`
- Updated the priority for some plugins.: `mtls-auth` changed from `1006` to `1600`
- Updated the priority for some plugins.: `oauth2` changed from `1004` to `1400`
- Updated the priority for some plugins.: `openid-connect` changed from `1000` to `1050`
- Updated the priority for some plugins.: `rate-limiting` changed from `901` to `910`
- Updated the priority for some plugins.: `rate-limiting-advanced` changed from `902` to `910`
- Updated the priority for some plugins.: `route-by-header` changed from `2000` to `850`
- Updated the priority for some plugins.: `route-transformer-advanced` changed from `800` to `780`
- Updated the priority for some plugins.: `pre-function` changed from `+inf` to `1000000`
- Updated the priority for some plugins.: `vault-auth` changed from `1003` to `1350`
- Kong plugins no longer support `CREDENTIAL_USERNAME` (`X-Credential-Username`). Use the constant `CREDENTIAL_IDENTIFIER` (`X-Credential-Identifier`) when setting the upstream headers for a credential.#8815

deployment

- Deprecated and stopped producing Amazon Linux 1 containers and packages. Amazon Linux 1 reached end-of-life on December 31, 2020.Kong/docs.konghq.com #3966
- Deprecated and stopped producing Debian 8 (Jessie) containers and packages. Debian 8 reached end-of-life in June 30, 2020.Kong/kong-build-tools #448

Core

- As of 3.0, Kong Gateway's schema library's `process_auto_fields` function will not make deep copies of data that is passed to it when the given context is `select`. This was done to avoid excessive deep copying of tables where we believe the data most of the time comes from a driver like `pgmoon` or `lmdb`.

  If a custom plugin relied on `process_auto_fields` not overriding the given table, it must make its own copy before passing it to the function now.#8796
- The deprecated `shorthands` field in Kong plugin or DAO schemas was removed in favor of the typed `shorthand_fields`. If your custom schemas still use `shorthands`, you need to update them to use `shorthand_fields`.#8815
- The support for `legacy = true/false` attribute was removed from Kong schemas and Kong field schemas.#8958
- The deprecated alias of `Kong.serve_admin_api` was removed. If your custom Nginx templates still use it, change it to `Kong.admin_content`.#8815
- The Kong singletons module `kong.singletons` was removed in favor of the PDK `kong.*`.#8874
- The data plane configuration cache was removed. Configuration persistence is now done automatically with LMDB.#8704
- `ngx.ctx.balancer_address` was removed in favor of `ngx.ctx.balancer_data`.#9043

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ong Gateway now stores the unnormalized path, but the regex path always pattern-matches with the
cent-encoding in the regex path pattern to ensure different forms of URI matches. That is no longer
c3986, write all other characters without percent-encoding.#9024

r a `route.path` is a regex pattern. From 3.0 onward, all regex paths must start with the `"~"` prefix, and all
t. The migration process should automatically convert the regex paths when upgrading from 2.x to

rative configuration to `3.0` for changes on `route.path`. Declarative configurations using older versions are

n files from 2.8 or earlier to 3.0. Old configuration files will overwrite the configuration and create
tion, `deck dump` the 3.0 file after migrations are completed.

d as of `3.0` and will be removed from Kong in `4.0` (see the Known Limitations section for additional

- We removed regex look-around and backreferences support in the the atc-router. These are rarely used features and removing support for them improves the speed of our regex matching. If your current regexes use look-around or backreferences you will receive an error when attempting to start Kong, showing exactly what regex is incompatible. Users can either switch to the `traditional` router flavor or change the regex to remove look-around / backreferences.

Admin API

- The Admin API endpoint `/vitals/reports` has been removed.
- `POST` requests on `/targets` endpoints are no longer able to update existing entities. They are only able to create new ones.#8596,#8798. If you have scripts that use`POST` requests to modify `/targets`, change them to `PUT`requests to the appropriate endpoints before updating to Kong Gateway 3.0.
- Insert and update operations on duplicated targets return a `409` error.#8179,#8768
- The list of reported plugins available on the server now returns a table of metadata per plugin instead of a boolean `true`.#8810

PDK

- The `kong.request.get_path()` PDK function now performs path normalization on the string that is returned to the caller. The raw, non-normalized version of the request path can be fetched via `kong.request.get_raw_path()`.#8823
- `pdk.response.set_header()`, `pdk.response.set_headers()`, `pdk.response.exit()` now ignore and emit warnings for manually set `Transfer-Encoding` headers.#8698
- The PDK is no longer versioned.#8585
- The JavaScript PDK now returns `Uint8Array` for `kong.request.getRawBody`,`kong.response.getRawBody`, and `kong.service.response.getRawBody`. The Python PDK returns `bytes` for `kong.request.get_raw_body`,`kong.response.get_raw_body`, and `kong.service.response.get_raw_body`. Previously, these functions returned strings.#8623
- The `go_pluginserver_exe` and `go_plugins_dir` directives are no longer supported. #8552. If you are using Go plugin server, migrate your plugins to use the Go PDK before upgrading.

Configuration

- The Kong constant `CREDENTIAL_USERNAME` with the value of `X-Credential-Username` has been removed.#8815
- The default value of `lua_ssl_trusted_certificate` has changed to `system`#8602 to automatically load the trusted CA list from the system CA store.
- It is no longer possible to use a `.lua` format to import a declarative configuration file from the `kong`CLI tool. Only JSON and YAML formats are supported. If your update procedure with Kong Gateway involves executing `kong config db_import config.lua`, convert the `config.lua` file into a `config.json` or `config.yml` file before upgrading.#8898
- The data plane config cache mechanism and its related configuration options (`data_plane_config_cache_mode` and `data_plane_config_cache_path`) have been removed in favor of LMDB.

migrations

- The migration helper library (mostly used for Cassandra migrations) is no longer supplied with Kong Gateway.#8781
- PostgreSQL migrations can now have an `up_f` part like Cassandra migrations, designating a function to call. The `up_f` part is invoked after the `up` part has been executed against the database for both PostgreSQL and Cassandra.

Known Issues

Core

- Kong Manager does not currently support the following features:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ot supported.

t 2.8 release. If this is a requirement for upgrading, Kong operators should upgrade to that version before

in this release, so it is not recommended to upgrade yet if you are an OpenTracing user. This will be

ible with SSL connections to PostgreSQL.

2

R

Feature

Core

- Added an option for GitHub Actions to build nginx/OpenResty with debug symbols.

CLI Command

- Added a `--lts_34_compatibility` option to the `check` command to perform configuration compatibility check for upgrading to version 3.4.x.x.

Bugfix

Core

- Disabled requests with both Content-Length and Transfer-Encoding by backporting the Nginx patch.

Dependency

Core

- Pinned `LPEG` to `1.1.0` to keep the version consistent across all active branches. This is not a version bump, it is just pinning the version already in use.

2.8.4.13

Release date 2024/09/20

Breaking Change

Core

- Fixed RPM relocation by setting the default prefix to `/`, and added a symbolic link for `resty` to handle missing `/usr/local/bin` in `PATH`.

Bugfix

Core

- Fixed an issue where luarocks-admin was not available in /usr/local/bin.

Plugin

- rate-limiting-advanced:
  - Fixed an issue where the sync timer may stop working due to race condition.

2.8.4.12

Release date 2024/07/29

Deprecation

Core

- Debian 10, CentOS 7, and RHEL 7 reached their End of Life (EOL) dates on June 30, 2024. As of this patch, Kong is not building Kong Gateway 2.8.x installation Kong is no longer providing official support for any Kong version running on these systems.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

x set to `/`.

DDITIONAL SECTION in DNS responses.

2.8.4.10

Release date 2024/06/18

Feature

Core

- add a Docker image for RHEL8.

Bugfix

Core

- **Vitals**: Fixed a bug that each data plane connecting to the control plane would trigger the control plane to create a redundant table rotater timer.

Plugin

- rate-limiting-advanced Refactored `kong/tools/public/rate-limiting` to keep the original interfaces unchanged (backward compatibility) and extend a new interface `new_instance` to provide isolation between different plugins. If you are using custom Rate Limiting plugins based on this library, please update the initialization code to the new format like 'local ratelimiting = require("kong.tools.public.rate-limiting").new_instance("custom-plugin-name")'. The old interface will be removed in the upcoming major release.

Dependency

Core

- Improve the robustness of lua-cjson when handling unexpected input.

2.8.4.9

Release date 2024/04/19

Bugfix

PDK

- **PDK:** fix kong.request.get_forwarded_port to always return a number which was caused by an incorrectly stored string value in ngx.ctx.host_port.

Core

- Fixed an issue where Vault configuration stayed sticky and cached even when configurations were changed.

Plugin

- degraphql:
  - Fixed an issue where GraphQL variables were not being correctly parsed and coerced into their defined types.

2.8.4.8

R

F

C

L 3.x

F

C

ython) would fail to apply a change to the plugin config via the Admin API.

ite is set to old

C

- update the permission of kong.logrotate to 644

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fix the missing router section for the output of the request-debugging
- Fix a bug that `/metrics` endpoint throws an error when database is down.
- Fixed the UDP socket leaking issue of the DNS module.

Plugin

- ldap-auth-advanced:
  - fix some cache-related issues which cause groups_required to not work properly and unexpected return codes after a non-200 response
- rate-limiting-advanced Fixed an issue where RLA and other similar plugins using the `rate-limiting` library, when used together, would interfere with each other and thus fail to synchronize counter data to the central data store
- rate-limiting-advanced Falling back to local strategy if sync_rate = 0 when redis goes down

Dependency

Core

- Bumped OpenSSL from 3.1.4 to 3.1.5.
- Bump `kong-lua-resty-kafka` to `0.18`.
- Bumped lua-kong-nginx-module to 0.2.3
- Bump `lua-resty-luasocket` to `1.1.2` for fixing luasocket#427.

Performance

Configuration

- Bumped default values of `nginx_http_keepalive_requests` and `upstream_keepalive_max_requests` to `10000`.

2.8.4.7

Release date 2024/02/08

Bugfix

Plugin

- rate-limiting-advanced The plugin now creates counter syncing timers when being executed instead of being created to reduce some meaningless error logs
- rate-limiting-advanced fix the return info and log of previous errors are missing when use redis cluster mode connection fails
- rate-limiting-advanced Check the error of queries in the redis pipeline
- rate-limiting-advanced fix an issue where if `sync_rate` is changed from a value greater than `0` to `0`, the namespace will be cleared unexpectedly
- rate-limiting-advanced fix some timer-related issues where the counter syncing timer can't be created or destroyed properly

2.8.4.6

Release date 2024/01/17

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

when secrets cannot be fetched

SSL verification failure in CLI mode. Users who use secrets management based on GCP should also ensure
ficate configuration.

- openid-connect:

- update time when calculating token expire

Dependency

Core

- Bump resty-openssl from 0.8.25 to 1.0.2
- Bump Alpine base image from `3.16` to `3.19`.
- bump lua-resty-healthcheck to 1.5.4

Performance

Configuration

- Bump `dns_stale_ttl` default to 1 hour so stale DNS record can be used for longer time in case of resolver downtime.

2.8.4.5

Release date 2023/11/28

Feature

Core

- Support observing the time consumed by some components in the given request.
- A unique Request ID is now populated in the error log, access log, error templates, log serializer, and in a new X-Kong-Request-Id header (configurable for upstream/downstream using the `headers` and `headers_upstream` configuration options).

Plugin

- openid-connect:
  - New field `unauthorized_destroy_session`, which when set to true, we destory the session (delete the user's session cookie) when the request is unauthorized. Default to true. Set to false to preserve the session.

Admin API

- Add counters such as routes, plugins, licenses, deployment info, etc. to the report component. Also, add a checksum and timestamp to the output.

Bugfix

Core

- Fix a problem that abnormal socket connection will be reused when querying Postgres database.
- Fix a keyring issue where a kong node fails to send keyring material when using cluster strategy
- Fix an issue that results in the critical error log 'unexpected eof while read' when an SSL peer does not send close_notify before closing the connection
- Dismiss confusing debug log from Redis tool of rate limiting #7077 #7101

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

hang risk

more predictable manner

orrect path in packages

P

the kong.log.serialize function.

P

g to version >= 2.8.4.1 due to the deprecated collector plugin still being used.

    - Fix issue on token revocation on logout where the code was revoking refresh token when it was supposed to revoke access token when using the discovered revocation endpoint.

- request-validator:
    - Fix an issue where the `allowed_content_types` configuration is unable to contain the "-" character caused by the over-strict validation rule.
- mtls-auth should not cache the network failure when doing revocation check

Admin API

- Fix an issue where unique violation errors were reported while trying to update the user_token with the same value on the same RBAC user.

Dependency

Core

- Bumped lua-resty-aws from 1.3.2 to 1.3.5
- Bump lua-kong-nginx-module from 0.2.0 to 0.2.2
- bump jq to 1.7
- bump OpenSSL to 3.1.4

Kong Manager

- Upgrade moment.js to v2.29.4 to fix a known CVE vulnerability.

Performance

Plugin

- reduce upstream health iteration latency spike during scrape

2.8.4.4

Release date 2023/10/12

Bugfix

Core

- Apply Nginx patch for detecting HTTP/2 stream reset attacks early (CVE-2023-44487)

2.8.4.3

Release date 2023/09/18

Breaking Change

Core

L

ıx 2023 according to AWS's decision

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ing lua-resty-aws as an underlying AWS library. The refactor simplifies the AWS-Lambda plugin code base
g scenarios.

setting `anonymous_reports=false`.

- The Redis strategy of Rate Limiting catches strategy connection failure.

- Fix an issue can't create developer with non-default workspace.

Plugin

- openid-connect:
  - If an invalid opaque token is provided but verified failed, print the correct error.
- rate-limiting-advanced:
  - cp should not create namespace or do sync.
  - Fix a bug where the rl cluster_events broadcast the wrong data in traditional cluster mode.
- response-transformer-advanced:
  - Do not load response body when `if_status` does not match.

PDK

- Fix a bug in the exit hook that cause customize headers to be lost.

Dependency

Core

- Bumped lua-protobuf from 0.3.3 to 0.4.2
- Bumped lua-resty-aws from 1.0.0 to 1.3.1
- Bumped lua-resty-gcp from 0.0.5 to 0.0.13

2.8.4.2

Release date 2023/07/07

Bugfix

Core

- Fixed a bug where internal redirects, such as those produced by the `error_page` directive, could interfere with worker process handling the request when *buffered proxying* is being used.

Plugin

- Fixed an issue with the Oauth 2.0 Introspection plugin where a request with JSON that is not a table failed.:
- Fixed an issue where the slow startup of the Go plugin server caused a deadlock.:

Kong Manager

- Fixed an issue where the Zipkin plugin didn't allow the addition of `static_tags` through the Kong Manager UI.
- Fixed an issue where some of the icons were not rendering correctly.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

21

- Redis Cluster: Added username and password authentication to Redis Cluster 6 and later versions.

Bugfix

Plugin

- **Forward Proxy**:
  - Fixed an issue which occurred when receiving an HTTP `408` from the upstream through a forward proxy. Nginx exited the process with this code, which resulted in Nginx ending the request without any contents.
- request-validator:
  - The plugin now allows requests carrying a `content-type` with a parameter to match its `content-type` without a parameter.

Core

- Fixed an issue where the RBAC token was not re-hashed after an update on the `user_token` field.
- Fixed the Dynatrace implementation. Due to a build system issue, Kong Gateway 2.8.4 packages prior to 2.8.4.1 didn't contain the debug symbols that Dynatrace requires.

Dependency

Core

- Bumped `pgmoon` from 2.2.0.1 to 2.3.2.0.

2.8.4.0

Release date 2023/03/28

Feature

Plugin

- aws-lambda:
  - Added the configuration parameter `aws_imds_protocol_version`, which lets you select the IMDS protocol version. This option defaults to `v1` and can be set to `v2` to enable IMDSv2.#9962

Bugfix

Core

- Fixed an issue where the OpenTracing module was not included in the Amazon Linux 2 package.
- Hybrid mode: Fixed an issue where enabling encryption on a data plane would cause the data plane to stop working after a restart.
- Fixed the systemd unit file, which was incorrectly named `kong.service` in 2.8.1.x and later versions. It has been renamed back to `kong-enterprise-edition.service` to align with previous versions.
- Fixed the Ubuntu ARM64 image, which was broken in 2.8.2.x and later versions.
- Router: Fixed an issue where the router used stale data when workers were respawned. #9396#9485
- Update the batch queues module so that queues no longer grow without bounds if their consumers fail to process the entries. Instead, old batches are now dropped

P

caches after routes were updated.

ng, where metrics would be published multiple times. This caused a memory leak, where memory usage

n multiple workspaces caused a 401 error. This occurred because of a caching issue.

in schemas: Azure Functions (`azure-functions`)

in schemas: gRPC Gateway (`grpc-gateway`)

- Added the missing `protocols` field to the following plugin schemas: gRPC Web (`grpc-web`)

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Added the missing `protocols` field to the following plugin schemas: Serverless pre-function (`pre-function`)
- Added the missing `protocols` field to the following plugin schemas: Prometheus (`prometheus`)
- Added the missing `protocols` field to the following plugin schemas: Proxy Caching (`proxy-cache`)
- Added the missing `protocols` field to the following plugin schemas: Request Transformer (`request-transformer`)
- Added the missing `protocols` field to the following plugin schemas: Session (`session`)
- Added the missing `protocols` field to the following plugin schemas: Zipkin (`zipkin`)

2.8.2.4

Release date 2023/01/23

Bugfix

Core

- Kong Gateway now statically links the BoringSSL PCRE library. This fixes an issue introduced in 2.8.2.3, where the BoringSSL library was dynamically linked, causing regex compilation to fail when routing requests with some versions of the library.

2.8.2.3

Release date 2023/01/06

Bugfix

Core

- Fixed a role precedence issue with RBAC. RBAC rules involving deny (negative) rules now correctly take precedence over allow (non-negative) roles.
- Fixed workspace filtering pagination on the overview page.
- Fixed a router issue where, in an environment with more than 50,000 routes, attempting to update a route caused a `500` error response.
- Fixed a timer leak that occurred whenever the generic messaging protocol connection broke in hybrid mode.
- Fixed a `tlshandshake` method error that occurred when SSL was configured on PostgreSQL, and the Kong Gateway had `stream_listen` configured with a stream proxy.

Plugin

- http-log:
  - Fixed the `could not update kong admin` internal error caused by empty headers. This error occurred when using this plugin with the Kong Ingress Controller.
- jwt-signer:
  - Fixed the error `attempt to call local 'err' (a string value)`.
- jwt:
  - Fixed an issue where the JWT plugin could potentially forward an unverified token to the upstream.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

erformance. Added new `kong.conf` options to switch high cardinality metrics `on` or `off`:
etheus_plugin_latency_metrics, prometheus_plugin_bandwidth_metrics, and

cks dictionary. Kong Gateway now clears old namespaces from the maintenance cycle schedule when a

verted to empty objects. Empty arrays are now preserved.

K

Core

- A required PCRE library is dynamically linked, where prior versions statically linked the library. Depending on the system PCRE version, this may cause regex compilation to fail when routing requests. Starting in 2.8.2.4 and later, Kong Gateway will return to statically linking the PCRE library.

2.8.2.2

Release date 2022/12/01

Bugfix

Core

- Added batch queues for the Datadog and StatsD plugins to reduce timer usage, fixing a `lua_max_running_timers are not enough` timer error.

  Whenever a request was processed, a new running timer was instantly created during the log phase. This was causing a shortage of timers under heavy traffic and led to unpredictable consequences, where internal timers were killed randomly and couldn't recover automatically. This would then trigger a `lua_max_running_timers are not enough` timer error and cause data planes to crash.

  #9521

- Fixed a timer leak that occurred whenever the generic messaging protocol connection would break in hybrid mode.

2.8.2.1

Release date 2022/11/21

Bugfix

Core

- **Kong Manager:**
  - Fixed an issue where admins needed the specific `rbac/role` permission to edit RBAC roles. Now, admins can edit RBAC roles with the `/admins` permission.
  - Fixed an issue where the client certificate ID didn't display properly in the upstream update form.
  - Fixed an issue in the service documents UI which allowed users to upload multiple documents. Since each service only supports one document, the documents would not display correctly. Uploading a new document now overrides the previous document.
  - Fixed an issue where the **New Workspace** button on the global workspace dashboard wasn't clickable on the first page load.
  - Fixed an RBAC issue where the roles page listed deleted roles.
  - Removed New Relic from Kong Manager. Previously, `VUE_APP_NEW_RELIC_LICENSE_KEY` and`VUE_APP_SEGMENT_WRITE_KEY` were being exposed in Kong Manager with invalid values.
  - Fixed an RBAC issue where permissions applied to specific endpoints (for example, an individual service or route) were not reflected in the Kong Manager UI.
  - Fixed an issue with group to role mapping, where it didn't support group names with spaces.
  - Fixed an issue with individual workspace dashboards, where right-clicking on **View All** and choosing "Open Link in New Tab" or "Copy Link" for services, routes, and plugins redirected to the default workspace and caused an `HTTP 404` error.
- **Dev Portal** : Fixed an issue where Dev Portal response examples weren't rendered when media type was vendor-specific.
- Targets with a weight of `0` are no longer included in health checks, and checking their status via the `upstreams/<upstream>/health` endpoint results in the status `HEALTHCHECK_OFF`. Previously, the `upstreams/<upstream>/health` endpoint was incorrectly reporting targets with `weight=0` as `HEALTHY`, and the health check was reporting the same targets as `UNDEFINED`.
- Fixed the default `logrotate` configuration, which lacked permissions to access logs.

Plugin

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ted by `group_member_attribute` weren't returned in search query results.

sts to silently fail on Kong Gateway data planes.

uld fail in the following situations:

ad no service.
ue.

service.

- Fixed the `Bad Gateway` error that would occur when using the Kafka Upstream plugin with the configuration `producer_async=false`.

- request-transformer:
  - Fixed an issue where empty arrays were being converted to empty objects. Empty arrays are now preserved.
- response-transformer:
  - Fixed an issue where the plugin couldn't process string responses.

2.8.2.0

Release date 2022/10/12

Bugfix

Core

- **Kong Manager** :
  - Fixed an issue where workspaces with zero roles were not correctly sorted by the number of roles.
  - Fixed the Cross Site Scripting (XSS) security vulnerability in the Kong Manager UI.
  - Fixed an issue where registering an admin without `admin_gui_auth` set resulted in a `500` error.
  - Fixed an issue that allowed unauthorized IDP users to log in to Kong Manager. These users had no access to any resources in Kong Manager, but were able to go beyond the login screen.
- Fixed OpenSSL vulnerabilities CVE-2022-2097 and CVE-2022-2068.
- Hybrid mode: Fixed an issue with consumer groups, where the control plane wasn't sending the correct number of consumer entries to data planes.
- Hybrid mode: Fixed an issue where sending a `PATCH` request to update a route after restarting a control plane caused a 500 error response.

Plugin

- **Forward Proxy**:
  - If the `https_proxy` configuration parameter is not set, it now defaults to `http_proxy` to avoid DNS errors.
- **GraphQL Proxy Cache Advanced**:
  - Fixed the error `function cannot be called in access phase (only in: log)`, which was preventing the plugin from working consistently.
- aws-lambda:
  - Fixed an issue where the plugin couldn't read environment variables in the ECS environment, causing permission errors.
- graphql-rate-limiting-advanced:
  - The plugin now returns a `500` error when using the `cluster` strategy in hybrid or DB-less modes instead of crashing.
- ldap-auth-advanced:
  - The characters `.` and `:` are now allowed in group attributes.
- openid-connect:
  - Fixed issues with OIDC role mapping where admins couldn't be added to more than one workspace, and permissions were not being updated.
- request-transformer-advanced:

verted to empty objects. Empty arrays are now preserved.

hitespace would return a `400 Bad Request`.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

usage when AWS vault is enabled. #23

usage when GCP vault is enabled. #7

Release date 2022/08/05

Feature

Core

- Added GCP integration support for the secrets manager. GCP is now available as a vault backend.

Plugin

- aws-lambda:
  - Added support for cross-account invocation through the `aws_assume_role_arn` and`aws_role_session_name` configuration parameters.#8900

Bugfix

Core

- Fixed an issue with excessive log file disk utilization on control planes.
- Fixed an issue with keyring encryption, where keyring was not decrypting keys after a soft reload.
- The router now detects static route collisions inside the current workspace, as well as with other workspaces.
- When using a custom plugin in a hybrid mode deployment, the control plane now detects compatibility issues and stops sending the plugin configuration to data planes that can't use it. The control plane continues sending the custom plugin configuration to compatible data planes.
- Optimized the Kong PDK function `kong.response.get_source()`.

Plugin

- acme:
  - The `domains` plugin parameter can now be left empty. When `domains` is empty, all TLDs are allowed. Previously, the parameter was labelled as optional, but leaving it empty meant that the plugin retrieved no certificates at all.
- mocking:
  - Fixed an issue where the plugin didn't accept empty values in examples.
- rate-limiting-advanced:
  - Fixed an issue with `cluster` strategy timestamp precision in Cassandra.
- response-transformer-advanced:
  - Fixed an issue with nested array parsing.

Kong Manager

- Fixed an issue with admin creation. Previously, when an admin was created with no roles, the admin would have access to the first workspace listed alphabetically.
- Fixed several issues with SNI listing. Previously, the SNI list was empty after sorting by the SSL certificate ID field. In 2.8.1.1, the SSL certificate ID field in the SNI list was empty.

2.8.1.2

R

F

C

to `enabled: false` and that service had a route with an enabled plugin, any new data planes would

`ncy` was set to `eventual` in `kong.conf`. This issue caused timers to be exhausted and failed to start any `any pending timers` error.

ope

k

ev Portal developers in the organization.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Fixed an issue that prevented developer role assignments from displaying in Kong Manager. When viewing a role under the Permissions tab in the Dev Portal section, the list of developers wouldn't update when a new developer was added. Kong Manager was constructing the wrong URL when retrieving Dev Portal assignees.
- Fixed empty string handling in Kong Manager. Previously, Kong Manager was handling empty strings as `""` instead of a null value.
- Improved Kong Manager styling by fixing an issue where content didn't fit on object detail pages.
- Fixed an issue that sometimes prevented clicking Kong Manager links and buttons in Safari.
- Fixed an issue where users were being navigated to the object detail page after clicking on the "Copy ID" button from the object list.
- Fixed an issue where the number of requests and error rate were not correctly displaying when Vitals was disabled.

Plugin

- http-log:
  - Log output is now restricted to the workspace the plugin is running in. Previously, the plugin could log requests from outside of its workspace.
- mocking:
  - Fixed an issue where `204` responses were not handled correctly and you would see the following error:`"No examples exist in API specification for this resource"`.
  - `204` response specs now support empty content elements.
- rate-limiting:
  - Fixed a PostgreSQL deadlock issue that occurred when the `cluster` policy was used with two or more metrics (for example, `second` and `day`.)

Deprecated

Core

- **Amazon Linux 1** : Support for running Kong Gateway on Amazon Linux 1 is now deprecated, as theAmazon Linux (1) AMI has ended standard support as of December 31, 2020. Starting with Kong Gateway 3.0.0.0, Kong is not building new Amazon Linux 1 images or packages, and Kong will not test package installation on Amazon Linux 1.

  If you need to install Kong Gateway on Amazon Linux 1, see the documentation for previous versions.
- **Debian 8** : Support for running Kong Gateway on Debian 8 ("Jessie") is now deprecated, as Debian 8 ("Jessie") has reached End of Life (EOL). Starting with Kong Gateway 3.0.0.0, Kong is not building new Debian 8 ("Jessie") images or packages, and Kong will not test package installation on Debian 8 ("Jessie").

  If you need to install Kong Gateway on Debian 8 ("Jessie"), see the documentation for previous versions.
- **Ubuntu 16.04** : Support for running Kong Gateway on Ubuntu 16.04 ("Xenial") is now deprecated, as Standard Support for Ubuntu 16.04 has ended as of April, 2021. Starting with Kong Gateway 3.0.0.0, Kong is not building new Ubuntu 16.04 images or packages, and Kong will not test package installation on Ubuntu 16.04.

  If you need to install Kong Gateway on Ubuntu 16.04, see the documentation for previous versions.

2.8.1.1

Release date 2022/05/27

Feature

C

quest emails for the Developer Portal using the following configuration parameters:

nd application request status update emails to developers.
end service access request emails to users specified in `smtp_admin_emails`.
dresses to send portal admin emails to, overriding values set in `smtp_admin_emails`.

portal email templates. For example, `{{email.developer_meta.preferred_name}}`.

P

SP server support with the following parameters: `http_proxy_host`, `http_proxy_port`,

usCode field now accepts string datatypes.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- kafka-upstream:
  - Added support for the `SCRAM-SHA-512` authentication mechanism.

Bugfix

Core

- Improved Kong Admin API and Kong Manager performance for organizations with many entities.
- Fixed an issue with keyring encryption, where the control plane would crash if any errors occurred during the initialization of the keyring module.
- Fixed an issue where Kong Manager did not display all RBAC users and Consumers in the organization.
- Fixed an issue where some areas in a row of a list were not clickable.

Plugin

- **Forward Proxy**:
  - Fixed an `invalid header value` error for HTTPS requests. The plugin now accepts multi-value response headers.
  - Fixed an error where basic authentication headers containing the =character weren't forwarded.
  - Fixed request errors that occurred when a scheme had no proxy set. The`https` proxy now falls back to the `http` proxy if not specified, and the`http` proxy falls back to `https`.
- graphql-rate-limiting-advanced:
  - Fixed `deserialize_parse_tree` logic when building GraphQL AST with non-nullable or list types.
- rate-limiting-advanced:
  - Fixed rate limiting advanced errors that appeared when the Rate Limiting Advanced plugin was not in use.
  - Fixed an error where rate limiting counters were not updating response headers due to incorrect key expiration tracking. Redis key expiration is now tracked properly in `lua_shared_dict kong_rate_limiting_counters`.

2.8.1.0

Release date 2022/04/07

Bugfix

Core

- Fixed an issue with RBAC where `endpoint=/kong workspace=*` would not let the `/kong` endpoint be accessed from all workspaces
- Fixed an issue with RBAC where admins without a top level `endpoint=*` permission could not add any RBAC rules, even if they had `endpoint=/rbac` permissions. These admins can now add RBAC rules for their current workspace only.
- Kong Manager
  - Serverless functions can now be saved when there is a comma in the provided value
  - Custom plugins now show an Edit button when viewing the plugin configuration
  - Editing Dev Portal permissions no longer returns a 404 error
  - Fix an issue where admins with access to only non-default workspaces could not see any workspaces
  - Show the workspace name when an admin only has access to non-default workspaces
  - ng Cassandra
  - AC edit page
  - er leads to a 404 error

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

to an nginx worker thread. This prevents data leaks when a worker is handling multiple requests at the
now bound to an nginx worker thread. This prevents data leaks when a worker is handling multiple

tarts

uilding it" was incorrectly logged as an `error`. This release converts it to the `info` log level.

the Rate Limiting Advanced plugin

nd balancer by adding conditional rebuilding

P

- **Forward Proxy**:
  - Use lowercase when overwriting the `host` header
- **LDAP Auth Advanced**:
  - Support passwords that contain a `:` character
- http-log:
  - Include provided query string parameters when sending logs to the `http_endpoint`
- jwt-signer:
  - Implement the `enable_hs_signatures` option to enable JWTs signed with HMAC algorithms
- openid-connect:
  - Provide valid upstream headers e.g. `X-Consumer-Id`, `X-Consumer-Username`
- rate-limiting-advanced:
  - Skip namespace creation if the plugin is not enabled. This prevents the error "[rate-limiting-advanced] no shared dictionary was specified" being logged.
- StatsD Advanced: Added support for setting `workspace_identifier` to `workspace_name`

Dependency

Core

- Bumped `openssl` from 1.1.1k to 1.1.1n to resolve CVE-2022-0778 #8635
- Bumped `openresty` from 1.19.3.2 to 1.19.9.1 #7727

2.8.0.0

Release date 2022/03/02

Feature

Core

- Improved tables in Kong Manager: (for PostgreSQL-backed instances only)
  - Click on a table row to access the entry instead of using the old **View** icon.
  - Search and filter tables through the **Filters** dropdown, which is located above the table.
  - Sort any table by clicking on a column title.
  - Tables now have pagination.
- Kong Manager with OIDC: Added the configuration option`admin_auto_create_rbac_token_disabled`to enable or disable RBAC tokens when automatically creating admins with OpenID Connect.
- If a license is present,`license_key` is now included in the `api` signal for`anonymous_reports`.
- **Beta feature** : Kong Gateway 2.8.0.0 introducessecrets management and vault support. You can now store confidential values such as usernames and passwords as secrets in secure vaults. Kong Gateway can then reference these secrets, making your environment more secure.

  The beta includes `get` support for the following vault implementations:

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

narked as_referenceable_. See the plugin section of the Kong Gateway 2.8 changelog for details.

e, and check out the documentation for the Kong Admin API `/vaults-beta` entity.

plementation details may change. This means it is intended for testing in staging environments only, nents.

ne.

ssions.

mode deployments. This configuration option sets the maximum payload size allowed to be sent across ent has large configurations that generate `payload too big` errors and don't get applied to the data planes,

Thanks, @andrewgkew! #8337

dev-portal

- The new `/developers/export` endpoint lets you export the list of developers and their statuses into CSV format.

Performance

- Improved the calculation of declarative configuration hash for big configurations. The new method is faster and uses less memory.#8204
- Multiple improvements in the Router, including:
  - The router builds twice as fast
  - Failures are cached and discarded faster (negative caching)
  - Routes with header matching are cached

  These changes should be particularly noticeable when rebuilding in DB-less environments.#8087#8010

Admin API

- The current declarative configuration hash is now returned by the `status`endpoint when Kong node is running in DB-less or data plane mode.#8214#8425

Plugin

- **Proxy Cache Advanced**:
  - Added Redis ACL support (Redis v6.0.0+ and Redis Sentinel v6.2.0+).
  - Added the `redis.sentinel_username` and `redis.sentinel_password` configuration parameters.
  - **Beta feature:** The `redis.password`, `redis.sentinel_username`, and `redis.sentinel_password`configuration fields are now marked as referenceable, which means they can be securely stored as secretsin a vault. References must follow a specific format.
- acme:
  - Added the `rsa_key_size` configuration parameter.

    Thanks, lodrantl! #8114
- canary:
  - Added the ability to configure `canary_by_header_name`. This parameter accepts a header name that, when present on a request, overrides the configured canary functionality.
    - If the configured header is present with the value `always`, the request will always go to the canary upstream.
    - If the header is present with the value `never`, the request will never go to the canary upstream.
  - If the configured header is present with the value `always`, the request will always go to the canary upstream.
  - If the header is present with the value `never`, the request will never go to the canary upstream.
- forward-proxy:
  - Added `http_proxy_host`, `http_proxy_port`, `https_proxy_host`, and`https_proxy_port` configuration parameters for mTLS support.

    These parameters replace the `proxy_port` and `proxy_host` fields, which are now **deprecated** and planned to be removed in 3.x.x.
  - The `auth_password` and `auth_username` configuration fields are now marked as referenceable, which means they can be securely stored assecretsin a vault. References must follow a specific format.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

s Sentinel v6.2.0+).

username configuration parameters.

ord, `redis.sentinel_username`, and `redis.sentinel_password`configuration fields are now marked as ored assecretsin a vault. References must follow a specific format.

he `cluster_name` configuration parameter. By default, this field generates a random string. You can also

hentication.password configuration fields are now marked as referenceable, which means they can be t follow a specific format.

- ldap-auth-advanced:

- **Beta feature:** The `ldap_password` and `bind_dn` configuration fields are now marked as referenceable, which means they can be securely stored assecretsin a vault. References must follow a specific format.

- openid-connect:
  - Added Redis ACL support (Redis v6.0.0+) for storing and retrieving a session. Use the `session_redis_username` and `session_redis_password` configuration parameters to configure it.

    These parameters replace the `session_redis_auth` field, which is now **deprecated** and planned to be removed in 3.x.x.
  - Added support for distributed claims. Set the `resolve_distributed_claims` configuration parameter to `true` to tell OIDC to explicitly resolve distributed claims.

    Distributed claims are represented by the `_claim_names` and `_claim_sources` members of the JSON object containing the claims.
  - **Beta feature:** The `client_id`, `client_secret`, `session_secret`, `session_redis_username`, and `session_redis_password` configuration fields are now marked as referenceable, which means they can be securely stored assecretsin a vault. References must follow a specific format.
- prometheus:
  - Added three new metrics:
    - `kong_db_entities_total` (gauge): total number of entities in the database.
    - `kong_db_entity_count_errors` (counter): measures the number of errors encountered during the measurement of `kong_db_entities_total`.
    - `kong_nginx_timers` (gauge): total number of Nginx timers, in Running or Pending state. Tracks `ngx.timer.running_count()` and`ngx.timer.pending_count()`.#8387
  - `kong_db_entities_total` (gauge): total number of entities in the database.
  - `kong_db_entity_count_errors` (counter): measures the number of errors encountered during the measurement of `kong_db_entities_total`.
  - `kong_nginx_timers` (gauge): total number of Nginx timers, in Running or Pending state. Tracks `ngx.timer.running_count()` and`ngx.timer.pending_count()`.#8387
- rate-limiting-advanced:
  - Added Redis ACL support (Redis v6.0.0+ and Redis Sentinel v6.2.0+).
  - Added the `redis.username` and `redis.sentinel_username` configuration parameters.
  - **Beta feature:** The `redis.username`, `redis.password`, `redis.sentinel_username`, and `redis.sentinel_password`configuration fields are now marked as referenceable, which means they can be securely stored assecretsin a vault. References must follow a specific format.
- rate-limiting:
  -
- response-ratelimiting:
  - Added Redis ACL support (Redis v6.0.0+ and Redis Sentinel v6.2.0+).
  - Added the `redis_username` configuration parameter.

    Thanks, @27ascii for the original contribution! #8213
- response-transformer-advanced:
  - Use response buffering from the PDK.
- vault-auth:
  - **Beta feature:** The `vaults.vault_token` form field is now marked as referenceable, which means it can be securely stored as asecretin a vault. References must follow a specific format.

E

C

and failed to start any other timers used by Kong, showing the error `too many pending timers`.

e was set to `off`, the data plane received no updates from the control plane.

ich occurred when accessing Routes or Services using TLS.

was not automatically generated and registered if it was not explicitly set.

using PKI for certificate verification in hybrid mode, you can now configure a list of Common Names ot set, only data planes with the same parent domain as the control plane cert are allowed.

g dot (`.`), the dot will be ignored, since according toRFC-3546the dot is not part of the hostname.#8269

tes with both a wildcard and a port (`route.*:80`) over wildcard-only routes (`route.*`), which have less

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- The internal DNS client isn't confused by the single-dot (`.`) domain, which can appear in `/etc/resolv.conf` in special cases like `search .`.#8307
- The Cassandra connector now records migration consistency level.

  Thanks, @mpenick! #8226

dev-portal

- When the SMTP configuration was broken or unresponsive, the API would respond with an error message that was a JavaScript Object (`[Object object]`) instead of a string. This happened when a user was registering on any given portal with broken SMTP. Now, if there is an error, the API responds with the string`Error sending email`.
- The `/document_objects` and `/services/:id/document_objects` endpoints no longer accept multiple documents per service. This was an issue, as each service can only have one document. Instead, posting a document to one of these endpoints now overrides the previous document.

balancer

- Targets now keep their health status when upstreams are updated.#8394
- One debug message which was erroneously using the `error` log level has been downgraded to the appropriate `debug` log level.#8410

Clustering

- Replaced a cryptic error message with a more useful one when there is a failure on SSL when connecting with the control plane.#8260

Admin API

- Fixed an incorrect `next` field that appeared when paginating Upstreams.#8249

PDK

- Phase names are now correctly selected when performing phase checks.#8208
- Fixed a bug in the go-PDK where, if `kong.request.getrawbody` was big enough to be buffered into a temporary file, it would return an an empty string.#8390

Plugin

- **External Plugins** :
  - Fixed incorrect handling of the Headers Protobuf Structure and representation of null values, which provoked an error on init with the go-pdk.#8267
  - Unwrap `ConsumerSpec` and `AuthenticateArgs`.

    Thanks, @raptium! #8280
  - Fixed a problem in the stream subsystem, where it would attempt to load HTTP headers.#8414
- **OAuth2 Introspection**:
  - Fixed issues with TLS connections when the IDP is behind a reverse proxy.
- **Proxy Cache Advanced**:
  - Fixed a `X-Cache-Status:Miss` error that occurred when caching large files.
- **mTLS Authentication**:

or, which occurred when accessing Routes or Services using TLS.

HTTP proxy and deprecated the `proxy_scheme` config attribute for removal in 3.0.#8406

header anymore when the header `Access-Control-Allow-Origin` is set to `*`.

configuration options in a single place instead of in two separate places.#8315

would break the plugin iterator, causing later plugins not to run.

- If plugin has no output, it will now return the raw body instead of attempting to restore the original response body.

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- jwt-signer:
  - Fixed an issue where the `enable_hs_signatures` configuration parameter did not work. The plugin now defines expiry earlier to avoid arithmetic on a nil value.
- oauth2:
  - The plugin clears the `X-Authenticated-UserId` and`X-Authenticated-Scope` headers when it is configured in logical OR and is used in conjunction with another authentication plugin.#8422
- openid-connect:
  - Fixed negative caching, which was loading wrong a configuration value.
- rate-limiting-advanced:
  - Fixed a 500 error that occurred when consumer groups were enforced but no proper configurations were provided. Now, if no specific consumer group configuration exists, the consumer group defaults to the original plugin configuration.
  - Fixed a timer leak that caused the timers to be exhausted and failed to start any other timers used by Kong, showing the error `too many pending timers`.

    Before, the plugin used one timer for each namespace maintenance process, increasing timer usage on instances with a large number of rate limiting namespaces. Now, it uses a single timer for all namespace maintenance.
  - Fixed an issue where the `local` strategy was not working with DB-less and hybrid deployments. We now allow `sync_rate = null` and `sync_rate = -1`when a `local` strategy is defined.
- rate-limiting:
  - Fixed a 500 error associated with performing arithmetic functions on a nil value by adding a nil value check after performing `ngx.shared.dict` operations.
- response-transformer-advanced:
  - In the `body_filter` phase, the plugin now sets the body to an empty string instead of `nil`.

Kong Manager

- Fixed an issue where OIDC authentication into Kong Manager failed when used with Azure AD.
- Fixed a performance issue with the Teams page in Kong Manager.
- Fixed an issue with checkboxes in Kong Manager, where the checkbox for the OAuth2 plugin's `hash_secret` value was labelled as *Required* and users were not able to uncheck it.
- Fixed an issue where Kong Manager was not updating plugin configuration when attempting to clear the `service.id` from a plugin.
- Fixes an issue with Route creation in Kong Manager, where a new route would default to `http` as the supported protocol. Now, creating a Route picks up the correct default value, which is `http,https`.
- Kong Manager now accurately lists `udp` as a protocol option for Route and Service objects on their configuration pages.
- Fixed an issue with Kong Manager OIDC authentication, which caused the error"`attempt to call method 'select_by_username_ignore_case' (a nil value)`"and prevented login with OIDC.
- Fixed a latency issue with OAuth2 token creation. These tokens are no longer tracked by the workspace entity counter, as the count is not needed by the Kong Manager UI.
- Fixed an issue where the plugin list table couldn't be sorted by the **Applied To** column.

Dependency

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

21

recated in favor of the embedded server approach.

new open-source CentOS images. Support for running open-source Kong Gateway on CentOS on is now

Running Kong Gateway Enterprise on CentOS is currently supported, but CentOS is planned to be fully deprecated in Kong Gateway 3.x.x.

- OpenID Connect plugin: The `session_redis_auth` field is now deprecated and planned to be removed in 3.x.x. Use`session_redis_username` and `session_redis_password` instead.
- Forward Proxy Advanced plugin: The `proxy_port` and `proxy_host` fields are now deprecated and planned to be removed in 3.x.x. Use`http_proxy_host` and `http_proxy_port`, or `https_proxy_host` and`https_proxy_port` instead.
- AWS Lambda plugin: The `proxy_scheme` field is now deprecated and planned to be removed in 3.x.x.

Related Documentation
Gateway Documentation
Tags
#changelog
Related Resources
Kong Gateway breaking changes

- Kong Gateway changelog
- 3.16.0.1
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.16.0.0
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.15.0.6
  - Bugfix
  - Dependency
  - Performance
- 3.15.0.5
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.15.0.4
  - Feature
  - Bugfix
- 3.15.0.3
  - Bugfix
  - Dependency
- 3.15.0.2
  - Bugfix
  - Dependency
  - Performance
- 3.15.0.1
  - Bugfix
- 3.15.0.0
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.14.0.16
  - Feature
  - Bugfix
  - Dependency

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Bugfix

- Performance
- 3.14.0.9
  - Bugfix
  - Dependency
- 3.14.0.8
  - Bugfix
- 3.14.0.7
  - Bugfix
  - Dependency
  - Performance
- 3.14.0.6
  - Bugfix
- 3.14.0.5
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.14.0.4
  - Bugfix
  - Dependency
- 3.14.0.3
  - Bugfix
- 3.14.0.2
  - Bugfix
  - Dependency
- 3.14.0.1
  - Bugfix
- 3.14.0.0
  - Breaking Change
  - Deprecation
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.13.0.11
  - Bugfix
  - Dependency
  - Performance
- 3.13.0.10
  - Bugfix
  - Performance
- 3.13.0.9
  - Bugfix
  - Dependency
- 3.13.0.8
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.13.0.7
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.13.0.6
  - Bugfix
- 3.13.0.5
  - Bugfix
  - Dependency
- 3.13.0.4

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

  - Bugfix
  - Dependency
  - Performance
- 3.12.0.10
  - Bugfix
  - Dependency
- 3.12.0.9
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.12.0.8
  - Bugfix
- 3.12.0.7
  - Bugfix
  - Dependency
- 3.12.0.6
  - Bugfix
  - Dependency
- 3.12.0.5
  - Bugfix
  - Dependency
  - Performance
- 3.12.0.4
  - Bugfix
  - Dependency
- 3.12.0.3
  - Bugfix
- 3.12.0.2
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.12.0.1
  - Bugfix
- 3.12.0.0
  - Breaking Change
  - Deprecation
  - Feature
  - Bugfix
  - Dependency
  - Performance
  - Known Issues
- 3.11.0.14
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.11.0.13
  - Bugfix
- 3.11.0.12
  - Bugfix
  - Dependency
- 3.11.0.11
  - Bugfix
- 3.11.0.10
  - Bugfix
  - Dependency
- 3.11.0.9
  - Bugfix

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Bugfix
- 3.11.0.1
  - Bugfix
  - Dependency
- 3.11.0.0
  - Deprecation
  - Feature
  - Bugfix
  - Dependency
  - Performance
  - Known Issues
- 3.10.0.19
  - Bugfix
  - Dependency
  - Performance
- 3.10.0.18
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.10.0.17
  - Bugfix
  - Dependency
- 3.10.0.16
  - Bugfix
  - Performance
- 3.10.0.15
  - Bugfix
  - Dependency
  - Performance
- 3.10.0.14
  - Bugfix
- 3.10.0.13
  - Bugfix
- 3.10.0.12
  - Bugfix
  - Dependency
- 3.10.0.11
  - Feature
  - Bugfix
  - Dependency
- 3.10.0.10
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.10.0.9
  - Bugfix
  - Dependency
- 3.10.0.8
  - Bugfix
  - Performance
- 3.10.0.7
  - Bugfix
  - Dependency
  - Performance
- 3.10.0.6
  - Feature
  - Bugfix
- 3.10.0.5

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

    - Deprecation
    - Feature
    - Bugfix
    - Dependency
    - Performance
    - Known Issues
- 3.9.1.2
    - Feature
    - Bugfix
    - Dependency
- 3.9.1.1
    - Bugfix
- 3.9.1.0
    - Feature
    - Bugfix
- 3.9.0.1
    - Bugfix
    - Dependency
- 3.9.0.0
    - Deprecation
    - Feature
    - Bugfix
    - Dependency
    - Known Issues
- 3.8.1.2
    - Feature
    - Bugfix
    - Dependency
- 3.8.1.1
    - Deprecation
    - Feature
    - Bugfix
    - Dependency
- 3.8.1.0
    - Feature
    - Bugfix
    - Dependency
- 3.8.0.0
    - Deprecation
    - Feature
    - Bugfix
    - Dependency
    - Performance
    - Feature
    - Known Issues
- 3.7.1.5
    - Feature
    - Bugfix
- 3.7.1.4
    - Feature
    - Bugfix
    - Dependency
- 3.7.1.3
    - Feature
    - Bugfix
    - Dependency
- 3.7.1.2
    - Deprecation
    - Feature
    - Bugfix

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Dependency
- 3.6.1.6
  - Bugfix
- 3.6.1.5
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.6.1.4
  - Feature
  - Bugfix
  - Dependency
- 3.6.1.3
  - Bugfix
- 3.6.1.2
  - Feature
  - Bugfix
  - Dependency
- 3.6.1.1
  - Bugfix
- 3.6.1.0
  - Feature
  - Bugfix
  - Performance
- 3.6.0.0
  - Breaking Change
  - Deprecation
  - Feature
  - Bugfix
  - Dependency
  - Performance
  - Known Issues
- 3.5.0.7
  - Deprecation
  - Feature
- 3.5.0.6
  - Bugfix
- 3.5.0.5
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.5.0.4
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.5.0.3
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
- 3.5.0.2
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.5.0.1

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Performance
- 3.4.3.24
  - Bugfix
  - Dependency
- 3.4.3.23
  - Bugfix
  - Dependency
  - Performance
- 3.4.3.22
  - Bugfix
  - Dependency
  - Performance
- 3.4.3.21
  - Bugfix
  - Dependency
- 3.4.3.20
  - Bugfix
  - Dependency
- 3.4.3.19
  - Bugfix
- 3.4.3.18
  - Feature
  - Bugfix
  - Dependency
- 3.4.3.17
  - Feature
  - Bugfix
  - Dependency
- 3.4.3.16
  - Dependency
- 3.4.3.15
  - Bugfix
  - Dependency
- 3.4.3.14
  - Bugfix
- 3.4.3.13
  - Feature
  - Bugfix
  - Dependency
- 3.4.3.12
  - Feature
  - Bugfix
  - Dependency
- 3.4.3.11
  - Bugfix
- 3.4.3.10
  - Bugfix
  - Dependency
- 3.4.3.9
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.4.3.8
  - Feature
  - Bugfix
  - Dependency
- 3.4.3.7
  - Bugfix
  - Dependency

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- 3.4.3.1
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 3.4.2.0
  - Feature
  - Bugfix
  - Dependency
- 3.4.1.1
  - Bugfix
  - Dependency
- 3.4.1.0
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
- 3.4.0.0
  - Feature
  - Bugfix
  - Dependency
  - Breaking Change
  - Known Issues
- 3.3.1.1
  - Bugfix
  - Dependency
- 3.3.1.0
  - Deprecation
  - Bugfix
- 3.3.0.0
  - Feature
  - Bugfix
  - Dependency
  - Breaking Change
  - Known Issues
- 3.2.2.5
  - Bugfix
  - Dependency
- 3.2.2.4
  - Bugfix
  - Dependency
  - Breaking Change
- 3.2.2.3
  - Deprecation
  - Bugfix
- 3.2.2.2
  - Bugfix
- 3.2.2.1
  - Deprecation
  - Bugfix
- 3.2.2.0
  - Bugfix
  - Known Issues
- 3.2.1.0
  - Deprecation
  - Feature
  - Bugfix
  - Dependency
  - Breaking Change

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Breaking Change
- 3.0.1.0
  - Feature
  - Bugfix
- 3.0.0.0
  - Feature
  - Bugfix
  - Dependency
  - Breaking Change
  - Known Issues
- 2.8.4.14
  - Feature
  - Bugfix
  - Dependency
- 2.8.4.13
  - Breaking Change
  - Bugfix
- 2.8.4.12
  - Deprecation
  - Dependency
- 2.8.4.11
  - Bugfix
- 2.8.4.10
  - Feature
  - Bugfix
  - Dependency
- 2.8.4.9
  - Bugfix
- 2.8.4.8
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 2.8.4.7
  - Bugfix
- 2.8.4.6
  - Bugfix
  - Dependency
  - Performance
- 2.8.4.5
  - Feature
  - Bugfix
  - Dependency
  - Performance
- 2.8.4.4
  - Bugfix
- 2.8.4.3
  - Breaking Change
  - Feature
  - Bugfix
  - Dependency
- 2.8.4.2
  - Bugfix
  - Dependency
- 2.8.4.1
  - Feature
  - Bugfix
  - Dependency
- 2.8.4.0
  - Feature

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

- Feature
- Bugfix
- 2.8.1.0
  - Bugfix
  - Dependency
- 2.8.0.0
  - Feature
  - Bugfix
  - Dependency
  - Deprecated

Did this doc help?

Yes No

Something wrong?
Report an Issue | Edit this Page
View all Kong documentation

Help us make these docs great!

Kong Developer docs are open source. If you find these useful and want to make them better, contribute today!
Contribute


Still need help?

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)




We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)

ly connecting, governing, and monetizing APIs and AI tokens across any model or cloud.

al Pricing

PI Specs Ingress Controller


lugins Traffic Control Plugins View all →

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)




We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)




We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)



T
©

We Value Your Privacy

English

By clicking "Accept All", you agree to the storing of cookies to enhance site navigation, usage and marketing efforts.

(Privacy Policy)