Release 2026.5

Copy Markdown link

Highlights

- **Account Lockdown**: Enterprise A new panic button for compromised accounts that can immediately cut off access, revoke tokens, end sessions, and leave an audit trail.
- **Conditional Access**: Enterprise New connectors verify device compliance and feed it into conditional access flows: Fleet (via Fleet certificates and an mTLS stage, without the authentik agent) and Google Chrome (via Chrome Enterprise Device Trust).
- **`AKQL` is now open source**: The `AKQL` search query language, previously enterprise-only, is now free for everyone to use.
- **Command Palette and wizard upgrades**: A new `Cmd + K` command palette to search the authentik UI, alongside reworked wizards including a new user creation wizard, improved binding wizard, and new invitation wizard.
- **Performance improvements**: The new Rust worker entrypoint drops memory usage by approximately 200 MB per worker container, and opens one fewer PostgreSQL connection per worker. The Admin interface is less resource-intensive through lazy-loaded modals.

Breaking changes

Listening on multiple IPs

For advanced use cases, authentik now supports setting listening settings to a comma-separated list of IPs. With this change, the default IP we listen on changed from `0.0.0.0` to `[::]` to better match ecosystem standards. Some IPv4-only environments might need to adapt those settings.

PostgreSQL custom connection options are deprecated

The `AUTHENTIK_POSTGRESQL__CONN_OPTIONS` and its replica equivalent are deprecated and will be removed in the next version. It was never properly used and may cause future breakages. If you're looking for a specific usage, open an issue to discuss alternative solutions.

New features and improvements

Account Lockdown Enterprise

Account Lockdown gives administrators and users a panic button to secure an account when compromise is suspected. From the Admin interface, an administrator can lock down a user directly from their detail page; users can also lock down their own account from **Settings** if they no longer trust their password or active sessions.

A lockdown can deactivate the account, invalidate the local authentik password, terminate active sessions, revoke API/app/recovery/verification/OAuth tokens and grants, and record the reason in the audit log. authentik includes a packaged blueprint with warnings, reason collection, and completion messages so teams can get started quickly and customize the experience where needed.

For setup details, refer to the Account Lockdown documentation.

Conditional access Enterprise

We've added two new connectors that verify device compliance and let you use them as a signal in conditional access flows.

Fleet: authentik can now verify user devices based on their Fleet certificates without requiring the authentik agent, using the Fleet Connector together with an mTLS stage. For details, refer to the Fleet Conditional Access documentation.

Google Chrome: authentik now includes a Google Device Trust connector that integrates with Chrome Enterprise Device Trust via the Chrome Verified Access API. This lets authentik validate that a user's Chrome browser or ChromeOS device is compliant — for example, running an up-to-date version with security patches applied. The

connector is especially useful for BYOD environments and remote workforces where device compliance can't be assumed.

Tap-to-login Secure Enclave support Enterprise

Endpoint Devices now support independent Secure Enclave keys for tap-to-login. This allows iPhone and Apple Watch credentials to be bound directly to a user, so tap-to-login can work without first pairing the credential to a specific endpoint device.

2FA attempt throttling

The Authenticator Validation stage can now throttle repeated failed attempts for email and SMS OTP devices, extending the same brute-force protection already available for TOTP and static authenticators. Admins can tune throttling behavior to slow down repeated guessing attempts without changing the user's login flow.

Import hashed passwords

authentik can now bootstrap and import users with pre-hashed Django passwords, making automated installs and migrations safer by avoiding plaintext passwords in deployment workflows.

Use `AUTHENTIK_BOOTSTRAP_PASSWORD_HASH` for the initial `akadmin` password, generate hashes with the new `hash_password` command, or import hashes later through blueprints and the user password-hash API.

Hashed-password imports update authentik's local password verifier only. Because authentik never receives the raw password, these imports are not written back to LDAP or Kerberos sources.

Command Palette

The new command palette lets you quickly navigate authentik without clicking through menus. Press `Cmd + K` (or `Ctrl + K` on Windows and Linux) from anywhere in the UI to open it, then start typing to jump to a page, run an action, or look up a user. You can also use `Cmd/Ctrl + /` to jump straight into search, or `Cmd/Ctrl + Shift + K` to open directly to the actions list.

Results are grouped by category, including pages within authentik, users, and documentation searches that open on docs.goauthentik.io. The palette is designed to make routine admin tasks faster — useful when you know what you want to do but don't want to hunt for the right menu.

WebAuthn Client Hints support

The WebAuthn Stage now supports the `hints` parameter from the WebAuthn Level 3 spec. Admins can configure one or more hints (`security-key`, `client-device`, or `hybrid`) to tell the browser which authenticator type to expect. The browser uses this to skip straight to the relevant selection UI during passkey registration and authentication, reducing friction especially in enterprise deployments where security keys are mandatory.

Keep in mind that hints are advisory — they only affect the browser UI, not policy. Authenticator type requirements still need to be enforced server-side.

`AKQL` is now open source

The `AKQL` search query language was previously an enterprise-only feature. `AKQL` is now free for everyone to use, allowing searches based on specific attributes such as `context.geo.country = "Germany"`. For the full syntax and a list of where you can use it, see the AKQL reference.

OAuth2 configurable grant types

OAuth2 providers now have a **Grant Types** setting that lets admins explicitly choose which grant types a given provider may use. The available options are Authorization Code, Implicit, Hybrid, Refresh token, Client credentials, Password, and Device-code. Existing providers default to having all grant types enabled to preserve current behavior, but you can now disable any grant types you don't want a particular client to use — useful for tightening security on individual integrations and disabling legacy flows like Implicit or Password where they aren't needed.

Improved UI and accessibility

Accessibility and user experience improvements have been made across the admin interface.

Form accessibility

Form labels have been updated to be more descriptive for screen readers, and now informing you of the full action that will be executed when the button is pressed. This change is being rolled out across the entire admin interface, starting with the most commonly used buttons and forms. These changes have all been reflected in the docs as well, helping to make authentik more accessible for all users.

Modal accessibility

In addition to general improvements to form accessibility, many of our modals now use the browser native `<dialog>` element, fixing several issues which prevented screen readers from properly traversing modal content. We'll be phasing out the remaining non-`<dialog>` modals over the next few releases to ensure a more consistent and accessible experience across the entire admin interface.

Wizard improvements

Wizards throughout authentik have been reworked to have fewer steps and cover of the most common use cases.

The invitation wizard in particular now makes it easy for administrators to send invites to new users. It guides admins through the process of configuring an invite system and sending the invites to users.

Service accounts are now created through the new user creation wizard, which has been reworked to be more intuitive and faster to use.

Mobile and tablet improvements

While authentik's admin interface is primarily designed for desktop use, we've made several improvements to make it more usable on mobile and tablet devices for those times when you need to make a quick change on the go.

Login improvements

The login flow has additional UI improvements to reduce friction and make it easier to use, including:

- An improved "Remember me" option that autofocuses the most appropriate input field based the presence of a username or password field.
- Better error handling and messaging for failed login attempts, including more specific error messages for WebAuthn when authentication fails.
- Additional mobile optimizations, such as better keyboard handling, field focus, and responsive design improvements to make the login flow easier to use on mobile and tablet devices.

Small general improvements

SAML provider issuer: authentik now automatically generates your SAML issuer URL. You can still override the default SAML issuer.

SAML provider unified endpoints: Instead of an individual endpoint for login and logout for redirect and post, there is now a single SAML endpoint that handles login and logout for both request methods.

Application Dashboard: The **My applications** page has been renamed to **Application Dashboard**, and related option labels have been updated to match. Our documentation and integration guides have been updated as well. You can now also hide applications from the **Application Dashboard** page using the new **Hide from Application Dashboard** toggle.

> **INFO**
>
> Before authentik 2026.5, an application was hidden by setting its **Launch URL** to `blank://blank`. Existing applications using that value are automatically migrated to using the **Hide from Application Dashboard** option upon upgrading.

Dependencies: We've removed 17 packages from authentik. Fewer dependencies mean less code to maintain and keep patched, and a smaller attack surface overall.

Performance improvements

The authentik worker now starts through a Rust entrypoint. Python still runs authentik's worker code, but the Rust process owns worker startup, health checks, metrics, and worker-status reporting. This removes an idle top-level Python process and has led to an approximately 200 MB drop in memory usage for a single worker container. If you're a developer, check the updated Developer Docs to install Rust.

The worker status reporting change also uses one fewer PostgreSQL connection per worker, which should put less load on the database.

The Admin interface is also less resource-intensive in the browser due to lazy-loaded modals.

New out-of-the-box experience

When setting up authentik for the first time, you will now automatically be redirected to the initial-setup flow instead of having to manually go there to complete your authentik installation.

New integration guides

An integration is how authentik connects to third-party applications, directories, and other identity providers. The following integration guides were recently added. A big thanks to our contributors!

- Absorb LMS (Thanks to **@dewi-tik**!)
- Anthropic (Thanks to **@dominic-r**!)
- Anthropic Workload Identity Federation (Thanks to **@dominic-r**!)
- Forgejo (Thanks to **@djagoo**!)
- grommunio (Thanks to **@snxRCS**!)
- Okta (Thanks to **@dewi-tik**!)
- OneUptime (Thanks to **@M-Slanec**!)
- PhotoPrism (Thanks to **@dominic-r**!)
- PostHog (Thanks to **@dominic-r**!)
- RabbitMQ (Thanks to **@djooberlee**!)
- Splunk Enterprise (Thanks to **@jhuesser**!)

- Technitium DNS (Thanks to **@scinca**!)

Integration guide updates

- The GitHub Enterprise integration docs were revamped and split into dedicated guides for GitHub Enterprise Cloud, GitHub Enterprise Managed Users, and GitHub Enterprise Server, making it easier to pick the right SAML and SCIM setup path. (Thanks to **@dominic-r**!)
- Integration guides that configure application-side roles and permissions now use authentik Application Entitlements, giving admins a more consistent pattern for mapping access. (Thanks to **@dominic-r**!)
- The Jellyseerr integration guide was updated for the project's move to Seerr. (Thanks to **@BreizhHardware**!)
- The Home Assistant guide now covers both supported community OIDC integrations, `christiaangoossens/hass-oidc-auth` and `cavefire/hass-openid`, with UI and YAML setup options. (Thanks to **@christiaangoossens**!)
- The NetBird guide was refreshed to match NetBird's current authentik provider setup, with separate paths for adding authentik as an external identity provider or fully replacing NetBird's embedded IdP. (Thanks to **@dominic-r**!)

Upgrading

This release does not introduce any new requirements. You can follow the upgrade instructions below; for more detailed information about upgrading authentik, refer to our Upgrade documentation.

> **UPGRADE IN ORDER AND UPGRADE ALL COMPONENTS**
>
> Upgrades MUST be performed sequentially by major version. If you are two or more major releases behind, you must first upgrade to each intermediate major release before upgrading to this one. Refer to our Upgrade documentation for more information on upgrade sequence.

> The version of the authentik instance and of any outposts must be the same. We recommend that you always upgrade any outposts at the same time you upgrade your authentik instance.

Docker Compose

To upgrade, download the new compose file and update the Docker stack with the new version, using these commands:

```
wget -O compose.yml
https://goauthentik.io/version/2026.5/lifecycle/container/compose.yml
docker compose up -d
```

The `-O` flag retains the downloaded file's name, overwriting any existing local file with the same name.

Kubernetes

Upgrade the Helm Chart to the new version, using the following commands:

```
helm repo update
helm upgrade authentik authentik/authentik -f values.yaml --version
^2026.5
```

Minor changes/fixes

- admin/files: allow configuring S3 signature version (#20639)
- admin/files: sign custom-domain S3 URLs for the final host (#21704)
- api: cleanup enums (#21201)
- api: make ordering null-aware (#22099)
- api: set authenticated session user agent nullable properties (#22059)
- blueprints: fix mismatched API schema and implementation (cherry-pick #22087 to version-2026.5) (#22171)

- blueprints: rework one-time import (#18074)
- core, web: update translations (#22129)
- core, web: Vendored client follow-ups (#21174)
- core: add cooldown to dependabot (#21286)
- core: add flag for future default behavior of requiring a binding to access an application (#16247)
- core: add logging when session decode fails (#21514)
- core: add support for hiding applications from the user dashboard (#21530)
- core: allow interfaces to specify alternative stylesheets (#20774)
- core: Application stats, device events & cleanup (#21225)
- core: Apply CSpell corrections. (#20191)
- core: complete rework to oobe and setup experience (#21753)
- core: redirect service accounts away from main UI like external users (#20900)
- core: refresh signed media URLs in flows (#21553)
- core: remove filter_not_expired for QS (#18274)
- core: simplify boolean (#21790)
- core: support hashed password in users API + automated install (#18686)
- core: survive the empty-queryset race in chunked_queryset (#21666)
- core: uncomment failFast in cspell config file (#21116)
- core: users/groups reduce number of database queries (#20431)
- core/applications: Optimize list applications when only_with_launch_url=true (#20428)
- crypto: improve discovery for mounted k8s TLS Secrets (#17636)
- docs,ci: fix main daily compose downloads + release template (#21448)
- docs: Improve docs on webauthn authenticator attachment (#22045)
- endpoints: remove `print` line (cherry-pick #22325 to version-2026.5) (#22327)
- endpoints/connectors/agent: cleanup leftover (#20808)
- enterprise: account lockdown (#18615)
- enterprise: fix account lockdown target handling (cherry-pick #22246 to version-2026.5) (#22252)
- enterprise/endpoints/connectors: add google_chrome (#19129)
- enterprise/endpoints/connectors: Fleet conditional access stage (#20978)

- enterprise/endpoints/connectors/agent: add independent secure enclave support for tap to login (#20766)
- enterprise/lifecycle: remove one review per object limitation (#21046)
- enterprise/providers/scim: add support for interactive OAuth2 (cherry-pick #22072 to version-2026.5) (#22337)
- enterprise/providers/ssf: more conformance fixes (#21521)
- enterprise/providers/ssf: test conformance (#21383)
- enterprise/search: move QL to open source (#21484)
- enterprise/stages/mtls: attempt fix freezegun (cherry-pick #22474 to version-2026.5) (#22501)
- enterprise/stages/mtls: fix traefik cert encoding (#20483)
- enterprise/stages/mtls: freeze time for expired certs (cherry-pick #22411 to version-2026.5) (#22415)
- events: add helper to log deprecation configuration_warning message (#21115)
- events: add index on Event.user.pk (#19576)
- events: add option to configure webhook CA (#20823)
- events: don't log cacheentry events (#21597)
- events: fix exception in volume endpoint, adjust simple table size (#21230)
- Fix redirect URI in Seafile integration documentation (#20532)
- flows: add warning message for expired password reset links (#21395)
- flows: preserve signed background URLs in CSS (#21868)
- flows: remove link to overview for non-internal user (cherry-pick #22362 to version-2026.5) (#22371)
- internal: Automated internal backport: CVE-2026-40165.sec.patch to authentik-2026.5 (#22290)
- internal: Automated internal backport: CVE-2026-40166.sec.patch to authentik-2026.5 (#22291)
- internal: Automated internal backport: CVE-2026-40172.sec.patch to authentik-2026.5 (#22292)
- internal: Automated internal backport: CVE-2026-41569.sec.patch to authentik-2026.5 (#22293)
- internal: Automated internal backport: CVE-2026-41577.sec.patch to authentik-2026.5 (#22294)

- internal: Automated internal backport: CVE-2026-42849.sec.patch to authentik-2026.5 (#22295)
- internal: Automated internal backport: GHSA-5wcc-hf24-rf5h.sec.patch to authentik-2026.5 (#22296)
- internal: Automated internal backport: GHSA-973w-j457-rp2m.sec.patch to authentik-2026.5 (#22297)
- internal: remove unix sockets on shutdown (#21081)
- internal/outpost: serialize websocket writes to prevent panic (#21728)
- internal/outpost/ak: fix ws URL on outpost restart (#21041)
- internal/web: remove authentication for metrics (#21077)
- lib/config: explicit some defaults (#21079)
- lib/config: support printing multiple values (#21080)
- lifecycle: disable gunicorn control socket (#21408)
- lifecycle/ak: Add manage support (cherry-pick #22176 to version-2026.5) (#22221)
- lifecycle/container: allow cross-compilation from arm64 to amd64 (#21817)
- lifecycle/container: fix OCI image labels (#21574)
- lifecycle/container: fix rust builds and pin toolchain version (#20300)
- lifecycle/container: only mount required packages directories (#21859)
- lifecycle/worker_process: fix healthchecks and metrics not reloading db connections after a failure (#21992)
- locale: fix de_DE locale placeholder (#22130)
- outposts: Create separate metrics service in Kubernetes (#21229)
- outposts: fix stale version in OutpostState (cherry-pick #22487 to version-2026.5) (#22505)
- outposts/controllers/k8s: add option to disable strict x509 checks (#21210)
- packages: use openapi-generator-ignore instead of deleting extra files (#21209)
- packages/ak-axum: init (#21313)
- packages/ak-axum/accept/catch_panic: add acceptor to catch panics in lower acceptors, streams and services (#21860)
- packages/ak-axum/accept/proxy_protocol: init (#21319)
- packages/ak-axum/accept/tls: init (#21318)
- packages/ak-axum/error: init (#21315)
- packages/ak-axum/extract/client_ip: init (#21321)

- packages/ak-axum/extract/host: init (#21323)
- packages/ak-axum/extract/scheme: init (#21322)
- packages/ak-axum/extract/trusted_proxy: init (#21320)
- packages/ak-axum/router: add X-Powered-By to all responses (#21940)
- packages/ak-axum/server: cleanup unix socket (#21477)
- packages/ak-axum/server: fix unix socket cleanup when allow_failure is unset (#21645)
- packages/ak-axum/server: init (#21317)
- packages/ak-axum/tracing: init (#21316)
- packages/ak-common, ak-axum: improve logging (#21476)
- packages/ak-common: rename from ak-lib (#21314)
- packages/ak-common: use imports where possible (#21478)
- packages/ak-common/arbiter: init (#21253)
- packages/ak-common/config: add set helper for tests (#21356)
- packages/ak-common/config: fix boolean parsing from env variable (#21835)
- packages/ak-common/config: fix string load broken after previous fix (#21854)
- packages/ak-common/config: init (#21256)
- packages/ak-common/db: init (#21357)
- packages/ak-common/mode: init (#21259)
- packages/ak-common/tls: init (#21262)
- packages/ak-common/tokio/proxy_protocol: init (#21311)
- packages/ak-common/tracing: get sentry config from API for outposts (#21625)
- packages/ak-common/tracing: init (#21263)
- packages/ak-common/tracing: make log level lowercase (#21991)
- packages/ak-lib: init (#21257)
- packages/client-go: init (#21139)
- packages/client-rust: fix portable sed usage (#21337)
- packages/client-rust: init (#21117)
- packages/client-ts: Fix TypeScript config, ESBuild warnings (#21863)
- packages/client-ts: init (#21120)
- packages/clients: only generate needed endpoints (#21578)

- packages/django-dramatiq-postgres: add index for (queue_name, state, eta) (#21175)
- packages/django-dramatiq-postgres: fix default value for HTTPServerThread (#21216)
- packages/django-postgres-cache: fix expiry and delete (#21307)
- packages/django-postgres-cache: rework to use ORM (#17771)
- packages/docusaurus-config: update config for docusaurus 3.10 (#21471)
- policies: remove BufferedPolicyAccessView (#20521)
- policies: remove BufferedPolicyAccessView leftovers (#21057)
- policies/event_matcher: Add query option to filter events (#21618)
- providers/oauth: make rp init logout oidc certification changes (#21815)
- providers/oauth: post_logout_redirect_uri support (#20011)
- providers/oauth2: Configure allowed grant types (#20363)
- providers/oauth2: evaluate property mappings in client credentials JWT flow (#20979)
- providers/oauth2: override RedirectURITypeEnum capitalization for generated API (#22037)
- providers/oauth2: require client_secret on device_code exchange for confidential clients (#21700)
- providers/proxy: fix oidc client not using socket in embedded outpost (#21280)
- providers/rac: add e2e tests (#21390)
- providers/saml: Add sls to saml overview (cherry-pick #22183 to version-2026.5) (#22368)
- providers/saml: generate issuer url when provider is set on app (#18022)
- providers/saml: handle XML declarations in unified endpoint (cherry-pick #22455 to version-2026.5) (#22539)
- providers/saml: make issuer url metadata url (cherry-pick #22178 to version-2026.5) (#22184)
- providers/saml: make unified saml endpoint (cherry-pick #20026 to version-2026.5) (#22187)
- providers/saml: Properly import audience from metadata. (cherry-pick #22181 to version-2026.5) (#22449)
- providers/saml: send logoutResponse on sp-init logout (#17691)

- providers/SCIM: Add discover support (#20658)
- providers/scim: add webex compatibility mode (#21208)
- providers/scim: ak_groups -> groups in tests (#20580)
- providers/scim: fix vCenter compatibility mode (#21830)
- providers/scim: use modified GroupMember class to support extra attributes on it (#20827)
- release: 2026.5.0-rc1
- release: 2026.5.0-rc2
- revert: web: Consistent use of "User Dashboard" (#22038) (#22046)
- root: add git attributes for generated/vendored (#21177)
- root: add more logging to worker requests (#21989)
- root: allow listening on multiple IPs (#20930)
- root: cleanup API generation (#21172)
- root: configure dependabot for cargo (#21118)
- root: configure freezegun to exclude cryptography (cherry-pick #22442 to version-2026.5) (#22448)
- root: ensure uv sync does not update uv.lock (#22084)
- root: fix `gen-changelog` and `gen-diff` (#20598)
- root: fix dependabot config for docker (#20380)
- root: fix gitignore binary paths (cherry-pick #22445 to version-2026.5) (#22485)
- root: fix log function to redirect output to stderr (#20858)
- root: fix rust build with uv-installed Python (#21858)
- root: fix rust setup (#21078)
- root: fix rustfmt config (#21312)
- root: fix scripts compose & gen-diff (#21389)
- root: fix test runner dropping exit code (#20630)
- root: include relative time for each test case in logs (#21445)
- root: init rust worker (#21324)
- root: init rust workspace (#20983)
- root: introduce allinone mode (#21990)
- root: makefile: remove spellcheck from lint-fix (#20924)
- root: misc API client and web typing fixes (#21388)

- root: only allow listen failure in dev (#21987)
- root: optimize api client generation speed (#21141)
- root: refreshed icon (cherry-pick #22265 to version-2026.5) (#22266)
- root: remove unused `django-cte` (#20090)
- root: run `npm i` with `npm@11.10.1` in all subdirectories (#20471)
- root: update rustls-webpki (#21769)
- root/channels: use group_send_blocking where possible (#21993)
- scripts/api_filter_schema: fix authentication (#21644)
- security: CVE-2026-25227 (#20239)
- security: CVE-2026-25748 (#20240)
- security: CVE-2026-25922 (#20241)
- source/saml: Add forceauthn to saml authnrequest (#20883)
- sources/ldap: Better Active Directory tests (#21281)
- sources/ldap: catch Google LDAP rate-limit errors during schema fetch (#21638)
- sources/ldap: Switch to new connection tracking, deprecated attribute-based connection (#21392)
- sources/oauth: correctly check requests' exception response (#21386)
- sources/oauth: ensure user ID is returned as str (#21880)
- sources/oauth: pick a single pkce method from OIDC discovery, not the whole list (#21689)
- sources/saml: improve exception handling for saml response parsing (#20125)
- stage/authenticator*: expand attempt throttling to email- and sms-based 2FA (#21751)
- stage/invitation: Send invite via email UI (#19823)
- stages/authenticator_webauthn: Add WebAuthn client hints support (#20700)
- stages/authenticator_webauthn: save attestation certificate when creating credential (#20095)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#20305)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#20642)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#20905)

- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#21290)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#21612)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#21999)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (#22128)
- stages/authenticator_webauthn: Update FIDO MDS3 & Passkey aaguid blobs (cherry-pick #22322 to version-2026.5) (#22323)
- stages/invitation: Invitation wizard (#20399)
- stages/user_write: refuse to write id/pk claims onto the user model (#21667)
- tasks: better error message for Retry exceptions (#18235)
- tasks: fix the occasional DatabaseError for no updated fields (#20629)
- tasks: fix workers API URL missing trailing / (#20954)
- tasks: improved tests (#18978)
- tasks: threads instead of forks (#19476)
- tenants: add option to mark flag as deprecated (#22063)
- tenants: fix default schema in initial migration (#21114)
- tenants: fix system flags removeable (cherry-pick #22163 to version-2026.5) (#22182)
- tests: add mixin to launch traefik for tests requiring SSL (#22011)
- tests: refactor test harness to split apart a single file (#21391)
- translate: Updates for project authentik and language bg_BG (#22112)
- translate: Updates for project authentik and language cs_CZ (#22115)
- translate: Updates for project authentik and language de_DE (#21825)
- translate: Updates for project authentik and language de_DE (#22113)
- translate: Updates for project authentik and language es_ES (#22116)
- translate: Updates for project authentik and language fi_FI (#22114)
- translate: Updates for project authentik and language fr_FR (#21056)
- translate: Updates for project authentik and language fr_FR (#21214)
- translate: Updates for project authentik and language fr_FR (#21285)
- translate: Updates for project authentik and language fr_FR (#21378)

- translate: Updates for project authentik and language fr_FR (#21474)
- translate: Updates for project authentik and language fr_FR (#22008)
- translate: Updates for project authentik and language fr_FR (#22015)
- translate: Updates for project authentik and language fr_FR (#22117)
- translate: Updates for project authentik and language it_IT (#22123)
- translate: Updates for project authentik and language ja_JP (#22118)
- translate: Updates for project authentik and language no_NO (#21862)
- translate: Updates for project authentik and language no_NO (#22120)
- translate: Updates for project authentik and language pl_PL (#22124)
- translate: Updates for project authentik and language pt_BR (#22111)
- translate: Updates for project authentik and language pt_PT (#22122)
- translate: Updates for project authentik and language ru_RU (#22119)
- translate: Updates for project authentik and language tr_TR (#22125)
- translate: Updates for project authentik and language zh-Hans (#22121)
- web, website: Update name to application dashboard (cherry-pick #22190 to version-2026.5) (#22374)
- web: Apply CSpell corrections. (#20190)
- web: build system had some legacy stuff that I found confusing while working on the CSS ordering (#20698)
- web: Clear remember me before navigation. (#21647)
- web: Close modal on route navigation (#21622)
- web: CodeSpell -> CSpell migration (#20188)
- web: Consistent use of "User Dashboard" (#22038)
- web: fix a few visual nits reported after the latest release (#22012)
- web: Fix admin table horizontal scrolling (#20960)
- web: Fix element property names with custom attributes. (#20396)
- web: fix identification stage OUIA attributes (#22049)
- web: Fix issue where default user path is not preferred. (cherry-pick #22139 to version-2026.5) (#22364)
- web: Fix table visibility checks, search params. (#21623)
- web: Fix Vendored Lex package. Add Unit Tests (#22083)
- web: Gracefully handle missing element construction. (#21787)

- web: link file picker to docs (#20995)
- web: lint/small type errors (#21179)
- web: merge MFA devices and tokens into unified Credentials tab (#21705)
- web: Normalize use of `.toJSON()` over `.json()` (#21621)
- web: Packagify Logger (#20541)
- web: Radio and Checkbox Input Revisions (#21792)
- web: remove native fieldset borders from action groups (#21334)
- web: rename SCIM provider "User filtering" section to "Filtering" (#20879)
- web: revert `tree-sitter` removal from lockfile (#20377)
- web: Supply our font and color choices to rapidoc. (#20775)
- web: User Wizard, Modal Revisions Merge Branch (#21336)
- web/a11y: Modal revisions, component name normalization (#21205)
- web/a11y: Modals, Command Palette (Merge branch) (#17812)
- web/admin: add outposts view page (#21167)
- web/admin: Allow binding users/groups in policy binding wizard and existing stage in stage binding wizard (#21697)
- web/admin: Cleanup spacing in and around cards (#21199)
- web/admin: fix log viewer layout for application access check (#21594)
- web/admin: fix missing icon on app view page (#21251)
- web/admin: fix policy/stage wizard label, fix connector create wizard, cleanup (#21781)
- web/admin: fix user list avatar (#21531)
- web/admin: fix user wizard close button (cherry-pick #22222 to version-2026.5) (#22243)
- web/admin: Improve WS-Fed algo selection logic (#20881)
- web/admin: include avatar in user list page (#21518)
- web/admin: legacy modal fixes and fix log viewer in form layout (cherry-pick #22168 to version-2026.5) (#22173)
- web/admin: maintenance: centralize types that are used across stages (#20398)
- web/admin: maintenance: give dialogs default exports (#20397)
- web/admin: more and more polish (#21303)
- web/admin: polish recent events, various button alignments and labels (#21232)

- web/admin: redirect stage: adds mention of static url (#22060)
- web/admin: remove side-padding on user paths (#22088)
- web/admin: show app events on app page (#21203)
- web/admin: use bindings form for app entitlements (#22007)
- web/admin: User wizard label adjust and deactivate navigation when wizard is finished (cherry-pick #22133 to version-2026.5) (#22191)
- web/e2e: accept options in NavigatorFixture.waitForPathname (#21507)
- web/elements: Add preserve-order, no-search and no-status attributes to ak-dual-select (#20749)
- web/elements: add scrollbar helpers and apply to Interface (#21511)
- web/elements: Add static table class (#21181)
- web/elements: add viewport helpers and extend intersection observer (#21508)
- web/elements: allow table per-column options (#21250)
- web/elements: default **@listen** target to host element and add split-button Dropdown (#21512)
- web/flow: bug: inspector button not hiding when unavailable (#20717)
- web/flow: extract lifecycle events peripheral to stage management into their own controllers (#20898)
- web/flow: fix typo in RedirectStage (#20488)
- web/flow: generate a single API object for network transactions and use it for the lifetime of the FlowExecutor (#20030)
- web/flow: provide labels for the stage import-and-invoke table (#20834)
- web/flow: provide layout url as needed (#20991)
- web/flow: refactor flow executor so component selection is in an easy-to-maintain table (#19999)
- web/flow: separate flow inspector lifecycle from flow executor lifecycle (#20063)
- web/flow: separate out independent behavior tracks from IdentificationStage (autoredirect, webauthn, captcha, remember me) (#20578)
- web/flow: Tidy identification stage (#20261)
- web/flow/stages: permit the form handler to look in the light or shadowDOM for controls (#20832)
- web/flows: fix continuous flow leftovers (#21158)
- web/flows: Fix username autofocus. (#21646)

- web/flows: update flow background (#22032)
- web/maintenance: no unknown attributes part 2 (#19014)
- web/rac: Ignore empty remote clipboard payloads (#22067)
- Web/release202604/nits 2 (#22040)
- web/stages: better wording for webauthn authenticator attachments options (#22062)
- web/style/flow: flow css barrel file (#20833)
- web/styles: add ak-c-loading-skeleton CSS component (#21510)
- web/styles: switch to upstream RedHat variable fonts and brighten orange palette (#21509)
- web/table: fetch on first render when already visible (cherry-pick #22376 to version-2026.5) (#22438)

Fixed in 2026.5.1

This release has been skipped.

Fixed in 2026.5.2

- endpoints/connectors/agent: allow federated auth via ssh hostkey lookup (cherry-pick #22594 to version-2026.5) (#22597)
- enterprise/providers/scim: fix last_updated for OAuth interactive (cherry-pick #22678 to version-2026.5) (#22700)
- events: fix Event.log_deprecation not checking that cause is a string (cherry-pick #22598 to version-2026.5) (#22683)
- packages/ak-common/db: fix certificates options not allowing file paths (cherry-pick #22680 to version-2026.5) (#22685)
- packages/ak-common/db: fix conn_max_age causing spinning (cherry-pick #22679 to version-2026.5) (#22686)
- providers/oauth2: fix session decode when upgrading from 2026.2 (cherry-pick #22684 to version-2026.5) (#22692)
- security: CVE-2026-47201
- security: GHSA-wr38-7xg8-fqxr

- security: GHSA-xp7f-xjjx-gwm8

Fixed in 2026.5.3

- blueprints: handle integrity exception when applying blueprints (cherry-pick #22599 to version-2026.5) (#22927)
- core: bump django from 5.2.14 to v5.2.15 (cherry-pick #22956 to version-2026.5) (#22962)
- endpoints/connectors/agent: fix exception with invalid auth type (cherry-pick #22943 to version-2026.5) (#22951)
- enterprise/providers/scim: fix interactive OAuth overriding refresh_token (cherry-pick #22858 to version-2026.5) (#22861)
- providers/oauth: skip post logout redirect matching if none are saved on the provider (cherry-pick #22718 to version-2026.5) (#22955)
- providers/radius: fix panic in log due to type (cherry-pick #22965 to version-2026.5) (#22967)
- tests/e2e: fix proxy tests failing due to in-use port (cherry-pick #22785 to version-2026.5) (#22792)
- web/admin: fix Docker outpost integration form CA Cert filter (cherry-pick #22863 to version-2026.5) (#22895)
- web/polyfill: polyfill customElements.getName for Safari < 17.4 (cherry-pick #22940 to version-2026.5) (#22963)

Fixed in 2026.5.4

- brands: select_related models accessed in the hot path (cherry-pick #23162 to version-2026.5) (#23524)
- core: bump goauthentik/fips-debian and fips-python in /lifecycle/container (cherry-pick #23362 to version-2026.5) (#23384)
- core: bump pydantic from 2.13.3 to 2.13.4 (cherry-pick #22207 to version-2026.5) (#23570)
- core: fix Invitation Emails Ignoring Selected Template (cherry-pick #23122 to version-2026.5) (#23133)

- core: handle missing tenant in setup migration (cherry-pick #23034 to version-2026.5) (#23762)
- core: preserve encoded avatar URLs (cherry-pick #23225 to version-2026.5) (#23394)
- docs: Americanize and minor fixes (cherry-pick #22600 to version-2026.5) (#22604)
- packages/ak-common/config: coerce file:// and env:// values to their native type (cherry-pick #23758 to version-2026.5) (#23759)
- packages/django-dramatiq-postgres/broker: fix race condition in broker causing completed tasks to be repeated (cherry-pick #23218 to version-2026.5) (#23257)
- packages/django-dramatiq-postgres/broker: purge at start of loop to ensure it runs (cherry-pick #23185 to version-2026.5) (#23188)
- packages/django-postgres-cache: avoid regex queries when listing keys if possible (cherry-pick #23160 to version-2026.5) (#23423)
- packages/django-postgres-cache: fix naive datetime warning (cherry-pick #23033 to version-2026.5) (#23235)
- packages/django-postgres-cache: remove custom get_or_set implementation (cherry-pick #23182 to version-2026.5) (#23213)
- policies: skip cache invalidation on User last_login update (cherry-pick #23159 to version-2026.5) (#23421)
- providers/*: fix missing declaration for can_discover for outgoing sync providers (cherry-pick #23035 to version-2026.5) (#23233)
- providers/ldap: remove incorrect validation for code authenticator extraction (cherry-pick #23006 to version-2026.5) (#23767)
- providers/oauth: Properly return error via post and for request objects (cherry-pick #23037 to version-2026.5) (#23529)
- providers/scim: account for users with no email during discovery (cherry-pick #23417 to version-2026.5) (#23485)
- providers/scim: allow failures during discovery (cherry-pick #23357 to version-2026.5) (#23365)
- root: Fix SECURITY.md versions (cherry-pick #23370 to version-2026.5) (#23372)
- root: bump pyo3 (cherry-pick #23036 to version-2026.5) (#23038)
- root: update crossbeam-epoch (cherry-pick #23794 to version-2026.5) (#23795)

- sources/ldap: avoid re-creating connections to LDAP server (cherry-pick #23520 to version-2026.5) (#23525)
- sources/ldap: optimize the connection endpoints (cherry-pick #23761 to version-2026.5) (#23765)
- stages/authenticator_webauthn: disable prevent_duplicate_devices by default (cherry-pick #23823 to version-2026.5) (#23826)
- tasks/schedules: fix paused schedules getting unpaused on startup (cherry-pick #23521 to version-2026.5) (#23527)
- tasks: add pre_delete for TasksModel to avoid OOM when deleting object with many tasks linked (cherry-pick #23664 to version-2026.5) (#23666)
- tasks: avoid useless query on monitoring_set (cherry-pick #23161 to version-2026.5) (#23424)
- web, core: Fix server-side message race condition, type mismatch. (cherry-pick #23151 to version-2026.5) (#23584)
- web/admin: fix spacing issues in wizard (cherry-pick #23484 to version-2026.5) (#23488)
- web/i18n: Fix stale flow locale, unsynchronized locale selector options (cherry-pick #23007 to version-2026.5) (#23148)
- web/stages/identification: Fix passkey autofill dropdown not showing on the identification stage (cherry-pick #23187 to version-2026.5) (#23189)
- web: Fix outline selector, lack of outline on focused checkboxes. (cherry-pick #23260 to version-2026.5) (#23825)
- web: Fix stale clipboard tokens, untranslated labels (cherry-pick #23063 to version-2026.5) (#23143)
- web: Fix user list default paths. (cherry-pick #23062 to version-2026.5) (#23127)
- web: Invitation Wizard Clean Up, Form Validation Fixes (cherry-pick #23316 to version-2026.5) (#23811)
- website: migrate brand assets to pkg (cherry-pick #22336 to version-2026.5) (#23222)

Fixed in 2026.5.5

- api/search: add number and boolean support in AKQL queries on JSON fields (#23418) (cherry-pick #24028 to version-2026.5) (#24033)

- endpoints: handle exception in connector controller sync setup (cherry-pick #23852 to version-2026.5) (#23854)
- lib/sync/outgoing: fix discover running for each page (cherry-pick #24016 to version-2026.5) (#24019)
- packages/django-dramatiq-postgres/broker: close unusable PostgreSQL connections (cherry-pick #24023 to version-2026.5) (#24035)
- providers/scim: improve error display when error doesn't conform to scim schema (cherry-pick #23955 to version-2026.5) (#23957)
- security: automated internal backport of patch 1817.sec.patch to authentik-2026.5 (#24058)
- security: automated internal backport of patch 1822.sec.patch to authentik-2026.5 (#24059)
- security: automated internal backport of patch 1887.sec.patch to authentik-2026.5 (#24060)
- security: automated internal backport of patch 1919.sec.patch to authentik-2026.5 (#24061)
- security: automated internal backport of patch 1934.sec.patch to authentik-2026.5 (#24062)
- sources/oauth: improve id_token validation for apple source (cherry-pick #24017 to version-2026.5) (#24020)
- stages/email: fix ungrammatical expiry time in password reset templates (cherry-pick #22758 to version-2026.5) (#23952)
- tests/openid_conformance: migrate to upstream images (cherry-pick #23828 to version-2026.5) (#23834)
- web/admin: licensing: add usage totals (cherry-pick #23665 to version-2026.5) (#23668)
- web: Fix Log Viewer Intersection Observer. (cherry-pick #23861 to version-2026.5) (#23949)
- web: fix table refresh button not refreshing table data (cherry-pick #23780 to version-2026.5) (#23878)
- web/flows: fix race condition in continuous login and support source stages in authentication flows (cherry-pick #23049 to version-2026.5) (#23558)

Fixed in 2026.5.6

- core: Form friendly error on uniqueness constraint. (cherry-pick #23864 to version-2026.5) (#23881)
- endpoints/connectors/agent: fix auth schema for device endpoints (cherry-pick #24164 to version-2026.5) (#24167)
- enterprise/endpoints/connectors/fleet: pass populate_policies (cherry-pick #24108 to version-2026.5) (#24112)
- internal/config: make storage file paths overwritable via env vars (cherry-pick #24177 to version-2026.5) (#24220)
- lifecycle/container: drop curl and runit (cherry-pick #24008 to version-2026.5) (#24114)
- packages/django-dramatiq-postgres/broker: use positive state filter for pending messages (cherry-pick #24074 to version-2026.5) (#24166)
- policies: filter policy engine (cherry-pick #24025 to version-2026.5) (#24168)
- providers/scim: exclude read-only id from group PATCH payload and fix null-members add check (cherry-pick #23950 to version-2026.5) (#24227)
- providers/scim: fix enum warning when de-serializing (cherry-pick #23553 to version-2026.5) (#24231)
- providers/scim: fix non-schema compliant group member removal (cherry-pick #23800 to version-2026.5) (#24229)
- root: fix make gen-changelog (cherry-pick #24122 to version-2026.5) (#24260)
- root: fix make gen-diff command (cherry-pick #22548 to version-2026.5) (#24121)
- root: in-process per-IP rate throttle (#23015) (#24217)
- stages/captcha: fix hcaptcha height (#20901) (#24216)
- web/admin: fix app view failing when no events permissions (cherry-pick #24131 to version-2026.5) (#24252)
- web/flow: revert locale-driven flow re-request from FlowExecutor (cherry-pick #24050 to version-2026.5) (#24068)

Fixed in 2026.5.7

- blueprints: fix mismatched stage name in example 2fa login flow (cherry-pick #24668 to version-2026.5) (#24751)
- blueprints: handle invalid yaml, add dry run to apply_blueprint (cherry-pick #24813 to version-2026.5) (#24820)
- brands: fix schema for current brand's flags (cherry-pick #24376 to version-2026.5) (#24407)
- core: add user type-active-username index (cherry-pick #25223 to version-2026.5) (#25241)
- core: bump django from 5.2.15 to v5.2.16 (cherry-pick #24526 to version-2026.5) (#24532)
- core: bump django from 5.2.16 to v5.2.17 (cherry-pick #24793 to version-2026.5) (#24815)
- core: bump goauthentik/fips-debian from f18dbc4 to ed780d in /lifecycle/container (cherry-pick #25503 to version-2026.5) (#25508)
- core: bump goauthentik/fips-python from 3.14.6-slim-trixie-fips to 3.14.7-slim-trixie-fips in /lifecycle/container (cherry-pick #25049 to version-2026.5) (#25059)
- core: bump goauthentik/fips-python from 6abe1b to 3ebb7c in /lifecycle/container (cherry-pick #25504 to version-2026.5) (#25507)
- core: bump h2 from 0.4.15 to 0.4.16 (cherry-pick #25183 to version-2026.5) (#25185)
- core: bump library/golang from 1.26.2-trixie to 1.26.5-trixie in /lifecycle/container (#24414)
- core: fix group source connection source object (cherry-pick #24626 to version-2026.5) (#24674)
- core: return the intended status code from error views for all request methods (cherry-pick #24902 to version-2026.5) (#24957)
- core: set days=1 as default token duration for new installs (cherry-pick #25341 to version-2026.5) (#25386)
- crypto: don't dispatch discovery if one is queued (cherry-pick #25483 to version-2026.5) (#25511)
- endpoints/agent: fix Secure Enclave key dropped on first Platform SSO user registration (cherry-pick #24587 to version-2026.5) (#24589)
- endpoints/agent: return 400 instead of 500 for invalid Platform SSO token requests (cherry-pick #24588 to version-2026.5) (#24592)

- endpoints/connectors/agent: fix auth schema correctly (cherry-pick #24327 to version-2026.5) (#24330)
- endpoints/connectors: fix integrity error when device with same name exists already (cherry-pick #25237 to version-2026.5) (#25339)
- endpoints: handle error in facts (cherry-pick #25028 to version-2026.5) (#25031)
- enterprise/endpoints/connectors/fleet: fix exception when host has no policies (cherry-pick #24355 to version-2026.5) (#24366)
- enterprise: increase cache duration and ensure summary is cached (cherry-pick #25187 to version-2026.5) (#25198)
- lib: avoid DNS resolution in fqdn_rand (cherry-pick #25728 to version-2026.5) (#25760)
- lib/expression: fix policy request context pollution (cherry-pick #25462 to version-2026.5) (#25466)
- lifecycle: fix server prometheus metrics getting registered early with pid instead of worker ID (cherry-pick #25883 to version-2026.5) (#25896)
- packages/django-dramatiq-postgres/broker: chunked purge queryset (cherry-pick #25102 to version-2026.5) (#25105)
- packages/django-dramatiq-postgres: minor fixes (cherry-pick #23181 to version-2026.5) (#24663)
- providers/oauth2: fix missing authorization event for oauth provider, add tests (cherry-pick #24819 to version-2026.5) (#24823)
- providers/radius: allow empty message authenticator (cherry-pick #25097 to version-2026.5) (#25196)
- providers/scim: fix display of SCIMRequestException (2026.8) (cherry-pick #24833 to version-2026.5) (#24954)
- providers/scim: fix scim changed detection for nested attributes (cherry-pick #24332 to version-2026.5) (#24442)
- providers/scim: ignore key casing in SCIM responses (cherry-pick #24441 to version-2026.5) (#24485)
- rbac: use constant-time comparison in SecretKeyFilter (cherry-pick #24888 to version-2026.5) (#24947)
- root: don't include debug info for rust release profile (cherry-pick #24664 to version-2026.5) (#24670)

- security: automated internal backport of patch 1751-secrets-read-permission.sec.patch to authentik-2026.5 (#25960)
- security: automated internal backport of patch 1877-group-hierarchy-roles.sec.patch to authentik-2026.5 (#25961)
- security: automated internal backport of patch 1914-saml.sec.patch to authentik-2026.5 (#25962)
- security: automated internal backport of patch 2032-authenticator-email-recipient-override.sec.patch to authentik-2026.5 (#25963)
- security: automated internal backport of patch 2190-libxml2-doctype.sec.patch to authentik-2026.5 (#25964)
- server/core: handle unsupported HTTP method (cherry-pick #22498 to version-2026.5) (#25364)
- stages/email: fix test_email ignoring the given stage (cherry-pick #25166 to version-2026.5) (#25189)
- stages/identification: dynamic captcha keys when stage embedded in identification stage (cherry-pick #24079 to version-2026.5) (#25500)
- tenants/settings: fix `flags` response (cherry-pick #25616 to version-2026.5) (#25829)
- web/admin: drop misleading delete consequences from user activation review (cherry-pick #24273 to version-2026.5) (#24786)
- web/admin: fix schedule form (cherry-pick #25778 to version-2026.5) (#25831)
- web: bump dompurify from 3.4.12 to 3.4.13 in /web (cherry-pick #24892 to version-2026.5) (#25001)
- web/elements/table: show scrollbar instead of overflowing off the page (cherry-pick #25232 to version-2026.5) (#25392)
- web/flows: fix missing required flag on password input (cherry-pick #24831 to version-2026.5) (#24836)
- web: preserve custom event action labels (cherry-pick #25655 to version-2026.5) (#25834)
- worker: fix healthcheck paths (cherry-pick #24481 to version-2026.5) (#25677)

Fixed in 2026.5.8

- core: bump rustls (cherry-pick #26142 to version-2026.5) (#26144)

- lib/expression: fix PickleError due to resolver match when using ak_call_policy (cherry-pick #25763 to version-2026.5) (#26071)
- packages/django-channels-postgres: refresh pool credentials on connection attempts (cherry-pick #26505 to version-2026.5) (#26549)
- root: bump cert-related deps due to emudhra (cherry-pick #27068 to version-2026.5) (#27070)
- root: don't fail websocket connections with non-UTF-8 headers (cherry-pick #26688 to version-2026.5) (#26707)
- stages/consent: fix integrity error when re-consenting after consent expired (cherry-pick #26866 to version-2026.5) (#26871)
- web/flows: check if localStorage is available for continuous login (cherry-pick #26267 to version-2026.5) (#26639)
- web/source/flows: fix flicker after webauthn (cherry-pick #25454 to version-2026.5) (#25835)

API Changes

authentik (v 2026.5.0)

What's New

POST /core/users/{id}/set_password_hash/

POST /core/users/account_lockdown/

GET /endpoints/agents/psso/ise/

POST /endpoints/agents/psso/ise/

GET /endpoints/agents/psso/ise/{uuid}/

PUT /endpoints/agents/psso/ise/{uuid}/

DELETE /endpoints/agents/psso/ise/{uuid}/

PATCH /endpoints/agents/psso/ise/{uuid}/

`GET` /endpoints/agents/psso/ise/{uuid}/used_by/

`GET` /endpoints/google_chrome/connectors/

`POST` /endpoints/google_chrome/connectors/

`GET` /endpoints/google_chrome/connectors/{connector_uuid}/

`PUT` /endpoints/google_chrome/connectors/{connector_uuid}/

`DELETE` /endpoints/google_chrome/connectors/{connector_uuid}/

`PATCH` /endpoints/google_chrome/connectors/{connector_uuid}/

`GET` /endpoints/google_chrome/connectors/{connector_uuid}/used_by/

`GET` /events/events/stats/

`POST` /managed/blueprints/import/

`GET` /stages/account_lockdown/

`POST` /stages/account_lockdown/

`GET` /stages/account_lockdown/{stage_uuid}/

`PUT` /stages/account_lockdown/{stage_uuid}/

`DELETE` /stages/account_lockdown/{stage_uuid}/

`PATCH` /stages/account_lockdown/{stage_uuid}/

`GET` /stages/account_lockdown/{stage_uuid}/used_by/

`POST` /stages/invitation/invitations/{invite_uuid}/send_email/

`GET` /tasks/workers/

`DELETE` /ssf/streams/{uuid}/

What's Deleted

`POST` /flows/instances/import/

`GET` **/tasks/workers**

What's Changed

`GET` **/admin/file/**

Parameters:

Changed: `usage` in `query`

`DELETE` **/admin/file/**

Parameters:

Changed: `usage` in `query`

`GET` **/admin/settings/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flags` (object)

    New required properties:

    - `core_default_app_access`

    New optional properties:

    - `policies_buffered_access_view`
    - Added property `core_default_app_access` (boolean)

      > Configure if applications without any policy/group/user bindings should be accessible to any user.

    - Deleted property `policies_buffered_access_view` (boolean)
    - Changed property `enterprise_audit_include_expanded_diff` (boolean)

> Include additional information in audit logs, may incur a performance penalty.

- Changed property `flows_continuous_login` (boolean)

  > Upon successful authentication, re-start authentication in other open tabs.

- Changed property `flows_refresh_others` (boolean)

  > Refresh other tabs after successful authentication.

`PUT` /admin/settings/

Request:

Changed content type : `application/json`

- Changed property `flags` (object)

  New required properties:

  - `core_default_app_access`

  New optional properties:

  - `policies_buffered_access_view`
  - Added property `core_default_app_access` (boolean)

    > Configure if applications without any policy/group/user bindings should be accessible to any user.

  - Deleted property `policies_buffered_access_view` (boolean)
  - Changed property `enterprise_audit_include_expanded_diff` (boolean)

    > Include additional information in audit logs, may incur a performance penalty.

  - Changed property `flows_continuous_login` (boolean)

> Upon successful authentication, re-start authentication in other open tabs.

- Changed property `flows_refresh_others` (boolean)

  > Refresh other tabs after successful authentication.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flags` (object)

    New required properties:

    - `core_default_app_access`

    New optional properties:

    - `policies_buffered_access_view`
    - Added property `core_default_app_access` (boolean)

      > Configure if applications without any policy/group/user bindings should be accessible to any user.

    - Deleted property `policies_buffered_access_view` (boolean)
    - Changed property `enterprise_audit_include_expanded_diff` (boolean)

      > Include additional information in audit logs, may incur a performance penalty.

    - Changed property `flows_continuous_login` (boolean)

      > Upon successful authentication, re-start authentication in other open tabs.

    - Changed property `flows_refresh_others` (boolean)

      > Refresh other tabs after successful authentication.

`PATCH` **/admin/settings/**

Request:

Changed content type : `application/json`

- Changed property `flags` (object)

  New required properties:

  - `core_default_app_access`

  New optional properties:

  - `policies_buffered_access_view`
  - Added property `core_default_app_access` (boolean)

    > Configure if applications without any policy/group/user bindings should be accessible to any user.

  - Deleted property `policies_buffered_access_view` (boolean)
  - Changed property `enterprise_audit_include_expanded_diff` (boolean)

    > Include additional information in audit logs, may incur a performance penalty.

  - Changed property `flows_continuous_login` (boolean)

    > Upon successful authentication, re-start authentication in other open tabs.

  - Changed property `flows_refresh_others` (boolean)

    > Refresh other tabs after successful authentication.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flags` (object)

New required properties:

- `core_default_app_access`

New optional properties:

- `policies_buffered_access_view`
- Added property `core_default_app_access` (boolean)

  > Configure if applications without any policy/group/user bindings should be accessible to any user.

- Deleted property `policies_buffered_access_view` (boolean)
- Changed property `enterprise_audit_include_expanded_diff` (boolean)

  > Include additional information in audit logs, may incur a performance penalty.

- Changed property `flows_continuous_login` (boolean)

  > Upon successful authentication, re-start authentication in other open tabs.

- Changed property `flows_refresh_others` (boolean)

  > Refresh other tabs after successful authentication.

`GET` /core/authenticated_sessions/{uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `user_agent` (object)

    > Get parsed user agent

    - Changed property `device` (object)

> User agent device

- Changed property `brand` (string)
- Changed property `model` (string)

- Changed property `os` (object)

> User agent os

- Changed property `major` (string)
- Changed property `minor` (string)
- Changed property `patch` (string)
- Changed property `patch_minor` (string)

`GET` /core/brands/{brand_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `flow_lockdown` (string)

`PUT` /core/brands/{brand_uuid}/

Request:

Changed content type : `application/json`

- Added property `flow_lockdown` (string)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `flow_lockdown` (string)

`PATCH` /core/brands/{brand_uuid}/

Request:

Changed content type : `application/json`

- Added property `flow_lockdown` (string)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `flow_lockdown` (string)

`POST` /events/events/export/

Parameters:

Added: `context_device` in `query`

> Context Device Primary Key

`GET` /lifecycle/iterations/latest/{content_type}/{object_id}/

Operation ID:

Changed: `lifecycle_iterations_latest_retrieve` to `lifecycle_iterations_list_latest`

Parameters:

Added: `ordering` in `query`

> Which field to use when ordering the results.

Added: `search` in `query`

> A search term.

Added: `user_is_reviewer` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

`GET` /policies/event_matcher/{policy_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `query` (string)
  - Changed property `app` (string)

    > Match events created by selected application. When left empty, all applications are matched.

    Added enum values:

    - `authentik.enterprise.endpoints.connectors.google_chrome`
    - `authentik.enterprise.stages.account_lockdown` Removed enum value:
    - `authentik.enterprise.search`
  - Changed property `model` (string)

    > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

    Added enum values:

    - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
    - `authentik_stages_account_lockdown.accountlockdownstage`

`PUT` /policies/event_matcher/{policy_uuid}/

Request:

Changed content type : `application/json`

- Added property `query` (string)
- Changed property `app` (string)

  > Match events created by selected application. When left empty, all applications are matched.

  Added enum values:

  - `authentik.enterprise.endpoints.connectors.google_chrome`
  - `authentik.enterprise.stages.account_lockdown` Removed enum value:
  - `authentik.enterprise.search`
- Changed property `model` (string)

  > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

  Added enum values:

  - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
  - `authentik_stages_account_lockdown.accountlockdownstage`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `query` (string)
  - Changed property `app` (string)

    > Match events created by selected application. When left empty, all applications are matched.

    Added enum values:

    - `authentik.enterprise.endpoints.connectors.google_chrome`

        - `authentik.enterprise.stages.account_lockdown` Removed enum value:
        - `authentik.enterprise.search`
    - Changed property `model` (string)

      > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

      Added enum values:

      - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
      - `authentik_stages_account_lockdown.accountlockdownstage`

`PATCH` /policies/event_matcher/{policy_uuid}/

Request:

Changed content type : `application/json`

- Added property `query` (string)
- Changed property `app` (string)

  > Match events created by selected application. When left empty, all applications are matched.

  Added enum values:

  - `authentik.enterprise.endpoints.connectors.google_chrome`
  - `authentik.enterprise.stages.account_lockdown` Removed enum value:
  - `authentik.enterprise.search`
- Changed property `model` (string)

  > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

Added enum values:

- `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
- `authentik_stages_account_lockdown.accountlockdownstage`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `query` (string)
  - Changed property `app` (string)

    > Match events created by selected application. When left empty, all applications are matched.

    Added enum values:

    - `authentik.enterprise.endpoints.connectors.google_chrome`
    - `authentik.enterprise.stages.account_lockdown` Removed enum value:
    - `authentik.enterprise.search`
  - Changed property `model` (string)

    > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

    Added enum values:

    - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
    - `authentik_stages_account_lockdown.accountlockdownstage`

`GET` /providers/saml/{id}/metadata/

Parameters:

Changed: `force_binding` in `query`

`GET` /providers/wsfed/{id}/metadata/

Parameters:

Changed: `force_binding` in `query`

`GET` /core/applications/{slug}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `meta_hide` (boolean)
    > Hide this application from the user's My applications page.

`PUT` /core/applications/{slug}/

Request:

Changed content type : `application/json`

- Added property `meta_hide` (boolean)
  > Hide this application from the user's My applications page.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `meta_hide` (boolean)
    > Hide this application from the user's My applications page.

`PATCH` /core/applications/{slug}/

Request:

Changed content type : `application/json`

- Added property `meta_hide` (boolean)

> Hide this application from the user's My applications page.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `meta_hide` (boolean)

    > Hide this application from the user's My applications page.

`GET` /core/authenticated_sessions/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > AuthenticatedSession Serializer

    - Changed property `user_agent` (object)

      > Get parsed user agent

      - Changed property `device` (object)

        > User agent device

        - Changed property `brand` (string)
        - Changed property `model` (string)

      - Changed property `os` (object)

        > User agent os

        - Changed property `major` (string)
        - Changed property `minor` (string)

- Changed property `patch` (string)
- Changed property `patch_minor` (string)

`POST` /core/brands/

Request:

Changed content type : `application/json`

- Added property `flow_lockdown` (string)

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `flow_lockdown` (string)

`GET` /core/brands/

Parameters:

Added: `flow_lockdown` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Brand Serializer

    - Added property `flow_lockdown` (string)

`GET` /core/brands/current/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `flow_lockdown` (string)
  - Changed property `flags` (object)

    New required properties:

    - `core_default_app_access`

    New optional properties:

    - `policies_buffered_access_view`
    - Added property `core_default_app_access` (boolean)

      > Configure if applications without any policy/group/user bindings should be accessible to any user.

    - Deleted property `policies_buffered_access_view` (boolean)
    - Changed property `enterprise_audit_include_expanded_diff` (boolean)

      > Include additional information in audit logs, may incur a performance penalty.

    - Changed property `flows_continuous_login` (boolean)

      > Upon successful authentication, re-start authentication in other open tabs.

    - Changed property `flows_refresh_others` (boolean)

      > Refresh other tabs after successful authentication.

`GET` /crypto/certificatekeypairs/

Parameters:

Changed: `key_type` in `query`

`POST` /endpoints/agents/connectors/check_in/

Request:

Changed content type : `application/json`

- Changed property `os` (object)

  > For example: {"family":"linux","name":"Ubuntu","version":"24.04.3 LTS (Noble Numbat)","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "mac_os", "name": "", "version": "26.2", "arch": "arm64"}

  New optional properties:

  - `arch`

`GET` /events/events/volume/

Parameters:

Added: `context_device` in `query`

> Context Device Primary Key

Changed: `history_days` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  Changed items (object): > Count of events of action created on day for a single event action

`GET` /events/transports/{uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webhook_ca` (string)

    > When set, the selected certificate is used to validate the certificate of the webhook server.

`PUT` /events/transports/{uuid}/

Request:

Changed content type : `application/json`

- Added property `webhook_ca` (string)

  > When set, the selected certificate is used to validate the certificate of the webhook server.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webhook_ca` (string)

    > When set, the selected certificate is used to validate the certificate of the webhook server.

`PATCH` /events/transports/{uuid}/

Request:

Changed content type : `application/json`

- Added property `webhook_ca` (string)

  > When set, the selected certificate is used to validate the certificate of the webhook server.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webhook_ca` (string)

> When set, the selected certificate is used to validate the certificate of the webhook server.

`GET` /flows/instances/{slug}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `authentication` (string)

    > Required level of authentication and authorization to access a flow.

    Added enum value:

    - `require_token`

`PUT` /flows/instances/{slug}/

Request:

Changed content type : `application/json`

- Changed property `authentication` (string)

  > Required level of authentication and authorization to access a flow.

  Added enum value:

  - `require_token`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `authentication` (string)

    > Required level of authentication and authorization to access a flow.

Added enum value:

- `require_token`

`PATCH` /flows/instances/{slug}/

Request:

Changed content type : `application/json`

- Changed property `authentication` (string)

  > Required level of authentication and authorization to access a flow.

  Added enum value:

  - `require_token`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `authentication` (string)

    > Required level of authentication and authorization to access a flow.

    Added enum value:

    - `require_token`

`POST` /lifecycle/iterations/

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `rule`

New optional properties:

- `min_reviewers`
- `reviewer_groups`
- `reviewers`
- Added property `rule` (object)
  - Property `id` (string)
  - Property `name` (string)
  - Property `reviewer_groups` (array)

    Items (object):

    - Property `pk` (string)
    - Property `name` (string)
  - Property `min_reviewers` (integer)
  - Property `reviewers` (array)

    Items (object):

    - Property `pk` (integer)
    - Property `uuid` (string)
    - Property `username` (string)

      > Required. 150 characters or fewer. Letters, digits and @/./+/-/_ only.
    - Property `name` (string)

      > User's display name.
- Deleted property `reviewer_groups` (array)
- Deleted property `min_reviewers` (integer)

- Deleted property `reviewers` (array)

POST **/policies/event_matcher/**

Request:

Changed content type : `application/json`

- Added property `query` (string)
- Changed property `app` (string)

  > Match events created by selected application. When left empty, all applications are matched.

  Added enum values:

  - `authentik.enterprise.endpoints.connectors.google_chrome`
  - `authentik.enterprise.stages.account_lockdown` Removed enum value:
  - `authentik.enterprise.search`

- Changed property `model` (string)

  > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

  Added enum values:

  - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
  - `authentik_stages_account_lockdown.accountlockdownstage`

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `query` (string)
  - Changed property `app` (string)

> Match events created by selected application. When left empty, all applications are matched.

Added enum values:

- `authentik.enterprise.endpoints.connectors.google_chrome`
- `authentik.enterprise.stages.account_lockdown` Removed enum value:
- `authentik.enterprise.search`

- Changed property `model` (string)

> Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

Added enum values:

- `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
- `authentik_stages_account_lockdown.accountlockdownstage`

`GET` /policies/event_matcher/

Parameters:

Added: `query` in `query`

Changed: `action` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Event Matcher Policy Serializer

    - Added property `query` (string)

- Changed property `app` (string)

  > Match events created by selected application. When left empty, all applications are matched.

  Added enum values:

  - `authentik.enterprise.endpoints.connectors.google_chrome`
  - `authentik.enterprise.stages.account_lockdown` Removed enum value:
  - `authentik.enterprise.search`

- Changed property `model` (string)

  > Match events created by selected model. When left empty, all models are matched. When an app is selected, all the application's models are matched.

  Added enum values:

  - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
  - `authentik_stages_account_lockdown.accountlockdownstage`

`GET` /policies/geoip/{policy_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `countries_obj` (array)

    Changed items (object):

    - Changed property `code` (string)

      Removed enum values:

- `AF`
- `AX`
- `AL`
- `DZ`
- `AS`
- `AD`
- `AO`
- `AI`
- `AQ`
- `AG`
- `AR`
- `AM`
- `AW`
- `AU`
- `AT`
- `AZ`
- `BS`
- `BH`
- `BD`
- `BB`
- `BY`
- `BE`
- `BZ`
- `BJ`
- `BM`
- `BT`
- `BO`
- `BQ`
- `BA`
- `BW`
- `BV`
- `BR`

- `IO`
- `BN`
- `BG`
- `BF`
- `BI`
- `CV`
- `KH`
- `CM`
- `CA`
- `KY`
- `CF`
- `TD`
- `CL`
- `CN`
- `CX`
- `CC`
- `CO`
- `KM`
- `CG`
- `CD`
- `CK`
- `CR`
- `CI`
- `HR`
- `CU`
- `CW`
- `CY`
- `CZ`
- `DK`
- `DJ`
- `DM`
- `DO`

- `EC`
- `EG`
- `SV`
- `GQ`
- `ER`
- `EE`
- `SZ`
- `ET`
- `FK`
- `FO`
- `FJ`
- `FI`
- `FR`
- `GF`
- `PF`
- `TF`
- `GA`
- `GM`
- `GE`
- `DE`
- `GH`
- `GI`
- `GR`
- `GL`
- `GD`
- `GP`
- `GU`
- `GT`
- `GG`
- `GN`
- `GW`
- `GY`

- `HT`
- `HM`
- `VA`
- `HN`
- `HK`
- `HU`
- `IS`
- `IN`
- `ID`
- `IR`
- `IQ`
- `IE`
- `IM`
- `IL`
- `IT`
- `JM`
- `JP`
- `JE`
- `JO`
- `KZ`
- `KE`
- `KI`
- `KW`
- `KG`
- `LA`
- `LV`
- `LB`
- `LS`
- `LR`
- `LY`
- `LI`
- `LT`

- `LU`
- `MO`
- `MG`
- `MW`
- `MY`
- `MV`
- `ML`
- `MT`
- `MH`
- `MQ`
- `MR`
- `MU`
- `YT`
- `MX`
- `FM`
- `MD`
- `MC`
- `MN`
- `ME`
- `MS`
- `MA`
- `MZ`
- `MM`
- `NA`
- `NR`
- `NP`
- `NL`
- `NC`
- `NZ`
- `NI`
- `NE`
- `NG`

- `NU`
- `NF`
- `KP`
- `MK`
- `MP`
- `NO`
- `OM`
- `PK`
- `PW`
- `PS`
- `PA`
- `PG`
- `PY`
- `PE`
- `PH`
- `PN`
- `PL`
- `PT`
- `PR`
- `QA`
- `RE`
- `RO`
- `RU`
- `RW`
- `BL`
- `SH`
- `KN`
- `LC`
- `MF`
- `PM`
- `VC`
- `WS`

- `SM`
- `ST`
- `SA`
- `SN`
- `RS`
- `SC`
- `SL`
- `SG`
- `SX`
- `SK`
- `SI`
- `SB`
- `SO`
- `ZA`
- `GS`
- `KR`
- `SS`
- `ES`
- `LK`
- `SD`
- `SR`
- `SJ`
- `SE`
- `CH`
- `SY`
- `TW`
- `TJ`
- `TZ`
- `TH`
- `TL`
- `TG`
- `TK`

- `TO`
- `TT`
- `TN`
- `TR`
- `TM`
- `TC`
- `TV`
- `UG`
- `UA`
- `AE`
- `GB`
- `UM`
- `US`
- `UY`
- `UZ`
- `VU`
- `VE`
- `VN`
- `VG`
- `VI`
- `WF`
- `EH`
- `YE`
- `ZM`
- `ZW`

`PUT` **/policies/geoip/{policy_uuid}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

- Changed property `countries_obj` (array)

  Changed items (object):

  - Changed property `code` (string)

    Removed enum values:

    - `AF`
    - `AX`
    - `AL`
    - `DZ`
    - `AS`
    - `AD`
    - `AO`
    - `AI`
    - `AQ`
    - `AG`
    - `AR`
    - `AM`
    - `AW`
    - `AU`
    - `AT`
    - `AZ`
    - `BS`
    - `BH`
    - `BD`
    - `BB`
    - `BY`
    - `BE`
    - `BZ`
    - `BJ`
    - `BM`
    - `BT`

- `BO`
- `BQ`
- `BA`
- `BW`
- `BV`
- `BR`
- `IO`
- `BN`
- `BG`
- `BF`
- `BI`
- `CV`
- `KH`
- `CM`
- `CA`
- `KY`
- `CF`
- `TD`
- `CL`
- `CN`
- `CX`
- `CC`
- `CO`
- `KM`
- `CG`
- `CD`
- `CK`
- `CR`
- `CI`
- `HR`
- `CU`
- `CW`

- `CY`
- `CZ`
- `DK`
- `DJ`
- `DM`
- `DO`
- `EC`
- `EG`
- `SV`
- `GQ`
- `ER`
- `EE`
- `SZ`
- `ET`
- `FK`
- `FO`
- `FJ`
- `FI`
- `FR`
- `GF`
- `PF`
- `TF`
- `GA`
- `GM`
- `GE`
- `DE`
- `GH`
- `GI`
- `GR`
- `GL`
- `GD`
- `GP`

- `GU`
- `GT`
- `GG`
- `GN`
- `GW`
- `GY`
- `HT`
- `HM`
- `VA`
- `HN`
- `HK`
- `HU`
- `IS`
- `IN`
- `ID`
- `IR`
- `IQ`
- `IE`
- `IM`
- `IL`
- `IT`
- `JM`
- `JP`
- `JE`
- `JO`
- `KZ`
- `KE`
- `KI`
- `KW`
- `KG`
- `LA`
- `LV`

- `LB`
- `LS`
- `LR`
- `LY`
- `LI`
- `LT`
- `LU`
- `MO`
- `MG`
- `MW`
- `MY`
- `MV`
- `ML`
- `MT`
- `MH`
- `MQ`
- `MR`
- `MU`
- `YT`
- `MX`
- `FM`
- `MD`
- `MC`
- `MN`
- `ME`
- `MS`
- `MA`
- `MZ`
- `MM`
- `NA`
- `NR`
- `NP`

- `NL`
- `NC`
- `NZ`
- `NI`
- `NE`
- `NG`
- `NU`
- `NF`
- `KP`
- `MK`
- `MP`
- `NO`
- `OM`
- `PK`
- `PW`
- `PS`
- `PA`
- `PG`
- `PY`
- `PE`
- `PH`
- `PN`
- `PL`
- `PT`
- `PR`
- `QA`
- `RE`
- `RO`
- `RU`
- `RW`
- `BL`
- `SH`

- KN
- LC
- MF
- PM
- VC
- WS
- SM
- ST
- SA
- SN
- RS
- SC
- SL
- SG
- SX
- SK
- SI
- SB
- SO
- ZA
- GS
- KR
- SS
- ES
- LK
- SD
- SR
- SJ
- SE
- CH
- SY
- TW

- `TJ`
- `TZ`
- `TH`
- `TL`
- `TG`
- `TK`
- `TO`
- `TT`
- `TN`
- `TR`
- `TM`
- `TC`
- `TV`
- `UG`
- `UA`
- `AE`
- `GB`
- `UM`
- `US`
- `UY`
- `UZ`
- `VU`
- `VE`
- `VN`
- `VG`
- `VI`
- `WF`
- `EH`
- `YE`
- `ZM`
- `ZW`

`PATCH` **/policies/geoip/{policy_uuid}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `countries_obj` (array)

    Changed items (object):

    - Changed property `code` (string)

      Removed enum values:

      - `AF`
      - `AX`
      - `AL`
      - `DZ`
      - `AS`
      - `AD`
      - `AO`
      - `AI`
      - `AQ`
      - `AG`
      - `AR`
      - `AM`
      - `AW`
      - `AU`
      - `AT`
      - `AZ`
      - `BS`
      - `BH`
      - `BD`
      - `BB`

- `BY`
- `BE`
- `BZ`
- `BJ`
- `BM`
- `BT`
- `BO`
- `BQ`
- `BA`
- `BW`
- `BV`
- `BR`
- `IO`
- `BN`
- `BG`
- `BF`
- `BI`
- `CV`
- `KH`
- `CM`
- `CA`
- `KY`
- `CF`
- `TD`
- `CL`
- `CN`
- `CX`
- `CC`
- `CO`
- `KM`
- `CG`
- `CD`

- `CK`
- `CR`
- `CI`
- `HR`
- `CU`
- `CW`
- `CY`
- `CZ`
- `DK`
- `DJ`
- `DM`
- `DO`
- `EC`
- `EG`
- `SV`
- `GQ`
- `ER`
- `EE`
- `SZ`
- `ET`
- `FK`
- `FO`
- `FJ`
- `FI`
- `FR`
- `GF`
- `PF`
- `TF`
- `GA`
- `GM`
- `GE`
- `DE`

- `GH`
- `GI`
- `GR`
- `GL`
- `GD`
- `GP`
- `GU`
- `GT`
- `GG`
- `GN`
- `GW`
- `GY`
- `HT`
- `HM`
- `VA`
- `HN`
- `HK`
- `HU`
- `IS`
- `IN`
- `ID`
- `IR`
- `IQ`
- `IE`
- `IM`
- `IL`
- `IT`
- `JM`
- `JP`
- `JE`
- `JO`
- `KZ`

- `KE`
- `KI`
- `KW`
- `KG`
- `LA`
- `LV`
- `LB`
- `LS`
- `LR`
- `LY`
- `LI`
- `LT`
- `LU`
- `MO`
- `MG`
- `MW`
- `MY`
- `MV`
- `ML`
- `MT`
- `MH`
- `MQ`
- `MR`
- `MU`
- `YT`
- `MX`
- `FM`
- `MD`
- `MC`
- `MN`
- `ME`
- `MS`

- `MA`
- `MZ`
- `MM`
- `NA`
- `NR`
- `NP`
- `NL`
- `NC`
- `NZ`
- `NI`
- `NE`
- `NG`
- `NU`
- `NF`
- `KP`
- `MK`
- `MP`
- `NO`
- `OM`
- `PK`
- `PW`
- `PS`
- `PA`
- `PG`
- `PY`
- `PE`
- `PH`
- `PN`
- `PL`
- `PT`
- `PR`
- `QA`

- `RE`
- `RO`
- `RU`
- `RW`
- `BL`
- `SH`
- `KN`
- `LC`
- `MF`
- `PM`
- `VC`
- `WS`
- `SM`
- `ST`
- `SA`
- `SN`
- `RS`
- `SC`
- `SL`
- `SG`
- `SX`
- `SK`
- `SI`
- `SB`
- `SO`
- `ZA`
- `GS`
- `KR`
- `SS`
- `ES`
- `LK`
- `SD`

- `SR`
- `SJ`
- `SE`
- `CH`
- `SY`
- `TW`
- `TJ`
- `TZ`
- `TH`
- `TL`
- `TG`
- `TK`
- `TO`
- `TT`
- `TN`
- `TR`
- `TM`
- `TC`
- `TV`
- `UG`
- `UA`
- `AE`
- `GB`
- `UM`
- `US`
- `UY`
- `UZ`
- `VU`
- `VE`
- `VN`
- `VG`
- `VI`

- `WF`
- `EH`
- `YE`
- `ZM`
- `ZW`

`GET` /providers/saml/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `url_issuer`
  - `url_unified`
  - `url_unified_init`
  - Added property `issuer_override` (string)

    > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

  - Added property `sign_logout_response` (boolean)
  - Added property `url_issuer` (string)

    > Get Issuer/EntityID URL

  - Added property `url_unified` (string)

    > Get unified SAML endpoint URL (handles SSO and SLO)

  - Added property `url_unified_init` (string)

    > Get IdP-initiated SAML URL

  - Deleted property `issuer` (string)

> Also known as EntityID

PUT /providers/saml/{id}/

Request:

Changed content type : `application/json`

- Added property `issuer_override` (string)

  > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Deleted property `issuer` (string)

  > Also known as EntityID

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `url_issuer`
  - `url_unified`
  - `url_unified_init`

  - Added property `issuer_override` (string)

    > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

  - Added property `sign_logout_response` (boolean)
  - Added property `url_issuer` (string)

    > Get Issuer/EntityID URL

- Added property `url_unified` (string)

  > Get unified SAML endpoint URL (handles SSO and SLO)

- Added property `url_unified_init` (string)

  > Get IdP-initiated SAML URL

- Deleted property `issuer` (string)

  > Also known as EntityID

`PATCH` /providers/saml/{id}/

Request:

Changed content type : `application/json`

- Added property `issuer_override` (string)

  > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Deleted property `issuer` (string)

  > Also known as EntityID

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `url_issuer`
  - `url_unified`
  - `url_unified_init`

  - Added property `issuer_override` (string)

> Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Added property `url_issuer` (string)

> Get Issuer/EntityID URL

- Added property `url_unified` (string)

> Get unified SAML endpoint URL (handles SSO and SLO)

- Added property `url_unified_init` (string)

> Get IdP-initiated SAML URL

- Deleted property `issuer` (string)

> Also known as EntityID

POST **/providers/saml/import_metadata/**

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `url_issuer`
  - `url_unified`
  - `url_unified_init`

- Added property `issuer_override` (string)

> Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)

- Added property `url_issuer` (string)

  > Get Issuer/EntityID URL

- Added property `url_unified` (string)

  > Get unified SAML endpoint URL (handles SSO and SLO)

- Added property `url_unified_init` (string)

  > Get IdP-initiated SAML URL

- Deleted property `issuer` (string)

  > Also known as EntityID

`GET` /providers/scim/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `auth_oauth_token_expires`
  - `auth_oauth_token_last_updated`
  - `auth_oauth_url_callback`
  - `auth_oauth_url_start`

  - Added property `auth_oauth_token_last_updated` (string)
  - Added property `auth_oauth_token_expires` (string)
  - Added property `auth_oauth_url_callback` (string)
  - Added property `auth_oauth_url_start` (string)
  - Changed property `compatibility_mode` (string)

    > Alter authentik behavior for vendor-specific SCIM implementations.

Added enum values:

- `webex`
- `vcenter`

- Changed property `auth_mode` (string)

  Added enum value:

  - `oauth_interactive`

`PUT` /providers/scim/{id}/

Request:

Changed content type : `application/json`

- Changed property `compatibility_mode` (string)

  > Alter authentik behavior for vendor-specific SCIM implementations.

  Added enum values:

  - `webex`
  - `vcenter`

- Changed property `auth_mode` (string)

  Added enum value:

  - `oauth_interactive`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `auth_oauth_token_expires`
  - `auth_oauth_token_last_updated`

    - `auth_oauth_url_callback`
    - `auth_oauth_url_start`
    - Added property `auth_oauth_token_last_updated` (string)
    - Added property `auth_oauth_token_expires` (string)
    - Added property `auth_oauth_url_callback` (string)
    - Added property `auth_oauth_url_start` (string)
    - Changed property `compatibility_mode` (string)

      > Alter authentik behavior for vendor-specific SCIM implementations.

      Added enum values:

      - `webex`
      - `vcenter`
    - Changed property `auth_mode` (string)

      Added enum value:

      - `oauth_interactive`

`PATCH` /providers/scim/{id}/

Request:

Changed content type : `application/json`

- Changed property `compatibility_mode` (string)

  > Alter authentik behavior for vendor-specific SCIM implementations.

  Added enum values:

  - `webex`
  - `vcenter`
- Changed property `auth_mode` (string)

Added enum value:

- `oauth_interactive`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `auth_oauth_token_expires`
  - `auth_oauth_token_last_updated`
  - `auth_oauth_url_callback`
  - `auth_oauth_url_start`
  - Added property `auth_oauth_token_last_updated` (string)
  - Added property `auth_oauth_token_expires` (string)
  - Added property `auth_oauth_url_callback` (string)
  - Added property `auth_oauth_url_start` (string)
  - Changed property `compatibility_mode` (string)

    > Alter authentik behavior for vendor-specific SCIM implementations.

    Added enum values:

    - `webex`
    - `vcenter`
  - Changed property `auth_mode` (string)

    Added enum value:

    - `oauth_interactive`

`GET` /providers/ssf/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `oidc_auth_providers_obj`
  - Added property `oidc_auth_providers_obj` (array)

    Items (object): > Provider Serializer

    - Property `pk` (integer)
    - Property `name` (string)
    - Property `authentication_flow` (string)

      > Flow used for authentication when the associated application is accessed by an un-authenticated user.

    - Property `authorization_flow` (string)

      > Flow used when authorizing this provider.

    - Property `invalidation_flow` (string)

      > Flow used ending the session from a provider.

    - Property `property_mappings` (array)

      Items (string):

    - Property `component` (string)

      > Get object component so that we know how to edit the object

    - Property `assigned_application_slug` (string)

      > Internal application name, used in URLs.

        - Property `assigned_application_name` (string)

          > Application's display Name.

        - Property `assigned_backchannel_application_slug` (string)

          > Internal application name, used in URLs.

        - Property `assigned_backchannel_application_name` (string)

          > Application's display Name.

        - Property `verbose_name` (string)

          > Return object's verbose_name

        - Property `verbose_name_plural` (string)

          > Return object's plural verbose_name

        - Property `meta_model_name` (string)

          > Return internal model name

    - Added property `push_verify_certificates` (boolean)

`PUT` /providers/ssf/{id}/

Request:

Changed content type : `application/json`

- Added property `push_verify_certificates` (boolean)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `oidc_auth_providers_obj`

- Added property `oidc_auth_providers_obj` (array)
- Added property `push_verify_certificates` (boolean)

`PATCH` /providers/ssf/{id}/

Request:

Changed content type : `application/json`

- Added property `push_verify_certificates` (boolean)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `oidc_auth_providers_obj`
  - Added property `oidc_auth_providers_obj` (array)
  - Added property `push_verify_certificates` (boolean)

`POST` /rbac/permissions/assigned_by_roles/{uuid}/assign/

Request:

Changed content type : `application/json`

- Changed property `model` (string)

  Added enum values:

  - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
  - `authentik_stages_account_lockdown.accountlockdownstage`

`PATCH` /rbac/permissions/assigned_by_roles/{uuid}/unassign/

Request:

Changed content type : `application/json`

- Changed property `model` (string)

  Added enum values:

  - `authentik_endpoints_connectors_google_chrome.googlechromeconnector`
  - `authentik_stages_account_lockdown.accountlockdownstage`

`GET` /rbac/permissions/roles/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `autocomplete`
  - Added property `autocomplete` (object)

`GET` /sources/group_connections/ldap/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `group_obj`
  - Added property `group_obj` (object)
    - Property `pk` (string)
    - Property `num_pk` (integer)

      > Get a numerical, int32 ID for the group

    - Property `name` (string)

- Property `is_superuser` (boolean)

  > Users added to this group will be superusers.

- Property `attributes` (object)

`PUT` /sources/group_connections/ldap/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `group_obj`
  - Added property `group_obj` (object)

`PATCH` /sources/group_connections/ldap/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `group_obj`
  - Added property `group_obj` (object)

`GET` /sources/saml/{slug}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `force_authn` (boolean)

    > When enabled, the IdP will re-authenticate the user even if a session exists.

`PUT` **/sources/saml/{slug}/**

Request:

Changed content type : `application/json`

- Added property `force_authn` (boolean)
  > When enabled, the IdP will re-authenticate the user even if a session exists.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `force_authn` (boolean)
    > When enabled, the IdP will re-authenticate the user even if a session exists.

`PATCH` **/sources/saml/{slug}/**

Request:

Changed content type : `application/json`

- Added property `force_authn` (boolean)
  > When enabled, the IdP will re-authenticate the user even if a session exists.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `force_authn` (boolean)
    > When enabled, the IdP will re-authenticate the user even if a session exists.

`GET` **/sources/user_connections/ldap/{id}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

New required properties:

- `user_obj`
- Added property `user_obj` (object)
  - Property `pk` (integer)
  - Property `username` (string)

    > Required. 150 characters or fewer. Letters, digits and @/./+/-/_ only.

  - Property `name` (string)

    > User's display name.

  - Property `is_active` (boolean)

    > Designates whether this user should be treated as active. Unselect this instead of deleting accounts.

  - Property `last_login` (string)
  - Property `email` (string)
  - Property `attributes` (object)
  - Property `uid` (string)

`PUT` /sources/user_connections/ldap/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `user_obj`
  - Added property `user_obj` (object)

`PATCH` /sources/user_connections/ldap/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  New required properties:

  - `user_obj`
  - Added property `user_obj` (object)

`GET` /ssf/streams/{uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `status` (string)

    Enum values:

    - `enabled`
    - `paused`
    - `disabled`
    - `disabled_deleted`
  - Changed property `provider_obj` (object)

    > SSFProvider Serializer

    New required properties:

    - `oidc_auth_providers_obj`
    - Added property `oidc_auth_providers_obj` (array)
    - Added property `push_verify_certificates` (boolean)
  - Changed property `delivery_method` (string)

Added enum values:

- `urn:ietf:rfc:8935`
- `urn:ietf:rfc:8936`

- Changed property `events_requested` (array)

  Changed items (string):

  Added enum values:

  - `https://schemas.openid.net/secevent/caep/event-type/token-claims-change`
  - `https://schemas.openid.net/secevent/caep/event-type/assurance-level-change`
  - `https://schemas.openid.net/secevent/caep/event-type/device-compliance-change`
  - `https://schemas.openid.net/secevent/caep/event-type/session-established`
  - `https://schemas.openid.net/secevent/caep/event-type/session-presented`
  - `https://schemas.openid.net/secevent/caep/event-type/risk-level-change`

`GET` /stages/invitation/invitations/{invite_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flow_obj` (object)

    > Flow Serializer

    - Changed property `authentication` (string)

      > Required level of authentication and authorization to access a flow.

Added enum value:

- `require_token`

`PUT` /stages/invitation/invitations/{invite_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flow_obj` (object)

    > Flow Serializer

    - Changed property `authentication` (string)

      > Required level of authentication and authorization to access a flow.

      Added enum value:

      - `require_token`

`PATCH` /stages/invitation/invitations/{invite_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `flow_obj` (object)

    > Flow Serializer

    - Changed property `authentication` (string)

      > Required level of authentication and authorization to access a flow.

      Added enum value:

      - `require_token`

`POST` **/core/applications/**

Request:

Changed content type : `application/json`

- Added property `meta_hide` (boolean)
  > Hide this application from the user's My applications page.

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `meta_hide` (boolean)
    > Hide this application from the user's My applications page.

`GET` **/core/applications/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Application Serializer

    - Added property `meta_hide` (boolean)
      > Hide this application from the user's My applications page.

`GET` **/core/user_consent/{id}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `application` (object)

    > Application Serializer

- Added property `meta_hide` (boolean)

  > Hide this application from the user's My applications page.

`GET` /endpoints/devices/{device_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `connections_obj` (array)

    Changed items (object):

    - Changed property `latest_snapshot` (object)
      - Changed property `vendor` (string)

        Added enum value:

        - `chrome.google.com`
  - Changed property `facts` (object)
    - Changed property `vendor` (string)

      Added enum value:

      - `chrome.google.com`
    - Changed property `data` (object)
      - Changed property `os` (object)

        > For example: {"family":"linux","name":"Ubuntu","version":"24.04.3 LTS (Noble Numbat)","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "mac_os", "name": "", "version": "26.2", "arch": "arm64"}

New optional properties:

- `arch`

`PUT` /endpoints/devices/{device_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `facts` (object)
    - Changed property `vendor` (string)

      Added enum value:

      - `chrome.google.com`
    - Changed property `data` (object)
      - Changed property `os` (object)

        > For example: {"family":"linux","name":"Ubuntu","version":"24.04.3 LTS (Noble Numbat)","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "mac_os", "name": "", "version": "26.2", "arch": "arm64"}

        New optional properties:

        - `arch`

`PATCH` /endpoints/devices/{device_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

- Changed property `facts` (object)
  - Changed property `vendor` (string)

    Added enum value:

    - `chrome.google.com`
  - Changed property `data` (object)
    - Changed property `os` (object)

      > For example: {"family":"linux","name":"Ubuntu","version":"24.04.3 LTS (Noble Numbat)","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "mac_os", "name": "", "version": "26.2", "arch": "arm64"}

      New optional properties:

      - `arch`

`GET` /events/events/

Parameters:

Added: `context_device` in `query`

> Context Device Primary Key

`GET` /events/rules/

Parameters:

Changed: `severity` in `query`

`POST` /events/transports/

Request:

Changed content type : `application/json`

- Added property `webhook_ca` (string)

  > When set, the selected certificate is used to validate the certificate of the webhook server.

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `webhook_ca` (string)

    > When set, the selected certificate is used to validate the certificate of the webhook server.

`GET` /events/transports/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > NotificationTransport Serializer

    - Added property `webhook_ca` (string)

      > When set, the selected certificate is used to validate the certificate of the webhook server.

`POST` /flows/instances/

Request:

Changed content type : `application/json`

- Changed property `authentication` (string)

  > Required level of authentication and authorization to access a flow.

  Added enum value:

    - `require_token`

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
    - Changed property `authentication` (string)

      > Required level of authentication and authorization to access a flow.

      Added enum value:

      - `require_token`

`GET` /flows/instances/

Parameters:

Changed: `denied_action` in `query`

Changed: `designation` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
    - Changed property `results` (array)

      Changed items (object): > Flow Serializer

      - Changed property `authentication` (string)

        > Required level of authentication and authorization to access a flow.

        Added enum value:

        - `require_token`

`GET` /lifecycle/iterations/open/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Mixin to validate that a valid enterprise license > exists before allowing to save the object

    New required properties:

    - `rule`

    New optional properties:

    - `min_reviewers`
    - `reviewer_groups`
    - `reviewers`
    - Added property `rule` (object)
    - Deleted property `reviewer_groups` (array)
    - Deleted property `min_reviewers` (integer)
    - Deleted property `reviewers` (array)

POST **/policies/geoip/**

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Changed property `countries_obj` (array)

    Changed items (object):

    - Changed property `code` (string)

Removed enum values:

- `AF`
- `AX`
- `AL`
- `DZ`
- `AS`
- `AD`
- `AO`
- `AI`
- `AQ`
- `AG`
- `AR`
- `AM`
- `AW`
- `AU`
- `AT`
- `AZ`
- `BS`
- `BH`
- `BD`
- `BB`
- `BY`
- `BE`
- `BZ`
- `BJ`
- `BM`
- `BT`
- `BO`
- `BQ`
- `BA`
- `BW`

- `BV`
- `BR`
- `IO`
- `BN`
- `BG`
- `BF`
- `BI`
- `CV`
- `KH`
- `CM`
- `CA`
- `KY`
- `CF`
- `TD`
- `CL`
- `CN`
- `CX`
- `CC`
- `CO`
- `KM`
- `CG`
- `CD`
- `CK`
- `CR`
- `CI`
- `HR`
- `CU`
- `CW`
- `CY`
- `CZ`
- `DK`
- `DJ`

- `DM`
- `DO`
- `EC`
- `EG`
- `SV`
- `GQ`
- `ER`
- `EE`
- `SZ`
- `ET`
- `FK`
- `FO`
- `FJ`
- `FI`
- `FR`
- `GF`
- `PF`
- `TF`
- `GA`
- `GM`
- `GE`
- `DE`
- `GH`
- `GI`
- `GR`
- `GL`
- `GD`
- `GP`
- `GU`
- `GT`
- `GG`
- `GN`

- `GW`
- `GY`
- `HT`
- `HM`
- `VA`
- `HN`
- `HK`
- `HU`
- `IS`
- `IN`
- `ID`
- `IR`
- `IQ`
- `IE`
- `IM`
- `IL`
- `IT`
- `JM`
- `JP`
- `JE`
- `JO`
- `KZ`
- `KE`
- `KI`
- `KW`
- `KG`
- `LA`
- `LV`
- `LB`
- `LS`
- `LR`
- `LY`

- `LI`
- `LT`
- `LU`
- `MO`
- `MG`
- `MW`
- `MY`
- `MV`
- `ML`
- `MT`
- `MH`
- `MQ`
- `MR`
- `MU`
- `YT`
- `MX`
- `FM`
- `MD`
- `MC`
- `MN`
- `ME`
- `MS`
- `MA`
- `MZ`
- `MM`
- `NA`
- `NR`
- `NP`
- `NL`
- `NC`
- `NZ`
- `NI`

- `NE`
- `NG`
- `NU`
- `NF`
- `KP`
- `MK`
- `MP`
- `NO`
- `OM`
- `PK`
- `PW`
- `PS`
- `PA`
- `PG`
- `PY`
- `PE`
- `PH`
- `PN`
- `PL`
- `PT`
- `PR`
- `QA`
- `RE`
- `RO`
- `RU`
- `RW`
- `BL`
- `SH`
- `KN`
- `LC`
- `MF`
- `PM`

- `VC`
- `WS`
- `SM`
- `ST`
- `SA`
- `SN`
- `RS`
- `SC`
- `SL`
- `SG`
- `SX`
- `SK`
- `SI`
- `SB`
- `SO`
- `ZA`
- `GS`
- `KR`
- `SS`
- `ES`
- `LK`
- `SD`
- `SR`
- `SJ`
- `SE`
- `CH`
- `SY`
- `TW`
- `TJ`
- `TZ`
- `TH`
- `TL`

- `TG`
- `TK`
- `TO`
- `TT`
- `TN`
- `TR`
- `TM`
- `TC`
- `TV`
- `UG`
- `UA`
- `AE`
- `GB`
- `UM`
- `US`
- `UY`
- `UZ`
- `VU`
- `VE`
- `VN`
- `VG`
- `VI`
- `WF`
- `EH`
- `YE`
- `ZM`
- `ZW`

`GET` **/policies/geoip/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > GeoIP Policy Serializer

    - Changed property `countries_obj` (array)

      Changed items (object):

      - Changed property `code` (string)

        Removed enum values:

        - `AF`
        - `AX`
        - `AL`
        - `DZ`
        - `AS`
        - `AD`
        - `AO`
        - `AI`
        - `AQ`
        - `AG`
        - `AR`
        - `AM`
        - `AW`
        - `AU`
        - `AT`
        - `AZ`
        - `BS`
        - `BH`
        - `BD`
        - `BB`
        - `BY`

- `BE`
- `BZ`
- `BJ`
- `BM`
- `BT`
- `BO`
- `BQ`
- `BA`
- `BW`
- `BV`
- `BR`
- `IO`
- `BN`
- `BG`
- `BF`
- `BI`
- `CV`
- `KH`
- `CM`
- `CA`
- `KY`
- `CF`
- `TD`
- `CL`
- `CN`
- `CX`
- `CC`
- `CO`
- `KM`
- `CG`
- `CD`
- `CK`

- `CR`
- `CI`
- `HR`
- `CU`
- `CW`
- `CY`
- `CZ`
- `DK`
- `DJ`
- `DM`
- `DO`
- `EC`
- `EG`
- `SV`
- `GQ`
- `ER`
- `EE`
- `SZ`
- `ET`
- `FK`
- `FO`
- `FJ`
- `FI`
- `FR`
- `GF`
- `PF`
- `TF`
- `GA`
- `GM`
- `GE`
- `DE`
- `GH`

- `GI`
- `GR`
- `GL`
- `GD`
- `GP`
- `GU`
- `GT`
- `GG`
- `GN`
- `GW`
- `GY`
- `HT`
- `HM`
- `VA`
- `HN`
- `HK`
- `HU`
- `IS`
- `IN`
- `ID`
- `IR`
- `IQ`
- `IE`
- `IM`
- `IL`
- `IT`
- `JM`
- `JP`
- `JE`
- `JO`
- `KZ`
- `KE`

- `KI`
- `KW`
- `KG`
- `LA`
- `LV`
- `LB`
- `LS`
- `LR`
- `LY`
- `LI`
- `LT`
- `LU`
- `MO`
- `MG`
- `MW`
- `MY`
- `MV`
- `ML`
- `MT`
- `MH`
- `MQ`
- `MR`
- `MU`
- `YT`
- `MX`
- `FM`
- `MD`
- `MC`
- `MN`
- `ME`
- `MS`
- `MA`

- `MZ`
- `MM`
- `NA`
- `NR`
- `NP`
- `NL`
- `NC`
- `NZ`
- `NI`
- `NE`
- `NG`
- `NU`
- `NF`
- `KP`
- `MK`
- `MP`
- `NO`
- `OM`
- `PK`
- `PW`
- `PS`
- `PA`
- `PG`
- `PY`
- `PE`
- `PH`
- `PN`
- `PL`
- `PT`
- `PR`
- `QA`
- `RE`

- `RO`
- `RU`
- `RW`
- `BL`
- `SH`
- `KN`
- `LC`
- `MF`
- `PM`
- `VC`
- `WS`
- `SM`
- `ST`
- `SA`
- `SN`
- `RS`
- `SC`
- `SL`
- `SG`
- `SX`
- `SK`
- `SI`
- `SB`
- `SO`
- `ZA`
- `GS`
- `KR`
- `SS`
- `ES`
- `LK`
- `SD`
- `SR`

- `SJ`
- `SE`
- `CH`
- `SY`
- `TW`
- `TJ`
- `TZ`
- `TH`
- `TL`
- `TG`
- `TK`
- `TO`
- `TT`
- `TN`
- `TR`
- `TM`
- `TC`
- `TV`
- `UG`
- `UA`
- `AE`
- `GB`
- `UM`
- `US`
- `UY`
- `UZ`
- `VU`
- `VE`
- `VN`
- `VG`
- `VI`
- `WF`

- `EH`
- `YE`
- `ZM`
- `ZW`

`GET` **/providers/oauth2/{id}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `grant_types` (array)

    Items (string):

    Enum values:

    - `authorization_code`
    - `implicit`
    - `hybrid`
    - `refresh_token`
    - `client_credentials`
    - `password`
    - `urn:ietf:params:oauth:grant-type:device_code`
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry

    - Added property `redirect_uri_type` (object)

      Enum values:

      - `authorization`
      - `logout`

`PUT` **/providers/oauth2/{id}/**

Request:

Changed content type : `application/json`

- Added property `grant_types` (array)
- Changed property `redirect_uris` (array)

  Changed items (object): > A single allowed redirect URI entry

  - Added property `redirect_uri_type` (object)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `grant_types` (array)
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry

    - Added property `redirect_uri_type` (object)

`PATCH` /providers/oauth2/{id}/

Request:

Changed content type : `application/json`

- Added property `grant_types` (array)
- Changed property `redirect_uris` (array)

  Changed items (object): > A single allowed redirect URI entry

  - Added property `redirect_uri_type` (object)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `grant_types` (array)
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry
    - Added property `redirect_uri_type` (object)

`GET` /providers/proxy/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry
    - Added property `redirect_uri_type` (object)

`PUT` /providers/proxy/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry
    - Added property `redirect_uri_type` (object)

`PATCH` /providers/proxy/{id}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry

    - Added property `redirect_uri_type` (object)

`POST` /providers/saml/

Request:

Changed content type : `application/json`

- Added property `issuer_override` (string)

  > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Deleted property `issuer` (string)

  > Also known as EntityID

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `url_issuer`
  - `url_unified`
  - `url_unified_init`
  - Added property `issuer_override` (string)

    > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Added property `url_issuer` (string)

  > Get Issuer/EntityID URL

- Added property `url_unified` (string)

  > Get unified SAML endpoint URL (handles SSO and SLO)

- Added property `url_unified_init` (string)

  > Get IdP-initiated SAML URL

- Deleted property `issuer` (string)

  > Also known as EntityID

`GET` /providers/saml/

Parameters:

Added: `issuer_override` in `query`

Added: `sign_logout_response` in `query`

Deleted: `issuer` in `query`

Changed: `logout_method` in `query`

Changed: `sls_binding` in `query`

Changed: `sp_binding` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > SAMLProvider Serializer

New required properties:

- `url_issuer`
- `url_unified`
- `url_unified_init`

- Added property `issuer_override` (string)

  > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

- Added property `sign_logout_response` (boolean)
- Added property `url_issuer` (string)

  > Get Issuer/EntityID URL

- Added property `url_unified` (string)

  > Get unified SAML endpoint URL (handles SSO and SLO)

- Added property `url_unified_init` (string)

  > Get IdP-initiated SAML URL

- Deleted property `issuer` (string)

  > Also known as EntityID

`POST` /providers/scim/

Request:

Changed content type : `application/json`

- Changed property `compatibility_mode` (string)

  > Alter authentik behavior for vendor-specific SCIM implementations.

  Added enum values:

  - `webex`

    - `vcenter`

- Changed property `auth_mode` (string)

  Added enum value:

    - `oauth_interactive`

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

    - `auth_oauth_token_expires`
    - `auth_oauth_token_last_updated`
    - `auth_oauth_url_callback`
    - `auth_oauth_url_start`
    - Added property `auth_oauth_token_last_updated` (string)
    - Added property `auth_oauth_token_expires` (string)
    - Added property `auth_oauth_url_callback` (string)
    - Added property `auth_oauth_url_start` (string)
    - Changed property `compatibility_mode` (string)

      > Alter authentik behavior for vendor-specific SCIM implementations.

      Added enum values:

        - `webex`
        - `vcenter`

    - Changed property `auth_mode` (string)

      Added enum value:

- `oauth_interactive`

`GET` /providers/scim/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > SCIMProvider Serializer

    New required properties:

    - `auth_oauth_token_expires`
    - `auth_oauth_token_last_updated`
    - `auth_oauth_url_callback`
    - `auth_oauth_url_start`
    - Added property `auth_oauth_token_last_updated` (string)
    - Added property `auth_oauth_token_expires` (string)
    - Added property `auth_oauth_url_callback` (string)
    - Added property `auth_oauth_url_start` (string)
    - Changed property `compatibility_mode` (string)

      > Alter authentik behavior for vendor-specific SCIM implementations.

      Added enum values:

      - `webex`
      - `vcenter`
    - Changed property `auth_mode` (string)

      Added enum value:

- `oauth_interactive`

`POST` /providers/ssf/

Request:

Changed content type : `application/json`

- Added property `push_verify_certificates` (boolean)

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `oidc_auth_providers_obj`
  - Added property `oidc_auth_providers_obj` (array)
  - Added property `push_verify_certificates` (boolean)

`GET` /providers/ssf/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > SSFProvider Serializer

    New required properties:

    - `oidc_auth_providers_obj`
    - Added property `oidc_auth_providers_obj` (array)
    - Added property `push_verify_certificates` (boolean)

`GET` **/providers/wsfed/**

Parameters:

Added: `issuer_override` in `query`

Added: `sign_logout_response` in `query`

Deleted: `issuer` in `query`

Changed: `logout_method` in `query`

Changed: `sls_binding` in `query`

Changed: `sp_binding` in `query`

`GET` **/rbac/permissions/assigned_by_roles/**

Parameters:

Changed: `model` in `query`

`POST` **/sources/group_connections/ldap/**

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `group_obj`
  - Added property `group_obj` (object)

`GET` **/sources/group_connections/ldap/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

- Changed property `results` (array)

  Changed items (object): > Group Source Connection

  New required properties:

  - `group_obj`
  - Added property `group_obj` (object)

`GET` /sources/kerberos/

Parameters:

Changed: `kadmin_type` in `query`

`GET` /sources/oauth/

Parameters:

Changed: `group_matching_mode` in `query`

Changed: `user_matching_mode` in `query`

`GET` /sources/plex/

Parameters:

Changed: `group_matching_mode` in `query`

Changed: `user_matching_mode` in `query`

`POST` /sources/saml/

Request:

Changed content type : `application/json`

- Added property `force_authn` (boolean)

  > When enabled, the IdP will re-authenticate the user even if a session exists.

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `force_authn` (boolean)

    > When enabled, the IdP will re-authenticate the user even if a session exists.

`GET` /sources/saml/

Parameters:

Added: `force_authn` in `query`

Changed: `name_id_policy` in `query`

Changed: `user_matching_mode` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > SAMLSource Serializer

    - Added property `force_authn` (boolean)

      > When enabled, the IdP will re-authenticate the user even if a session exists.

`GET` /sources/telegram/

Parameters:

Changed: `group_matching_mode` in `query`

Changed: `user_matching_mode` in `query`

`POST` /sources/user_connections/ldap/

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  New required properties:

  - `user_obj`
  - Added property `user_obj` (object)

`GET` /sources/user_connections/ldap/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > User source connection

    New required properties:

    - `user_obj`
    - Added property `user_obj` (object)

`GET` /ssf/streams/

Parameters:

Changed: `delivery_method` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > SSFStream Serializer

    - Added property `status` (string)

- Changed property `provider_obj` (object)

  > SSFProvider Serializer

  New required properties:

  - `oidc_auth_providers_obj`
  - Added property `oidc_auth_providers_obj` (array)
  - Added property `push_verify_certificates` (boolean)

- Changed property `delivery_method` (string)

  Added enum values:

  - `urn:ietf:rfc:8935`
  - `urn:ietf:rfc:8936`

- Changed property `events_requested` (array)

  Changed items (string):

  Added enum values:

  - `https://schemas.openid.net/secevent/caep/event-type/token-claims-change`
  - `https://schemas.openid.net/secevent/caep/event-type/assurance-level-change`
  - `https://schemas.openid.net/secevent/caep/event-type/device-compliance-change`
  - `https://schemas.openid.net/secevent/caep/event-type/session-established`
  - `https://schemas.openid.net/secevent/caep/event-type/session-presented`
  - `https://schemas.openid.net/secevent/caep/event-type/risk-level-change`

`GET` /stages/authenticator/validate/{stage_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webauthn_hints` (array)

    Items (string):

    Enum values:

    - `security-key`
    - `client-device`
    - `hybrid`
  - Added property `email_otp_throttling_factor` (number)
  - Added property `sms_otp_throttling_factor` (number)
  - Added property `totp_otp_throttling_factor` (number)
  - Added property `static_otp_throttling_factor` (number)

`PUT` /stages/authenticator/validate/{stage_uuid}/

Request:

Changed content type : `application/json`

- Added property `webauthn_hints` (array)
- Added property `email_otp_throttling_factor` (number)
- Added property `sms_otp_throttling_factor` (number)
- Added property `totp_otp_throttling_factor` (number)
- Added property `static_otp_throttling_factor` (number)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webauthn_hints` (array)
  - Added property `email_otp_throttling_factor` (number)
  - Added property `sms_otp_throttling_factor` (number)
  - Added property `totp_otp_throttling_factor` (number)
  - Added property `static_otp_throttling_factor` (number)

`PATCH` /stages/authenticator/validate/{stage_uuid}/

Request:

Changed content type : `application/json`

- Added property `webauthn_hints` (array)
- Added property `email_otp_throttling_factor` (number)
- Added property `sms_otp_throttling_factor` (number)
- Added property `totp_otp_throttling_factor` (number)
- Added property `static_otp_throttling_factor` (number)

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `webauthn_hints` (array)
  - Added property `email_otp_throttling_factor` (number)
  - Added property `sms_otp_throttling_factor` (number)

- Added property `totp_otp_throttling_factor` (number)
- Added property `static_otp_throttling_factor` (number)

`GET` /stages/authenticator/webauthn/{stage_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `hints` (array)
  - Added property `prevent_duplicate_devices` (boolean)

    > When enabled, a given device can only be registered once.

`PUT` /stages/authenticator/webauthn/{stage_uuid}/

Request:

Changed content type : `application/json`

- Added property `hints` (array)
- Added property `prevent_duplicate_devices` (boolean)

  > When enabled, a given device can only be registered once.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `hints` (array)
  - Added property `prevent_duplicate_devices` (boolean)

    > When enabled, a given device can only be registered once.

`PATCH` /stages/authenticator/webauthn/{stage_uuid}/

Request:

Changed content type : `application/json`

- Added property `hints` (array)
- Added property `prevent_duplicate_devices` (boolean)

  > When enabled, a given device can only be registered once.

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Added property `hints` (array)
  - Added property `prevent_duplicate_devices` (boolean)

    > When enabled, a given device can only be registered once.

`POST` /stages/invitation/invitations/

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Changed property `flow_obj` (object)

    > Flow Serializer

    - Changed property `authentication` (string)

      > Required level of authentication and authorization to access a flow.

      Added enum value:

      - `require_token`

`GET` /stages/invitation/invitations/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Invitation Serializer

    - Changed property `flow_obj` (object)

      > Flow Serializer

      - Changed property `authentication` (string)

        > Required level of authentication and authorization to access a flow.

        Added enum value:

        - `require_token`

POST **/stages/prompt/prompts/preview/**

Request:

Changed content type : `application/json`

- Changed property `type` (string)

  Added enum values:

  - `alert_info`
  - `alert_warning`
  - `alert_danger`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `fields` (array)

Changed items (object): > Serializer for a single Prompt field

- Changed property `type` (string)

  Added enum values:

  - `alert_info`
  - `alert_warning`
  - `alert_danger`

`GET` /core/user_consent/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > UserConsent Serializer

    - Changed property `application` (object)

      > Application Serializer

      - Added property `meta_hide` (boolean)
        > Hide this application from the user's My applications page.

`GET` /endpoints/devices/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object):

    - Changed property `facts` (object)

- Changed property `vendor` (string)

  Added enum value:

  - `chrome.google.com`

- Changed property `data` (object)

  - Changed property `os` (object)

    > For example: {"family":"linux","name":"Ubuntu","version":"24.04.3 LTS (Noble Numbat)","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "windows","name":"Server 2022 Datacenter","version":"10.0.20348.4405","arch":"amd64"} {"family": "mac_os", "name": "", "version": "26.2", "arch": "arm64"}

    New optional properties:

    - `arch`

`GET` /flows/bindings/

Parameters:

Changed: `invalid_response_action` in `query`

`GET` /flows/executor/{flow_slug}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  Updated `ak-stage-session-end` component:

  - Added property `overview_url` (string)

Updated `ak-provider-iframe-logout` component:

- Changed property `logout_urls` (array)

  Changed items (object): > Data for a single logout URL

  New required properties:

  - `url`
  - Added property `url` (string)
  - Added property `provider_name` (string)
  - Added property `binding` (string)
  - Added property `saml_request` (string)
  - Added property `saml_response` (string)
  - Added property `saml_relay_state` (string)

Updated `ak-provider-saml-native-logout` component:

- Added property `saml_binding` (string)

  Enum values:

  - `redirect`
  - `post`
- Added property `saml_response` (string)
- Added property `saml_relay_state` (string)
- Deleted property `relay_state` (string)
- Deleted property `binding` (string)

Updated `ak-stage-prompt` component:

- Changed property `fields` (array)

  Changed items (object): > Serializer for a single Prompt field

  - Changed property `type` (string)

    Added enum values:

    - `alert_info`
    - `alert_warning`
    - `alert_danger`

POST **/flows/executor/{flow_slug}/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`

  Updated `ak-stage-session-end` component:

  - Added property `overview_url` (string)

  Updated `ak-provider-iframe-logout` component:

  - Changed property `logout_urls` (array)

    Changed items (object): > Data for a single logout URL

    New required properties:

    - `url`
    - Added property `url` (string)
    - Added property `provider_name` (string)
    - Added property `binding` (string)
    - Added property `saml_request` (string)

- Added property `saml_response` (string)
- Added property `saml_relay_state` (string)

Updated `ak-provider-saml-native-logout` component:

- Added property `saml_binding` (string)
- Added property `saml_response` (string)
- Added property `saml_relay_state` (string)
- Deleted property `relay_state` (string)
- Deleted property `binding` (string)

Updated `ak-stage-prompt` component:

- Changed property `fields` (array)

  Changed items (object): > Serializer for a single Prompt field

  - Changed property `type` (string)

    Added enum values:

    - `alert_info`
    - `alert_warning`
    - `alert_danger`

`POST` /providers/oauth2/

Request:

Changed content type : `application/json`

- Added property `grant_types` (array)
- Changed property `redirect_uris` (array)

  Changed items (object): > A single allowed redirect URI entry

- Added property `redirect_uri_type` (object)

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `grant_types` (array)
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry
    - Added property `redirect_uri_type` (object)

`GET` /providers/oauth2/

Parameters:

Changed: `client_type` in `query`

Changed: `issuer_mode` in `query`

Changed: `sub_mode` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > OAuth2Provider Serializer
    - Added property `grant_types` (array)
    - Changed property `redirect_uris` (array)

      Changed items (object): > A single allowed redirect URI entry
      - Added property `redirect_uri_type` (object)

POST **/providers/proxy/**

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Changed property `redirect_uris` (array)

    Changed items (object): > A single allowed redirect URI entry

    - Added property `redirect_uri_type` (object)

GET **/providers/proxy/**

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > ProxyProvider Serializer

    - Changed property `redirect_uris` (array)

      Changed items (object): > A single allowed redirect URI entry

      - Added property `redirect_uri_type` (object)

POST **/stages/authenticator/validate/**

Request:

Changed content type : `application/json`

- Added property `webauthn_hints` (array)
- Added property `email_otp_throttling_factor` (number)
- Added property `sms_otp_throttling_factor` (number)

- Added property `totp_otp_throttling_factor` (number)
- Added property `static_otp_throttling_factor` (number)

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `webauthn_hints` (array)
  - Added property `email_otp_throttling_factor` (number)
  - Added property `sms_otp_throttling_factor` (number)
  - Added property `totp_otp_throttling_factor` (number)
  - Added property `static_otp_throttling_factor` (number)

`GET` /stages/authenticator/validate/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > AuthenticatorValidateStage Serializer
    - Added property `webauthn_hints` (array)
    - Added property `email_otp_throttling_factor` (number)
    - Added property `sms_otp_throttling_factor` (number)
    - Added property `totp_otp_throttling_factor` (number)
    - Added property `static_otp_throttling_factor` (number)

`POST` /stages/authenticator/webauthn/

Request:

Changed content type : `application/json`

- Added property `hints` (array)
- Added property `prevent_duplicate_devices` (boolean)

  > When enabled, a given device can only be registered once.

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`
  - Added property `hints` (array)
  - Added property `prevent_duplicate_devices` (boolean)

    > When enabled, a given device can only be registered once.

`GET` /stages/authenticator/webauthn/

Parameters:

Deleted: `friendly_name` in `query`

Deleted: `stage_uuid` in `query`

Changed: `authenticator_attachment` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > AuthenticatorWebAuthnStage Serializer

    - Added property `hints` (array)

- Added property `prevent_duplicate_devices` (boolean)

  > When enabled, a given device can only be registered once.

`GET` /stages/prompt/prompts/{prompt_uuid}/

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `type` (string)

    Added enum values:

    - `alert_info`
    - `alert_warning`
    - `alert_danger`

`PUT` /stages/prompt/prompts/{prompt_uuid}/

Request:

Changed content type : `application/json`

- Changed property `type` (string)

  Added enum values:

  - `alert_info`
  - `alert_warning`
  - `alert_danger`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `type` (string)

Added enum values:

- `alert_info`
- `alert_warning`
- `alert_danger`

`PATCH` /stages/prompt/prompts/{prompt_uuid}/

Request:

Changed content type : `application/json`

- Changed property `type` (string)

  Added enum values:

  - `alert_info`
  - `alert_warning`
  - `alert_danger`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `type` (string)

    Added enum values:

    - `alert_info`
    - `alert_warning`
    - `alert_danger`

`GET` /stages/user_login/

Parameters:

Changed: `geoip_binding` in `query`

Changed: `network_binding` in `query`

`GET` **/tasks/tasks/**

Parameters:

Changed: `state` in `query`

`PUT` **/core/transactional/applications/**

Request:

Changed content type : `application/json`

- Changed property `app` (object)

  > Application Serializer

  - Added property `meta_hide` (boolean)

    > Hide this application from the user's My applications page.

- Changed property `provider` (object)

  Updated `authentik_providers_ssf.ssfprovider` provider_model:

  - Added property `push_verify_certificates` (boolean)

  Updated `authentik_providers_saml.samlprovider` provider_model:

  - Added property `issuer_override` (string)

    > Also known as EntityID. Providing a value overrides the default issuer generated by authentik.

  - Added property `sign_logout_response` (boolean)

  - Deleted property `issuer` (string)

    > Also known as EntityID

  Updated `authentik_providers_scim.scimprovider` provider_model:

  - Changed property `compatibility_mode` (string)

    > Alter authentik behavior for vendor-specific SCIM implementations.

Added enum values:

- `webex`
- `vcenter`

- Changed property `auth_mode` (string)

  Added enum value:

  - `oauth_interactive`

  Updated `authentik_providers_oauth2.oauth2provider` provider_model:

- Added property `grant_types` (array)
- Changed property `redirect_uris` (array)

  Changed items (object): > A single allowed redirect URI entry

  - Added property `redirect_uri_type` (object)

`POST` /stages/prompt/prompts/

Request:

Changed content type : `application/json`

- Changed property `type` (string)

  Added enum values:

  - `alert_info`
  - `alert_warning`
  - `alert_danger`

Return Type:

Changed response : **201 Created**

- Changed content type : `application/json`

  - Changed property `type` (string)

Added enum values:

- `alert_info`
- `alert_warning`
- `alert_danger`

`GET` /stages/prompt/prompts/

Parameters:

Changed: `type` in `query`

Return Type:

Changed response : **200 OK**

- Changed content type : `application/json`
  - Changed property `results` (array)

    Changed items (object): > Prompt Serializer

    - Changed property `type` (string)

      Added enum values:

      - `alert_info`
      - `alert_warning`
      - `alert_danger`

Result

API changes broke backward compatibility

authentik (v 2026.5.6)

What's Changed

POST /endpoints/agents/connectors/auth_fed/

POST /endpoints/agents/connectors/enroll/

GET /endpoints/agents/connectors/agent_config/

POST /endpoints/agents/connectors/check_in/

Result

API changes are backward compatible

Help us improve this content

We welcome your knowledge and expertise. If you see areas of the documentation that you can improve (fix a typo, correct a technical detail, add additional context, etc.) we would really appreciate your contribution.

- Edit on GitHub
- Contributor Guide
- Open an issue
- Get Enterprise Support