

# Commit 0c739c8



golang-not-rust and cplee authored last week · ✓ 1/1 · Verified

Merge commit from fork

Co-authored-by: Casey Lee <cplee@nektos.com>

master · v0.2.86

1 parent 10add23 commit 0c739c8

4 files changed +35 -0 lines changed

↑ Top ⚙️

Filter files...

- pkg/runner
  - command.go
  - command\_test.go
- testdata
  - GITHUB\_ENV-use-in-env-ctx
    - push.yml
  - commands
    - push.yml

4 files changed +35 -0 lines changed

Search within code ⚙️

pkg/runner/command.go



```

@@ -51,10 +51,18 @@ func (rc *RunContext) commandHandler(ctx context.Context)
common.LineHandler {
51 51         defCommandLogger := logger.WithFields(logrus.Fields{"command": command,
        "kvPairs": kvPairs, "arg": arg, "raw": line})
52 52         switch command {

```

```

53 53         case "set-env":
54 +         if rc.Env["ACTIONS_ALLOW_UNSECURE_COMMANDS"] != "true" {
55 +             defCommandLogger.Errorf("The `set-env` command is disabled.
           Please upgrade to using Environment Files or opt into unsafe commands by setting
           the `ACTIONS_ALLOW_UNSECURE_COMMANDS` environment variable to `true`.")
56 +             break
57 +         }
54 58         rc.setEnv(ctx, kvPairs, arg)
55 59         case "set-output":
56 60         rc.setOutput(ctx, kvPairs, arg)
57 61         case "add-path":
62 +         if rc.Env["ACTIONS_ALLOW_UNSECURE_COMMANDS"] != "true" {
63 +             defCommandLogger.Errorf("The `add-path` command is disabled.
           Please upgrade to using Environment Files or opt into unsafe commands by setting
           the `ACTIONS_ALLOW_UNSECURE_COMMANDS` environment variable to `true`.")
64 +             break
65 +         }
58 66         rc.addPath(ctx, arg)
59 67         case "debug":
60 68         defCommandLogger.Debugf(" \U0001F4AC %s", line)

```

pkg/runner/command\_test.go

```

@@ -18,12 +18,23 @@ func TestSetEnv(t *testing.T) {
18 18     a := assert.New(t)
19 19     ctx := context.Background()
20 20     rc := new(RunContext)
21 + rc.Env = map[string]string{"ACTIONS_ALLOW_UNSECURE_COMMANDS": "true"}
21 22     handler := rc.commandHandler(ctx)
22 23
23 24     handler("::set-env name=x::valz\n")
24 25     a.Equal("valz", rc.Env["x"])
25 26 }
26 27
28 + func TestSetEnvBlocked(t *testing.T) {
29 +     a := assert.New(t)
30 +     ctx := context.Background()
31 +     rc := new(RunContext)
32 +     handler := rc.commandHandler(ctx)
33 +

```

```

34 + handler("::set-env name=x::valz\n")
35 + a.Equal("", rc.Env["x"])
36 + }
37 +
27 38 func TestSetOutput(t *testing.T) {
28 39     a := assert.New(t)
29 40     ctx := context.Background()
@@ -58,6 +69,7 @@ func TestAddpath(t *testing.T) {
58 69     a := assert.New(t)
59 70     ctx := context.Background()
60 71     rc := new(RunContext)
72 + rc.Env = map[string]string{"ACTIONS_ALLOW_UNSECURE_COMMANDS": "true"}
61 73     handler := rc.commandHandler(ctx)
62 74
63 75     handler("::add-path::/zoo\n")
@@ -67,12 +79,23 @@ func TestAddpath(t *testing.T) {
67 79     a.Equal("/boo", rc.ExtraPath[0])
68 80 }
69 81
82 + func TestAddPathBlocked(t *testing.T) {
83 +     a := assert.New(t)
84 +     ctx := context.Background()
85 +     rc := new(RunContext)
86 +     handler := rc.commandHandler(ctx)
87 +
88 +     handler("::add-path::/zoo\n")
89 +     a.Empty(rc.ExtraPath)
90 + }
91 +
70 92 func TestStopCommands(t *testing.T) {
71 93     logger, hook := test.NewNullLogger()
72 94
73 95     a := assert.New(t)
74 96     ctx := common.WithLogger(context.Background(), logger)
75 97     rc := new(RunContext)
98 + rc.Env = map[string]string{"ACTIONS_ALLOW_UNSECURE_COMMANDS": "true"}
76 99     handler := rc.commandHandler(ctx)
77 100
78 101     handler("::set-env name=x::valz\n")

```

```
@@ -96,6 +119,7 @@ func TestAddpathADO(t *testing.T) {
96 119     a := assert.New(t)
97 120     ctx := context.Background()
98 121     rc := new(RunContext)
122 +     rc.Env = map[string]string{"ACTIONS_ALLOW_UNSECURE_COMMANDS": "true"}
99 123     handler := rc.commandHandler(ctx)
100 124
101 125     handler("##[add-path]/zoo\n")
```

...testdata/GITHUB\_ENV-use-in-env-ctx/push.yml

```
@@ -4,6 +4,7 @@ jobs:
4 4     runs-on: ubuntu-latest
5 5     env:
6 6         MYGLOBAENV3: myglobalval3
7 +     ACTIONS_ALLOW_UNSECURE_COMMANDS: "true"
7 8     steps:
8 9     - run: |
9 10         echo MYGLOBAENV1=myglobalval1 > $GITHUB_ENV
```

pkg/runner/testdata/commands/push.yml

```
@@ -4,6 +4,8 @@ on: push
4 4     jobs:
5 5         build:
6 6             runs-on: ubuntu-latest
7 +             env:
8 +                 ACTIONS_ALLOW_UNSECURE_COMMANDS: "true"
7 9             steps:
8 10            - name: TEST set-env
9 11              run: echo "::set-env name=foo::bar"
```

## Comments 0



Please [sign in](#) to comment.

