

owntone / owntone-server Public

<> Code Issues 107 Pull requests 6 Actions Wiki Security and quality

# Commit d4784eb

**ejurgensen** committed on Mar 8 · 5 / 5

[daap] Protect against sql injection via integer-mapped fields

master · 29.1

1 parent [f77e029](#) commit d4784eb

**1 file changed** +3 -1 lines changed

Top

- src/parsers
  - daap\_parser.y

**1 file changed** +3 -1 lines changed

src/parsers/daap\_parser.y

```

@@ -292,6 +292,7 @@ static void sql_append_dmap_clause(struct daap_result
 *result, struct ast *a)
292 292     bool is_equal = (a->type == DAAP_T_EQUAL);
293 293     char escape_char;
294 294     char *key;
295 + long long int intval;
295 296
296 297     if (!k || k->type != DAAP_T_KEY || !(key = (char *)k->data))
297 298     {
@@ -360,7 +361,8 @@ static void sql_append_dmap_clause(struct daap_result
 *result, struct ast *a)
360 361         return;
361 362     }
362 363

```

```
363 - sql_append(result, "%s", (char *)v->data);
364 + intval = strtoll((char *)v->data, NULL, 10);
365 + sql_append(result, "%lld", intval);
364 366 }
365 367
366 368 /* Creates the parsing result from the AST */
.....
↓
```

## Comments 0



Please [sign in](#) to comment.