

This repository was archived by the owner on Jan 23, 2026. It is now read-only.

supabase / auth-js Public archive

<> Code Issues 13 Pull requests 5 Security and quality 1 Insights

Insecure path routing on malformed user input

Low staaldraad published **GHSA-8r88-6cj9-9fh5** on May 26, 2025

Package

 @supabase/auth-js (npm)

Affected versions

<= 2.69.1

Patched versions

2.70.0

Description

Impact

The library functions `getUserById`, `deleteUser`, `updateUserById`, `listFactors` and `deleteFactor` did not require the user supplied values to be valid UUIDs. This could lead to a URL path traversal, resulting in the wrong API function being called.

Implementations that follow security best practice and validate user controlled inputs, such as the `userId` are not affected by this.

Patches

Strict value checks have been added to all affected functions. These functions now require that the `userId` and `factorId` parameters MUST be valid UUID (v4).

Patched version: >= 2.69.1

Workarounds

Implementations that follow security best practice and validate user controlled inputs, such as the `userId` are not affected by this. It is recommended that users of the auth-js library always follow security best practice and validate all inputs, before passing these to other functions or libraries.

References

[#1063](#)

Severity

Low

CVE ID

CVE-2025-48370

Weaknesses

No CWEs

Credits



kos0ng

Reporter