

team-alembic / ash_authentication_phoenix Public

<> Code Issues 11 Pull requests 1 Discussions Actions Projects

Commit a3253fb



zachdaniel authored on Jun 17, 2025 · ✖ 12 / 14 · Verified

improvement: revoke stored sessions on log out (#634)

main (#634) · v3.0.0-rc.3 ... 3.0.0-rc.3

1 parent [88c35b4](#) commit a3253fb

10 files changed +57 -21 lines changed

[↑ Top](#)

🔍 Filter files...

- ✓ dev/dev_web/controllers
 - auth_controller.ex
- ✓ documentation/tutorials
 - get-started.md
- ✓ lib
 - ✓ ash_authentication_phoenix
 - controller.ex
 - plug.ex
 - ✓ mix/tasks
 - ash_authentication_phoenix.install.ex
 - mix.exs
 - mix.lock
- ✓ test
 - ✓ mix/tasks
 - ash_authentication_phoenix.install_test.exs
 - support

- accounts
 - user.ex
 - auth_controller.ex

10 files changed +57 -21 lines changed

Search within code



dev/dev_web/controllers/auth_controller.ex

```
@@ -26,7 +26,7 @@ defmodule DevWeb.AuthController do
  @impl true
  def sign_out(conn, _params) do
    conn
-    |> clear_session()
+    |> clear_session(:ash_authentication_phoenix)
    |> render("sign_out.html")
  end
end
```

documentation/tutorials/get-started.md

```
@@ -116,7 +116,7 @@ defmodule ExampleWeb.AuthController do
  return_to = get_session(conn, :return_to) || ~p"/"
  conn
-  |> clear_session()
+  |> clear_session(:my_app)
  |> redirect(to: return_to)
  end
end
```

lib/ash_authentication_phoenix/controller.ex

```
@@ -77,6 +77,7 @@ defmodule AshAuthentication.Phoenix.Controller do
  """
  79 79 alias AshAuthentication.Plug.Dispatcher
+ 80 80 alias AshAuthentication.Plug.Helpers
 80 81 alias Plug.Conn
 81 82
```

82	83	@type t :: module
<div style="display: flex; justify-content: center; align-items: center; gap: 10px;"> ⋮ ↓ ↑ ⋮ </div>		
@@ -107,7 +108,7 @@ defmodule AshAuthentication.Phoenix.Controller do		
107	108	@behaviour AshAuthentication.Phoenix.Controller
108	109	@behaviour AshAuthentication.Plug
109	110	import Phoenix.Controller
110	-	import Plug.Conn
111	+	import Plug.Conn, except: [clear_session: 1]
111	112	import AshAuthentication.Phoenix.Plug
112	113	import AshAuthentication.Phoenix.Controller
113	114	
<div style="display: flex; justify-content: center; align-items: center; gap: 10px;"> ⋮ ↓ ↑ ⋮ </div>		
@@ -137,15 +138,6 @@ defmodule AshAuthentication.Phoenix.Controller do		
137	138	> render("failure.html")
138	139	end
139	140	
140	-	@doc false
141	-	@impl true
142	-	@spec sign_out(Conn.t(), map) :: Conn.t()
143	-	def sign_out(conn, _params) do
144	-	conn
145	-	> clear_session()
146	-	> render("sign_out.html")
147	-	end
148	-	
149	141	@doc false
150	142	@impl true
151	143	@spec call(Conn.t(), any) :: Conn.t()
<div style="display: flex; justify-content: center; align-items: center; gap: 10px;"> ⋮ ↓ ↑ ⋮ </div>		
@@ -203,7 +195,36 @@ defmodule AshAuthentication.Phoenix.Controller do		
203	195	end
204	196	end
205	197	
206	-	defoverridable success: 4, failure: 3, sign_out: 2
198	+	defoverridable success: 4, failure: 3
207	199	end
208	200	end
201	+	
202	+	defmacro clear_session(_conn) do
203	+	raise ""

```

204 +   Using clear_session/1 in your `auth_controller` is deprecated. Please use
      `clear_session/2` instead,
205 +   passing the conn and the otp_app.
206 +
207 +   For example:
208 +
209 +       conn
210 +       |> clear_session(conn, :my_app)
211 +
212 +
213 +   This ensures that session tokens & bearer tokens are revoked on logout.
214 +
215 +   If you wish to retain the old behavior (not advised), call
      `Plug.Conn.clear_session/1` directly.
216 +   """
217 +   end
218 +
219 +   @doc """
220 +   Clears the session and revokes bearer and session tokens.
221 +
222 +   This ensures that session tokens & bearer tokens are revoked on logout.
223 +   """
224 +   def clear_session(conn, otp_app) do
225 +     conn
226 +     |> Helpers.revoke_bearer_tokens(otp_app)
227 +     |> Helpers.revoke_session_tokens(otp_app)
228 +     |> Plug.Conn.clear_session()
229 +   end

```

```
209 230   end
```

lib/ash_authentication_phoenix/plug.ex

...

```

↑... @@ -49,6 +49,18 @@ defmodule AshAuthentication.Phoenix.Plug do
49 49     Helpers.revoke_bearer_tokens(conn, otp_app)
50 50     end
51 51
52 + @doc """
53 + Revoke all token(s) in the session.
54 +
55 + A wrapper around `AshAuthentication.Plug.Helpers.revoke_session_tokens/2` with
56 + the `otp_app` as extracted from the endpoint.

```

```

57 +   """
58 +   @spec revoke_session_tokens(Conn.t(), any) :: Conn.t()
59 +   def revoke_session_tokens(conn, _opts) do
60 +     otp_app = conn.private.phoenix_endpoint.config(:otp_app)
61 +     Helpers.revoke_session_tokens(conn, otp_app)
62 +   end
63 +
52 64   @doc """
53 65   Store the actor in the connections' session.
54 66   """

```



...tasks/ash_authentication_phoenix.install.ex



```

↑... @@ -98,14 +98,15 @@ if Code.ensure_loaded?(Igniter) do
98 98     if router do
99 99         web_module = Igniter.Libs.Phoenix.web_module(igniter)
100 100        overrides = Igniter.Libs.Phoenix.web_module_name(igniter,
            "AuthOverrides")
101 +         otp_app = Igniter.Project.Application.app_name(igniter)
101 102
102 103         igniter
103 104         |> Igniter.Project.Formatter.import_dep(:ash_authentication_phoenix)
104 105         |> Igniter.compose_task("igniter.add_extension", ["phoenix"])
105 106         |> setup_routes_alias()
106 107         |> warn_on_missing_modules(options, argv, install?)
107 108         |> do_or_explain_tailwind_changes()
108 -         |> create_auth_controller()
109 +         |> create_auth_controller(otp_app)
109 110         |> create_overrides_module(overrides)
110 111         |> add_auth_routes(overrides, options, router, web_module)
111 112         |> create_live_user_auth(web_module)
↓...
↑... @@ -318,7 +319,7 @@ if Code.ensure_loaded?(Igniter) do
318 319         )
319 320         end
320 321
321 -         defp create_auth_controller(igniter) do
322 +         defp create_auth_controller(igniter, otp_app) do
322 323             Igniter.Project.Module.create_module(
323 324             igniter,

```

```

324 325      Igniter.Libs.Phoenix.web_module_name(igniter, "AuthController"),
    ↓
    ↑
372 373          return_to = get_session(conn, :return_to) || ~p"/"
373 374
374 375          conn
375 -      |> clear_session()
376 +      |> clear_session(:#{otp_app})
376 377          |> put_flash(:info, "You are now signed out")
377 378          |> redirect(to: return_to)
378 379      end
    ↓

```

```

▼ mix.exs
    ↑
118 118      # Run "mix help deps" to learn about dependencies.
119 119      defp deps do
120 120          [
121 -          {:ash_authentication, "~> 4.8"},
121 +          {:ash_authentication, "~> 4.9 and >= 4.9.1"},
122 122          {:ash_phoenix, "~> 2.0"},
123 123          {:ash, "~> 3.0"},
124 124          {:jason, "~> 1.0"},
    ↓

```

```

▼ mix.lock
    ...
1 1  %{}
2 -  "ash": {:hex, :ash, "3.5.19",
    "defd1c6b94475352a7b69f430b792fb64e3a9f7ca030195737bb97dc0f1311b5", [:mix],
    [[:decimal, "~> 2.0", [hex: :decimal, repo: "hexpm", optional: false]], {:ecto,
    "~> 3.7", [hex: :ecto, repo: "hexpm", optional: false]], {:ets, "~> 0.8", [hex:
    :ets, repo: "hexpm", optional: false]], {:igniter, ">= 0.6.4 and < 1.0.0-0",
    [hex: :igniter, repo: "hexpm", optional: true]], {:jason, ">= 1.0.0", [hex:
    :jason, repo: "hexpm", optional: false]], {:picosat_elixir, "~> 0.2", [hex:
    :picosat_elixir, repo: "hexpm", optional: true]], {:plug, ">= 0.0.0", [hex:
    :plug, repo: "hexpm", optional: true]], {:reactor, "~> 0.11", [hex: :reactor,
    repo: "hexpm", optional: false]], {:simple_sat, ">= 0.1.1 and < 1.0.0-0", [hex:
    :simple_sat, repo: "hexpm", optional: true]], {:spark, ">= 2.2.65 and < 3.0.0-

```

```

0", [hex: :spark, repo: "hexpm", optional: false]}, {:splode, ">= 0.2.6 and <
1.0.0-0", [hex: :splode, repo: "hexpm", optional: false]}, {:stream_data, "~>
1.0", [hex: :stream_data, repo: "hexpm", optional: false]}, {:telemetry, "~>
1.1", [hex: :telemetry, repo: "hexpm", optional: false]]}, "hexpm",
"ded976230b1ef823aeb25008cc62de6545bf3ad6208cf1f3badb598fa6c01375"},
3 - "ash_authentication": {:hex, :ash_authentication, "4.9.0",
"0286b5df6e5006d16811b18f0efcd691fa7895a0a3aa1b091986a61da31a2a8a", [:mix],
[{:argon2_elixir, "~> 4.0", [hex: :argon2_elixir, repo: "hexpm", optional:
true]}], {:ash, ">= 3.4.29 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional:
false]}], {:ash_postgres, "~> 2.0", [hex: :ash_postgres, repo: "hexpm", optional:
true]}], {:assent, "~> 0.2.13", [hex: :assent, repo: "hexpm", optional: false]}],
{:bcrypt_elixir, "~> 3.0", [hex: :bcrypt_elixir, repo: "hexpm", optional:
false]}], {:castore, "~> 1.0", [hex: :castore, repo: "hexpm", optional: false]}],
{:finch, "~> 0.19", [hex: :finch, repo: "hexpm", optional: false]}], {:igniter,
 "~> 0.4", [hex: :igniter, repo: "hexpm", optional: true]}], {:jason, "~> 1.4",
 [hex: :jason, repo: "hexpm", optional: false]}], {:joken, "~> 2.5", [hex: :joken,
repo: "hexpm", optional: false]}], {:plug, "~> 1.13", [hex: :plug, repo: "hexpm",
optional: false]}], {:spark, "~> 2.0", [hex: :spark, repo: "hexpm", optional:
false]}], {:splode, "~> 0.2", [hex: :splode, repo: "hexpm", optional: false]}],
"hexpm", "dde0c702b26e7354d81ea4a9bb334c27ce11a59876df8c5d4d5b0bebe4b7ad4e"},
2 + "ash": {:hex, :ash, "3.5.21",
"389303c193962d67fd59da18a3557f5015fd5daeddaa77150db539bc7203d1a1", [:mix],
[{:decimal, "~> 2.0", [hex: :decimal, repo: "hexpm", optional: false]}], {:ecto,
 "~> 3.7", [hex: :ecto, repo: "hexpm", optional: false]}], {:ets, "~> 0.8", [hex:
:ets, repo: "hexpm", optional: false]}], {:igniter, ">= 0.6.4 and < 1.0.0-0",
 [hex: :igniter, repo: "hexpm", optional: true]}], {:jason, ">= 1.0.0", [hex:
:jason, repo: "hexpm", optional: false]}], {:picosat_elixir, "~> 0.2", [hex:
:picosat_elixir, repo: "hexpm", optional: true]}], {:plug, ">= 0.0.0", [hex:
:plug, repo: "hexpm", optional: true]}], {:reactor, "~> 0.11", [hex: :reactor,
repo: "hexpm", optional: false]}], {:simple_sat, ">= 0.1.1 and < 1.0.0-0", [hex:
:simple_sat, repo: "hexpm", optional: true]}], {:spark, ">= 2.2.65 and < 3.0.0-
0", [hex: :spark, repo: "hexpm", optional: false]}], {:splode, ">= 0.2.6 and <
1.0.0-0", [hex: :splode, repo: "hexpm", optional: false]}], {:stream_data, "~>
1.0", [hex: :stream_data, repo: "hexpm", optional: false]}], {:telemetry, "~>
1.1", [hex: :telemetry, repo: "hexpm", optional: false]}], "hexpm",
"cb90005d1972e22d0d2ae514394e43e0d67cce18c4485595aa3d3e4bbf25260f"},
3 + "ash_authentication": {:hex, :ash_authentication, "4.9.1",
"f5465abb973777ed7150c94f89902d0050d4debca1cf6ba8930e18e4de379a08", [:mix],
[{:argon2_elixir, "~> 4.0", [hex: :argon2_elixir, repo: "hexpm", optional:
true]}], {:ash, ">= 3.4.29 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional:

```

```

false}}, {:ash_postgres, "~> 2.0", [hex: :ash_postgres, repo: "hexpm", optional:
true}}, {:assent, "~> 0.2.13", [hex: :assent, repo: "hexpm", optional: false}},
{:bcrypt_elixir, "~> 3.0", [hex: :bcrypt_elixir, repo: "hexpm", optional:
false}}, {:castore, "~> 1.0", [hex: :castore, repo: "hexpm", optional: false}},
{:finch, "~> 0.19", [hex: :finch, repo: "hexpm", optional: false}}, {:igniter,
 "~> 0.4", [hex: :igniter, repo: "hexpm", optional: true}}, {:jason, "~> 1.4",
 [hex: :jason, repo: "hexpm", optional: false}}, {:joken, "~> 2.5", [hex: :joken,
repo: "hexpm", optional: false}}, {:plug, "~> 1.13", [hex: :plug, repo: "hexpm",
optional: false}}, {:spark, "~> 2.0", [hex: :spark, repo: "hexpm", optional:
false}}, {:splode, "~> 0.2", [hex: :splode, repo: "hexpm", optional: false}},
"hexpm", "e5022a1d149c04fc529277a8174f0004b617d5530f080ce4e98a9452c5586970"},

```

```

4 4 "ash_phoenix": {:hex, :ash_phoenix, "2.3.6",
"c2bea1673af52f305b2fe0c04999bd1f0dc8e127d4757a3d7f42d0b9dea16a7a", [:mix],
[{:ash, ">= 3.5.13 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional: false]},
{:igniter, "~> 0.6", [hex: :igniter, repo: "hexpm", optional: true]}, {:inertia,
 "~> 2.3", [hex: :inertia, repo: "hexpm", optional: true]}, {:phoenix, "~> 1.5.6
or ~> 1.6", [hex: :phoenix, repo: "hexpm", optional: false]}, {:phoenix_html,
 "~> 4.0", [hex: :phoenix_html, repo: "hexpm", optional: false]},
{:phoenix_live_view, "~> 0.20.3 or ~> 1.0-rc.1", [hex: :phoenix_live_view, repo:
"hexpm", optional: false]}, {:spark, ">= 2.2.29 and < 3.0.0-0", [hex: :spark,
repo: "hexpm", optional: false]}], "hexpm",
"6923dca70fe1d533864134999f4d9c5c59ef745a6b50982d42d60c18966474cd"},

```

```

5 5 "assent": {:hex, :assent, "0.2.13",
"11226365d2d8661d23e9a2cf94d3255e81054ff9d88ac877f28bdfdf38fa4ef31", [:mix],
[{:certifi, ">= 0.0.0", [hex: :certifi, repo: "hexpm", optional: true]},
{:finch, "~> 0.15", [hex: :finch, repo: "hexpm", optional: true]}, {:jose, "~>
1.8", [hex: :jose, repo: "hexpm", optional: true]}, {:mint, "~> 1.0", [hex:
:mint, repo: "hexpm", optional: true]}, {:req, "~> 0.4", [hex: :req, repo:
"hexpm", optional: true]}, {:ssl_verify_fun, ">= 0.0.0", [hex: :ssl_verify_fun,
repo: "hexpm", optional: true]}], "hexpm",
"bf9f351b01dd6bceea1d1f157f05438f6765ce606e6eb8d29296003d29bf6eab"},

```

```

6 6 "bcrypt_elixir": {:hex, :bcrypt_elixir, "3.3.2",
"d50091e3c9492d73e17fc1e1619a9b09d6a5ef99160eb4d736926fd475a16ca3", [:make,
:mix], [{:comeonin, "~> 5.3", [hex: :comeonin, repo: "hexpm", optional: false]},
{:elixir_make, "~> 0.6", [hex: :elixir_make, repo: "hexpm", optional: false]}],
"hexpm", "471be5151874ae7931911057d1467d908955f93554f7a6cd1b7d804cac8cef53"},

```



▼ ...ash_authentication_phoenix.install_test.exs



```

@@ -142,7 +142,7 @@ defmodule Mix.Tasks.AshAuthenticationPhoenix.InstallTest
do
142 142     return_to = get_session(conn, :return_to) || ~p"/"
143 143
144 144     conn
145 145     -     |> clear_session()
145 145     +     |> clear_session(:test)
146 146     |> put_flash(:info, "You are now signed out")
147 147     |> redirect(to: return_to)
148 148     end

```

test/support/accounts/user.ex

```

@@ -96,6 +96,8 @@ defmodule Example.Accounts.User do
96 96     end
97 97
98 98     authentication do
99 99     +     session_identifer(:jti)
100 100    +
99 101     add_ons do
100 102     confirmation :confirm do
101 103     monitor_fields([:email])

```

test/support/auth_controller.ex

```

@@ -26,7 +26,7 @@ defmodule AshAuthentication.Phoenix.Test.AuthController do
26 26     @impl true
27 27     def sign_out(conn, _params) do
28 28     conn
29 29     -     |> clear_session()
29 29     +     |> clear_session(:ash_authentication_phoenix)
30 30     |> render(:signed_out)
31 31     end
32 32     end

```

Comments 0



Please [sign in](#) to comment.