

team-alembic / ash_authentication_phoenix Public

<> Code Issues 12 Pull requests 5 Discussions Actions Projects

Commit a3253fb



zachdaniel authored on Jun 17, 2025 · ✖ 12 / 14 · Verified

improvement: revoke stored sessions on log out (#634)

main (#634) · v3.0.0-rc.4 · 3.0.0-rc.3

1 parent [88c35b4](#) commit a3253fb

10 files changed

+57 -21 ■■■■■■

Top



- v dev/dev_web/controllers
 - auth_controller.ex
- v documentation/tutorials
 - get-started.md
- v lib
 - v ash_authentication_phoenix
 - controller.ex
 - plug.ex
 - v mix/tasks
 - ash_authentication_phoenix.install.ex
 - mix.exs
 - mix.lock
- v test
 - v mix/tasks
 - ash_authentication_phoenix.install_test.exs

- ✓ support
- ✓ accounts
 - user.ex
 - auth_controller.ex

🔍 Search within code ⚙️

```

dev/dev_web/controllers/auth_controller.ex
@@ -26,7 +26,7 @@ defmodule DevWeb.AuthController do
  @impl true
  def sign_out(conn, _params) do
    conn
-    |> clear_session()
+    |> clear_session(:ash_authentication_phoenix)
    |> render("sign_out.html")
  end
end

```

```

documentation/tutorials/get-started.md
@@ -116,7 +116,7 @@ defmodule ExampleWeb.AuthController do
  return_to = get_session(conn, :return_to) || ~p"/"
  conn
-  |> clear_session()
+  |> clear_session(:my_app)
  |> redirect(to: return_to)
end
end

```

```

lib/ash_authentication_phoenix/controller.ex
@@ -77,6 +77,7 @@ defmodule AshAuthentication.Phoenix.Controller do
  ""
  alias AshAuthentication.Plug.Dispatcher
+  alias AshAuthentication.Plug.Helpers
  alias Plug.Conn

```

81	82	
82	83	<code>@type t :: module</code>
		<div style="text-align: center;"> ⌵ ⌶ </div> <code>@@ -107,7 +108,7 @@ defmodule AshAuthentication.Phoenix.Controller do</code>
107	108	<code>@behaviour AshAuthentication.Phoenix.Controller</code>
108	109	<code>@behaviour AshAuthentication.Plug</code>
109	110	<code>import Phoenix.Controller</code>
110	-	<code>import Plug.Conn</code>
	111	<code>+ import Plug.Conn, except: [clear_session: 1]</code>
111	112	<code>import AshAuthentication.Phoenix.Plug</code>
112	113	<code>import AshAuthentication.Phoenix.Controller</code>
113	114	
		<div style="text-align: center;"> ⌵ ⌶ </div> <code>@@ -137,15 +138,6 @@ defmodule AshAuthentication.Phoenix.Controller do</code>
137	138	<code> > render("failure.html")</code>
138	139	<code>end</code>
139	140	
140	-	<code>@doc false</code>
141	-	<code>@impl true</code>
142	-	<code>@spec sign_out(Conn.t(), map) :: Conn.t()</code>
143	-	<code>def sign_out(conn, _params) do</code>
144	-	<code>conn</code>
145	-	<code> > clear_session()</code>
146	-	<code> > render("sign_out.html")</code>
147	-	<code>end</code>
148	-	
149	141	<code>@doc false</code>
150	142	<code>@impl true</code>
151	143	<code>@spec call(Conn.t(), any) :: Conn.t()</code>
		<div style="text-align: center;"> ⌵ ⌶ </div> <code>@@ -203,7 +195,36 @@ defmodule AshAuthentication.Phoenix.Controller do</code>
203	195	<code>end</code>
204	196	<code>end</code>
205	197	
206	-	<code>defoverridable success: 4, failure: 3, sign_out: 2</code>
	198	<code>+ defoverridable success: 4, failure: 3</code>
207	199	<code>end</code>
208	200	<code>end</code>
	201	<code>+ </code>
	202	<code>+ defmacro clear_session(_conn) do</code>

```

203 +   raise ""
204 +   Using clear_session/1 in your `auth_controller` is deprecated. Please use
      `clear_session/2` instead,
205 +   passing the conn and the otp_app.
206 +
207 +   For example:
208 +
209 +       conn
210 +       |> clear_session(conn, :my_app)
211 +
212 +
213 +   This ensures that session tokens & bearer tokens are revoked on logout.
214 +
215 +   If you wish to retain the old behavior (not advised), call
      `Plug.Conn.clear_session/1` directly.
216 +   ""
217 + end
218 +
219 + @doc ""
220 + Clears the session and revokes bearer and session tokens.
221 +
222 + This ensures that session tokens & bearer tokens are revoked on logout.
223 + ""
224 + def clear_session(conn, otp_app) do
225 +   conn
226 +   |> Helpers.revoke_bearer_tokens(otp_app)
227 +   |> Helpers.revoke_session_tokens(otp_app)
228 +   |> Plug.Conn.clear_session()
229 + end

```

```
209 230 end
```

lib/ash_authentication_phoenix/plug.ex

...

↑

```
@@ -49,6 +49,18 @@ defmodule AshAuthentication.Phoenix.Plug do
```

```
49 49     Helpers.revoke_bearer_tokens(conn, otp_app)
```

```
50 50     end
```

```
51 51
```

```
52 + @doc ""
```

```
53 + Revoke all token(s) in the session.
```

```
54 +
```

```
55 + A wrapper around `AshAuthentication.Plug.Helpers.revoke_session_tokens/2` with
```

```

56 +   the `otp_app` as extracted from the endpoint.
57 +   """
58 +   @spec revoke_session_tokens(Conn.t(), any) :: Conn.t()
59 +   def revoke_session_tokens(conn, _opts) do
60 +     otp_app = conn.private.phoenix_endpoint.config(:otp_app)
61 +     Helpers.revoke_session_tokens(conn, otp_app)
62 +   end
63 +

```

```

52 64   @doc """
53 65   Store the actor in the connections' session.
54 66   """

```



...tasks/ash_authentication_phoenix.install.ex



```
@@ -98,14 +98,15 @@ if Code.ensure_loaded?(Igniter) do
```

```

98 98         if router do
99 99             web_module = Igniter.Libs.Phoenix.web_module(igniter)
100 100            overrides = Igniter.Libs.Phoenix.web_module_name(igniter,
                "AuthOverrides")
101 +            otp_app = Igniter.Project.Application.app_name(igniter)
101 102
102 103            igniter
103 104            |> Igniter.Project.Formatter.import_dep(:ash_authentication_phoenix)
104 105            |> Igniter.compose_task("igniter.add_extension", ["phoenix"])
105 106            |> setup_routes_alias()
106 107            |> warn_on_missing_modules(options, argv, install?)
107 108            |> do_or_explain_tailwind_changes()
108 -            |> create_auth_controller()
109 +            |> create_auth_controller(otp_app)
109 110            |> create_overrides_module(overrides)
110 111            |> add_auth_routes(overrides, options, router, web_module)
111 112            |> create_live_user_auth(web_module)

```



```
@@ -318,7 +319,7 @@ if Code.ensure_loaded?(Igniter) do
```

```

318 319         )
319 320         end
320 321
321 -         defp create_auth_controller(igniter) do
322 +         defp create_auth_controller(igniter, otp_app) do
322 323             Igniter.Project.Module.create_module(

```

```

323 324         igniter,
324 325         Igniter.Libs.Phoenix.web_module_name(igniter, "AuthController"),
@@ -372,7 +373,7 @@ if Code.ensure_loaded?(Igniter) do
372 373         return_to = get_session(conn, :return_to) || ~p"/"
373 374
374 375         conn
375 -         |> clear_session()
376 +         |> clear_session(:#{otp_app})
376 377         |> put_flash(:info, "You are now signed out")
377 378         |> redirect(to: return_to)
378 379     end

```

mix.exs

```

@@ -118,7 +118,7 @@ defmodule AshAuthentication.Phoenix.MixProject do
118 118     # Run "mix help deps" to learn about dependencies.
119 119     defp deps do
120 120         [
121 -         {:ash_authentication, "~> 4.8"},
121 +         {:ash_authentication, "~> 4.9 and >= 4.9.1"},
122 122         {:ash_phoenix, "~> 2.0"},
123 123         {:ash, "~> 3.0"},
124 124         {:jason, "~> 1.0"},

```

mix.lock

```

@@ -1,6 +1,6 @@
1 1     %{
2 -     "ash": {:hex, :ash, "3.5.19",
      "defd1c6b94475352a7b69f430b792fb64e3a9f7ca030195737bb97dc0f1311b5", [:mix],
      [{:decimal, "~> 2.0", [hex: :decimal, repo: "hexpm", optional: false]}, {:ecto,
      "~> 3.7", [hex: :ecto, repo: "hexpm", optional: false]}, {:ets, "~> 0.8", [hex:
      :ets, repo: "hexpm", optional: false]}, {:igniter, ">= 0.6.4 and < 1.0.0-0",
      [hex: :igniter, repo: "hexpm", optional: true]}, {:jason, ">= 1.0.0", [hex:
      :jason, repo: "hexpm", optional: false]}, {:picosat_elixir, "~> 0.2", [hex:
      :picosat_elixir, repo: "hexpm", optional: true]}, {:plug, ">= 0.0.0", [hex:
      :plug, repo: "hexpm", optional: true]}, {:reactor, "~> 0.11", [hex: :reactor,
      repo: "hexpm", optional: false]}, {:simple_sat, ">= 0.1.1 and < 1.0.0-0", [hex:

```

```

:~> simple_sat, repo: "hexpm", optional: true}}, {:spark, ">= 2.2.65 and < 3.0.0-0", [hex: :spark, repo: "hexpm", optional: false]}, {:splode, ">= 0.2.6 and < 1.0.0-0", [hex: :splode, repo: "hexpm", optional: false]}, {:stream_data, "~> 1.0", [hex: :stream_data, repo: "hexpm", optional: false]}, {:telemetry, "~> 1.1", [hex: :telemetry, repo: "hexpm", optional: false]]}, "hexpm", "ded976230b1ef823aeb25008cc62de6545bf3ad6208cf1f3badb598fa6c01375"},
3 - "ash_authentication": {:hex, :ash_authentication, "4.9.0", "0286b5df6e5006d16811b18f0efcd691fa7895a0a3aa1b091986a61da31a2a8a", [:mix], [{:argon2_elixir, "~> 4.0", [hex: :argon2_elixir, repo: "hexpm", optional: true]}, {:ash, ">= 3.4.29 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional: false]}, {:ash_postgres, "~> 2.0", [hex: :ash_postgres, repo: "hexpm", optional: true]}, {:assent, "~> 0.2.13", [hex: :assent, repo: "hexpm", optional: false]}, {:bcrypt_elixir, "~> 3.0", [hex: :bcrypt_elixir, repo: "hexpm", optional: false]}, {:castore, "~> 1.0", [hex: :castore, repo: "hexpm", optional: false]}, {:finch, "~> 0.19", [hex: :finch, repo: "hexpm", optional: false]}, {:igniter, "~> 0.4", [hex: :igniter, repo: "hexpm", optional: true]}, {:jason, "~> 1.4", [hex: :jason, repo: "hexpm", optional: false]}, {:joken, "~> 2.5", [hex: :joken, repo: "hexpm", optional: false]}, {:plug, "~> 1.13", [hex: :plug, repo: "hexpm", optional: false]}, {:spark, "~> 2.0", [hex: :spark, repo: "hexpm", optional: false]}, {:splode, "~> 0.2", [hex: :splode, repo: "hexpm", optional: false]]}, "hexpm", "dde0c702b26e7354d81ea4a9bb334c27ce11a59876df8c5d4d5b0bebe4b7ad4e"},
2 + "ash": {:hex, :ash, "3.5.21", "389303c193962d67fd59da18a3557f5015fdfdaeddaa77150db539bc7203d1a1", [:mix], [{:decimal, "~> 2.0", [hex: :decimal, repo: "hexpm", optional: false]}, {:ecto, "~> 3.7", [hex: :ecto, repo: "hexpm", optional: false]}, {:ets, "~> 0.8", [hex: :ets, repo: "hexpm", optional: false]}, {:igniter, ">= 0.6.4 and < 1.0.0-0", [hex: :igniter, repo: "hexpm", optional: true]}, {:jason, ">= 1.0.0", [hex: :jason, repo: "hexpm", optional: false]}, {:picasat_elixir, "~> 0.2", [hex: :picasat_elixir, repo: "hexpm", optional: true]}, {:plug, ">= 0.0.0", [hex: :plug, repo: "hexpm", optional: true]}, {:reactor, "~> 0.11", [hex: :reactor, repo: "hexpm", optional: false]}, {:simple_sat, ">= 0.1.1 and < 1.0.0-0", [hex: :simple_sat, repo: "hexpm", optional: true]}, {:spark, ">= 2.2.65 and < 3.0.0-0", [hex: :spark, repo: "hexpm", optional: false]}, {:splode, ">= 0.2.6 and < 1.0.0-0", [hex: :splode, repo: "hexpm", optional: false]}, {:stream_data, "~> 1.0", [hex: :stream_data, repo: "hexpm", optional: false]}, {:telemetry, "~> 1.1", [hex: :telemetry, repo: "hexpm", optional: false]]}, "hexpm", "cb90005d1972e22d0d2ae514394e43e0d67cce18c4485595aa3d3e4bbf25260f"},
3 + "ash_authentication": {:hex, :ash_authentication, "4.9.1", "f5465abb973777ed7150c94f89902d0050d4debca1cf6ba8930e18e4de379a08", [:mix], [{:argon2_elixir, "~> 4.0", [hex: :argon2_elixir, repo: "hexpm", optional:

```

```

true]], {:ash, ">= 3.4.29 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional:
false]], {:ash_postgres, "~> 2.0", [hex: :ash_postgres, repo: "hexpm", optional:
true]], {:assent, "~> 0.2.13", [hex: :assent, repo: "hexpm", optional: false]],
{:bcrypt_elixir, "~> 3.0", [hex: :bcrypt_elixir, repo: "hexpm", optional:
false]], {:castore, "~> 1.0", [hex: :castore, repo: "hexpm", optional: false]],
{:finch, "~> 0.19", [hex: :finch, repo: "hexpm", optional: false]], {:igniter,
 "~> 0.4", [hex: :igniter, repo: "hexpm", optional: true]], {:jason, "~> 1.4",
 [hex: :jason, repo: "hexpm", optional: false]], {:joken, "~> 2.5", [hex: :joken,
repo: "hexpm", optional: false]], {:plug, "~> 1.13", [hex: :plug, repo: "hexpm",
optional: false]], {:spark, "~> 2.0", [hex: :spark, repo: "hexpm", optional:
false]], {:splode, "~> 0.2", [hex: :splode, repo: "hexpm", optional: false]],
"hexpm", "e5022a1d149c04fc529277a8174f0004b617d5530f080ce4e98a9452c5586970"},

```

```

4 4 "ash_phoenix": {:hex, :ash_phoenix, "2.3.6",
"c2bea1673af52f305b2fe0c04999bd1f0dc8e127d4757a3d7f42d0b9dea16a7a", [:mix],
[{:ash, ">= 3.5.13 and < 4.0.0-0", [hex: :ash, repo: "hexpm", optional: false]],
{:igniter, "~> 0.6", [hex: :igniter, repo: "hexpm", optional: true]], {:inertia,
 "~> 2.3", [hex: :inertia, repo: "hexpm", optional: true]], {:phoenix, "~> 1.5.6
or ~> 1.6", [hex: :phoenix, repo: "hexpm", optional: false]], {:phoenix_html,
 "~> 4.0", [hex: :phoenix_html, repo: "hexpm", optional: false]],
{:phoenix_live_view, "~> 0.20.3 or ~> 1.0-rc.1", [hex: :phoenix_live_view, repo:
"hexpm", optional: false]], {:spark, ">= 2.2.29 and < 3.0.0-0", [hex: :spark,
repo: "hexpm", optional: false]]}, "hexpm",
"6923dca70fe1d533864134999f4d9c5c59ef745a6b50982d42d60c18966474cd"},

```

```

5 5 "assent": {:hex, :assent, "0.2.13",
"11226365d2d8661d23e9a2cf94d3255e81054ff9d88ac877f28bdfdf38fa4ef31", [:mix],
[{:certifi, ">= 0.0.0", [hex: :certifi, repo: "hexpm", optional: true]],
{:finch, "~> 0.15", [hex: :finch, repo: "hexpm", optional: true]], {:jose, "~>
1.8", [hex: :jose, repo: "hexpm", optional: true]], {:mint, "~> 1.0", [hex:
:mint, repo: "hexpm", optional: true]], {:req, "~> 0.4", [hex: :req, repo:
"hexpm", optional: true]], {:ssl_verify_fun, ">= 0.0.0", [hex: :ssl_verify_fun,
repo: "hexpm", optional: true]]}, "hexpm",
"bf9f351b01dd6bceea1d1f157f05438f6765ce606e6eb8d29296003d29bf6eab"},

```

```

6 6 "bcrypt_elixir": {:hex, :bcrypt_elixir, "3.3.2",
"d50091e3c9492d73e17fc1e1619a9b09d6a5ef99160eb4d736926fd475a16ca3", [:make,
:mix], [{:comeonin, "~> 5.3", [hex: :comeonin, repo: "hexpm", optional: false]],
{:elixir_make, "~> 0.6", [hex: :elixir_make, repo: "hexpm", optional: false]]},
"hexpm", "471be5151874ae7931911057d1467d908955f93554f7a6cd1b7d804cac8cef53"},

```



...ash_authentication_phoenix.install_test.exs



```

@@ -142,7 +142,7 @@ defmodule Mix.Tasks.AshAuthenticationPhoenix.InstallTest
do
142 142     return_to = get_session(conn, :return_to) || ~p"/"
143 143
144 144     conn
145 145     -     |> clear_session()
145 145     +     |> clear_session(:test)
146 146     |> put_flash(:info, "You are now signed out")
147 147     |> redirect(to: return_to)
148 148     end

```

test/support/accounts/user.ex

```

@@ -96,6 +96,8 @@ defmodule Example.Accounts.User do
96 96     end
97 97
98 98     authentication do
99 99     +     session_identifer(:jti)
100 100    +
99 101     add_ons do
100 102     confirmation :confirm do
101 103     monitor_fields([:email])

```

test/support/auth_controller.ex

```

@@ -26,7 +26,7 @@ defmodule AshAuthentication.Phoenix.Test.AuthController do
26 26     @impl true
27 27     def sign_out(conn, _params) do
28 28     conn
29 29     -     |> clear_session()
29 29     +     |> clear_session(:ash_authentication_phoenix)
30 30     |> render(:signed_out)
31 31     end
32 32     end

```

Comments 0



Please [sign in](#) to comment.